

Best Available COPY

72679-5

Copper Paint No. 1

ACTIVE INGREDIENTS (All Colors)	
CUPROUS OXIDE	27.76%
INERT INGREDIENTS	72.24%
(Copper as Metallic) 24.6%	
TOTAL	100.00%

27.47%

24.4%

72.53%

This Product Contains Petroleum Distillates

WARNING - Keep Out Of Reach Of Children

IF SWALLOWED: Drink promptly a large quantity of water. Avoid Alcohol. Get Medical Attention. **IF INHALED:** Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get Medical Attention. **IF ON SKIN:** Wash with plenty of soap and water. If irritation persists, Get Medical Attention. **IF IN EYES:** Flush with plenty of water for at least 15 minutes. Get Medical Attention.

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

ONE GALLON

WARNING! COMBUSTIBLE

HARMFUL OR FATAL IF SWALLOWED.
See CAUTIONS elsewhere on label.

EPA Registration No. 72679-5

1/31/2000

ACCEPTED

JAN 31 2000

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 72679-5

1/2

5-64976
EPA Reg. No. 72649-5
Pesticide, registered under
Federal Insecticide, Fungicide, and
Rodenticide Act as amended, for the
control of marine organisms.
JAN 3 1 2000
ACCEPTED

ANTI-FOULING COPPER PAINT

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS & DOMESTIC ANIMALS

WARNING

CAUSES EYE IRRITATION. Harmful if absorbed through skin. Avoid contact with skin, eyes, or clothing. Wear protective clothing, such as gloves, long sleeved cotton shirt, long pants and hat. May be fatal if swallowed. Do not breathe vapor or spray mist while spraying paint or sanding boat surface. Wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

ENVIRONMENTAL HAZARDS

This Material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL or CHEMICAL HAZARDS

Do Not Use or Store Near An Open Flame

STORAGE AND DISPOSAL

STORAGE - Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Store in a cool, dry area away from heat or open flame.

PESTICIDE DISPOSAL - Paint that cannot be used according to label instructions must be disposed of according to federal, state or local procedures under the Resources Conservation and Recovery Act.

CONTAINER DISPOSAL - Dispose of container by triple rinse (or equivalent) and recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures. If burned stay out of smoke.

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

This is a cuprous oxide pigmented coating, formulated especially to prevent the attachment of both plant and animal fouling on boats, barges, crab pots, lobster pots, and vessels immersed in both sea water and brackish water.

When used over steel or aluminum surfaces, a primer coating is required to prevent accelerated corrosion. This coating requires no primer when used directly over fiberglass or wood. For optimum performance, two (2) coats are recommended. The theoretical coverage of this product is at least 400 square feet per gallon when applied to the recommended dry film thickness.

To prepare the surface coating, remove all old coating and fouling residue by either washing with high pressure water, scraping or by disc sanding. Be sure to use the proper protective equipment to prevent inhalation or ingestion of the paint dust generated.

Clean dry surface, free of scale, corrosion, dirt, grease, oil, marine fouling, or other foreign matter will provide the optimum performance of this coating when used for either complete coating or touch-up. Inadequate surface preparation will result in unsatisfactory performance. Be sure to remove all dust, debris and other surface contaminants that are generated by the cleaning process prior to painting.

Mix the coating with either a high speed mixer or paint shaker for minimum of five (5) minutes to insure complete pigment reincorporation. Thin in the event that the coating is too thick to apply easily. Thin with mineral spirits or VM & P Naphtha.

Apply by either brush, roller or spray. Be sure to follow mixing instructions and apply the correct film thickness. Allow a minimum of four (4) hours between coats and a minimum of two (2) hours before undocking vessel.

Manufactured By:

3.785 LITERS

SHACKELFORD-PORTER
Copper Paints, Inc.

2/2