



73092-1

3-15-2000

1/6

 <p style="text-align: center;">U.S. ENVIRONMENTAL PROTECTION AGENCY Office of Pesticide Programs Registration Division (H7505C) 401 "M" St., S.W. Washington, D.C. 20460</p> <p style="text-align: center;">NOTICE OF PESTICIDE: <input checked="" type="checkbox"/> Registration <input type="checkbox"/> Reregistration</p> <p>(under FIFRA, as amended)</p>	EPA Reg. Number: 73092-1	Date of Issuance: MAR 15 2000
	Term of Issuance: Conditional	
	Name of Pesticide Product: Superspeed SP52	
Name and Address of Registrant (include ZIP Code): H. Marcel Guest Ltd. Riverside Works, Collyhurst Road Manchester, M40 7RU, England		
<p>Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.</p> <p>On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.</p> <p>Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.</p> <p>This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:</p> <ol style="list-style-type: none"> 1. Submit and/or cite all data required for registration/ reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4. 2. Make the following label changes: <ol style="list-style-type: none"> a. Revise the EPA Registration Number to read, "EPA Reg. No. "73092-1". 		
Signature of Approving Official: Marshall Swindell, PM 33 Regulatory Management Branch 1 Antimicrobial Division (7510C)	 Date: MAR 15 2000	

Page 2

EPA Registration No. 73092-1

b. On page one of your product labeling , change the words "Distributed by:" to "Manufactured by:"

c. Please note that the company name and address shown on the front page of your product labeling is for a distributorship. The primary company name and address must be listed on the label.

d. Change the initial "HMG" wherever it appears on the labeling to "H. Marcel Guest Ltd."

3. The revised Confidential Statement of Formula dated March 14, 2000 (page 1 of 2) and March 15, 2000 (page 2 of 2) complies with 40 CFR part 158.175 and PR Notice 91-2, agrees with the label and is acceptable.


3. Submit two (2) copies of the revised final printed labeling before you release the product for shipment.

A stamped copy of the label is enclosed for your records.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely,



Marshall Swindell
Product Manager 33
Regulatory Management Branch 1
Antimicrobial Division (7510C)

Enclosure

3/6

Superspeed SP52

Antifouling Bottom Paint

- High performance
- One system for all vessel types
- Easy to use
- Saves money and increases performance
- Commercial and non-commercial use

Active Ingredient

Cuprous oxide 18.7%

Other Ingredients

81.3%

TOTAL

100.0%

KEEP OUT OF REACH OF CHILDREN

CAUTION

PRECAUTIONARY STATEMENTS

Hazards to Humans & Domestic Animals

CAUTION: Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long sleeved cotton shirt, long pants, and a hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding the boat surface, wear a mask or respirator approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

FIRST AID

If in Eyes: Flush with plenty of water. Call a physician if irritation persists.

If on skin: Wash with plenty of soap and water. Get medical attention if irritation persists.

If swallowed: Call a physician or Poison Control Center. Do not induce vomiting because of aspiration hazard.

If inhaled: Remove to fresh air. If discomfort or breathing difficulty occurs obtain medical attention. If victim is not breathing, give artificial respiration, preferably mouth to mouth.

Net Contents:

Distributed by:

HMG America LLC
 P.O. Box 313
 Roebuck, SC 29376

ACCEPTED
with COMMENTS
in EPA Letter Dated:

MAR 15 2000

Under the Federal Insecticide,
 Fungicide, and Rodenticide Act as
 amended, for the pesticide,
 registered under EPA Reg. No.

73092-1

EPA Reg. No.
 EPA Est. No.

4/16

Environmental Hazards

This product is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris at an approved landfill.

Physical/Chemical Hazards

Flammable. Do not use or store near heat, sparks, or open flame. Use only carbon dioxide, foam or dry chemical extinguishers in case of fire. DO NOT use water.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Ferrous Metals (new surfaces)

Surface Preparation: Dry abrasive blast to near white metal to obtain a surface profile of 50 – 75 microns. Then apply one coat of Epoxy blast primer, then an intermediate coat of Epoxy primer followed by Superspeed SP52 antifoulant to the following specifications.

AREA:

@ 20° C Product	Over-coating, Minimum	Over-coating, Maximum	Dry Film Thickness	Wet Film Thickness	Coverage	Application Methods
SP52 Leisure	30 minutes	>1 year	60-80 mils	120-160 mils	10-15 m ²	Brush, Roller
SP52 Commercial	30 minutes	> 1 year	150 mils	300 mils	6-10 m ²	Airless spray, Agitated spray, Spray
Ditto, depending on location, vessel and usage						
Submersion: 6 hours or greater, depending on ambient temperature and final thickness						

Ferrous Metals (existing surfaces)

Surface preparation (depending on state of hull): Degrease by solvent-wiping or washing with detergent solution and rinsing with potable water. Dry abrasive blast to near white metal to obtain a surface profile of 50-75 microns. Then apply one coat of Epoxy blast primer, then an intermediate coat of Epoxy primer followed by Superspeed SP52 antifoulant as specified above.

Wood (new surfaces)

Surfaces preparation: Remove all wood shavings, dust and other imperfections. Then apply three coat of wood primer followed by Superspeed SP52 antifoulant as specified above.

**ACCEPTED
with COMMENTS
in EPA Letter Dated:**

MAR 15 2000

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

73092-1

5/6

Wood (existing surfaces)

Surface preparation: Pressure wash to remove all marine growth, salt and other imperfections. Allow to dry thoroughly. Then apply one coat of wood primer followed by Superspeed SP52 antifoulant as specified above.

Non-ferrous Metals (new surfaces)

Surface preparation: Acid wash to roughen surface. Degrease with a suitable degreaser. Then wash the entire surface. Apply two coats of Epoxy primer followed by Superspeed SP52 antifoulant as specified above.

Non-ferrous Metals (existing surfaces)

Surface preparation: Pressure wash to remove all marine growth, salt and other imperfections. Then apply two coats of Epoxy primer where necessary followed by Superspeed SP52 antifoulant as specified above.

Fiberglass (new surfaces)

Surface preparation: Lightly sand the gel coat with fine sandpaper. Remove all traces of dust using Cleaner/Thinner. Then apply two coats of Epoxy primer followed by Superspeed SP52 antifoulant as specified above. The end use of the vessel will have a bearing on the required thickness of the paint. Boat builders should speak with our technical staff for specifications.

Fiberglass (existing surfaces)

Surface preparation: Pressure wash to remove all marine growth, salt and other imperfections. Spot prime any bare fiberglass patches using an Epoxy primer followed by Superspeed SP52 antifoulant as specified above.

Storage and Disposal

Do not contaminate water, food, or feed by storage and disposal.

Pesticide Storage: Keep container tightly closed when not in use. Store in a well-ventilated area.

Pesticide Disposal: Paint chips, spent abrasives, and any other waste materials from removal of old paint must be disposed of in a sanitary landfill (or, if required by Federal, State or local regulations, handled as a hazardous waste). If possible, use all of the contents by application according to label instructions. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA, Manage excess paint, rinsate, and other application wastes in accordance with Federal, State, and local requirements. Consult your State pesticide or Environmental control agency, nearest EPA Regional Office, or the RCRA/Superfund Hotline (800-424-9346) for waste disposal guidance;

Container Disposal: Triple rinse container if intended for recycling or reconditioning. Empty paint containers with small amounts of dried residue must be disposed of in a sanitary landfill (or, if required by Federal, State or local regulations, handled as a hazardous waste).

**ACCEPTED
with COMMENTS
in EPA Letter Dated:**

MAR 15 2000
Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.
73092-1

6/6

Disclaimer: The performance of marine coatings and paints is dependent on many factors out of our control, such as preparation, proper application and environmental conditions. HMG cannot guarantee this product is suitable for your particular application or purpose. Implied warranties of fitness for a particular purpose and merchantability are excluded.

HMG shall not under any circumstance be liable for incidental or consequential liabilities. By purchase or use of this product, the buyer/user agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at HMG's option.

**ACCEPTED
with COMMENTS
in EPA Letter Dated:**

MAR 15 2000

**Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.**

73092-1