

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, D.C. 20460

OFFICE OF PREVENTION, PESTICIDES AND TOXIC SUBSTANCES

APR 2 2 2009

Ms. Juli Mann Paralegal Specialist for, Steptoe and Johnson, LLP 1330 Connecticut Ave., NW Washington, DC 20036-1795

Subject: AfterShock Fungicidal Coating

EPA Registration Number 73884-1 Your Notification Dated April 9th, 2009 EPA Received Date April 9th, 2009

The notification referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, FIFRA, as amended, to update the container disposal statements as per PR Notice 2007-4 and correct a typographical error as PR Notice 98-10, is acceptable.

The notification has been part of the permanent record of this file.

If you have any questions concerning this letter, please contact Karen M. Leavy-Munk at (703)-308-6237.

Sincerely,

Marshall Swindell

Product Manager 33

Regulatory Management Branch I Antimicrobial Division(7510C)

2047

Please read instructions on revers	e before completing form	<u></u>	Fo			0, Approval expires 5-31-98		
United States				Registrat	ion	OPP Identifier Number		
SEPA Environmental Protection Ag		ency	Amendmo	ent				
Washington, DC 20460			•	X Other				
Application for Pesticide – Section I								
Company/Product Number 73884-1			EPA Product Manager Marshall Swindell 3. Proposed Classification					
Company/Product (Name) AfterShock Fungicidal Coating	•		PM # 33		X Nor			
5. Name and Address of Applicant (Include ZIP Code) Fiberlock Technologies, Inc. 150 Dascomb Road Andover, MA 01810-5873 Check if this is a new address			6. Expedited Review. In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical in composition and labeling to: EPA Reg No. Product Name					
Section - II								
Amendment – Explain below Resubmission in response to Agency letter dated			Final printed labels in response to Agency letter dated "Me Too" Application					
X Notification – Explain below Other – Explain below								
Explanation: Use additional page(s) if necessary. (For Section I and Section II.) Notification of label changs per PR Notice 2007-4 and typographical corrections per PR Notice 98-10. This notification is consistent with the guidance in PR Notice 2007-4 and PR Notice 98-10 and the requirements of EPA's regulations at 40 CFR §§ 152.46, 156.10, 156.140, 156.144, 156.146, and 156.156. No other changes have been made to the labeling or the Confidential Statement of Formula for this product. I understand that it is a violation of 18 U.S.C. Sec. 1001 to willfully make any false statement to EPA. I further understand that if the amended label is not consistent with the requirements of 40 CFR §§ 152.46, 156.10, 156.140, 156.144, 156.146, and 156.156, this product may be in violation of FIFRA and I may be subject to enforcement action and penalties under sections 12 and 14 of FIFRA.								
Section III								
Material This Product Will be	e Packaged in:							
Child-Resistant Packaging Yes	Unit Packaging Yes	Wa	ter Soluble Packagir Yes	g	X Me	of Container tal – epoxy lined		
X No	X No	X			X Pla	astic ass		
*Certification must be submitted		•	res" okage wgt	No. per container		per ner (Specify)		
Location of Net Contents In X Label		1. Size(s) Retail 30, 55 gallon	Container	X	On Label	pel directions		
6. Manner in Which Label is Affixed to Product		Lithograph X Paper glue						
X Paper glued Stenciled								
Section IV								
1. Contact Person (Complete	items directly below for iden	tification of indiv	ridual to be contacted					
Name Juli Mann		Telephone No. (Include Area Code)						
Johnson, LLP, Authorized agent 202-429-3095 Certification 6. Date Application								
I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law								
2. Signature		3. Title				(Stamped)		
Juli Mann		Paralegal S	Paralegal Specialist, Steptoe & Johnson, LLP					
4. Typed Name Juli Mann		5. Date April 9, 200						

STEPTOE & JOHNSON

ATTORNEYS AT LAW

WRITER'S DIRECT DIAL 202.429.3095

I330 Connecticut Avenue, NW Washington, DC 20036-1795 Tel 202.429.3000 Fax 202.429.3902 steptoe.com

Via HAND DELIVERY

April 9, 2009

Document Processing Desk (NOTIF)
Office of Pesticide Programs (7504P)
U.S. Environmental Protection Agency
Room S-4900, One Potomac Yard
2777 South Crystal Drive
Arlington, VA 22202-4501

Attention: Marshall Swindell (PM 33)

AfterShock Fungicidal Coating (EPA Reg. No. 73884-1)

Notification of Label Changes per PR Notices 2007-4 and 98-10

Dear Marshall:

Re:

On behalf of our client, Fiberlock Technologies, enclosed please find a notification for AfterShock Fungicidal Coating to update the container disposal statements per PR Notice 2007-4 and correct a typographical error per PR Notice 98-10. This notification is consistent with both PR Notices 2007-4 and 98-10.

Enclosed is EPA Form 8570-1, with the required certification statement, along with one copy of the proposed label with changes highlighted. Please let me know if you have any questions or need anything further.

Regards,

Juli Mann

Paralegal Specialist

ecc: Fiberlock Technologies, Inc.

40f 7
Page 1 of 4

AfterShock® Fungicidal Coating

CAUTION Keep Out of Reach of Children

See back panel for additional Precautionary Statements

ACTIVE INGREDIENT:

 Chlorothalonil
 0.48%

 OTHER INGREDIENTS
 99.52%

 TOTAL
 100.00%

EPA Reg. No. 73884-1 EPA Est. No. 73884-MA-01

> accepted APR 22 Z009

5 U.S. Gallons (18.925 Liters) Net

8390 WHITE

Maž VOC Contents (380 g/d) 3 2 lbs/gai

AfterShock is an extremely durable acrylic finish, developed to withstand moist, humid conditions that provide the ideal environment for fungal growth. This easy to apply coating offers the ultimate in durability in combination with excellent fungicidal characteristics.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Check with all local, state, and federal regulations before beginning work or using this product. Fix the source of any moisture problems prior to remediation. Do not attempt to salvage damaged or structurally unsound building materials. Consult with a qualified professional to perform a thorough inspection and supply work specifications appropriate to the project.

AfterShock is designed to kill residual mold and mildew remaining after precleaning contaminated surfaces, as well as to inhibit the future growth and spread of mold and midlew on the cured film surface in residential & institutional buildings. AfterShock is recommended for use on interior wall surfaces such as plaster, wallboard, Sheetrock[®], concrete, masonry block, wood, primed metal and galvanized metal. AfterShock is also recommended for use on interior wood framing, primed metal, concrete, and wallboard inside the wall cavity. Do not use for HVAC system applications.

SURFACE PREPARATION

AfterShock is supplied ready to use. Stir thoroughly. Do not mix with any other coatings, solvents, or colors in oil. Remove damaged materials and clean surfaces. Patch surface irregularities with an appropriate patching compound. AfterShock is self-priming over bare gypsum drywall, composition board, ceiling tile and concrete. Do not apply when air or surface temperature is below 50°F or when drying conditions are poor. Keep from freezing. Use adequate ventilation during application.

APPLICATION TOOLS

Apply AfterShock with brush, roller or airless spray equipment. If using airless spray equipment, AfterShock can be successfully applied with a .017 -.019 tip setting.

COVERAGE

Smooth Surfaces- 300-350 ft² per gallon Porous Surfaces- 175-300 ft² per gallon Spray- 50% of above

MOLD & MILDEW CONTROL

Remove gross filth or heavy soil. For heavily soiled areas, a pre-cleaning step is required. Apply AfterShock generously and uniformly by brush or airless spray and ensure that the surface is completely coated. Allow to air dry. Clean and inspect regularly for damage to coating film- reapply if cured coating film becomes damaged. AfterShock will kill all existing visible mold and mildew on the wall surface. and then will prevent the growth of mold and mildew on the surface of the cured film.

DRYING TIME @ 70°F 50% R.H. To Touch - 1 Hour

CLEAN UP

Clean tools and drippings with warm soapy water before AfterShock dries.

ŭψ

STORAGE AND DISPOSAL

Do not containinate water, food or feed by storage or disposal

Pesticide Storage: Close container after each use. Keep from freezing.

Pesticide Disposal: Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

Container Disposal:

Plastic Containers: Nonrefillable container. Do not reuse or refill this container. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or if allowed by state and local authorities, by burning. If burned, stay out of smoke.

Metal Containers: <u>Nonrefillable container</u>. <u>Do not reuse or refill this container</u>. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or by other preedures approved by state and local authorities.

Proposition 65 Warning: This product contains a chemical(s) known to the State of California to cause cancer.

FIRST AID:	
Have the product label or Marketment.	ASDS with you when calling a poison control center or doctor, or going for
IF IN EYES	 Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
IF INHALED	 Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.
IF SWALLOWED	 Immediately call a poison control center or doctor. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.
IF ON SKIN OR CLOTHING	 Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.
YOUR I	FOR MEDICAL ASSISTANCE, CALL OCAL POISON CONTROL CENTER or 1-800-222-122200

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS

CAUTION

Harmful if swallowed or inhaled. Avoid breathing spray mist. Avoid contact with skin, eyes or clothing. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash clothing before reuse.

When applying with a sprayer, applicater should wear a dust/mist filtering respirator (MSHA/NIOSH approval number prefix TC-21C) or a NIOSH approved respirator with any R, P, N, or HE filter.

PHYSICAL AND CHEMICAL HAZARDS

Do not apply this product in or on electrical equipment due to the possibility of shock hazard

CAS No.: CHEMICAL INGREDIENTS: 7732-18-5 Water 13463-67-7 Titanium dioxide 25265-77-4 2,2,4-Trimethyl-1,3-Pentenediol Monoisobutyrate 57-55-6 Propylene glycol Not available Latex resin solid*

HMIS HAZARD RATING

Health 1 Flammability

Reactivity

Personal Protection

HMIS HAZARD INDEX

0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe

PERSONAL PROTECTION CODE: E = Safety Glasses, Gloves, and Protective Clothing for all applications (Dust Respirator – for spray applications only)

FIBERLOCK TECHNOLOGIES, INC.

150 Dascomb Road Andover, MA 01810

Batch code:

EPA Approved 8-5-2004

Edit date: 4-9-09 Notification to update container disposal statements per PR Notice 2007

^{*}contents partially unknown