
 <p>U.S. ENVIRONMENTAL PROTECTION AGENCY Office of Pesticide Programs Antimicrobials Division (7510C) 1200 Pennsylvania Avenue, N.W. Washington, D.C. 20460</p> <p>NOTICE OF PESTICIDE: <u> X </u> Registration <u> </u> Re-registration</p> <p>(under FIFRA, as amended)</p>	EPA Reg. Number:	Date of Issuance:
	74412-1	MAR 22 2002
	Term of Issuance: UNCONDITIONAL	
Name of Pesticide Product:		
Trident 51		
Name and Address of Registrant (include ZIP code):		
Envirotech Bottom Paint Corp. 930 S.E. 9th Lane Cape Coral, FL 33904		
<p>Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Antimicrobials Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.</p> <p>On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended.</p> <p>Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.</p> <p>This product is conditionally registered in accordance with FIFRA Section 3(c)(7)(A) provided that you:</p> <ol style="list-style-type: none"> Submit and/or cite all data required for registration of your product under FIFRA Section 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for re-registration of your product under FIFRA Section 4, or as required by registration review under FIFRA Section 3(g). Make the following labeling changes: <ol style="list-style-type: none"> The label must include the EPA Registration Number "EPA Reg. No. 74412-1" and EPA Establishment No. 		
Signature of Approving Official:	Date:	
 Marshall Swindell Product Manager, Team 33, Regulatory Management Branch I Antimicrobials Division	MAR 22 2002	

(b) Revise the ingredient statement to read:

Active Ingredient:	
Calcium Carbonate.....	50.00%
Other Ingredients.....	50.00%
Total.....	100.00%

(c) Move the following statement under the use directions:

“Soap and Water Cleanup”


3. Submit three copies of a final printed production label.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA Section 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the accepted label is enclosed for your records.

If you have any questions concerning this letter, please contact myself at 703-308-6341, or Portia Jenkins at (703) 308-6230.

Sincerely,



Marshall Swindell
Product Manager 33
Regulatory Management Branch 1
Antimicrobial Division(7510C)

Enclosure

TRIDENT 51

ONE US GALLON
BOTTOM PAINT
WATER BASED ANTIFOULANT

MAY BE APPLIED ON
FIBERGLASS, WOOD,
ALUMINIUM AND STEEL
BOAT BOTTOMS

INGREDIENTS:
50% CALCIUM CARBONATE
50% INERT INGREDIENTS

CAUTION: KEEP OUT OF REACH OF CHILDREN
SEE ADDITIONAL PRECAUTIONS ON BACK PANEL

ENVIROTECH BOTTOM PAINT CORP.
930 S.E. 9TH LANE, CAPE CORAL, FL 33904
TEL. 239 458 0302 FAX 239 458 0501

DISCLAIMER FOR LABEL

THE PERFORMANCE OF ANY MARINE PAINT OR COATING DEPENDS ON MANY FACTORS OUTSIDE THE CONTROL OF ENVIROTECH BOTTOM PAINT COMPANY, INCLUDING SURFACE

PREPARATION, PROPER APPLICATION AND ENVIRONMENTAL CONDITIONS; THEREFORE, ENVIRONMENTAL BOTTOM PAINT COMPANY CAN NOT GUARANTEE THIS PRODUCT'S SERVICABILITY FOR YOUR PARTICULAR PURPOSE OR APPLICATION. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. ENVIRONMENTAL BOTTOM PAINT COMPANY SHALL NOT UNDER ANY CIRCUMSTANCES

BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. BY PURCHASING OR USE OF THIS PRODUCT, BUYER AGREES THAT THE SOLE AND EXCLUSIVE REMEDY, IF ANY, IS LIMITED TO THE REFUND OF THE PURCHASE PRICE OR REPLACEMENT OF PRODUCT AT ENVIRONMENTAL BOTTOM PAINT COMPANY'S OPTION.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

MAR 22 2004

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

74412-1

FRONT LABEL

TRIDENT BOTTOM PAINT

TRIDENT 51 Bottom Paint: A highly effective hard antifouling bottom paint. Protects against attachment of barnacles, algae, coral, sponges, mollusks and other marine or fresh water growth. For use in both salt and fresh water. Do not apply to any surfaces other than boat bottoms.

Directions for use: It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Generally the area surface is clean and dry before painting. When sanding is necessary on surfaces, remove sanding dust by clean air blast, clean soft brushes, or wiping with clean rags, then follow by tack rag wipe to insure complete removal of sanding dust. **NOTE:** Face mask should be used when sanding. Air paint well before and during use. Apply generously with brush or roller at package consistency. If sanding is necessary due to overcoat, use water sparingly to thin. Trident Bottom Paint is very thick by nature. Do not spray paint. Do not apply at temperatures below 40 degrees, or if rain is expected before the coating is dry.

Coverage: Approximately one gallon per 300 square feet. Multiply boat length by boat width, multiply by 2 and then divide by 300 to obtain the amount of Trident 51 needed.

Number of Coats: 2 coats are recommended, hence the 2 in the above equation.

Color: Water based color dependent may be added to any bottom paint to obtain preferred color. Color is consistent with Trident 51 formula and will be provided at point of purchase by Trident 51.

Drying Time at 70 degrees and 60% Relative Humidity:

Between coats: 4 hours minimum. Before launching: 6 hours minimum or overnight, but no longer than 7 days.

Thinner: Use water sparingly.

Cleaner: Use soap and water.

Old Bottom Paints: After hauling the boat, allow the hull to dry thoroughly of absorbed water before repainting. When sanding old bottom paint, always wear safety glasses, dust mask, light long sleeve shirt, long pants and gloves. When job is complete, thoroughly wash protective items and body with soap and water.

Wood Halls: Sand wood surfaces with 80-100 grit wet or dry sandpaper before applying Trident Primer. Apply 2 coats of Trident Bottom Paint allowing 4 hours drying time between coats.

Fiberglass Reinforced Plastic: Down the bottom with a good chemical thinner/solvent. Remove all glossy areas with 100-220 grit sandpaper to dull and roughen the surface. Wipe off sanding dust with clean cloth or tack rag and use thinner/solvent again. Use particular care when sanding fiberglass. (see precautionary statement below).

Steel Surfaces: Sandblast to near-white surface and apply Trident 51 Primer and allow to dry before applying Trident Bottom Paint. If hull is new, simply apply Primer and then Trident Bottom Paint, allowing to dry 4 hours between coats.

Aluminum Reinforced Plastic: Wash, scrape and or sand to remove loose or flaking paint to prepare a sound bonding surface. Apply Trident Primer, let dry and apply Trident Bottom Paint.

Precautionary Statement: Hazardous to humans and domestic animals. Caution. May cause moderate eye irritation, do not inhale, or breathe vapor. Wash hands with soap and water before eating, drinking, chewing gum, using tobacco, or using toilet. After completion of job, wash clothing and body with soap and water. Unprotected persons should be kept out of work area by a minimum of 100 feet. **AVOID CONTACT** with eyes, skin and clothing when preparing bottom surface and painting (see **OLD BOTTOM PAINTS**). Wear full face shield to avoid breathing vapor, dust, or chips from sanding or painting. When sanding or applying paint to boat bottom, wear a supplied air or powered air purifying respirator (PAPR) as approved by NIOSH for use with paints and coatings. Wear a Tyvek hooded overall or the exact equivalent (with overall hood), impervious gloves and footwear to prevent hands, lower legs and feet. Wash all clothing and protective items with soap and water. If contaminated, discard after completion of each job. Wash body thoroughly with soap and water after handling and before eating, smoking or performing other bodily functions.

FIRST AID: If in eyes: flush eyes open and rinse gently with water for 15 to 20 minutes. Remove any contact lenses after 5 minutes of rinsing, then continue rinsing process. Call a Poison Control Center or Doctor for treatment advice. If swallowed: Call a Poison Control Center or Doctor immediately for treatment advice. Sip water if able to swallow. Do not induce vomiting unless so advised by Poison Control or Doctor. If breathing affected: move to fresh air. Call Poison Control or Doctor for further treatment advice. If not breathing: call 911 and give artificial respiration, preferably mouth to mouth. If on skin: remove contaminated clothing and wash body with soap and water thoroughly. Contact Poison Control or Doctor for treatment advice.

ENVIRONMENTAL HAZARDS: Pesticides are toxic to fish and aquatic invertebrates. Do not discharge effluent containing this product into any water unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit. Permitting authority must be notified in writing prior to discharge. Do not discharge effluent into sewer system without notifying local sewage plant authority. Contact State Water Board or Regional Office of EPA for guidance. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips or dust of paint removed to enter water. Dispose of paint debris in a approved landfill. **FOLLOW ALL PRECAUTIONS** as recorded above.

STORAGE AND DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Open containers may retain product residue (vapors and or liquids).

PESTICIDE DISPOSAL: Pesticide wastes are extremely hazardous. Improper disposal of excess waste is a violation of Federal Law. Contact local EPA office for additional instructions in accord with this label.

CONTAINER DISPOSAL: Triple rinse (or equivalent) recycle, recondition or puncture and dispose of in a sanitary landfill, or by other approved Federal, State and Local procedures.

BACK LABEL

RECORDED
with COMMENTS
in EPA Letter Dated:
MAR 27 2004

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

74412-1