HERCULES

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS DANGER

CAUSES SEVERE BURNS OF EYES. EYE CONTACT MAY CAUSE LOSS OF VISION. MAY BURN THE SKIN. MAY BE HARMFUL OR FATAL IF SWALLOWED. Do not take internally. Do not get into eyes, on skin or on clothing. Chemical worker's goggles must be worn when handling. Do not inhale vapor or mist, Use with adequate ventilation. Immediately remove and wash contaminated clothing before reuse. Wash thoroughly after handling. This product may cause skin sensitization in some people.

PERSONAL PROTECTIVE EQUIPMENT Applicators and other handlers must wear.

- Coveralls over short-sleeved shirt and short pants
- Socks and chemical resistant footwear
- Goodes or face shield
- Chemical-resistant gloves (such as barrier laminate, butyl nitrile, or neoprene rubber, polyvinyl chloride or viton)
- A respirator with either an organic-vapor (OV) removing cartridge with a prefilter approved for pesticides (MSHA/NIOSH approval number prefix TC-23C), or canister approved for pesticides (MSHA/NIOSH approval number prefices TC-14G).

USER SAFETY REQUIREMENTS


Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

USER SAFETY RECOMMENDATIONS

Users should wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet. Users should remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users should remove personal protective equipment immediately after handling this product. Wash outside of gloves before removing. As soon as possible wash thoroughly and change into clean clothing.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuares, oceans or other waters unless in accordance with the requirements of a National Polluntant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Secondary biological treatment of DBNPA effluent is required for all uses except for use in secondary oil recovery systems. Do not discharge effluent containing this product to sever systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA Apply this pesticide only as specified or this tabel.



umber: al ID: Net Weight: Packaging Date:

SLIME-TROL[®] RX508

SLIME CONTROL AGENT

MADE IN USA

ACTIVE INGREDIENTS:

2,2-Dibromo-3nitrilopropionamide	 20.0%
INERT INGREDIENTS*	80.0%
TOTAL	 100.0%

*Inert ingredients include solubilizing and dispersing agents.

CONTENTS: LIQUID POUNDS PER GALLON: 10.6 (60°F) EPA REGISTRATION NUMBER: 74655-9 EPA ESTABLISHMENT NUMBER: 74655-GA-01

KEEP OUT OF REACH OF CHILDREN DANGER

FIRST AID

IF IN EYES:

Hold eye open and rinse slowly and gently with water for 15-20 minutes Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eve.

Call a poison control center or doctor for treatment advice.

IF INHALED:

Move person to fresh air.

If person is not breathing, call 911 or ambulance, and then give artificial respiration, preferable mouth-to-mouth if possible. Call a poison control center or doctor for treatment advice.

IF SWALLOWED:

Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water is able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person. IF ON SKIN OR CLOTHING:

Take off contaminated clothing.

Rinse skin immediately with plenky of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.


For Emergency Information Call 302-594-5000

Have the product container or label with you when calling a poison control center or doctor, or going for treatment. For emergency information call 302-594-5000

NOTE TO PHYSICIAN:

Probable mucosal damage may contraindicate use of gastric lavage.

For Industrial Use. Technical advice regarding specific site problems is available from Hercules Incorporated, Pulp & Paper Division. A Material Safety Data Sheet containing more detailed information relative to this product is available upon request.



DIRECTIONS FOR USE: It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

GENERAL PRECAUTIONS AND RESTRICTIONS

Do not apply this product in a way that will contact workers or other persons, either directly or through drift. Only protected handlers may be in the area during application.

PULP AND PAPER SYSTEMS

This product aids in the control of objectionable bacteria and fungi in pulp, paper mill and the additive system, and for the preservation of pulp, pigment slurries, emulsions, adhesives, defoamers, polymers and paper products. NOTE: Add this product separately to the system. DO NOT mix it with other additives in order to avoid decomposition of this product due to the high pH of many additive formulations. Add this product to the system at any point to insure uniform mixing. Additions can be made continuously or intermittently, or as needed. The frequency of the feeding and duration of the treatment will depend upon the severity of contamination. BADLY FOULED SYSTEMS must be cleaned before treatment is begun.

FOR SLIME CONTROL

The product should be added directly to the pulp and paper mill system. Apply at a point in the system where the product will be uniformly mixed. INTERMITTENT OR SLUG METHOD - INITIAL DOSE: When the system is noticeably fouled, add this product at the rate of 0.1 to 1.0 pound per ton of pulp or paper produced. Additions to additive system should be made directly at the rate of 0.5 to 4.0 pound (60 to 480 ppm) per 1000 gallons. Repeat until control is achieved. SUBSEQUENT DOSE: When microbial control is evident, add this product at the rate of 0.1 to 0.5 pound per ton of pulp and paper produced. Treat the system as needed to maintain control. Additions to the additive system may be reduced to 0.25 to 2.0 pound (30 to 240 ppm) per 1000 gallons. CONTINUOUS FEED METHOD - INITIAL DOSE: When the system is noticeably fouled, add this product at the rate of 0.1 to 0.5 pound per ton of pulp or paper produced. Additions to the additive system should be made directly at the rate of 0.5 to 4.0 pound (60 to 480 ppm) per 1000 gallons. Repeat until control is achieved. SUBSEQUENT DOSE: Maintain the following level by continuous feed of this product at the rate of 0.1 to 0.3 pound per ton of pulp and paper produced. Additions to the additive system should be at the rate of 0.1 to 1.5 pound (12 to 180 ppm) per 1000 gallons.

FOR PRESERVATION

This product should be added directly to the material to be preserved prior to manufacturing into the finished product, i.e., pulp, broke, polymers, defoamers, alum, emulsions, adhesives, paper mill coatings, pigmant slurries and paper products. The dosage rate will depend upon the material to be preserved and the storage time. The usual additions should be 200 to 300 ppm and under extreme conditions of spoilage the dosage rate should be increased

to 250 to 800 ppm. The above recommendations are based on a maximum storage time of two weeks. For storage time greater than two weeks, the maximum concentration should be increased to 1000ppm.

STORAGE AND DISPOSAL

PESTICIDE STORAGE: Keep container lightly closed. Protect from freezing. Store in a dry place. Do not store at elevated temperatures.

PESTICIDE DISPOSAL: Do not contaminate water, food or feed by storage or disposal Pesticide wastes are acutely hazardous and/or toxic, improper disposal of excess pesticide, spray midure, or insate is a wiokation of Federal Law. If these wastes cannot be disposed of disposed or disposed or disposed or access pesticide, use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance CONTAINER DISPOSAL -

METAL & PLASTIC CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incinerate or burn, if allowed by state and local authorities. If burned, stay out of smoke.

FIBER DRUMS WITH LINERS: Completely empty liner by shaking and tapping sides and bottom to loosen clinging particles. Empty residue into application equipment. Then dispose of liner and drum in a sanitary landfit or incinerate if allowed by state and local authorities. Do not reuse empty drum or liner.

Hercules Incorporated, Pulp & Paper Division, N. Market Street, Wilmington, DE 18984 Emergency and Business Phone: 302-594-5000

6

50

4

2003

o'