

74681-1

6/16/2003

BLUE WATER® MARINE PAINT



HIGHEST LOADED COPPER ABLATIVE PLATINUM SERIES

BW-1275
MARINE BLUE


One Gallon 3.785 Liters

- Tremendous Protection for Extreme Fouling Conditions
- Eliminates Heavy Sanding
- No Paint Bulldrop

Keep Out of Reach of Children

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS

MANUFACTURED BY
BLUE WATER MARINE PAINT
1999 ELIZABETH STREET
NORTH BRUNSWICK, NJ 08812
1-800-432-4333
www.bluelwatermarinepaint.com



36-25-D 01/17/03

ACCIDENT

JUN 16 2003

Under the Federal Insecticide, Fungicide, and Pesticide Act as amended, for the pesticide, registered under
EPA Reg. No. 74681-1

TEMA

ACCEPTED

JUN 16 2003

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under
EPA Reg. No. 74681-1

ACTIVE INGREDIENTS:
CUPROUS OXIDE 67.0%
INERT INGREDIENTS 33.0%
TOTAL 100.0%

EPA REG. 74681-1
EPA ESTABLISHMENT 74681-NJ-1
CONTAINS PETROLEUM DISTILLATE

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes, or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed by accident. Do not breathe dust vapor or spray mist. Wear a mask or respirator approved by the Mining Enforcement and Safety Administration and/or National Institute for Occupational Safety and Health. Wash hands thoroughly after handling. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling and before eating, drinking, and smoking.

FIRST AID

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. If present, remove contact lenses. If present, continue rinsing. Call poison control center or doctor immediately.

IF SWALLOWED: Call a poison control center or doctor immediately. Do not induce vomiting. If person vomits, turn head to one side. Rinse mouth if able to do so by a poison control center or doctor.

IF ON SKIN OR CLOTHING: Take off contaminated clothing and wash skin with water for 15-20 minutes. If irritation continues, call a doctor for treatment.

IF INHALED: Move person to fresh air. If person is not breathing, call ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor immediately for further information.

For additional information in case of emergency, call 1-800-526-5000. Have the product container or label available when you call. Call a poison control center or doctor for treatment.

ENVIRONMENTAL HAZARD

This paint is toxic to birds, fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, canals, oceans, or public waters unless product is specifically identified and addressed in a NPDES permit. Do not discharge effluent containing this product to sewage systems without previously notifying the sewage plant authority. For guidance contact your State Water Board or Regional Office of the U.S. Environmental Protection Agency.

PHYSICAL AND CHEMICAL HAZARDS

Do not use or store near heat or open flame.

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

Product Description: Copper Pro™ 67 provides antifouling protection against barnacles, algae and hydroids in salt and freshwater on boat bottoms only. Its ablative copolymer base renders a smooth finish with durability and abrasion resistance. Copper Pro 67 releases biocide by the constant exposure of new paint film to the water. Copper Pro 67 has universal application over all types of properly prepared bottom paints (except aluminum). For use on fast fiberglass boats as well as wood and steel hulls.

Surface Preparation: Surface must always be clean, dry and properly prepared prior to painting. Failure to do so will lead to ineffective protection and/or peeling. All sanding must be wiped clean with BW-1100 to remove sanding residue.

Universal Application: Apply 3 coats of antifoulant to all surfaces. Allow 24 hours between coats. If surface is not completely smooth, apply 1 coat of BW-216 Thinner to fill any imperfections. Then apply 3 coats of antifoulant.

On Barn Wood: Scrub bottom clean at haul-out. Repaint only if old paint is sound and tight; if not, remove it by sanding or with paint remover. If old paint is rough, sand it with 100-150 grit sandpaper. Prepare seams, nicks and chips as below. Spotcoat any scuffs with antifoulant. Apply 3 coats of antifoulant.

On Barn Fiberglass: Scrub by washing until surface is clean, then allow to dry. Repeat until surface is smooth. Fill any imperfections with BW-216 Thinner. Then apply 3 coats of antifoulant.

Theoretical Coverage: Depending on surface conditions, one gallon of bottom paint will usually cover over 400 square feet of surface when brushed or rolled.

Clean Up: Use BW-216 Thinner for cleaning equipment and paint brushes.

Estimated Dry Times: Bottom paints are designed for overcoating after an overnight dry. Prior to launching, allow a minimum dry of overnight and maximum of 60 days. If drying conditions are poor, or if paint was applied too thickly, longer periods of drying will be required. Fresh coats of paint must be thoroughly dry before overcoating.

Yearly Repainting: Scrub bottom clean at haul-out. Repaint only if old paint is sound and tight; if not, remove it by sanding or with paint remover. If old paint is rough, sand it with 100-150 grit sandpaper. Prepare seams, nicks and chips as below. Spotcoat any scuffs with antifoulant. Apply 3 coats of antifoulant.

On Barn Wood: If seams are not flush, fill them with seam compound. Dry several days until skin forms. Do not sand. Fill nicks with trowel cement, dry, hard, sand, apply antifoulant (reduced 10%) then follow with 2 additional unreduced coats of antifoulant.

On Barn Fiberglass: Scrub by washing until surface is clean, then allow to dry. Repeat until surface is smooth. Fill any imperfections with BW-216 Thinner. Then apply 3 coats of antifoulant.

On Barn Fiberglass: Scrub by washing until surface is clean, then allow to dry. Repeat until surface is smooth. Fill any imperfections with BW-216 Thinner. Then apply 3 coats of antifoulant.

On Barn Fiberglass: Scrub by washing until surface is clean, then allow to dry. Repeat until surface is smooth. Fill any imperfections with BW-216 Thinner. Then apply 3 coats of antifoulant.

Physical and Chemical Hazards: Do not eat, drink or smoke while using this product. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Store in a cool, dry place. Keep away from children. Do not contaminate water by disposal of wastes.