

U.S. ENVIRONMENTAL PROTECTION AGENCY Office of Pesticide Program Registration Division (H7505C) 401 "M" St., S.W. Washington, D.C. 20460

NOTICE OF PESTICIDE: <u>X</u> Registration Reregistration

(under FIFRA, as amended)

EPA Reg. Number:

Date of Issuance:

SEP 1 5 2004

74681-4

Term of Issuance: Expiration

Date 06/15/05

Name of Pesticide Product:

Copper Pro SCX 67

Name and Address of Registrant (include ZIP Code):

Blue Water Marine Paint 1999 Elizabeth Street North Brunswick, NJ 08902

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c) (5) when the Agency request all registrants of similar product to submit such data; and submit acceptable response required for reregistration of your product under FIFRA section 4.

The Agency is currently reviewing additional information submitted by your supplier. In order to allow the Agency time to review this information we are extending this time limited registration to June 15, 2005.

Signature of Approving Official:

SEP 15 2004

Marshall Swindel1 Product Manager 33

Regulatory Management Branch I Antimicrobials Division (7510C)

EPA Form 8570-6

As requested in the original registration notice you must delete the picture of the dolphins on the front-panel of the label. The picture of the dolphins implies an environmental safety claim.

2. This conditional registration will expire automatically June 15, 2005. If you fail to satisfy the conditions imposed in the registration, EPA may issue a Notice To Cancel under Section 6(e) of FIFRA.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely yours,

Marshall Swindell Product Manager 33

Regulatory Management Branch I Antimicrobials Division (7510C)

Enclosure

BULE WATER®

Since the day good home proof had not shown tolk and contained to the same proof had been something to the same proof to

Pasticipa menta de tenor rinante la 3 visitation di biana. La Divisi, tendra dell'
proved of by une bicontrina il biana l'appealation, comment
posticicho or employmentali control appealation or fronta faces
reservativo di bia provent EPA popinial office de protesso di

Triple fines combines, then letter to represent the section of the purchase and dispress of the section of the sec

EMANUFACTURED BY AN BLUE WATER MARINE PAIN 1900 ELIZABETH STREET SE NORTH BEATSWICK NJ. 0890

www.bauwalarmari.popalni.co



ACCEPTED
with COMMENTS
in EPA Letter Dated:

SEP 1 5 2004

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 7468/-4

HIG BOUST PLATINUM

> BW-1277 MARINE BLUE

One Gallon 3.785 Liters

WARNING: Keep Out of Reach of Children
SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS

COPPER AS METALLIC \$ 59.50 EPA REG. 74681 4 17 EPA ESTABLISHMENT 74681 CONTAINS PETROLEUM DISTILLATE

PRECAUTIONARY STATEMENTS HAZAROS TO HUMANS AND DOMESTIC ANIMALS?

Causes eve irritation: Harmful if absorbed through skin. Avoid contact with skin eyes, or clothing. Wear protective clothing such as gloves, long sleeved cotton shirt, long parits and hat. May be tatal if swallowed or inhaled. Do not breathe dust, vapor of spray mist. Wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and by the National Institute for Occupational Safety and Health while sanding boat surfaces. Remove contaminated clothing and wash before reuse. Wash thoroughly with soarr and water after handling FIRST AID

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 min utes. Remove contact lenses, if present, after the first 5 minutes; then continue rinsing. Call a poison control center or doctor for treatment advices:

IF SWALLOWED; Call a poison control center or doctor immediately for treatment advice. Have a person stp a glass of water if able to smallow, Do pot induce your iting unless told to do so by a poison control center of doctor.

IF ON SKIN OR CLOTHING: Take off contaminated clothing Rinse skin Immediately with plenty of water for 15-20 minutes. Call a poison control center or doc-

tor for treatment if 13.22 is a first special Call a poison control center or doctor immediately for further treatment advice. For additional information in case of emergency call toll free Chemtrec-1-800-424-9300 168

Have the product container or label with you when calling a polison control center or doctor or poing for treatment.

ENVIRONMENTAL HAZARDS This paint is took to birds, fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries; oceans, or public waters unless product is specifically identified and addressed in a NPDES permit. Do not discharge effluent containing this product to sewage systems without previously notifying the sewage plant authority. For guidance contact your State Water Board or Regional Office of the U.S. Environmental Protection Agency.

FACE PHYSICAL AND CHEMICAL HAZARDS (A) Do not use or store mear heat or open flame.

nd fresh water on boat bottoms only. SC SLIME CONTROL XTRAM - acts like a screen to prevent slime and aloae. Its abla tive copolymer base renders a smooth finish with durability and abrasion resistance. Coppet Pro™ SCX™ 67 releases biocide by the constant exposure of new paint film to a and tight if not, remove it by sanding or with the water. Copper Pro™ SCX™ 67 has universal application over all types of properly prepared bottom paints (except aluminum); For use on fast fiberglass boats, as well as any scutts with antifoulant. Apply 3 coats of wood and steel hulls; extended protection is antifoulant.

possible; since performance is directly pro
On Bare Wood: If seams are not flush, fill portional to the amount of paint applied

Surface Preparation: Surface must always days until skin forms. Do not sand, Fill nicks be clean, dry and properly prepared prior to with trowel cement, dry hard, sand, apply painting, failure to do so will lead to eventual antifoulant (reduced 10%) then follow with 2 ally blistering and/or peeling; All sanded sur-additional unreduced coats of antifoulant. taces must be wiped clean with BW-216 Da Bare Fiberglass: Dewax by washing with Thinner to remove sanding residue

General Application: For use on boats on once with clean paper towels or rags; repeat; rolled on fiberglass wood, steel and previous sandpaper Fill any chips with Irowel cement, push painted surfaces per application systems below. Do not use on aluminum. Apply Prokote Epoxy, then apply 3 coats of at least 3 coats for best performance, as the families and life of the paint is proportional to the number of On Bere Steet: Sandblast surface to a near of coats applied. * J. Cont. 19.5

Mixing and Thinning: Shake or mix thoroughly and stir continuously while using Thin when necessary with BW-216 Thinner.

face conditions, one gallon of bottom paint antifoulant. will usually cover over 400 square feet of surface when brushed or rolled.

ing conditions are poor or il paint was applied too thickly, longer periods of drying will be required. Fresh coats of paint must be thoroughly dry before overcoating.

Yearly Repainting: Scrub bottom clean at haul-out. Repaint only if old paint is sound paint remover, if old paint is rough, sand it with 100-150 grit sandpaper. Prepare seams, nicks and chips as below. Spotcoat

them with seam compound. Dry several

888-216 Thinner, remove dissolved wax at policity that true waterline. Can be brushed be said hard to a dull finish with 80-100 orit

white metal; remove blast residue with a Ebroom and airhose. Wipe off with BW-216 Thinner, Do not sand. Fill in any imperfections with fairing compound. Sand smooth and wipe clear. Apply 5 coats of BW-2000 Theoretical Coverage: Depending on sur- Prokote Epoxy, then apply 3 coats of

ACCEPTED wish COMMENTS in EPA Letter Dated

SEP 1 5 2004

Under the Pecieral Insecticide. Pungicide, and Rodenticide Acr as amended, for the pesticide. registered under EPA Reg. No:

74681-4