



U.S. ENVIRONMENTAL PROTECTION AGENCY  
Office of Pesticide Programs  
Registration Division (H7505C)  
401 "M" St., S.W.  
Washington, D.C. 20460

EPA Reg. Number:  
74681-7

Date of Issuance:  
JAN 26 2005

NOTICE OF PESTICIDE:  
  x   Registration  
       Reregistration

Term of Issuance:  
Conditional

Name of Pesticide Product:  
Kolor Royal Blue

(under FIFRA, as amended)

Name and Address of Registrant (include ZIP Code):

Blue Water Marine Paint  
1999 Elizabeth Street  
North Brunswick, NJ 08902

**Note:** Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistration under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit and/or cite all data or other material required for registration/reregistration of your product under FIFRA sec. 3(c)(5) or FIFRA sec. 4 when the Agency requires all registrants of similar products to submit such data.
2. Make the following labeling changes:
  - a) Add the phrase, "EPA Registration No.74681-7"

Signature of Approving Official:

Marshall Swindell, Product Manager (33)  
Regulatory Management Branch I  
Antimicrobials Division (7510C)

Date:

JAN 26 2005

- b) You must delete the wildlife images from the labels. We note that you have previously petitioned the Agency to allow the images to remain on all labels of prior registration. This petition request is still under consideration, and you will be contacted once a determination has been made.
- c) The ingredient statement must appear on the front panel of the label with the product name and signal word.
- d) Revised the footnote below the in ingredient statement and metallic must be declared as "Copper As Metallic 23.26".
- e) Change "Brightest" to "Bright" on the front panel of the label (this is a comparative claim and is not permitted)
- f) The text on the far left of you label appears to be below the minimum type size requirement of 6 points. If this is true you must increase the type size of this text.
- g) You are required to use the complete product name (i.e., Kolor Royal Blue) throughout the label text, or a reference statement such as "this product", this "antifoulant", etc.
- h) Change "Active Ingredients" to "Active Ingredient" since there is only one active ingredient in your product.

3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,



Marshall Swindell  
Product Manager 33  
Regulatory Management Branch I  
Antimicrobials Division (7501C)

Enclosure

# BLUE WATER<sup>®</sup> MARINE PAINT

# KOLOR<sup>™</sup>

## MULTI SEASON SELF POLISHING ABLATIVE KOLOR SERIES

8611  
**ROYAL BLUE**

One Gallon 3.785 Liters

**WARNING** Keep Out of Reach of Children  
SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS

- Brightest Colors Including White
- Perfect for Aluminum, Fiberglass, Wood & Steel Boats
- Excellent for Trailer Boats
- Can be Applied Over Most Antifoulings
- No Paint Buildup
- Eliminates Heavy Sanding
- Great Protection for Tough Fouling Conditions

ACCEPTED  
with COMMENTS  
in EPA Letter Dated:

JAN 26 2005

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 246-87

**RECIPIENT:** The purchaser of this product shall be responsible for the correct use of the product in accordance with the label directions and for the proper disposal of the product. The purchaser shall be responsible for the proper disposal of the product. The purchaser shall be responsible for the proper disposal of the product.

#### STORAGE AND DISPOSAL

Store in a dry area away from heat and sunlight. Do not store in a container that is not properly labeled. Do not store in a container that is not properly labeled.

#### PESTICIDE DISPOSAL

Pesticide wastes are toxic. Improper disposal of pesticide wastes is a violation of Federal law. If there is a spill or leak of this pesticide, you should immediately notify your local environmental control agency. A notification should be made at the nearest EPA regional office.

#### CONTAINER DISPOSAL

Triple rinse container, then offer it for recycling or reuse, if available. Do not reuse container for any other purpose. Do not reuse container for any other purpose.

#### MANUFACTURED BY

**BLUE WATER MARINE PAINT**  
1989 ELIZABETH STREET  
NORTH BRUNSWICK, NJ 08902  
1-800-628-8422  
[www.bluewatermarinepaint.com](http://www.bluewatermarinepaint.com)



### ACTIVE INGREDIENTS:

COPPER THIOCYANATE	45.00%
INERT INGREDIENTS	55.00%
TOTAL:	100.00%

COPPER AS METALLIC = 39.97%  
EPA REG. 74681-  
EPA ESTABLISHMENT 74681-NJ-1  
CONTAINS PETROLEUM DISTILLATE

ACCEPTED  
with COMMENTS  
in EPA Letter Dated:

JAN 26 2005

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No.

74681-7

### PRECAUTIONARY STATEMENTS

#### HAZARDS TO HUMANS AND DOMESTIC ANIMALS

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes, or clothing. Wear protective clothing such as gloves, long sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray mist. Wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and by the National Institute for Occupational Safety and Health while sanding boat surfaces. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

#### FIRST AID

**IF IN EYES:** Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a poison control center or doctor for treatment advices.

**IF SWALLOWED:** Call a poison control center or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor.

**IF ON SKIN OR CLOTHING:** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment.

**IF INHALED:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth to mouth, if possible. Call a poison control center or doctor immediately for further treatment advice. For additional information in case of emergency call toll free Chemtrec-1-800-424-9300.

Have the product container or label with you when calling a poison control center or doctor or going for treatment.

#### ENVIRONMENTAL HAZARDS

This paint is toxic to birds, fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or public waters unless product is specifically identified and addressed in a NPDES permit. Do not discharge effluent containing this product to sewage systems without previously notifying the sewage plant authority. For guidance contact your State Water Board or Regional Office of the U.S. Environmental Protection Agency.

#### PHYSICAL AND CHEMICAL HAZARDS

Do not use or store near heat or open flame.

### DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

**Product Description:** KOLOR™ bottom paint has the cleanest, brightest colors and the most selection for bottom paint on the market today. Not only do we have the whitest white and the blackest black, we also have 100's of color combinations to choose from. Combine all of that with a multi-season self polishing ablative copolymer, and our KOLOR™ bottom paint line is as effective as it is clean & vibrant. KOLOR™ provides antifouling protection against barnacles, algae and hydroids in salt and fresh water on boat bottoms only. KOLOR™ has universal application over all types of properly prepared bottom paints. For use on fiberglass, aluminum, wood & steel hulls.

**Surface Preparation:** Surface must always be clean, dry and properly prepared prior to painting. Failure to do so will lead to eventually blistering and/or peeling. All sanded surfaces must be wiped clean with Dewaxer - 973 to remove sanding residue.

**General Application:** For use on boats below the true waterline. Can be brushed or rolled on fiberglass, wood, steel and previously painted surfaces per application systems below. Do not use on aluminum. Apply at least 2 coats for best performance, as the life of the paint is proportional to the number of coats applied.

**Mixing and Thinning:** Shake or mix thoroughly and stir continuously while using. Thin when necessary with Reducer - 974.

**Theoretical Coverage:** Depending on surface conditions, one gallon of bottom paint will usually cover over 400 square feet of surface when brushed or rolled.

**Clean Up:** Use Reducer - 974 for cleaning equipment and paint brushes.

**Estimated Dry Times:** Bottom paints are

designed for overcoating after an overnight dry. Prior to launching, allow a minimum dry of overnight. If drying conditions are poor, or if paint was applied too thickly, longer periods of drying will be required. Fresh coats of paint must be thoroughly dry before overcoating.

**Yearly Repainting:** Scrub bottom clean at haul-out. Repaint only if old paint is sound and tight; if not, remove it by sanding or with paint remover. If old paint is rough, sand it with 100-150 grit sandpaper. Prepare seams, nicks and chips as below. Spotcoat any scuffs with antifoulant. Apply 2 coats of antifoulant.

**On Bare Fiberglass:** Dewax by washing with Dewaxer - 973, remove dissolved wax at once with clean paper towels or rags; repeat; sand hard to a dull finish with 80-100 grit sandpaper. Fill any chips with trowel cement, dry hard, sand. Apply 3-5 coats of 8000A / 8000B Bottom Protect High Build Epoxy Primer, then apply 2 coats of antifoulant.

**On Bare Aluminum:** Dewax by washing with Dewaxer - 973, remove dirt / oils at once with clean paper towels or rags; repeat; sand hard to a dull finish with 80-100 grit sandpaper. Apply 3-5 coats of 8000A / 8000B Bottom Protect High Build Epoxy Primer, then apply 2 coats of antifoulant.

**On Bare Wood:** If seams are not flush, fill them with seam compound. Dry several days until skin forms. Do not sand. Fill nicks with trowel cement, dry hard, sand, apply antifoulant (reduced 10%) then follow with 2 additional unreduced coats of antifoulant.

**On Bare Steel:** Sandblast surface to a near white metal; remove blast residue with a broom and airhose. Wipe off with Dewaxer - 973. Do not sand. Fill in any imperfections with fairing compound. Sand smooth and wipe clean. Apply 3-5 coats of 8000A / 8000B Bottom Protect High Build Epoxy Primer, then apply 2 coats of antifoulant.

h/h