

74681-7

1/13/2009

1 of 4



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
 WASHINGTON D.C., 20460

OFFICE OF
 PREVENTION, PESTICIDES AND
 TOXIC SUBSTANCES

Blue Water Marine Paint
 1999 Elizabeth Street
 North Brunswick, NJ 08902

JAN 13 2009

Attention: Don Schnurr
 Regulatory Manager

Subject: Kolor Royal Blue
 EPA Reg. No. 74681-7
 Letter Dated September 29, 2008

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, is acceptable provided the following changes are incorporated in the labeling:

- Under the "STORAGE AND DISPOSAL language, include the following: "In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations".
- Under the PESTICIDE DISPOSAL language, add the following:

"Triple rinse container promptly after emptying. Triple rinse as follows: Empty remaining contents into application equipment or a mix tank and drain for 10 seconds after the begins to drip. Fill the container 1/10th full with thinner and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or recycling. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times. Then offer the container for recycling or reconditioning, or puncture and dispose of in sanitary landfill, or by other approved state and local procedures".


- Under the CONTAINER DISPOSAL language, add the following:

"Nonrefillable Container. Do not reuse or refill this container. Offer for recycling if available".

The alternate labels you submitted with this application were not approved as part of this amendment. The Agency does not stamp alternate labels. Furthermore, the Agency has no record that the alternate brand names you listed in this application were approved by EPA. If you are currently marketing these products without approval, you are in violation of EPA regulations. You can submit these brand names through notification (PR Notice 98-10) for approval. Alternate brand labels can only differ from the basic product name label by formatting and deletion of some claims.

A stamped label is enclosed for your records. If you have any questions concerning this letter, please contact Demson Fuller at (703) 308-8062.

Sincerely,



Marshall Swindell
Product Manager (33)
Regulatory Management Branch 1
Antimicrobials Division (7510C)

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

Product Description: KOLOR bottom paint has the cleanest, brightest colors and the most selection for bottom paint on the market today.

(Not only do we have the whitest white and the blackest black, we also have 100's of color combinations to choose from. Combine all of that with a multi-season self-polishing abative copolymer, and our bottom paint line is as effective as it is clean & vibrant. This product provides antifouling protection against barnacles, algae and hydroids in salt and fresh water on boat bottoms only. This product has universal application over all types of properly prepared bottom paints for use on fiberglass, aluminum, wood & steel hulls.

Surface Preparation: Surface must always be clean, dry and properly prepared prior to painting. Failure to do so will lead to eventual blistering and/or peeling. All sanded surfaces must be wiped clean with Dewaxer 973 to remove sanding residue.

General Application: For use on boats below the true waterline (can be brushed or rolled on fiberglass, wood, steel and previously painted surfaces per application systems below). Apply at least 2 coats for best performance, as the line of the paint is proportional to the number of coats applied.

Mixing and Thinning: Shake or mix thoroughly and stir continuously while using thin when necessary with Reducer - 974.

Theoretical Coverage: Depending on surface conditions, one gallon of bottom paint will usually cover over 400 square feet of surface when brushed or rolled.

Clean Up: Use Reducer - 974 for cleaning equipment and paint brushes.

Estimated Dry Times: Bottom paints are

designed for overcoating after an overnight dry. Prior to painting, allow a minimum of 24 hours of overnight drying conditions at 60°F or higher. If paint was applied too thickly, or gel periods of drying will be required. Fresh coats of paint must be thoroughly dry before overcoating.

Yearly Repainting: Scrub bottom clean annually. Repaint only if old paint is soured and tight or if not remove it by sanding or with paint remover. If old paint is tough, sand it with 100-150 grit sandpaper. Prepare seams, nicks and chips as below. Splice coat any scuffs with antifouling. Apply 2 coats of antifouling.

On Bare Fiberglass: Dewax by washing with Dewaxer 973, remove dissolved wax at once with clean paper towels or rags, repeat sand hard to a dull finish with 80-100 grit sandpaper. Fill any chips with trowel cement dry hard sand. Apply 3-5 coats of 8000A/8000B Bottom Protect High Build Epoxy Primer, then apply 2 coats of antifouling.

On Bare Aluminum: Dewax by washing with Dewaxer 973, remove dirt/oils at once with clean paper towels or rags, repeat sand hard to a dull finish with 80-100 grit sandpaper. Apply 3-5 coats of 8000A/8000B Bottom Protect High Build Epoxy Primer, then apply 2 coats of antifouling.

On Bare Wood: If seams are not flush, fill them with seam compound. Dry several days until skin forms. Do not sand. Fill nicks with trowel cement, dry hard sand, apply antifouling (reduced 10%) then follow with 2 additional un-reduced coats of antifouling.

On Bare Steel: Sand blast surface to a near white metal, remove blast residue with a broom and air hose. Wipe off with Dewaxer 973. Do not sand. Fill in any imperfections with fairing compound. Sand smooth and wipe clean. Apply 3-5 coats of 8000A/8000B Bottom Protect High Build Epoxy Primer, then apply 2 coats of antifouling.

ACCEPTED
WATER COMPANY
JAN 1 2009
ACCEPTED
WATER COMPANY
JAN 1 2009

Does Not Federal In...
...and ...
...for the ...
...under ...

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray mist. Wear a mask or respirator (if approved by the Mining, Enforcement and Safety Administration and by the National Institute for Occupational Safety and Health) while sanding boat surfaces. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

FIRST AID

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses if present after the first 5 minutes, then continue rinsing. Call a poison control center or doctor for treatment advice.
IF SWALLOWED: Call a poison control center or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor.
IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment.
IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor immediately for further treatment advice. For additional information in case of emergency, call toll free Chemtrec 1-800-424-9309.
Have the product container or label with you when calling a poison control center or doctor or going to treatment.

ENVIRONMENTAL HAZARDS

This paint is toxic to birds, fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or public waters unless product is specifically identified and addressed in a NPDES permit. Do not discharge effluent containing this product to sewage systems without previously notifying the sewage plant authority. For guidance contact your State Water Board or Regional Office of the U.S. Environmental Protection Agency.

PHYSICAL AND CHEMICAL HAZARDS

Do not use or store near heat or open flame.