

74681-7

6/2/2009

1097



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON D.C., 20460

OFFICE OF
PREVENTION, PESTICIDES AND
TOXIC SUBSTANCES

JUN - 2 2009

Blue Water Marine Paint
1999 Elizabeth Street
North Brunswick, NJ 08902

Attention: Don Schnurr
Regulatory Manager

Subject: Kolor Royal Blue
EPA Reg. No. 74681-7
Letter Dated September 29, 2008

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, is acceptable. The Agency has no objections to the addition of the precautionary statement "Causes Skin Irritation" to your label.

A stamped label is enclosed for your records. If you have any questions concerning this letter, please contact Demson Fuller at (703) 308-8062.

Sincerely,

A handwritten signature in cursive script that reads "M Swindell".

Marshall Swindell
Product Manager (33)
Regulatory Management Branch 1
Antimicrobials Division (7510C)

2007

ACCEPTED
with COMMENTS
EPA Letter Dated:

JUN - 2 2009

BLUE WATER[®] MARINE PAINT

Under the Federal Insecticide,
Fungicide and Rodenticide Act as
authorized by the Environmental Protection Agency

Label No. 74681-7

DISCLAIMER: The performance of any marine paint on a vessel is based on the manufacturer's instructions. The manufacturer is not responsible for any damage to property or equipment caused by the use of this product. The manufacturer is not responsible for any damage to property or equipment caused by the use of this product. The manufacturer is not responsible for any damage to property or equipment caused by the use of this product.

STORAGE AND DISPOSAL

Store in a dry area away from heat and severe cold. Keep partially full containers tightly sealed. Do not contaminate water, food, or feed by storage or disposal. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

PESTICIDE DISPOSAL

Pesticide wastes are toxic. Improper disposal of excess pesticides or waste is a violation of federal laws. If these wastes can not be disposed of by the user according to label instructions, contact your state pesticide or environmental control agency or hazardous waste representative at the nearest EPA regional office for guidance. Triple rinse container (after spraying) with soap and water. Empty remaining contents into application equipment for a tank, tank and drain for 10 seconds after the pump begins to drip. Fill the container 1/10th full with thinner and recap. Shake for 10 seconds. Pour rinse into application equipment or a tank or store for later use or recycling. Repeat this procedure two more times. Then offer the container for recycling or conditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

CONTAINER DISPOSAL

Triple rinse container, then offer for recycling or reconditioning or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities. Non-refillable container. Do not reuse or refill this container. Other authority information available.

MANUFACTURED BY

BLUE WATER MARINE PAINT

1999 ELIZABETH STREET

NORTH BRUNSWICK, NJ 08902

1-800-432-4333

www.bluewatermarinepaint.com



Bright Colors Including White

Perfect for Aluminum

Fiberglass, Wood & Steel Boats

Excellent for Trailer Boats

Can Be Applied Over Most

Antifouling

No Primer Buildup

Eliminates Heavy Sanding

Great Protection for Tough

Fouling Conditions

1.5 Gallon / 85 Liter

KOLOR[™]

MULTI SEASON

SELF POLISHING

ABJACTIVE

PR SERIES

8611

BLUE

100% Lead-free
100% Cadmium-free
100% Mercury-free

ACCEPTED
with COMMENTS
EPA Letter Dated:

JUN - 2 2009

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide
registered under EPA Reg. No. 74681-7

ACTIVE INGREDIENT
COPPER THIOCYANATE 45.00%
INERT INGREDIENTS 55.00%
TOTAL 100.00%
COPPER AS METALLIC - 23.26%
EPA REG. 74681-7
EPA ESTABLISHMENT 74681-NJ-1
CONTAINS PETROLEUM DISTILLATE

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

May be fatal if swallowed. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. May be fatal if absorbed through skin. Do not get in eyes, on skin, or on clothing. Wear proper gloves & clothing jointly approved by the Mining Enforcement and Safety Administration and by the National Institute for Occupational Safety. Remove and wash contaminated clothing before reuse. May be fatal if inhaled. Do not breathe dust, vapor or spray mist. Causes skin irritation. Remove and wash contaminated clothing before reuse. Causes substantial but temporary eye injury. Do not get in eyes or on clothing. Wear specific goggles & respirator jointly approved by the Mining Enforcement and Safety Administration and by the National Institute for Occupational Safety.

FIRST AID

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a poison control center or doctor for treatment advice.

IF SWALLOWED: Call a poison control center or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor.

IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor immediately for further treatment advice. For additional information in case of emergency, call toll free Chemtrec: 1-800-424-9300.

Have the product container or label with you when calling a poison control center or doctor or going for treatment.

ENVIRONMENTAL HAZARDS

This paint is toxic to birds, fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or public waters unless product is specifically identified and addressed in a NPDES permit. Do not discharge effluent containing this product to sewage systems without previously notifying the sewage plant authority. For guidance, contact your State Water Board or Regional Office of the U.S. Environmental Protection Agency.

PHYSICAL AND CHEMICAL HAZARDS

Do not use or store near heat or open flame.

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

Product Description: KOLOR™ bottom paint has the cleanest, brightest colors and the most selection for bottom paint on the market today. Not only do we have the whitest white and the blackest black, we also have 100's of color combinations to choose from. Combine all of that with a multi-season self-polishing, abrasive copolymer, and our bottom paint line is as effective as it is clean & vibrant. This product provides antifouling protection against barnacles, algae and hydroids in salt and fresh water on boat bottoms only. This product has universal application over all types of properly prepared bottom paints. For use on fiberglass, aluminum, wood & steel hulls.

Surface Preparation: Surface must always be clean, dry and properly prepared prior to painting. Failure to do so will lead to eventually blistering and/or peeling. All sanded surfaces must be wiped clean with Dewaxer - 973 to remove sanding residue.

General Application: For use on boats below the true waterline. Can be brushed or rolled on fiberglass, wood, steel and previously painted surfaces per application systems below. Can use on aluminum. Apply at least 2 coats for best performance, as the life of the paint is proportional to the number of coats applied.

Mixing and Thinning: Shake or mix thoroughly and stir continuously while using. Thin when necessary with Reducer - 974.

Theoretical Coverage: Depending on surface conditions, one gallon of bottom paint will usually cover over 400 square feet of surface when brushed or rolled.

Clean Up: Use Reducer - 974 for cleaning equipment and paint brushes.

Estimated Dry Times: Bottom paints are designed for overcoating after an overnight dry. Prior to launching, allow a minimum dry of overnight. If drying conditions are poor, or if paint was applied too thickly, longer periods of drying will be required. Fresh coats of paint must be thoroughly dry before overcoating.

Yearly Repainting: Scrub bottom clean at haul-out. Repaint only if old paint is sound and tight. If not, remove it by sanding or with paint remover. If old paint is rough, sand it with 100-150 grit sandpaper. Prepare seams, nicks and chips as below. Spotcoat any scuffs with antifoulant. Apply 2 coats of antifoulant.

On Bare Fiberglass: Dewax by washing with Dewaxer - 973, remove dissolved wax at once with clean paper towels or rags, repeat sand hard to a dull finish with 80-100 grit sandpaper. Fill any chips with trowel cement, dry hard, sand. Apply 3-5 coats of 8000A/8000B Bottom Protect High Build Epoxy Primer, then apply 2 coats of antifoulant.

On Bare Aluminum: Dewax by washing with Dewaxer - 973, remove dirt/oils at once with clean paper towels or rags, repeat sand hard to a dull finish with 80-100 grit sandpaper. Apply 3-5 coats of 8000A/8000B Bottom Protect High Build Epoxy Primer, then apply 2 coats of antifoulant.

On Bare Wood: If seams are not flush, fill them with seam compound. Dry several days until skin forms. Do not sand. Fill nicks with trowel cement, dry hard, sand, apply antifoulant (reduced 10%), then follow with 2 additional unreduced coats of antifoulant.

On Bare Steel: Sandblast surface to a near white metal, remove blast residue with a broom and air hose. Wipe off with Dewaxer - 973. Do not sand. Fill in any imperfections with fairing compound. Sand smooth and wipe clean. Apply 3-5 coats of 8000A/8000B Bottom Protect High Build Epoxy Primer, then apply 2 coats of antifoulant.

307

FRONT PANEL

KOLOR™

MULTI SEASON SELF POLISHING ABLATIVE KOLOR SERIES

ACCEPTED
with COMMENTS
EPA Letter Dated:

JUN - 2 2009

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No. 74681-7

- Bright Colors Including White
- Perfect for Aluminum, Fiberglass, Wood & Steel Boats
- Excellent for Trailer Boats
- Can be Applied Over Most Antifouling
- No Paint Buildup
- Eliminates Heavy Sanding
- Great Protection for Tough Fouling Conditions

WARNING: Keep Out of Reach of Children
SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS

One Gallon 3.785 Liters

LEFT PANEL

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of our company including surface preparation, proper application, and environmental condition. Therefore, we cannot guarantee this product's suitability for your particular purpose or application. Implied warranties of fitness for a particular purpose and of merchantability are excluded. We shall not, under any circumstances, be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that the sole exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product, at the company's option.

STORAGE AND DISPOSAL

Store in a dry area away from heat and severe cold. Keep partially used container tightly sealed. Do not contaminate water, food or feed by storage or disposal. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

PESTICIDE DISPOSAL

Pesticide wastes are toxic. Improper disposal of excess pesticides or rinsate is a violation of federal law. If these wastes cannot be disposed of by use according to label instructions, contact your state pesticide or environmental control agency, or hazardous waste representative at the nearest EPA regional office for guidance. Triple rinse container after emptying. Triple rinse as follows: Empty remaining contents into application equipment or a mix tank and drain for 10 seconds after the begins to drip. Fill the container 1/10th full with thinner and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or recycling. Drain for 10 seconds after flow begins to drip. Repeat this procedure two more times. Then offer the container for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approval state and local procedures.

CONTAINER DISPOSAL

Triple rinse container, then offer it for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities. Nonrefillable Container. Do not reuse or refill this container. Offer for recycling if available.

MANUFACTURED BY BLUE WATER MARINE PAINT

1999 ELIZABETH STREET
NORTH BRUNSWICK, NJ 08902
1-800-628-8422
www.bluewatermarinepaint.com

ACCEPTED
with COMMENTS
EPA Letter Dated:

JUN - 2 2009

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No. 74481-7

6087

ACCEPTED
with COMMENTS
EPA Letter Dated:

BACK INSTRUCTIONS

ACTIVE INGREDIENT:

COPPER THIOCYANATE 45.00%

INERT INGREDIENTS 55.00%

TOTAL: 100.00%

COPPER AS METALLIC = 23.26%

EPA REG. 74681-7

EPA ESTABLISHMENT 74681-NJ-1

CONTAINS PETROLEUM DISTILLATE

JUN - 2 2009

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No. 74681-7

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

May be fatal if swallowed. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. May be fatal if absorbed through skin. Do not get in eyes, on skin, or on clothing. Wear proper gloves & clothing jointly approved by the Mining Enforcement and Safety Administration and by the National Institute for Occupational Safety. Remove and wash contaminated clothing before reuse. May be fatal if inhaled. Do not breathe dust, vapor or spray mist. Causes skin irritation. Remove and wash contaminated clothing before reuse. Causes substantial but temporary eye injury. Do not get in eyes or on clothing. Wear specific goggles & respirator jointly approved by the Mining Enforcement and Safety Administration and by the National Institute for Occupational Safety.

FIRST AID

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a poison control center or doctor for treatment advices.

IF SWALLOWED: Call a poison control center or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor.

IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth to mouth, if possible. Call a poison control center or doctor immediately for further treatment advice. For additional information in case of emergency call toll free Chemtrec- 1-800-424-9300. Have the product container or label with you when calling a poison control center or doctor or going for treatment.

ENVIRONMENTAL HAZARDS

This paint is toxic to birds, fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or public waters unless product is specifically identified and addressed in a NPDES permit. Do not discharge effluent containing this product to sewage systems without previously notifying the sewage plant authority. For guidance contact your State Water Board or Regional Office of the U.S. Environmental Protection Agency.

PHYSICAL AND CHEMICAL HAZARDS

Do not use or store near heat or open flame.

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its

7097

labeling.

Product Description: KOLOR™ bottom paint has the cleanest, brightest colors and the most selection for bottom paint on the market today. Not only do we have the whitest white and the blackest black, we also have 100's of color combinations to choose from. Combine all of that with a multi-season self polishing ablative copolymer, and our bottom paint line is as effective as it is clean & vibrant. This product provides antifouling protection against barnacles, algae and hydroids in salt and fresh water on boat bottoms only. This product has universal application over all types of properly prepared bottom paints. For use on fiberglass, aluminum, wood & steel hulls.

Surface Preparation: Surface must always be clean, dry and properly prepared prior to painting. Failure to do so will lead to eventually blistering and/or peeling. All sanded surfaces must be wiped clean with Dewaxer – 973 to remove sanding residue.

General Application: For use on boats below the true waterline. Can be brushed or rolled on fiberglass, wood, steel and previously painted surfaces per application systems below. Can use on aluminum. Apply at least 2 coats for best performance, as the life of the paint is proportional to the number of coats applied.

Mixing and Thinning: Shake or mix thoroughly and stir continuously while using. Thin when necessary with Reducer – 974.

Theoretical Coverage: Depending on surface conditions, one gallon of bottom paint will usually cover over 400 square feet of surface when brushed or rolled.

Clean Up: Use Reducer – 974 for cleaning equipment and paint brushes.

Estimated Dry Times: Bottom paints are designed for overcoating after an overnight dry. Prior to launching, allow a minimum dry of overnight. If drying conditions are poor, or if paint was applied too thickly, longer periods of drying will be required. Fresh coats of paint must be thoroughly dry before overcoating.

Yearly Repainting: Scrub bottom clean at haul-out. Repaint only if old paint is sound and tight; if not, remove it by sanding or with paint remover. If old paint is rough, sand it with 100-150 grit sandpaper. Prepare seams, nicks and chips as below. Spotcoat any scuffs with antifoulant. Apply 2 coats of antifoulant.

On Bare Fiberglass: Dewax by washing with Dewaxer – 973, remove dissolved wax at once with clean paper towels or rags; repeat; sand hard to a dull finish with 80-100 grit sandpaper. Fill any chips with trowel cement, dry hard, sand. Apply 3-5 coats of 8000A / 8000B Bottom Protect High Build Epoxy Primer, then apply 2 coats of antifoulant.

On Bare Aluminum: Dewax by washing with Dewaxer – 973, remove dirt / oils at once with clean paper towels or rags; repeat; sand hard to a dull finish with 80-100 grit sandpaper. Apply 3-5 coats of 8000A / 8000B Bottom Protect High Build Epoxy Primer, then apply 2 coats of antifoulant.

On Bare Wood: If seams are not flush, fill them with seam compound. Dry several days until skin forms. Do not sand. Fill nicks with trowel cement, dry hard, sand, apply antifoulant (reduced 10%) then follow with 2 additional unreduced coats of antifoulant.

On Bare Steel: Sandblast surface to a near white metal; remove blast residue with a broom and airhose. Wipe off with Dewaxer – 973. Do not sand. Fill in any imperfections with fairing compound. Sand smooth and wipe clean. Apply 3-5 coats of 8000A / 8000B Bottom Protect High Build Epoxy Primer, then apply 2 coats of antifoulant

ACCEPTED
with COMMENTS
EPA Letter Dated:

JUN - 2 2004

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended for the pesticide,
registered under EPA Reg. No. 74681-7