



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

October 26, 2021

Brian Hogan
Agent – KRK Consulting LLC
Blue Water Marine Paint
14805 49th Street North
Clearwater, FL 33762

Subject: Notification per PRN 98-10 – Adding an alternate brand name and label changes
Product Name: Shelter Island Plus
EPA Registration Number: 74681-28
Received Date: 08/13/2021
Action Case Number/Decision Number: 00316764

Dear Brian Hogan,

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) lists examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Assurance.

The alternate brand name “Armor Antifoulant Paint” has been added to the product record.

If you have any questions, you may contact Carlos Corona via email at Corona.Carlos@epa.gov.

Sincerely,

A handwritten signature in black ink, appearing to read "Eric Miederhoff".

For Eric Miederhoff
Product Manager Team 31
Regulatory Management Branch I
Antimicrobials Division (7510P)
Office of Pesticide Programs

Notes to reviewer are bracketed []
Statements in parenthesis are optional or alternative text ()

[Brand Name]
Shelter Island Plus™

[Alternative Brand Names – Can appear on label anywhere the brand name is listed]

Marine AF Copper Free Plus

Armor Antifoulant Paint

NOTIFICATION

74681-28

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

10/26/2021

**KEEP OUT OF REACH OF CHILDREN
DANGER**

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

[OPTIONAL MARKETING STATEMENTS:]

Multi-Seasonal Antifouling
Copper Free Antifouling
No Copper or Tin Compounds
Compatible With All Hull Types Including Aluminum
Contains Combination of Patented SCX Biocides
Good Protection for Moderate to High Fouling Conditions
Eliminates Heavy Sanding, Compatible With Other Existing Bottom Systems

Dual-Biocide

8241 Deep Blue

8242 Black

8246 White

Contains Ecomea

For Fiberglass, Wood & Aluminum

Prevents Slime & Algae

Withstands Frequent Trailing and Launching

Copper Free

Flexdel

Antifoulant Paint

[Optional Graphics]



8 11577 01595 9

[ABOVE BAR CODE WILL APPEAR ON EACH CAN AND THE NUMBERS PROVIDED THE ABOVE WILL CORRESPOND WITH THE BAR CODE ISSUED FOR THAT PRODUCT.]



FRONT - LEFT PANEL

ACTIVE INGREDIENT:

Tralopyril	5.60%	(CAS No. 122454-29-9)
ZINC PYRITHIONE	4.00%	(CAS No. 13463-41-7)
INERT INGREDIENTS	90.40%	
TOTAL:	100.00%	

EPA REG. No. 74681-28

EPA ESTABLISHMENT NO. 746891-NJ-1 44891-FL-1

CONTAINS PETROLEUM DISTILLATES, xylene or xylene range aromatic Solvents

Manufactured (By) (For):

(Blue Water Marine Paint) (New Nautical Coatings, Inc.)

1999 ELIZABETH STREET

NORTH BRUNSWICK, NJ 08902

1-800-628-8422

www.bluewatermarinepaint.com

14805 49th Street North

Clearwater, FL 33762

[Above will be used with contents and manufacturer depending on the size]

[Net Contents:] {Gallon 3.785 Liters}, {Quart 0.9463 Liters}

{Batch Code} [to appear on front or back panel of the label or immediate container depending on the container type/size]

STORAGE AND DISPOSAL

Do not contaminate food, feed or water by storage or disposal.

STORAGE

Store in a dry area away from heat and severe cold. Keep partially used container tightly sealed.

PESTICIDE DISPOSAL

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by the use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

Non-refillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

BACK PANEL

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Occupational handlers' employers must verify that any handler who uses a respirator is: fit tested and fit-checked, trained and examined by a qualified practitioner to ensure physical ability to safely wear the style of respirator to be worn. A qualified practitioner is a physician or other licensed health care professional who will evaluate the ability of a worker to wear a respirator. The initial evaluation consists of a questionnaire that asks about the medical conditions (such as a heart condition) that would be problematic for respirator use. If concerns are identified, then additional evaluations, such as a physical exam, might be necessary. The initial evaluation must be done before respirator use begins. Handlers must be reexamined by a qualified medical practitioner if their health status of respirator style or use-conditions change. Upon request by local/state/federal/tribal enforcement personnel, employers must provide documentation demonstrating how they have complied with these requirements.

Product Description

(Shelter Island Plus) (This product) is a high performance, solvent based antifouling paint that uses a high-end technology of tralopyril and zinc pyrithione biocides and zinc oxide. (Shelter Island Plus) (This product) provides multi-season protection against barnacles, algae, slime and hydroids in salt water on boat bottoms only. Its abrasive copolymer base renders a smooth finish with durability and abrasion resistance. (Shelter Island Plus) (This product) releases its biocide by the constant exposure of new paint film to the water. (Shelter Island Plus) (This product) has universal application over all types of properly prepared bottom paints. For use on fiberglass boats, as well as aluminum, wood and steel hulls.

Surface Preparation: Surface must always be clean, dry and properly prepared prior to painting. Failure to do so will lead to eventually blistering and/or peeling. All sanded surfaces must be wiped clean with Dewaxer 973 to remove sanding residue.

General Application: For use on boats below the true waterline. Can be brushed or rolled on fiberglass, wood, aluminum steel and previously painted surfaces per application systems below. Apply ~~at least 2~~ coats for best performance. ~~as the life of the paint is proportional to the number of coats applied.~~ Certain areas of the hull such as the leading edge of the keel and rudder, the waterline and the bow stem polish faster than other areas. On these areas, an additional coat of paint is recommended to ensure that the paint does not polish away before other areas of bottom. Apply only in outdoor, non-enclosed spaces. Do not apply by spray. Do not apply this product in a way that will contact adults, children, pets, either directly or through drift.

Spray Drift Management: A variety of factors including weather conditions (e.g. wind direction, wind speed, temperature, relative humidity) and method of application can influence pesticide drift. The applicator must evaluate all factors and make appropriate adjustments when applying this product.

Mixing and Thinning: Shake or mix thoroughly and stir continuously while using. Thin only when necessary with Thinner 974.

Theoretical Coverage: Depending on surface conditions, one gallon of bottom paint will usually cover over 400 square feet when brushed or rolled

Clean Up: Use ~~Reducer~~ Thinner 974 ~~or 975~~ for cleaning equipment and paint brushes.

Estimated Dry Times: Bottom paints are designed for over coating after an overnight dry. Prior to launching, allow a minimum dry of overnight. If drying conditions are poor, or if paint was applied too thickly, longer periods of drying will

be required. Fresh coats of paint must be thoroughly dry before over coating.

Yearly Repainting: Scrub bottom clean at haul-out. Repaint only if old paint is sound and tight; if not, remove it by sanding or with paint remover. If old paint is rough, sand it with 100-150 grit sandpaper. Prepare seams, nicks and chips as below. Spot coat any bare areas with Shelter Island Plus or with Barriershield Primer on bare metals. Apply 2 coats of (Shelter Island Plus) (this product).

On Bare Wood: If seams are not flush, fill them with seam compound. Dry several days until skin forms. Do not sand. Fill nicks with trowel cement, dry hard, sand, apply first coat of (Shelter Island Plus) (this product) reduced 10% with Thinner 974, then follow with 2 additional coats of (Shelter Island Plus) (this product).

On Bare Fiberglass: Dewax by washing with Dewaxer 973, remove dissolved wax at once with clean paper towels or rags; repeat; sand hard to dull finish with 80-100 grit sandpaper. Fill any chips with trowel cement, dry hard, sand. Apply 3-5 coats of Bottom Protect Epoxy Primer. Then apply 2 coats of Shelter Island Plus.

On Bare Steel: Sandblast surface to a near white metal; remove blast residue with a broom and air hose. Wipe off with Dewaxer 973. Apply one or two coats of ~~Blue Water Marine Strontium Chromate Epoxy Primer~~ Chromate Free Epoxy Primer followed by 3-4 coats of Bottom Protect Epoxy Primer. Allow to properly dry and apply two coats of (Shelter Island Plus) (this product).

On Bare Aluminum: Sandblast as above but with a non-metallic abrasive only. Apply one or two coats of ~~Blue Water Strontium Chromate Epoxy Primer~~ Chromate Free Epoxy Primer followed by 3-4 coats of Bottom Protect Epoxy Primer. Allow to properly dry and apply two coats of (Shelter Island Plus) (this product).

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes irreversible eye damage. Prolonged or repeated skin contact may cause allergic reactions in some individuals. Do not get in eyes or on clothing. Harmful if swallowed, inhaled or absorbed through skin. Avoid contact with skin, eyes or clothing. Do not breathe vapor. Wash thoroughly with soap and water after handling. Wear a NIOSH-approved respirator with an organic vapor (OV) cartridge with a combination N, R, or P filter with NIOSH approval number prefix TC-84A or NIOSH approved powered air purifying respirator with HE filter with NIOSH approval number prefix TC-23C or a NIOSH gas mask with an organic vapor canister with NIOSH approval number prefix TC-14G.

Users must wear chemical resistant gloves, protective eyewear (goggles, safety glasses, or face shields), long sleeved shirt and long pants, socks and shoes.

Follow manufacturer's instructions for cleaning / maintaining Personal Protective Equipment (PPE). If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry.

PERSONAL PROTECTION EQUIPMENT (PPE)

Occupational handlers in the sprayman position applying this product are required to wear a NIOSH approved full facepiece supplied-air respirator (PF 1000) during use OR a continuous flow supplied air or powered air purifying respirator equipped with a hood that covers the face, neck, and shoulders. The air or powered air purifying respirator is required to have an assigned protection factor of 1,000, per NIOSH standards, and must be used with an organic vapor cartridge and a high efficiency (HEPA) pre-filter. The spray man must wear safety glasses beneath the hood respirator. Occupational handlers in the line tender position applying this product are required to wear a NIOSH approved air-purifying half-face mask elastomeric respirator (PF 10) with any R or P filter during use.

ENVIRONMENTAL HAZARDS

This paint is toxic to birds, fish and aquatic invertebrates and may contaminate water thru runoff. Do not apply directly to water by cleaning of equipment or disposal of wastes or allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product into sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARDS

FLAMMABLE: Do not use or store near open flame.

FIRST AID	
IF IN EYES:	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
IF ON SKIN OR CLOTHING:	Take off contaminated clothing. Rinse skin immediately with plenty of water for 15 – 20 minutes. Call a poison control center or doctor for treatment advice.
IF SWALLOWED:	Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.
IF INHALED:	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.
Have the product container or label with you when calling a poison control center or doctor or going for treatment. You may also contact 1-800-222-1222 for emergency medical treatment information.	
For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night. Within USA and Canada 1-800-424-9300. Outside USA and Canada +1-703-741-5970 CHEMTREC. Account #15570.	

Disclaimer: The performance of any marine paint or coating depends on many factors outside the control of our company including surface preparation, proper application, and environmental condition. Therefore, we cannot guarantee this product's suitability for your particular purpose or application. Implied warranties of fitness for a particular purpose and of merchantability are excluded. We shall not, under any circumstances, be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that the sole exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product, at the company's option.