

74681-32

7/13/2012

1/7



U S ENVIRONMENTAL PROTECTION AGENCY

Office of Pesticide Programs
Antimicrobials Division (7510P)
1200 Pennsylvania Avenue NW
Washington D C 20460

EPA Reg Number

74681-32

Date of Issuance

JUL 13 2012

Term of Issuance

Conditional

Name of Pesticide Product

Copper Shield Uno

NOTICE OF PESTICIDE

x Registration
Reregistration

(under FIFRA as amended)

Name and Address of Registrant (include ZIP Code)

Don Schnurr
Blue Water Marine Paint
1999 Elizabeth Street
North Brunswick NJ 08902

Note Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce In any correspondence on this product always refer to the above EPA registration number

On the basis of information furnished by the registrant the above named pesticide is hereby registered/reregistered under the Federal Insecticide Fungicide and Rodenticide Act

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency In order to protect health and the environment the Administrator on his motion may at any time suspend or cancel the registration of a pesticide in accordance with the Act The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others

This product is conditionally registered in accordance with FIFRA sec 3(c)(7)(a) provided that you

- 1 Submit and/or cite all data required for registration of your product under FIFRA sec 3(c)(5) when the Agency requires all registrants of similar products to submit such data, and submit acceptable responses required for re-registration of your product under FIFRA section 4
2 Make the labeling changes listed below before you release the product for shipment
a Revise the "EPA Registration Number to read, EPA Reg No 74681-32"

Signature of Approving Official

Marshall Swindell
Product Manager Team-33
Regulatory Management Branch I
Antimicrobials Division (7510P)

[Handwritten signature of Marshall Swindell]

Date

JUL 13 2012


Page 2
EPA Reg No 74681-32

- b To satisfy OPPTS 830 6317 (Storage Stability) and OPPTS 830 6320 (Corrosion Characteristics) requirements, results for a minimum of 1 year from a GLP-compliant storage stability and corrosion characteristics study must be provided
- c The ingredient statement must be moved to the front panel In addition, when the statement is placed on the front panel, it must be aligned properly

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec 6(e) Your release for shipment of the product constitutes acceptance of these conditions

A stamped copy of the label is enclosed for your records Submit one (3) copies of your final printed labeling prior to release of this product for shipment If you have any questions concerning this letter, please contact Demson Fuller at (703) 308-8062

Sincerely,



Marshall Swindell
Product Manager Team-33
Regulatory Management Branch I
Antimicrobials Division (7510P)

Enclosure (Stamped Label)

FRONT PANEL

BLUE WATER®
MARINE PAINT

COPPER SHIELD
UNO™

ACCEPTED
with COMMENTS
in EPA Letter Dated:
JUL 13 2012

Under Fungicide
amended for use as a biocide
registered under EPA Reg No: 74681-32

FULL SEASON
COPPER ABLATIVE

BRONZE SERIES

- Self Polishing Ablative
- Full Season Protection
- No Paint Buildup
- Eliminates Heavy Sanding
- Good Protection for Moderate Fouling Conditions

WARNING: Keep Out of Reach of Children
SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS

One Gallon 3 785 Liters

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

~~May be fatal if swallowed~~ Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. May be fatal if absorbed through skin. Do not get in eyes, on skin, or on clothing. Wear proper gloves & clothing jointly approved by the Mining Enforcement and Safety Administration and by the National Institute for Occupational Safety. Remove and wash contaminated clothing before reuse. May be fatal if inhaled. Do not breathe dust, vapor or spray mist. Causes skin irritation. Remove and wash contaminated clothing before reuse. Causes substantial but temporary eye injury. Do not get in eyes or on clothing. Wear safety goggles & respirator jointly approved by the Mining Enforcement and Safety Administration and by the National Institute for Occupational Safety.

ACCEPTED
with Comments
JUL 13 2012

FIRST AID

IF IN EYES. Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a poison control center or doctor for treatment advices.

Insecticide
Fungicide, and Rodenticide Act as
amended by the FIFRA
registered under EPA Reg No
74681 32

IF SWALLOWED Call a poison control center or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor.

IF ON SKIN OR CLOTHING Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment.

IF INHALED Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth to mouth, if possible. Call a poison control center or doctor immediately for further treatment advice. For additional information in case of emergency call toll free Chemtrec- 1-800-424-9300. Have the product container or label with you when calling a poison control center or doctor or going for treatment.

ENVIRONMENTAL HAZARDS

This paint is toxic to birds, fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or public waters unless product is specifically identified and addressed in a NPDES permit. Do not discharge effluent containing this product to sewage systems without previously notifying the sewage plant authority. For guidance contact your State Water Board or Regional Office of the U S Environmental Protection Agency.

PHYSICAL AND CHEMICAL HAZARDS

Do not use or store near heat or open flame.

DISCLAIMER The performance of any marine paint or coating depends on many factors outside the control of our company including surface preparation, proper application, and environmental condition. Therefore, we cannot guarantee this product's suitability for your particular purpose or application. Implied warranties of fitness for a particular purpose and of merchantability are excluded. We shall not, under any circumstances, be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that the sole exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product, at the company's option.

BACK INSTRUCTIONS

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling

Product Description COPPER SHIELD UNO™ provides full season antifouling protection against barnacles, algae and hydroids in salt and fresh water on boat bottoms only. Its ablative copolymer base renders a smooth finish with durability and abrasion resistance. COPPER SHIELD UNO™ releases biocide by the constant exposure of new paint film to the water. COPPER SHIELD UNO™ has universal application over all types of properly prepared bottom paints (except aluminum). For use on fiberglass boats, as well as wood and steel hulls.

Surface Preparation Surface must always be clean, dry and properly prepared prior to painting. Failure to do so will lead to eventually blistering and/or peeling. All sanded surfaces must be wiped clean with Dewaxer – 973 to remove sanding residue.

General Application For use on boats below the true waterline. Can be brushed or rolled on fiberglass, wood, steel and previously painted surfaces per application systems below. Do not use on aluminum. Apply at least 2 coats for best performance, as the life of the paint is proportional to the number of coats applied.

Mixing and Thinning Shake or mix thoroughly and stir continuously while using. Thin when necessary with Reducer – 974.

Theoretical Coverage Depending on surface conditions, one gallon of bottom paint will usually cover over 400 square feet of surface when brushed or rolled.

Clean Up Use Reducer – 974 for cleaning equipment and paint brushes.

Estimated Dry Times Bottom paints are designed for overcoating after an overnight dry. Prior to launching, allow a minimum dry of overnight. If drying conditions are poor, or if paint was applied too thickly, longer periods of drying will be required. Fresh coats of paint must be thoroughly dry before overcoating.

Yearly Repainting Scrub bottom clean at haul-out. Repaint only if old paint is sound and tight, if not, remove it by sanding or with paint remover. If old paint is rough, sand it with 100-150 grit sandpaper. Prepare seams, nicks and chips as below. Spotcoat any scuffs with antifoulant. Apply 2 coats of antifoulant.

On Bare Wood If seams are not flush, fill them with seam compound. Dry several days until skin forms. Do not sand. Fill nicks with trowel cement, dry hard, sand, apply antifoulant (reduced 10%) then follow with 2 additional unreduced coats of antifoulant.

On Bare Fiberglass Dewax by washing with Dewaxer – 973, remove dissolved wax at once with clean paper towels or rags, repeat, sand hard to a dull finish with 80-100 grit sandpaper. Fill any chips with trowel cement, dry hard, sand. Apply 3-5 coats of 8000A / 8000B Bottom Protect High Build Epoxy Primer, then apply 2 coats of antifoulant.

On Bare Steel Sandblast surface to a near white metal, remove blast residue with a broom and airhose. Wipe off with Dewaxer – 973. Do not sand. Fill in any imperfections with fairing compound. Sand smooth and wipe clean. Apply 3-5 coats of 8000A / 8000B Bottom Protect High Build Epoxy Primer, then apply 2 coats of antifoulant.

ACCEPTED
with COMMENTS
in EPA Letter Dated
JUL 13 2012

Under the Federal Insecticide, Fungicide and Rodenticide Act, amended with the amendments registered under EPA Reg No 74681-32

7/7

**BLUE WATER
MARINE PAINT**

999 ELIZA BETH STREET
RT 8 UNSWI N, NJ 0890
SA

www.bbluewatermarinepaint.com
Phone (732) 821-4333
(800) 32-4333
Fax (732) 821-8180

E-Mail to Negron Juan@EPA.GOV
Re Blue Water Marine Paint Copper Shield UNO EPA
Reg #74681-GE 32

Juan per our discussion, attached are the revised EPA Form 8570 4 revised as we discussed and our revised product label with the change in cuprous declaration I have also included the documents that seem to never arrive These cover the revised Product Chemistry sections per OPPTS 830 Guidelines Parts A and B as well as a revised Data Matrix per a previous discussion with Demsom Fuller Please review and add to our file for this registration Thanks again

NOT
INCLUDED
UNLESS STATED
THESE
WERE
RECEIVED
LAST WEEK

Jack Lockey