

75341-11

10/5/2009

1093



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OCT 5 2009

OFFICE OF
PREVENTION, PESTICIDES
AND TOXIC SUBSTANCES

Teri Muchow, Manager – Regulatory Administration
Osmose Utilities Services, Inc.
980 Ellicott Street
Buffalo, NY 14209

Subject: Cop-R-Nap
EPA Registration Number: 75341-11
Application Date: August 31, 2009
Receipt Date: September 1, 2009

Dear Ms. Muchow:

The following amendment, submitted in connection with registration under the Federal, Insecticide, Fungicide, and Rodenticide Act (FIFRA), is acceptable.

Proposed Amendment:

Revised label per 40 CFR Part 156 & 40 CFR Part 146(d).

General Comments:

A copy of the stamped label is enclosed for your files.

Should you have further questions concerning this letter, please contact me by telephone at 703-308-6427 or by email at carlisle.sharon@epa.gov or Killian Swift by telephone at 703-308-6346 or by email at swift.killian@epa.gov. When submitting information or data in response to this letter, a copy of this letter should accompany the submission to facilitate processing.

Sincerely,

A handwritten signature in black ink that reads "ShaRon Carlisle".

ShaRon Carlisle
(Acting) Product Manager 34
Regulatory Management Branch II
Antimicrobials Division (7510P)

Enclosure: Stamped Accepted Label

20f3

COP-R-NAP™

**COPPER NAPHTHENATE SOLUTION
COPPER FUNGICIDE - INSECTICIDE FOR WOOD
PREVENTS WOOD DECAY - TERMITES, MILDEW**
INCLUDING POLES AND POLETOPS, BORE HOLES,
POSTS, BEAMS, LUMBER, BRIDGE AND MINE TIMBERS AND PILING
For Exterior Use Only

ACTIVE INGREDIENT:
Copper naphthenate* 68.00%
INERT INGREDIENT: 32.00%
TOTAL 100.00%

*8% copper as metal

CONTAINS PETROLEUM DISTILLATES

**KEEP OUT OF REACH OF CHILDREN
WARNING**

See other precautionary statements on side panel.

FIRST AID

If inhaled	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth to mouth, if possible. Call a poison control center or doctor for further treatment advice.
If on skin or clothing	Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice
If in eyes	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
If swallowed	Call poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person.
Have the product container or label with you when calling a poison control center or doctor, or going for treatment. In case of medical questions, emergencies, or accidents involving this product, call CHEMTREC at 1-800-424-9300.	
Note To Physician: Contains petroleum distillate – vomiting may cause aspiration pneumonia.	

EPA EST. NO. 3008-NY-1

EPA REG. NO. 75341-11


Osmose®

Distributed by:
Osmose Utilities Services, Inc.
980 Ellicott Street
Buffalo, NY 14209

NET CONTENTS: 5 Gallons (Product weight 8.3 lbs. per gallon.)

BATCH NUMBER: _____

Osmose is a registered trademark of Osmose, Inc.



3093

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING: Causes substantial but temporary eye injury and skin irritation. Harmful if swallowed, inhaled or absorbed through the skin. Do not get in eyes, on skin or on clothing. Wear goggles, face shield, or safety glasses. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Do not breathe vapors or mist during brush, roll, spray or dip applications. Wear a NIOSH/MHSA-approved mist/vapor respirator when spraying for continued or prolonged use of this product or for frequent use of this product.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not apply directly to water, to areas where surface water is present, or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment washwaters.

PHYSICAL OR CHEMICAL HAZARDS

Combustible: Do not use, pour, spill or store near heat or open flame. Close container after each use.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Wood Preservation: For the control of fungal rot and decay, mold and mildew, moss, termites (including Formosan termites) and other wood destroying insects in wood products.

APPLICATION SITE

COP-R-NAP is only intended for use on exterior wood. Do not apply to food or feed contact surfaces. Do not contaminate drinking water with treated articles. COP-R-NAP Wood Preservative provides protection against moisture, rot and mildew on any natural wood surface. This copper naphthenate wood preservative and insecticide will preserve, protect and seal wood surfaces that will be in contact with soil, water or concrete.

The copper fungicide gives a green cast to COP-R-NAP Wood Preservative. This product is not intended for use as a stain. The green color will fade within a few months when exposed to sunlight. Oil or alkyd stains or paints can be applied over COP-R-NAP Preservative after overnight dry but the green may bleed through lighter colors. Do not over coat COP-R-NAP Wood Preservative with latex paint or clear finishes until thoroughly cured (6 to 12 months).

Application of this product may produce a strong, lingering unpleasant odor.

PREPARATION

Wood should be clean, dry and seasoned.

APPLICATION

Stir before using. Dilute 1 gallon of this concentrate solution with 3 gallons of a hydrocarbon solution (#2 fuel oil, mineral spirits, etc.) Shake well.

COP-R-NAP Wood Preservative should be applied liberally by brush, roller, spray, total immersion, surface flooding or internal injection under pressure for the prevention and control of fungal decay organisms.

Dipping - Wood should be dipped for 3 to 30 minutes per inch of thickness. Fence posts, piles, poles, foundation timber and heavy wooden members should be free of bark, dry, and well seasoned and immersed in the product for a period of 12 to 48 hours to be an effective wood preserver.

Internal Treatment - To internally treat previously treated utility poles or other foundation timbers apply COP-R-NAP solution to interior cavity of wood structure through prepared openings using air or mechanical pressure pump. Apply 1 gallon or to refusal.

Use one coat on materials to be finished with paint or stain. If no finish is to be used, apply two liberal coats within the hour. Thoroughly cover ends. The more preservative absorbed by the wood, the longer and more effective the protection. Clean painting equipment with mineral spirits for quick clean up. One gallon will treat approximately 200 - 300 square feet.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

STORAGE: Store at temperature between 0°F and 120°F. If the product has been spilled or is leaking, remove the source of the spill or leak. Recover free liquid. Spread absorbant, then pick up and place in containers. Then, where applicable, wash area with detergent and water. Store product in the original container only. Keep container closed when not in use.

PESTICIDE DISPOSAL: Wastes resulting from use of this product should be disposed of according to state and local regulations.

CONTAINER HANDLING: *Nonrefillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying.*

For five (5) gallon pails, triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container 1/4 full with diesel fuel and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

For 55 gallon drum, triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container 1/4 full with diesel fuel. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat the procedure two more times. Then offer for recycling if available or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities

AUG-2009

ACCEPTED
OCT 5 2009
Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 75341-11