
2000 132 75483-4 9/2/2003 WC5711AMS.PDF 10 INC R 1 mCide™ 5711 A ACCEPTED **ACTIVE INGREDIENTS:** Potassium dimethyldithiocarbamate...... 12.50% SEP 0 2 2003 Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 75483-4

KEEP OUT OF REACH OF CHILDREN DANGER

See back panel for additional precautionary statements

IN CASE OF MEDICAL EMERGENCY call CHEMTREC at 800-424-9300 (USA) or 703-527-3887 (INTERNATIONAL)



IRULE	(GRAPHIC RE	C	Э	32
ACCEPTED SEP 12 2003		• • • • • •			
Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the	AmCide™ 5	711			
pesticide, registered under EPA Reg. No. 75748-3-4	PRECAUTIONARY S ZARDS TO HUMANS AND				
	DANGE	R			
	and skin damage. Harmful if swallowe ar goggles or face shield and rubber ol				10.

FIRST AID Call a poison control center or doctor for treatment advice. Have the product container or tabel with you when calling a poison control center or doctor, or going for treatment. You may also contact the National Poison Control is 1-800-858-7378 for emergency medical treatment information. **IF SWALLOWED** Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person. IF ON SKIN OR Take off contaminated clothing. CLOTHING Rinse skin immediately with plenty of water for 15-20 minutes. . Hold eye open and rinse slowly and gently with water for 15-20 minutes. IF IN EYES Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. **IF INHALED** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not apply in marine and/or estuarine oil fields. Do not discharge effluent containing this product into lakes. streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

DIRECTIONS FOR USE: It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

This product is used to control sulfate-reducing bacteria in petroleum secondary-recovery waterflooring operations. In systems fouled with microbiological deposits, this product should be added as a slug dose to provide a concentration of 32 to 64 ppm (3.9 to 7.8 fluid oz, of this product per 1000 gallon of water treated). This should be followed by a continuous addition of this product employing a chemical-metering pump to maintain a concentration of 32 ppm, based on total weight of water treated. Both slug additions and continuous addition of this product should be made at the heater treater dump, gathering lines, or receiving tanks. Addition should always be made upstream to the filter. This product is also used to inhibit the growth of fungi and bacteria in water-based drilling muds, completion fluids, packer fluids, and other waterbased fluids containing starch, gums, sugars, and other organic materials. For these purposes this product is added at rates of 11.82 to 19.85 gallons per 100 barrels of fluid (0.28 to 0.47% by volume).

This product is used in industrial and/or commercial recirculating cooling tower systems and industrial air-washing systems to control microbiological slime. Prior to the use of this product, in industrial and/or commercial recirculating cooling tower systems, systems should be cleaned to remove algal growth, microbiological slime, and other deposits. Then make an initial slug addition of 9.5 to 14.2 fl. oz. of this product per 1000 gallons of water to provide 80 to 120 ppm of the product, based on the total weight of water in the system. Repeat initial dosage until control is evident. Make subsequent slug additions of 4.7 to 14.2 fl. oz. of this product per 1000 gallons of water (40 to 120 ppm this product) every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug addition should be made in the sump or recirculating cooling tower systems.

This product is used in industrial air-washing systems which maintain effective mist-eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 22.2 to 28.4 fl. oz. of this product per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 16.5 to 28.4 fl. oz. of this product per 1000 gallons of water should be employed every 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or the water collection trays of the airwash system

STORAGE and DISPOSAL: Do not contaminate water, food, or feed by storage or disposal.

STORAGE: Do not expose to extreme temperatures. Do not stack more than four drume high. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use. PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance. CONTAINER DISPOSAL: PLASTIC: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke. METAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

HMIS RATING: Health-2; Flammability-0; Reactivity-1; Personal Protection-B .



Manufactured by: AmSolv Manufacturing Company Marketed by: AmSolv Holding Company • 100 West Sterrett Road • Waxahachie, TX 75165