

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

MAY 19 2004

Mr. Timothy C. Moses
Senior VP
Nova BioGenetics, Inc.
8601 Dunwoody Pl., Suite 338
Atlanta, GA 30350

SUBJECT: BST Protectant RTU 75
EPA Registration Number: 75497-5
Application Dated: April 1, 2004
Receipt Date: April 20, 2004

Dear Mr. Timothy C. Moses:

The following amendment, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA), as amended, is acceptable subject to the conditions listed below.

- Correct name of Active Ingredient as per Agency request

Conditions

In future submissions to the Agency, list all packaging sizes on the Application for Pesticide such that the application is in agreement with the label for this product.

Make the following revisions to the label:

1. As per PR Notice 2001-1 add the following statement to the First Aid section of the label: *"Have the product container or label with you when calling a poison control center or a doctor, or going for treatment."*
2. Add the following clarification in each instance (3 times) that this language appears on your label: *"Polyurethane and cellulose foam for household, industrial and institution sponges and mops"* or simply *"and cellulose"* referring to the foam to be treated in the Approved Residential Use section.

CONCURRENCES

SYMBOL	7510C						
SURNAME	J. J. [Signature]						
DATE	5/19/04						

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

2/12

3. Delete the following surfaces from the Approved commercial applications in homes, offices, automobiles..." as they are not appropriate for these sites:

- "Concrete additive for sewer pipes, manholes..."
- "Concrete additive for repair and renewal of sewer pipes..."
- "Non-woven disposable diapers"
- "Pre-moistened towelettes and tissue wipes..."

4. Revise the bullet on page 9 as follows: "Effective on modern hard non-porous washable surfaces *made of* fiberglass, glazed porcelain..."

5. Revise the Container Disposal statement to read exactly as follows such that the appropriate language is used for metal containers: "Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or *by other procedures approved by state and local authorities.*"

General Comments

A stamped copy of the accepted labeling is enclosed. Submit one (1) copy of your final printed labeling before distributing or selling the product bearing the revised labeling. Should you have any questions concerning this letter, please contact Tracy Lantz at (703) 308-6415.

Sincerely,



Velma Noble
Product Manager (31)
Regulatory Management Branch I
Antimicrobials Division (7510C)

Enclosure: Stamped Label
7510C:T.Lantz:5/17/04:75497-5a

CONCURRENCES

SYMBOL								
SURNAME								
DATE								



BST Protectant RTU 75

MICROBIOSTATIC AGENT*

Active Ingredient:	Octadecylaminodimethyltrihydroxysilyl propyl ammonium chloride.....	0.75%
Other Ingredients:	99.25%
TOTAL		<hr/>
INGREDIENTS:	100.00%

**KEEP OUT OF REACH OF CHILDREN
CAUTION**

Lot No. _____

EPA Reg. No. 75497-5

EPA EST. xxxxx-GA-xx

NET CONTENTS: 2, 4, 8, 16, 20, 22, 32 or 36 fluid oz.; 0.5, 1, 5, 55, 150, 300, or 450 gal.

FIRST AID

IF ON SKIN:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

IF INHALED:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible.
- Call a poison control center or doctor for further treatment advice.

IF IN EYES:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing.
- Call poison control center or doctor for treatment advice.

ACCEPTED
with COMMENTS
in EPA Letter Dated:
MAY 19 2004

IF SWALLOWED:

- Call a poison control center or doctor immediately for treatment advice.
- Have person sip a glass of water if able to swallow.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give anything by mouth to an unconscious person.

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No. 75497-5

3/12

* A microbiostatic agent is an agent that inhibits the growth of odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew), and algae. This product does not protect users or others against food-borne or disease-causing bacteria.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Causes moderate eye irritation. Avoid contact with eyes and skin. Harmful if inhaled or absorbed through the skin. Avoid breathing vapors or spray mist. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS

Commercial and industrial uses: This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

De-activation may be required during clean up if a spill occurs. De-activation of BST Protectant RTU 75 can be achieved by the addition of anionic surfactant (such as soap, sulfonates, sulfates) in quantity equivalent to that of BST Protectant RTU 75.

Residential use: This pesticide is toxic to fish. Do not contaminate water by cleaning of equipment or disposal of pesticide. Do not apply directly to water.

DIRECTIONS FOR USE

Approved commercial and industrial applications

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Wear protective eyewear (goggles or face shield) and gloves when using this product. Dry treated areas and articles such as clothing before use. Remove children and pets from treated area until completely dry.

BST Protectant RTU 75 can be applied to organic or inorganic substrates by brushing, dipping, padding, soaking, spraying, fogging or by using foam finishing techniques.

The substrate can be dried at temperatures from ambient to a maximum of 160° C (320° F) to effect complete condensation of silanol groups and to remove water, solvents and/or traces of methanol from hydrolysis. Optimum application and drying conditions, such as time and temperature, should be determined for each application before use. If necessary, reapply BST Protectant RTU 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.

4/12

BST Protectant RTU 75 when used as a concrete additive is added directly during concrete preparation. Use 40 fluid ounces per cubic feet of concrete. Addition of BST Protectant RTU 75 reduces deterioration of sewer pipes and manholes by inhibiting microbiologically induced corrosion.

Approved commercial and industrial applications

The active ingredient in BST Protectant RTU 75 is effective against odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae as a static agent. BST Protectant RTU 75 can be used as a final bacteriostatic finish on the following items to impart bacteriostatic/fungistatic (mold and mildew) and algaestatic activity.

- Air filters for furnaces, air-conditioners, air purification devices, automobiles, recirculating air handling systems
- Air filters/materials
- Aquarium filter material
- Bed sheets, blankets, and bedspreads
- Buffer pads (abrasive and polishing)
- Carpets and draperies
- Concrete additive for sewer pipes, manholes and concrete sewer structures; not to be used in treatment of storm drains
- Concrete additive for repair and renewal of sewer pipes and manholes and concrete sewer structures; not to be used in treatment of storm drains
- Fiberfill for upholstery, sleeping bags, apparel, where the fiber is cotton, natural down, nylon, polyester, rayon, or wool
- Fiberglass ductboard
- Fire hose fabric
- Humidifier belts
- Mattress pads and ticking
- Men's underwear and outerwear
- Non-woven disposable diapers
- Non-woven polyester
- Outerwear apparel (jackets, sweaters, sweatshirts, coats, raincoats, overcoats, jerseys, ponchos)
- Polyurethane foam for household, industrial, and institutional sponges and mops
- Polyurethane and polyethylene foam, when covered
- Polyurethane foam for packaging and cushioning in non-food contact applications
- Polyurethane foam used as a growth medium for non-food crops and plants
- Pre-moistened towelettes and tissue wipes (these do not impart pesticidal properties)
- Roofing materials - defined as shingles, roofing granules, wood shakes, felt, stone and synthetic overcoats
- Sand bags, tents, tarpaulins, sails, and ropes
- Athletic and casual shoes
- Shoe insoles
- Shower curtains
- Socks comprised of nylon, nylon/orlon, cotton/nylon, linen/Lycra, acrylic/polypropylene/nylon/Lycra, wool/silk/nylon/Lycra and wool/acrylic/nylon/Lycra
- Throw rugs
- Toweling made of 100 percent cotton, 100 percent polyester, and blends of the two fibers
- Toilet tank and seat covers
- Umbrellas

- Upholstery made of acetates, acrylics, cotton, fiberglass, nylon, polyester, polyethylene, polyolefins, polypropylene, rayon, spandex, vinyl, wool
- Vacuum cleaner bags and filters
- Vinyl paper-wallpaper for non-food contact surfaces
- Disposable wiping cloths that can be used for multiple purposes such as dusting or washing furniture, cars, walls, windows, floors, appliances, dishes, counter tops; the wiping cloths do not impart pesticide properties
- Women's hosiery
- Women's intimate apparel

DIRECTIONS FOR USE

**Approved commercial applications in homes, offices, automobiles and institutions
e.g., schools, hospitals, daycare centers, churches, correctional facilities**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Wear protective eyewear (goggles or face shield) and gloves when using this product. Dry treated areas and articles such as clothing before use. Remove children and pets from treated area until completely dry. Clean surfaces prior to application.

The active ingredient in BST Protectant RTU 75 is effective against odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae as a static agent. BST Protectant RTU 75 can be used as a final bacteriostatic finish on the following items to impart bacteriostatic/fungistatic (mold and mildew) and algaestatic activity.

- Air filters for furnaces, air-conditioners, air purification devices, automobiles, recirculating air handling systems
- Air filters/materials
- Aquarium filter material
- Bed sheets, blankets, and bedspreads
- Buffer pads (abrasive and polishing)
- Carpets and draperies
- Concrete additive for sewer pipes, manholes and concrete sewer structures; not to be used in treatment of storm drains
- Concrete additive for repair and renewal of sewer pipes and manholes and concrete sewer structures; not to be used in treatment of storm drains
- Fiberfill for upholstery, sleeping bags, apparel, where the fiber is cotton, natural down, nylon, polyester, rayon, or wool
- Fiberglass ductboard
- Fire hose fabric
- Humidifier belts
- Mattress pads and ticking
- Men's underwear and outerwear
- Non-woven disposable diapers
- Non-woven polyester
- Outerwear apparel (jackets, sweaters, sweatshirts, coats, raincoats, overcoats, jerseys, ponchos)
- Polyurethane foam for household, industrial, and institutional sponges and mops
- Polyurethane and polyethylene foam, when covered
- Polyurethane foam for packaging and cushioning in non-food contact applications
- Polyurethane foam used as a growth medium for non-food crops and plants

- Pre-moistened towelettes and tissue wipes (these do not impart pesticidal properties)
- Roofing materials - defined as shingles, roofing granules, wood shakes, felt, stone and synthetic overcoats
- Sand bags, tents, tarpaulins, sails, and ropes
- Athletic and casual shoes
- Shoe insoles
- Shower curtains
- Socks comprised of nylon, nylon/orlon, cotton/nylon, linen/Lycra, acrylic/polypropylene/nylon/Lycra, wool/silk/nylon/Lycra and wool/acrylic/nylon/Lycra
- Throw rugs
- Toweling made of 100 percent cotton, 100 percent polyester, and blends of the two fibers
- Toilet tank and seat covers
- Umbrellas
- Upholstery made of acetates, acrylics, cotton, fiberglass, nylon, polyester, polyethylene, polyolefins, polypropylene, rayon, spandex, vinyl, wool
- Vacuum cleaner bags and filters
- Vinyl paper-wallpaper for non-food contact surfaces
- Disposable wiping cloths that can be used for multiple purposes such as dusting or washing furniture, cars, walls, windows, floors, appliances, dishes, counter tops; the wiping cloths do not impart pesticide properties
- Women's hosiery
- Women's intimate apparel

For Pump Spray Application: Using pump sprayer, spray entire area 4"- 6" from the surface making sure the surface is completely covered. Apply and then let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. Test for staining and color-fastness of fabrics and carpets by treating and drying a small, concealed area prior to application. One gallon of BST Protectant RTU 75 treats approximately 200 square feet. When treating coarser substrates, more BST Protectant RTU 75 may be required due to absorption. A fan may be used to assist in drying carpeting.

For Commercial Spray Application: For commercial application equipment (*i.e.*, carpet/upholstery steamers, rotary jet extraction cleaners, pressure sprayers) apply and then let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. Test for staining and color-fastness of fabrics and carpets by treating and drying a small, concealed area prior to application. One gallon of BST Protectant RTU 75 treats approximately 200 square feet. When treating coarser substrates, more BST Protectant RTU 75 may be required due to absorption. Dry carpet areas and surfaces before re-entry and dry articles before use. A fan may be used to assist in drying carpeting.

For Dipping/Soaking Application: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough BST Protectant RTU 75 to completely submerge item. Completely submerge item in solution for 3 minutes. Remove item and dry. Test for staining and color-fastness of fabrics by treating and drying a small, concealed area prior to application. Do not reuse solution after dipping/soaking.

The substrate can be dried at room temperatures or at temperatures to a maximum of 160° C (320° F), for example in a clothes dryer. Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply BST Protectant RTU 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.

7/13

DIRECTIONS FOR USE
For residential applications

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Wear protective eyewear (goggles or face shield) and gloves when using this product. Dry treated areas and articles such as clothing before use. Remove children and pets from treated area until completely dry. Clean surfaces prior to application.

Approved residential uses

The active ingredient in BST Protectant RTU 75 is effective against odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae as a static agent.

	Pest controlled	Method of Application
Bedsheets, blankets, bedspreads, curtains, draperies (washable only), underwear, socks, intimate apparel, hosiery, throw rugs, toweling, toilet tank covers, shower curtains, shoe insoles, outerwear apparel (jackets, sweaters, sweatshirts, coats, raincoats, overcoats, jerseys, ponchos). BST Protectant RTU 75 can be applied to fabrics made of acetates, acrylics, cotton, fiberglass, linen, Lycra, nylon, orlon, polyester, polyethylene, polyolefins, polypropylene, rayon, silk, spandex, vinyl, and wool	Odor causing bacteria, bacteria which cause staining and discoloration, and fungi (mold and mildew)	<p>DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough BST Protectant RTU 75 to completely submerge item. Keep item in solution for 3 minutes. Remove item and wring excess liquid. Drying may be attained by dripping dry or wringing excess liquid from treated item. For larger items (e.g., bedspreads, curtains, draperies), place in washing machine on spin cycle to aid in the removal of excess liquid. Test staining and color-fastness of fabric and carpets by treating and drying a small concealed area prior to application. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160 °C (320 °F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply BST Protectant RTU 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, and mildew stains return.</p> <p>SPRAY: Clean surface prior to application. Using a trigger pump sprayer or pressure sprayer, spray the entire surface area 4"-6" from the surface making sure the surface is completely covered. Let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. Test staining and color-fastness of fabric by treating and drying a small concealed area prior to application. If necessary, reapply BST Protectant RTU 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, and mildew stains return.</p>
Air filters and air filter material for <ul style="list-style-type: none"> • Furnaces, air conditioners • Air purification systems • Automobiles • Recirculating air handling systems • Vacuum cleaner filters • Aquariums 	Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew), and algae	<p>SPRAY: When treating filters, remove filter from the unit. Using a trigger pump sprayer or pressure sprayer, spray the entire surface area 4"- 6" from the surface making sure the surface is completely covered. Apply and then let stand until dry. If necessary, reapply BST Protectant RTU 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.</p>

8/12

	Pest controlled	Method of Application
Carpeting	Odor causing bacteria, bacteria which cause staining and discoloration, and fungi (mold and mildew)	SPRAY: Apply to clean carpet surface. Using a trigger pump sprayer or pressure sprayer, spray the entire surface area 4"- 6" from the surface making sure the surface is completely covered. For rotary jet extraction cleaners and carpet steamers, add BST Protectant RTU 75 directly to the cleaning tank, then operate the equipment in accordance with manufacturer's instructions. Apply and then let stand until dry. Test staining and color-fastness of carpets by treating and drying a small concealed area prior to application. BST Protectant RTU 75 treats approximately 200 square feet per gallon (50 square feet per quart). When treating coarser substrates (e.g., wool carpeting), more BST Protectant RTU 75 may be required due to absorption. Dry carpet areas and surfaces before re-entry. A fan may be used to assist in drying carpeting. Remove children and pets from treated area until completely dried. If necessary, reapply BST Protectant RTU 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, and mildew stains return.
Mattress pad and mattress ticking and upholstery composed of acetates, acrylics, cotton, fiberglass, nylon, polyester, polyethylene, polyolefins, polypropylene, rayon, spandex, vinyl, wool; fiberfill to be used in upholstery, sleeping bags, apparel, where the fiber is cotton, natural down, nylon, rayon or wool	Odor causing bacteria, bacteria which cause staining and discoloration, and fungi (mold and mildew)	SPRAY: Clean surfaces prior to application. Using a trigger pump sprayer spray the entire surface area 4"- 6" from the surface making sure the surface is completely covered. Apply and then let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. Test staining and color-fastness of fabric by treating and drying a small concealed area prior to application. When applying to mattress pads and ticking do not soak. Remove children and pets from treated area until completely dried. If necessary, reapply BST Protectant RTU 75 every three months or when odor, staining and discoloration due to bacteria, mold stains and mildew stains return.
Tents, tarpaulins, sails, ropes	Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew), and algae	SPRAY: Clean surface prior to application. Using a trigger pump sprayer or pressure sprayer, spray the entire surface area 4"-6" from the surface making sure the surface is completely covered. Let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. Test staining and color-fastness of fabric by treating and drying a small concealed area prior to application. If necessary, reapply BST Protectant RTU 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough BST Protectant RTU 75 to completely submerge item. Keep item in solution for three minutes. Remove item and

2/16

		wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160 °C (320 °F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply BST Protectant RTU 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.
	Pest controlled	Method of Application
Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats)	Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew), and algae	SPRAY: Make sure the roof is clean prior to application. Using a pressure sprayer, spray the entire surface area 6"-12" from the surface making sure the surface is completely covered. After applying BST Protectant RTU 75, let stand until dry. BST Protectant RTU 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply BST Protectant RTU 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.
	Pest controlled	Method of Application
Buffer pads (polishing and abrasive), Polyurethane for household sponges and mops, vacuum cleaner bags, umbrellas, casual shoes, athletic shoes	Odor causing bacteria, bacteria which cause staining and discoloration, and fungi (mold and mildew)	SPRAY: Clean surface prior to application. Using a trigger pump sprayer or pressure sprayer, spray the entire surface area 4"-6" from the surface making sure the surface is completely covered. Let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. If necessary, reapply BST Protectant RTU 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, and mildew stains return.
	Pest controlled	Method of Application
Tubs, glazed tiles, vanity tops, shower curtains, shower stalls (areas), sinks, washable walls, wall paper for non-food contact, floors, window sills, cabinets, garbage cans, appliances, refrigerators (exterior), fiberglass, formica, glazed tiles, glazed porcelain, synthetic marble, plastic, vinyl	Odor causing bacteria, bacteria which cause staining and discoloration, and fungi (mold and mildew)	SPRAY: Using a trigger pump sprayer, spray the entire surface area 4"- 6" from the surface making sure the surface is completely covered. Let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. If necessary, reapply BST Protectant RTU 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, and mildew stains return.

Imparts microbiostatic properties.

Use on carpet and upholstery to inhibit odor causing bacteria, bacteria which cause staining and discoloration, and fungi (mold and mildew). Unscented.

Use on carpet and upholstery to inhibit the growth of odor causing bacteria.

Use on carpet and upholstery to inhibit the growth of bacteria which cause staining and discoloration.

Use on carpet and upholstery to inhibit the growth of fungi (mold and mildew).

Use on carpet and upholstery to inhibit the growth of odor causing bacteria, bacteria which cause staining and discoloration, and fungi (mold and mildew).

Provides an invisible microbiostatic coating to inhibit the growth of odor causing bacteria.

10/12

Provides an invisible microbiostatic coating to inhibit the growth of bacteria which cause staining and discoloration.

Provides an invisible microbiostatic coating to inhibit the growth of fungi (mold and mildew).

Provides an invisible microbiostatic coating to inhibit the growth of algae.

Provides an invisible microbiostatic coating to inhibit the growth of odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew), and algae.

Prevents deterioration caused by bacteria and fungi (mold and mildew).

Inhibits deterioration caused by bacteria.

Resists development of microbial odors.

Resists development of stains and discoloration due to bacteria.

Resists development of stains due to fungi (mold and mildew).

Resists stains due to algae.

Resists development of microbial odors, stains and discoloration due to bacteria, fungi (mold and mildew), and algae.

Provides/creates an invisible barrier to inhibit the growth of odor causing bacteria.

Provides/creates an invisible barrier to inhibit the growth of bacteria which cause staining and discoloration.

Provides/creates an invisible barrier to inhibit the growth of fungi (mold and mildew).

Provides/creates an invisible barrier to inhibit the growth of algae.

Provides/creates an invisible barrier to inhibit the growth of odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew), and algae.

Inhibits the growth of odor causing bacteria between cleanings.

Inhibits the growth of bacteria which cause staining and discoloration between cleanings.

Inhibits the growth of fungi (mold and mildew) between cleanings.

Inhibits the growth of algae between cleanings.

Inhibits the growth of odor causing bacteria which cause staining and discoloration, fungi (mold and mildew), and algae between cleanings.

Mold, mildew, odor protector and inhibitor.

BST Protectant RTU 75 is an antimicrobial agent effective against odor causing bacteria.

BST Protectant RTU 75 is an antimicrobial agent effective against bacteria which cause staining and discoloration.

BST Protectant RTU 75 is an antimicrobial agent effective against fungi (mold and mildew).

BST Protectant RTU 75 is an antimicrobial agent effective against algae.

BST Protectant RTU 75, an antimicrobial agent, controls the source of odors on surfaces in the home, in the bathroom, in the kitchen.

Bacteriostatic, fungistatic (mold and mildew), algaestatic.

BST Protectant RTU 75, an antimicrobial agent, inhibits smelly odors caused by mold and mildew that can grow even in the cleanest of homes.

BST Protectant RTU 75, an antimicrobial agent, inhibits the growth of odor causing bacteria.

Effective on hard non-porous washable bathroom and kitchen surfaces and fixtures around the home.

Effective on modern hard non-porous washable surfaces like fiberglass, glazed porcelain, Formica®, stainless steel, synthetic marble.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage and disposal.

Pesticide Storage: Store in original, tightly closed containers below 30°C (86°F) and above 0°C (32°F) in a secure area inaccessible to children and away from food or feed.

Pesticide Disposal: Wastes resulting from the use of this product may be disposed of on site. **[residential use]**

Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility. **[commercial/industrial use]**

Container Disposal: Securely wrap original container in several layers of newspaper and discard in trash. **[residential use]**

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke. **[commercial/industrial use]**

FOR MORE INFORMATION CONCERNING THIS PRODUCT, PLEASE CONSULT THE MATERIAL SAFETY DATA SHEET (MSDS). THE MSDS CAN BE OBTAINED BY WRITING NOVA BIOGENETICS, INC. AT 8601 DUNWOODY PL., STE. 338, ATLANTA, GA 30350.

IMPORTANT: WARRANTY AND DISCLAIMER INFORMATION

Nova BioGenetics, Inc., warrants that the product conforms to its chemical description and is reasonably fit for the purposes stated in this bulletin when used in accordance with directions under normal conditions of use; but this warranty of fitness for a particular purpose does not extend to the use of this product contrary to bulletin instructions, or under abnormal conditions, or under conditions not reasonably foreseeable to the seller, and buyer assumes the risk of any such use. NOVA BIOGENETICS SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY, INCLUDING THE WARRANTY OF MERCHANTABILITY.

12/12