



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

July 27, 2023

Tara Conley
Director, Reg Affairs
Electronic Transmittal: tconley@prombiocides.com

Subject: Notification per PRN 98-10 – Added ABN and Updated Company Name on Label
Product Name: Extracide F150
EPA Registration Number: 80285-15
Received Date: 5/23/2023
Action Case Number: 00452382

Dear Tara Conley:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records. The alternate brand name Promex CMT 1.5 has been added to the product record.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) lists examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Assurance.

If you have any questions, you may contact Steven Snyderman at (202) 564-0910 or via email at Snyderman.Steven@epa.gov.

Sincerely,

A handwritten signature in black ink that reads "Steven Snyderman".

Steven Snyderman, Product Manager 33
Regulatory Management Branch II
Antimicrobials Division (7510M)
Office of Pesticide Programs

Enclosure: Stamped Final Label

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: CORROSIVE. CAUSES EYE DAMAGE AND SKIN BURNS. MAY BE FATAL IF ABSORBED THROUGH THE SKIN OR SWALLOWED. MAY CAUSE ALLERGIC SKIN REACTION. HARMFUL IF INHALED. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Wash thoroughly with soap and water after handling and before eating drinking or using tobacco. Remove contaminated clothing and wash before reuse. Avoid breathing vapor or mist.

ENVIRONMENTAL HAZARDS

This chemical is toxic to aquatic plants, fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer system without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label

NOTIFICATION

80285-15

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

07/27/2023

PROMEX™ CMT1.5

Industrial microbiocide for use in Adhesives and Tackifier Preservation, Air Conditioner and Air Refrigeration Condensate Water Systems, Air Washer Systems, Aqueous Compositions*, Brewery Pasteurizer and Can Warmer Systems, Building Material Preservation, Coal Slurry Systems, Commercial Photoprocessing Systems*, Dispersed Pigments*, Electrodeposition Paint Components, Evaporative Condenser Water Systems, Fountain Solutions and Ink/Ink Components*, Hydrostatic Sterilizer Water Systems, Immersion Ultrasonic Tank Water*, In-container Preservation, Industrial Process Water Systems, Industrial Scrubbing Systems, Industrial Wastewater Treatment Systems*, Influent Water Filtration Systems, Laboratory Equipment Water Baths*, Metal Working and Metal Cleaning Fluid Preservation, Oil Field Injection Waters, Paint and Coating Preservation, Paint Spray Booth Systems, Photoplate Processing*, Polymer Latexes, Pulp and Papermills*, Recirculating Closed Loop Water Cooling Systems, Recirculating Electrodeposition Systems, Recirculating Water Cooling Towers, Retort Water Systems, Reverse Osmosis and Ultra Filtration Systems, Recirculating Water Cooling Towers, Retort Water Systems, Reverse Osmosis and Ultra Filtration Systems, Sewage Systems*, Textile Chemicals Preservation*, Water Based Hydraulic Fluid Preservation, and Wood and Wood Products*.

*Not For Use in the State of California

ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one.....	1.2%
2-Methyl-4-isothiazolin-3-one.....	0.4%
OTHER INGREDIENTS	98.4%
TOTAL	100.0%

DANGER

KEEP OUT OF REACH OF CHILDREN

FIRST AID	
IF ON SKIN:	<ul style="list-style-type: none"> • Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15-20 min. • Call a poison control center or doctor for treatment advice.
IF IN EYES:	<ul style="list-style-type: none"> • Hold eye open and rinse slowly and gently with water for 15-20 min. • Remove contact lenses, if present, after first 5 min., then continue rinsing eye. • Call a poison control center or doctor for treatment advice.
IF INHALED:	<ul style="list-style-type: none"> • Move person to fresh air. • If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible. • Call a poison control center or doctor for further treatment advice.
IF SWALLOWED:	<ul style="list-style-type: none"> • Call a poison control center or doctor immediately for treatment advice. • Do not induce vomiting unless told to do so by a poison control center or doctor. • Have person sip a glass of water if able to swallow. Do not give anything to an unconscious person.
Have the product container or label with you when calling a poison control center or doctor, or going for treatment. In case of emergency, call poison control center at 1-800-222-1222 for treatment advice.	
NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be necessary.	

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage, disposal or cleaning of equipment.

PESTICIDE STORAGE

Keep this product in the original container when not in use. Container must be stored and transported in an upright position to prevent spilling the contents.

PESTICIDE DISPOSAL

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER HANDLING

Nonrefillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying. Triple Rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times. Then offer for recycling if available, or reconditioning if appropriate, or puncture and dispose of in a sanitary landfill or by incineration.

EPA Reg. No. **80285-15**

EPA Est. No **81981-SC-001**
 44392-TN-001
 44392-TN-003



Manufactured for:
PromChemie AG
Austrasse 79, P.O. Box 26
FL-9490 Vaduz, Liechtenstein
Telephone (Int'l): +(011) 423-236-1818

NET WEIGHT:	450 lbs
AVG GROSS WT:	469 lbs
AVG. TARE WT:	19 lbs
LOT / BATCH :	



DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

ADHESIVE AND TACKIFIER PRESERVATION

PROMEX CMT 1.5 microbicide is recommended as an in-container preservative for the control of bacteria and fungi in water soluble and water dispersed adhesive such as animal glues, vegetable glues, natural rubber lattices, polyvinyl acetate, styrene-butadiene and acrylic lattices. **PROMEX CMT 1.5** microbicide is recommended as a preservative for tackifiers derived from rosin and hydrocarbon resins. Add 0.43 – 1.65 pounds (195 – 750 grams) of **PROMEX CMT 1.5** to each 1000 pounds (454 kilograms) of fluid to provide 425 – 1675 ppm product.

AIR WASHER SYSTEMS / PAINT SPRAY BOOTHS

For use only in industrial air washing systems that maintain effective mist eliminating components. Add to the air washer sump, chill water sump or paint spray booth to ensure uniform mixing, 35 - 883 ppm **PROMEX CMT 1.5** microbicide (0.3 - 7.46 pounds or 4.5 - 113 fluid ounces of **PROMEX CMT 1.5** per 1000 gallons of water in the system) depending upon the severity of contamination to control microbial biofilms, bacteria, fungi, and algae which cause fouling in industrial air washer systems and paint spray booths. **INTERMITTENT OR SLUG METHOD INITIAL DOSE:** When the system is noticeably fouled, apply 148 - 883 ppm **PROMEX CMT 1.5** microbicide (1.26 - 7.46 pounds or 19 - 113 fluid ounces of **PROMEX CMT 1.5** per 1000 gallons of water in the system.) Repeat until control is achieved. **SUBSEQUENT DOSE:** When microbial control is evident, add 35 - 219 ppm **PROMEX CMT 1.5** microbicide (0.3 - 1.86 pounds or 4.5 - 28 fluid ounces of **PROMEX CMT 1.5** per 1000 gallons of water) in the system weekly or as needed to maintain control. Badly fouled systems should be cleaned before treatment is begun. **CONTINUOUS FEED METHOD INITIAL DOSE:** When the system is noticeably fouled, apply 148 - 883 ppm **PROMEX CMT 1.5** microbicide (1.26 - 7.46 pounds or 19 - 113 fluid ounces of **PROMEX CMT 1.5** per 1000 gallons of water in the system.) **SUBSEQUENT DOSE:** Maintain this treatment level by adding a continuous feed of 35 - 219 ppm **PROMEX CMT 1.5** (0.3 - 1.86 pounds or 4.5 - 28 fluid ounces of **PROMEX CMT 1.5** per 1000 gallons of makeup water). Clean badly fouled systems before treatment is begun.

AQUEOUS COMPOSITIONS *

PROMEX CMT 1.5 microbicide is recommended as an in-container preservative for the control of bacteria and fungi in aqueous products such as: fiberglass sizing solutions and aqueous emulsions and dispersions including surfactants, stabilized oil/water emulsions, surface preparation compounds, foam control products, nutrient solutions and pesticides formulations. Add 0.5 – 3.3 pounds (227 - 1.5 kilograms) of **PROMEX CMT 1.5** per 1000 pounds (454 kilograms) of aqueous product to provide 500 – 3300 ppm product. CONCENTRATES: **PROMEX CMT 1.5** microbicide should be added to concentrates at a level to ensure that the final use dilution of the product will contain 500-300 ppm product.

BUILDING MATERIAL PRESERVATION

PROMEX CMT 1.5 is recommended as an in-container preservative for the control of bacteria and fungi in building materials such as mastics, caulks, joint cements, concrete admixtures, spackling and grouting. Add 0.43 – 1.65 pounds (195 – 750 grams) of **PROMEX CMT 1.5** to each 1000 pounds (454 kilograms) of fluid to provide 425 – 1675 ppm product.

COMMERCIAL PHOTOPROCESSING SYSTEM PRESERVATION *

PROMEX CMT 1.5 microbicide is recommended to prevent microbial slime formation or accumulation in filters and ion exchange resin tanks of commercial photoprocessing system. For the maintenance of a non-fouled system, use at 32 – 64 fluid ounces (2 – 4 pounds) per 1000 gallons fluid in the system once weekly, or as needed to maintain control. This corresponds to 250 -500 ppm of **PROMEX CMT 1.5**. For a noticeably fouled system, use an initial dose of 64 – 148 fluid ounces (4 – 10 pounds) per 1000 gallons fluid to be followed by subsequent maintenance dosage. This corresponds to 500 – 1167 ppm **PROMEX CMT 1.5**. Increased frequency of treatment may be required depending on rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc. The preservative should be dispensed into the final rinse or used water collection tank.

DISPERSED PIGMENT PRESERVATION *

PROMEX CMT 1.5 microbicide is recommended for the control of microbial biofilms, bacteria and fungi in the manufacture and storage of dispersed pigments such as kaolin and montmorillite clays, titanium dioxide, calcium carbonate, calcium sulfate, barium sulfate, magnesium silicate, and kiesegelur used in paint and paper productions. Add 0.43 - 1.65 pounds of **PROMEX CMT 1.5** (195 - 750 grams) to each 1000 pounds (453 kilograms) of fluid to provide 425 to 1675 ppm product (6.25 - 25 ppm active isothiazolones).

IN-CONTAINER PRESERVATION

PROMEX CMT 1.5 microbicide is recommended as an in-container preservative for the control of bacteria and fungi in liquid and semi-solid or solid household consumer, janitorial and industrial products, such as air fresheners, automotive products, fabric softeners, hand cleaners, polishes for floors and furniture, shoe polishes, moist sponges, mops, and towelettes, spray starch, waxes and automotive polishes, hand and automatic dish detergents, stain pretreatment products, liquid laundry detergents and car washes, household cleaners, industrial cleaners, liquid hand soaps, oil and grease removers, carpet cleaners, carpet shampoos and spot removers, waterless hand cleaners, raw materials for cleaning products, surfactants and silicone emulsions. Add 0.4 – 1.5 pounds of **PROMEX CMT 1.5** (180 – 680 grams) to each 1000 pounds (454 kilograms) of product to be treated to provide 400 – 1500 ppm **PROMEX CMT 1.5**. To ensure uniform mixing, slowly disperse **PROMEX CMT 1.5** into product with agitation. **PROMEX CMT 1.5** microbicide may be added to those products formulated as concentrates which are in turn diluted for use at a level to ensure that the final use-dilution product will contain between 400 – 1500 ppm **PROMEX CMT 1.5**. Add 0.4 – 1.5 pounds of **PROMEX CMT 1.5** (180 – 680 grams) per 1000 pounds (454 kilograms) of product to be treated. To ensure uniform distribution, slowly disperse **PROMEX CMT 1.5** into product with agitation. **PROMEX CMT 1.5** microbicide may be added to those products formulated as concentrates which are in turn diluted for use at a level to ensure that the final use-dilution product will contain between 400 – 1500 ppm **PROMEX CMT 1.5**. Add 0.4 – 1.5 pounds of **PROMEX CMT 1.5** (180 – 680 grams) per 1000 pounds (454 kilograms) of product with agitation. Mix thoroughly until evenly dispersed throughout product. Wet wipes containing a solution preserved with this product may not be used for personal care, as baby wipes, or for food contact.

INDUSTRIAL RECIRCULATING CLOSED LOOP WATER COOLING SYSTEMS

To maintain control of microbial slimes, bacteria, fungi and algae, add **PROMEX CMT 1.5** microbicide to the reservoir, recirculating line or some other point to ensure uniform mixing. **INITIAL DOSE:** When the system is noticeably fouled, apply 148 - 883 ppm **PROMEX CMT 1.5** microbicide (1.26 - 7.46 pounds or 19 - 113 fluid ounces of **PROMEX CMT 1.5** per 1000 gallons of water in the system). Repeat until control is achieved. Clean badly fouled systems before treatment is begun. **SUBSEQUENT DOSE:** When microbial control is evident, add 35 - 219 ppm **PROMEX CMT 1.5** microbicide (0.3 - 1.86 pounds or 4.5 - 28 fluid ounces of **PROMEX CMT 1.5** per 1000 gallons of water in the system) weekly or as needed to maintain control.

INDUSTRIAL RECIRCULATING WATER COOLING TOWERS

For the control of microbial slimes, bacteria, algae, and fungi add **PROMEX CMT 1.5** microbicide to the tower basin, distribution box, or some other point to ensure uniform mixing. **INITIAL DOSE:** When the system is noticeably fouled, apply 148 - 883 ppm **PROMEX CMT 1.5** microbicide (1.26 - 7.46 pounds or 19 - 113 fluid ounces of **PROMEX CMT 1.5** per 1000 gallons of water in the system). Repeat until control is achieved. Clean badly fouled systems before treatment is begun. **SUBSEQUENT DOSE:** When microbial control is evident, add 35 - 219 ppm **PROMEX CMT 1.5** microbicide (0.3 - 1.86 pounds or 4.5 - 28 fluid ounces of **PROMEX CMT 1.5** per 1000 gallons of water in the system) weekly or as needed to maintain control.

INDUSTRIAL WASTEWATER TREATMENT SYSTEMS AND SEWAGE SYSTEMS *

PROMEX CMT 1.5 microbicide is recommended for the control of microbial biofilms, bacteria, fungi, and algae in industrial wastewater treatment and sewage systems. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. **INITIAL DOSE:** When the system is noticeably fouled, apply 148 - 883 ppm **PROMEX CMT 1.5** microbicide (1.26 - 7.46 pounds or 19 – 113 fluid ounces of **PROMEX CMT 1.5** per 1000 gallons of water in the system.) Repeat until control is achieved. Clean badly fouled systems before treatment is begun. **SUBSEQUENT DOSE:** When microbial control is evident, add 35 - 219 ppm **PROMEX CMT 1.5** microbicide (0.3 - 1.86 pounds or 4.5 - 28 fluid ounces of **PROMEX CMT 1.5** per 1000 gallons of water in the system) weekly or as needed to maintain control.

METAL CLEANING FLUID PRESERVATION

PROMEX CMT 1.5 microbicide is recommended as a preservative for use in the manufacture and use of alkaline, acid, and emulsion-based metal cleaning fluids typically used in electroplating, phosphating, galvanizing and general metal cleaning operations. For addition to a metal cleaning concentrate, add **PROMEX CMT 1.5** at a level to ensure that the final use-dilution fluid will contain 425 - 1675 ppm product. For direct addition to a fouled system, add 54 - 214 fluid ounces (3.6 - 14.1 pounds) of **PROMEX CMT 1.5** to each 1000 gallons of use-dilution metal cleaning fluid every 3 to 4 weeks to provide 425 - 1675 ppm product. A higher dosage range and/or increased frequency of treatment may be required depending upon rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc. The preservative should be dispensed as an additive into the circulating use-dilution metal cleaning fluid using a metering pump or by manual pouring and uniformly dispersed throughout the system.

OIL FIELD INJECTION WATERS:

For the control of microbial biofilm-forming and sulfate-reducing bacteria in oil and gas field water systems, including enhanced recovery injection fluids, drilling, fracturing and completion fluids, slug treat with 67 - 332 ppm **PROMEX CMT 1.5** microbicide depending on the severity of contamination. **INITIAL DOSE:** Add 166 - 332 ppm **PROMEX CMT 1.5** (6.9 - 13.9 gallons or 58.0 - 116.8 pounds **PROMEX CMT 1.5** per 1000 barrels of water) at a point in the system where it will be uniformly mixed. Repeat treatment after three days or as needed until control is achieved. **SUBSEQUENT DOSE:** Add 67 - 166 ppm **PROMEX CMT 1.5** (2.8 - 6.9 gallons or 23.5 - 58.0 pounds **PROMEX CMT 1.5** per 1000 barrels of water) every seven days or as needed to maintain control.

PAINT AND COATING PRESERVATION

PROMEX CMT 1.5 microbicide is recommended as an in container preservative for the control of bacteria and fungi in water-based coatings such as paper and wood coatings and paints used for architectural product finishes and special purpose coatings. Add 0.43 - 1.65 pounds (195 - 750 grams) of **PROMEX CMT 1.5** to each 1000 pounds (454 kilograms) of fluid to provide 425 - 1675 ppm product.

PHOTOPLATE PROCESSING, FOUNTAIN SOLUTIONS AND INK/INK COMPONENTS *

PROMEX CMT 1.5 microbicide is recommended for the control of bacteria and fungi in photoplate processing chemicals, fountain solutions, and printing inks and ink components. **PROMEX CMT 1.5** should be added to achieve 0.1% to 0.3% on a total weight basis. **PROMEX CMT 1.5** should be added to fountain solution concentrates at a level to ensure that the final use-dilution of the product will contain 0.1% to 0.3% **PROMEX CMT 1.5** on a total weight basis. To ensure uniform mixing, add **PROMEX CMT 1.5** to the product slowly with agitation. The actual concentration required will depend upon the specific substance to be treated, frequency of repeated microbial contamination expected and level of protection required.

POLYMER LATEX PRESERVATION *

PROMEX CMT 1.5 microbicide is recommended for the control of bacteria and fungi in the manufacture and storage of synthetic and natural polymer lattices including: acrylic, styrene/butadiene, carboxylated styrene/butadiene, ethylene/vinyl acetate; biopolymers intended for industrial use, such as a xanthum gum, gum arabic, guar gum, protein-derived polymers, starches, casein-derived polymers lattices; and solution polymers. Add 0.43 - 3.3 pounds of **PROMEX CMT 1.5** (195 grams - 1.5 kilograms) to each 1000 pounds (453 kilograms) of emulsion to provide 425 - 3350 ppm product (6.25 - 50 ppm active isothiazolones). **NOTE:** To ensure uniform mixing, add **PROMEX CMT 1.5** to latex or solutions slowly with agitation. The actual required concentrations will depend upon such factors as the specific substance to be treated, frequency of repeated microbial contamination expected, and level of production required.

PULP AND PAPER MILLS *

For the control of microbial biofilms, bacteria, algae and fungi, add **PROMEX CMT 1.5** microbicide to the Beater, Hydropulper, or Fan or Brake Storage Pumps or some other point in the system to ensure uniform mixing. Apply 0.44 to 1.5 lb (7 - 23 fluid ounces) of **PROMEX CMT 1.5** microbicide per ton (dry basis) of pulp or paper produced as a slug dose. If needed, repeat daily. Clean badly fouled systems before initial treatment.

RECIRCULATING ELECTRODEPOSITION SYSTEMS METHOD OF ADDITION:

PROMEX CMT 1.5 microbicide is recommended as a tankside additive for the control of microbial biofilms, bacteria, fungi, and algae in recirculating electrodeposition systems and associated rinse systems. Alternatively, **PROMEX CMT 1.5** microbicide may be added through the components of the electrodeposition paint prior to their addition to the electrodeposition system. **TANK SIDE ADDITION TO ELECTRODEPOSITION SYSTEMS:**

PROMEX CMT 1.5 microbicide should be dispensed into the recirculating rinse system, ultrafilter permeate, or final distilled rinse system at a point to ensure uniform mixing. **INITIAL DOSE:** When the system is noticeably fouled, add 667 - 2333 ppm **PROMEX CMT 1.5** microbicide (6.7 - 23.3 gallons per 10,000 gallons of fluid in the system). This will provide 10 - 35 ppm of active ingredient. Repeat until control is achieved. **SUBSEQUENT DOSE:** When microbial control is evident, add 333 - 1000 ppm **PROMEX CMT 1.5** microbicide (3.3 - 10 gallons per 10,000 gallons of fluid in the system). This will provide 5 - 15 ppm of active ingredient. A change of frequency of treatment may be required depending upon the rate of dilution of the preservative with the makeup fluid, the nature and severity of contamination level of control required, filtration effectiveness and system design.

TREATMENT OF ELECTRODEPOSITION PAINT COMPONENTS: INITIAL DOSE OF PAINT COMPONENTS:

PROMEX CMT 1.5 microbicide should be added to the resin, pigment, or other component of the electrodeposition paint at a level to ensure that the final use-dilution fluid will contain 333 - 2333 ppm product (5 - 35 ppm active ingredient).

SUPPLEMENTAL TANKSIDE DOSING OF ELECTRODEPOSITION SYSTEMS:

If additional microbial control is necessary, **PROMEX CMT 1.5** microbicide may be added to the electrodeposition system tankside to supplement microbicide incorporated through paint components. **INITIAL DOSE:** If the system becomes noticeably fouled, add 667 - 2333 ppm **PROMEX CMT 1.5** microbicide (6.7 - 23.3 gallons per 10,000 gallons of fluid in the system). This will provide 10 - 35 ppm of active ingredient. Repeat until control is achieved. **SUBSEQUENT DOSE:** When microbial control is evident, add 333 - 1000 ppm **PROMEX CMT 1.5** microbicide (3.3 - 10 gallons per 10,000 gallons of fluid in the system) weekly or as needed. This will provide 5 - 15 ppm of active ingredient. **NOTE:** Regardless of the manner of incorporation, the total active ingredient level in the system should at no time exceed 35 ppm (equivalent to 2333 ppm **PROMEX CMT 1.5** microbicide or 23.3 gallons per 10,000 gallons system fluid).

TEXTILE CHEMICALS PRESERVATION *

Use **PROMEX CMT 1.5** microbicide for the control of bacteria and fungi in the manufacture and storage of textile processing chemicals such as fiber lubricants, spin finishes, sizes, dyestuffs, textile printing inks, dispersants, thickeners, dye fixatives, hand builders and weighters. These textile processing chemicals are commonly used in the production of natural and synthetic fibers and fabrics. Add 0.4 - 1.67 pounds (181 - 757 grams) of **PROMEX CMT 1.5** to each 1000 pounds (454 kilograms) of fluid to provide 400 - 1667 ppm product.

ULTRA FILTRATION UNITS AND NON-MEDICAL/NON-POTABLE REVERSE OSMOSIS SYSTEMS: \

PROMEX CMT 1.5 Microbicide is recommended for the control of microbial biofilms, bacteria and fungi in ultra filtration units and nonmedical/non-potable reverse osmosis systems. Use of **PROMEX CMT 1.5** microbicide in potable water or dialysis is prohibited. Add 10 - 333 ppm of **PROMEX CMT 1.5** microbicide (0.15 - 5 ppm active ingredient) into industrial ultra filtration or reverse osmosis systems by either continuous feed or periodic injection. Compatibility of **PROMEX CMT 1.5** microbicide with reverse osmosis membranes should be confirmed with membrane manufacturers. For the control of bacteria and fungi in carbon beds, add 10 - 333 ppm of **PROMEX CMT 1.5** microbicide (0.15 - 5 ppm active ingredient) by either continuous or batch feed. For periodic membrane cleaning, add 0.4 - 1.0 lb. of **PROMEX CMT 1.5** microbicide to every 120 gallons of cleaning solution (6 - 15 ppm active ingredient). Clean badly fouled systems before treatment is begun.

WATER BASED HYDRAULIC FLUID PRESERVATION

PROMEX CMT 1.5 microbicide is recommended as a preservative for use in the manufacture and use of high water-based hydraulic fluids and invert emulsion hydraulic fluids typically prepared by emulsifying 40% by volume water in 60% by volume of mineral oil using an oil soluble emulsifying agent. For the maintenance of a non-fouled system, use **PROMEX CMT 1.5** at 110 - 135 fluid ounces (7.2 - 8.8 pounds) per 1000 gallons fluid every 8 weeks. This corresponds to 980 - 1200 ppm product. For a noticeably fouled system, use an initial dose of 135 - 235 fluid ounces (8.8 - 15.4 pounds) per 1000 gallons fluid to be followed by subsequent maintenance dosage. This corresponds to 1200 - 2100 ppm product. Increased frequency of treatment may be required depending upon rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc. The preservative should be dispensed as an additive into the circulating use-dilution of the hydraulic fluid using a metering pump or by manual pouring and uniformly dispersed throughout the system.

WOOD AND WOOD PRODUCTS:

PROMEX CMT 1.5 microbicide is recommended for the protection of wood and wood products, such as landscape timbers, fences, posts, pilings, cross ties, decks, and similar exterior structures from mold and mildew. Treat southern yellow pine, hemlock, ponderosa pine, and other soft woods with 148 - 1000 ppm **PROMEX CMT 1.5** (1.26 - 8.4 pounds or 13 - 128 fluid ounces of **PROMEX CMT 1.5** per 1000 gallons) as an aqueous dip or pressure treatment for mold and mildew control. Thoroughly wet and allow to dry. A single application will afford protection for 12 weeks.

WATER SYSTEMS

For the control of microbial slimes, bacteria, fungi and algae, add **PROMEX CMT 1.5** microbicide to air conditioner/refrigeration condensate water systems, can warmers, coal slurry systems, evaporative condenser water systems, hydrostatic sterilizer water systems, immersion ultrasonic tank water[*], industrial scrubbing systems, influent water filtration systems, laboratory equipment water baths[*], brewery pasteurizers, retort water systems, and industrial process water systems. Add **PROMEX CMT 1.5** microbicide at some point in the system to ensure uniform mixing. **INITIAL DOSE:** When the system is noticeably fouled, apply 148 - 883 ppm **PROMEX CMT 1.5** microbicide (1.26 - 7.46 pounds or 19 - 113 fluid ounces of **PROMEX CMT 1.5** per 1000 gallons of water in the system). Repeat until control is achieved. Clean badly fouled systems before treatment is begun. **SUBSEQUENT DOSE:** When microbial control is evident, add 35 - 219 ppm **PROMEX CMT 1.5** microbicide (0.3 - 1.86 pounds or 4.5 - 28 fluid ounces of **PROMEX CMT 1.5** per 1000 gallons of water in the system) weekly or as needed to maintain control.

WOOD AND WOOD PRODUCTS*

PROMEX CMT 1.5 microbicide is recommended for the protection of wood and wood products, such as landscape timbers, fences, posts, pilings, cross ties, decks, and similar exterior structures from mold and mildew. Treat southern yellow pine, hemlock, ponderosa pine, and other soft woods with 148 - 1000 ppm **PROMEX CMT 1.5** (1.26 - 8.4 pounds or 13 - 128 fluid ounces of **PROMEX CMT 1.5** per 1000 gallons) as an aqueous dip or pressure treatment for mold and mildew control. Thoroughly wet and allow to dry. A single application will afford protection for 12 weeks.

*Not For Use in the State of California

CONDITIONS OF SALE AND WARRANTY - PROMCHEMIE AG warrants that this product conforms to its chemical description and is reasonably fit for the purpose stated on the label only when used in accordance with label directions as defined under the Directions for Use on this label. **PROMCHEMIE AG** makes no other express or implied warranties, either of merchantability or fitness, for a particular use. Handling, storage, and use of the product by Buyer or User are beyond the control of **PROMCHEMIE AG** and Seller. Risks such as ineffectiveness or other unintended consequences resulting from, but not limited to, failure to follow directions will be assumed by the Buyer or User. To the extent permitted by law, neither **PROMCHEMIE AG** nor seller shall be liable for consequential, special, or indirect damages resulting from the use, handling, application, storage, or disposal of this product.
