

82971-1

5/11/2009

lof6



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, D.C. 20460

OFFICE OF
PREVENTION, PESTICIDES AND
TOXIC SUBSTANCES

Mr. Eric Knipe
President
Princestone Corporation
9663 Santa Monica Blvd, #587
Beverly Hills, CA 90210

MAY 1 2009

RE: Notification of Primary Brand Name Change: C60 Professional™
EPA Reg. Number: 82971-1
Date of Submission: February 4, 2009

Dear Mr. Knipe:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 dated February 4, 2009, for the product, Bludwater. The Registration Division (RD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the actions requested fall within the scope of PRN 98-10. The label submitted with the application has been stamped "Notification" and will be placed in our records.

If you have any questions, please call me directly at 703-305-6249 or Joyce Edwards of my staff at 703-308-5479.

Sincerely,

A handwritten signature in black ink, appearing to read "Linda Arrington".

Linda Arrington
Notifications & Minor Formulations Team Leader
Registration Division (7505P)
Office of Pesticide Programs



United States
Environmental Protection Agency
Washington, DC 20460

Registration
Amendment ☐
Other ☒

Case Number

Application for Pesticide - Section I

1. Company/Product Number 82971-1	2. EPA Product Name: Richard Gethen or Adam Heyward	3. Proposed Classification <input checked="" type="checkbox"/> New <input type="checkbox"/> Reregulated
4. Company/Product Name CSO Professional	5. Name and Address of Applicant (Include ZIP Code) Princeton Corp. 9063 Santa Monica Blvd, 4587 Beverly Hills, CA 90210	6. Expected Review. In accordance with 40 CFR 152.10, my product is similar or identical in composition and labeling to: EPA Reg. No. 82971-1 MAY 01 2009
<input checked="" type="checkbox"/> Check if sale is a new address Product Name: Silverwater		

Section - II

<input type="checkbox"/> Amendment - English below. <input type="checkbox"/> Reevaluation in response to Agency letter dated ____ <input checked="" type="checkbox"/> Reevaluation - English below.	<input type="checkbox"/> Final product label in response to Agency letter dated ____ <input type="checkbox"/> "No Tor" Application. <input type="checkbox"/> Other - English below.
---	--

Explanation: Use additional pages if necessary. (For section I and Section II.)

Notification of Primary Brand Name per Notice 98-10. This notification is consistent with the provisions of PR Notice 98-10 and EPA regulations at 40 CFR 152.46 and no other changes have been made to the labeling or the confidential statement of formula of this product. I understand that it is a violation of 18 U.S.C. Sec. 1001 (see Page 2).

Section - III

1. Should this Product Will be Produced by:			
Cash/Reseller Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Other Suitable Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	
* Certification must be submitted <input type="checkbox"/> Yes <input type="checkbox"/> No	Unit Packaging w/o. <input type="checkbox"/> Yes <input type="checkbox"/> No	No. per container <input type="checkbox"/> Yes <input type="checkbox"/> No	No. per container <input type="checkbox"/> Yes <input type="checkbox"/> No
1. Location of this Company's Information <input type="checkbox"/> Label <input type="checkbox"/> Container	2. Status of this Certification <input type="checkbox"/> New <input type="checkbox"/> Amendment		3. Location of Label Directions <input type="checkbox"/> On Label <input type="checkbox"/> On Labeling accompanying product
4. Material in Which Label is Affixed to Product <input type="checkbox"/> Other _____			

Section - IV

1. Contact Point: (Provide name, company, address, telephone, fax, e-mail, or other means of communication, if necessary, to provide this information.)		2. Type of Container	
Eric Knipe		<input type="checkbox"/> Metal <input type="checkbox"/> Plastic <input type="checkbox"/> Glass <input type="checkbox"/> Paper <input type="checkbox"/> Other (Specify) _____	
3. Certification: (Provide name, company, address, telephone, fax, e-mail, or other means of communication, if necessary, to provide this information.)		4. Date Application Received (Specify)	
Eric Knipe		February 4, 2009	
5. Signature: (Provide name, company, address, telephone, fax, e-mail, or other means of communication, if necessary, to provide this information.)		6. Date	
Eric Knipe		February 4, 2009	

Do not leave this form blank. Provide address and telephone.

Name: Eric Knipe, Jr.

Address: Applicant Corp.

C & E, Inc.
9601 Wilshire Blvd,
Suite 620
Beverly Hills, CA 90210

(310) 383-3240
(310) 383-0055
evknipe@gmail.com

February 9, 2009

Via Facsimile: (703) 305-7670
and U.S. Express Mail

Ms. Kathleen O'Malley
U.S. Environmental Protection Agency
Document Processing Desk (NEWCO)
Office of Pesticide Programs
Room S4900, One Potomac Yard
2777 Crystal Drive
Arlington, VA 22202

RE: Registration Numbers: Request for Company Name Change and Product Name Change
82971-1 Bluewater
(New Name: C60 PROFESSIONAL™)

Dear Ms. O'Malley:

This letter is to replace the letter I sent to Adrienne Turner (Document Processing Desk (NEWCO) dated February 4, 2009. Regarding the above captioned registration numbers, this is to notify you that the corporate name of C & E, Inc. has been changed to Princetone Corp. and remains under the same ownership of Eric Knipe (aka Eric Von Knipe) and there is no asset change. The product name Bluewater has been changed to C60 PROFESSIONAL™.

The new address for Princetone Corp. is as follows:


New Corporate Name:	Princetone Corp.
Corporate Contacts:	Eric Knipe (aka Eric von Knipe)
Contact Phone Number:	(310) 383-0055
Contact Email Addresses:	evknipe@gmail.com
Official Mailing Address:	Princetone Corp. 9663 Santa Monica Blvd., #587 Beverly Hills, CA 90210

The old address was:	C & E, Inc.
	9601 Wilshire Blvd., Suite 620
	Beverly Hills, CA 90210

Effective Date:	February 9, 2009
-----------------	------------------

4 of 6

Section II (cont.)



Date : February 4, 2009

C C C C C C
 C C C C C C
 C C C C C C
 C C C C C C
 C C C C C C
 C C C C C C

C60 PROFESSIONAL™
Wood Preservative/Mold Control

For the preservation, protection and preventative treatment of wood against decay fungi *mold* and wood-destroying insects and for remedial control of such pests in infested wood.

Active Ingredient:
Disodium Octaborate Tetrahydrate 10% (12% BAE)*
(Na₂B₈O₁₃·4H₂O)
Inert ingredients 90%

* 10% Disodium Octaborate Tetrahydrate active ingredient is equivalent to 12% Boric acid, Acid Equivalents-BAE

Keep out of reach of children

CAUTION

FIRST AID

IF SWALLOWED:

- Call a poison control center or doctor immediately for treatment advice.
- Have person sip a glass of water if able to swallow.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give anything by mouth to an unconscious person.

IF IN EYES:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

IF ON SKIN OR CLOTHING:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

IF INHALED:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for treatment advice.

Have the product container or label with you when calling a poison center or doctor, or going for treatment.

Precautionary statements:

Caution

Hazards to humans and domestic animals

Harmful if swallowed. Avoid contact with eyes. Wash thoroughly after handling. Avoid contamination of food and feed. Do not leave container where children or animals may gain access.

PERSONAL PROTECTIVE EQUIPMENT: Applicators and other handlers must wear a long-sleeved shirt and long pants which cover the entire arm and leg skin surface, socks, water-resistant boots, chemical resistant gloves and chemical resistant protective eyewear – splash goggles are recommended. When applying this product in confined spaces such as crawl spaces and attic, a ventilation exhaust system is recommended. If this is impractical, the use of a NIOSH approved respirator designed for dusts/mists is recommended. Clean spills and over-spray with a clean damp cloth or use an absorbent. Dispose of spill as required by state guidelines and laws.

EPA Reg. No.
EPA Est.

82971-
82971

Net contents _____ Gallons

Manufactured by:

Princetone Corp.
9663 Santa Monica Blvd, #587
Beverly Hills, CA 90210

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

Storage: Store in a dry place. Do not store where children or animals may gain access.

Pesticide disposal: Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

Container disposal: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or if allowed by state and local authorities, by burning. If burned, stay out of smoke.

Environmental hazards

C60 PROFESSIONAL™ solutions carelessly spilled or applied to cropland or growing plants, including trees and shrubs, may kill or seriously retard plant growth. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

Target organisms

C60 PROFESSIONAL™ is an effective treatment for wood against decay, fungi, common molds including brown (i.e. Poria), white, and wet rots.

Preparation of treatment solution

C60 PROFESSIONAL™ is a ready-to-use solution that can be applied without any preparation of the solution.

If using as a foam: Simply add a surfactant/foaming agent to the solution. Typically 1-2 ounces of foaming agent added to the aqueous solution will produce foam with the desired expansion ratios of approximately 20 to 1 (approx. 20 gallons of foam per 1 gallon of C60 PROFESSIONAL™ aqueous solution). C60 PROFESSIONAL™ foam should be of a consistency that adheres to wood surfaces, so that run-off is minimized. Since each foam machine can produce different foams, refer to the manufacturer manuals and the surfactant's label for specific instructions.

NOTIFICATION

MAY 01 2009

Directions for use

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

General Information

C60 PROFESSIONAL™ is a ready-to-use solution with fungicidal/fungistatic properties. This product cannot be tank mixed with other products. This product will protect only treated wood and gypsum facing.

This product can be used in coatings to treat all interior and exterior wood structural components which when utilized will be protected from rain and not in direct contact with the ground. The treatment of lumber is permanent even after cutting and finishing providing the wood is not exposed to water for a prolonged period of time or in contact with the ground.

This product can be used for preventative treatment of wood in existing structures (before signs of infestation), for pre-treatment of wood during construction and for remedial treatment of wood infested with mold and fungus, as listed below.

C60 PROFESSIONAL™ is recommended for wood and cellulose materials, in accordance with the specific treatment methods described herein. This product should be applied only to treat bare wood, plywood and particle board where an intact water repellent barrier such as paint, stain or a sealer is not present. **Do not apply to foam-board.**

C60 PROFESSIONAL™ is effective for all interior and exterior wood that will be protected from excessive rain and not in direct contact with soil. Types of wood include, but are not limited to, all types of lumber, logs and plywood. **Use of this product does not substitute for mechanical alteration, soil treatment or foundation treatment, but is merely a supplement.**

This product is toxic to wood-destroying molds and fungi, but surface etching of treated wood by target organisms may occur. Application of **C60 PROFESSIONAL™** to control wood-destroying organisms must be part of an Integrated Pest Management (IPM) strategy. Current Princestone Corp. specifications and technical bulletins must be followed for all treatment methods.

Do not use to treat lumber that will contact soil or be exposed to leaching by weather.

Application

C60 PROFESSIONAL™ may be used as a solution or foam. For remedial control of mold, fungi and common molds attacking wood, or for protection of wood against future infestations, 2 applications of the **C60 PROFESSIONAL™** aqueous solution are normally required.

Solutions

Apply solutions by brush or spray until the wood surface is thoroughly wet, at a rate of approximately 1 gallon per 200 square feet of wood surface area. Spray evenly using a medium or coarse spray at low pressure (20-30 psi). Best results and penetration will be obtained when ambient temperatures are above 55°F. Do not spray frozen wood, painted or waterproofed surfaces.

Foam

Apply foam so that all accessible wood surfaces are covered with foam at a rate of approximately 1 gallon per 200 square feet of wood surface area. Spray evenly using a medium or coarse spray at low pressure (20-30 psi). Where possible, place foam between wood joints or abutting wood surfaces. In wall voids, inject enough foam to contact drywall and wood surfaces of studs in the wall or the target area desired. Best results and penetration will be obtained when ambient temperatures are above 55°F. Do not foam frozen wood, painted or waterproofed surfaces.

Pressure processes

Pressure treatment procedures must rigidly adhere to the standards of Mold Free, Inc. and/or those of the American Wood Preservers' Association. If several species are being treated at once, choose the treating schedule for the most difficult to treat species.

Preventative treatment

Application of **C60 PROFESSIONAL™** solution and foam will prevent infestation of mold and fungus.

Current Princestone Corp. specifications/technical bulletins should be followed for all treatment methods to ensure adequate chemical loadings in wood.

Notice Because of many varying conditions affecting use and application, manufacturer warns buyer that these may impair or vary the results or effects of the use of this product. In any event, complete prevention of decay by fungi or other organisms is not guaranteed. Neither manufacturer nor seller shall be liable in respect to any injury or damages suffered by reason of the use of this product for a purpose not indicated by the label, or when used contrary to the directions or instructions hereon, nor with respect to breach of any warranty not expressly specified herein. Buyer accepts this material subject to these terms, and assumes all risk of usage and handling except when used or handled in accordance with this label. There are no express warranties on *Princestone Corp.* or implied warranties of merchantability or fitness for any particular purpose, except as specifically stated herein. Manufacturer shall not be liable for any consequential damages based on the use of this product.

Directions for use continued

Drilling and injecting

Application may also be by drilling and then injecting the solution or foam under pressure into sound wood or until runoff is observed from entry/exit holes of infested wood. Injection holes (approximately 1/8 inch diameter) should be drilled in the area of suspected infestation, preferably in a diamond pattern with the long axis (12-16 inches) along the grain and the short axis (4-6 inches) across. Drill holes approximately 3/4 of the thickness of the beam. The solution is injected under pressure (65-70 psi) for 15-60 seconds in each hole. Please refer to Princestone Corp. technical bulletin for further details.

Remedial treatment

C60 PROFESSIONAL™ solution and foam will penetrate dry wood down to 1/2 inch below treated surfaces.

Attics, crawlspaces and basements

Spray **C60 PROFESSIONAL™** to all accessible wood: rafters, trusses, top-plates, ceiling joists, plywood, particleboard, flooring, sub-floor etc. This application will control an infestation even when certain parts of the gallery are not directly sprayed. This has been a very effective technique in spot treating for control of mold and fungus.

Pre-treatment to wood – new construction

Spray or foam applications of **C60 PROFESSIONAL™** may also be made to wood during construction. Apply solution to all accessible surfaces of bare wood at a rate of approximately 1 gallon per 200 square feet of wood surface area. Application should be performed after framing and roofing are in place and before drywall and insulation are installed. Avoid spraying electrical components. Protect wood from excessive rain.

Exterior wood

C60 PROFESSIONAL™ can be applied to bare siding, trim or logs. Applications can be made by spray or pressure injection techniques. Painted or sealed wood can be treated by pressure injection or the sealing coat can be removed prior to application. Following treatment, exterior wood surfaces should be sealed. Wood should be completely dry before a sealing coat (paint, varnish or waterproofing seal) can be applied.

Decks

C60 PROFESSIONAL™ can be used to treat wood decks. Prepare the deck by removing any dirt, debris or sealants that will interfere with the application and absorption of **C60 PROFESSIONAL™**. After the deck has dried (dry to the touch) two applications of **C60 PROFESSIONAL™** can then be applied to the wood. Protect any surrounding plants, ornaments from accidental contact with the solution. Following treatment the deck should be allowed to dry before a sealing coat is applied.

C60 PROFESSIONAL™ is FOR NON-FOOD USE ONLY.

This product cannot be tank mixed with other products. In the home, remove or cover exposed food, food handling surfaces, and cooking utensils. Wash thoroughly after treatment and before reuse.

Do not use in any type of food processing plant (meat, poultry, shell egg, etc.) or food handling area. **DO NOT APPLY TO FOOD.** Do not use in cafeterias, kitchens, bakeries, meat packing plants, food processing plants, or any type of food handling establishment.

Do not apply in classrooms when in use. Do not use in aircraft cabins. Do not apply to patient rooms in hospitals and nursing homes while occupied.

Such applications are not a substitute for mechanical alteration, soil treatment or foundation treatment but are merely a supplement.

When spraying overhead interior areas of homes, apartment buildings and all other dwellings, cover or protect surfaces below the area being treated with plastic sheeting or other material which can be disposed of if contamination from dripping or splashing occurs.

NOTIFICATION

MAY 01 2009