



U.S. ENVIRONMENTAL PROTECTION AGENCY

Office of Pesticide Programs
Antimicrobials Division (7510P)
1200 Pennsylvania Ave., N.W.
Washington, D.C. 20460

EPA Reg. Number:

87857-5

Date of Issuance:

11/20/25

NOTICE OF PESTICIDE:

☒ Registration
☐ Reregistration
(under FIFRA, as amended)

Term of Issuance:

Conditional

Name of Pesticide Product:

Extracide F1.5

Name and Address of Registrant (include ZIP Code):

Ivy Zhang, Regulatory Director
Agent for Dalian Bio-Chem Company Limited
c/o REACH24H USA INC.
11921 Freedom Drive, Suite 550,
Reston, VA 20190 USA
Electronic Transmittal: pesticideapp@reach24h.com

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Antimicrobials Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA).

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA section 3(c)(7)(A). You must comply with the following conditions:

1. Submit and/or cite all data required for registration/reregistration/registration review of your product under FIFRA when the Agency requires all registrants of similar products to submit such data.

Signature of Approving Official:

Steven Snyderman, Product Manager 33
Regulatory management Branch II
Antimicrobials Division (7510M)
Office of Pesticide Programs

Date:

11/20/25

2. You are required to comply with the data requirements described in the DCI identified below:

- a. 5-Chloro-2-methyl-4-isothiazolin-3-one: GDCI-107103-1709
- b. 2-Methyl-4-isothiazolin-3-one: GDCI-107104-1479

You must comply with all of the data requirements within the established deadlines. If you have questions about the Generic DCI listed above, you may contact the Reevaluation Team Leader (Team 36): <https://www.epa.gov/pesticide-contacts/contacts-office-pesticide-programs-antimicrobials-division>

3. Make the following label changes before you release the product for shipment:

- Revise the EPA Registration Number to read, “EPA Reg. No. 87857-5.”

4. Submit one copy of the final printed label for the record before you release the product for shipment.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under FIFRA and is subject to review by the Agency. See FIFRA section 2(p)(2). If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) lists examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process, FIFRA section 12(a)(1)(B). Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Assurance.

If you fail to satisfy these data requirements, EPA will consider appropriate regulatory action including, among other things, cancellation under FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions. A stamped copy of the label is enclosed for your records. Please also note that the record for this product currently contains the following CSFs:

- Basic CSF dated, 06/05/2025
- Alternate CSF 1 dated, 06/05/2025

If you have any questions, please contact Srinivas Gowda by phone at 202-565-0078, or via email at gowda.srinivas@epa.gov.

Enclosure: Stamped Final Label

EXTRACIDE F1.5

Non-public health industrial microbicide for use in Adhesives and Tackifier Preservation, Air Conditioner and Air Refrigeration Condensate Water Systems, Air Washer Systems, Aqueous Compositions [*], Brewery Pasteurizer and Can Warmer Systems, Building Material Preservation, Coal Slurry Systems, Commercial Photoprocessing Systems [*], Dispersed Pigments [*], Electrodeposition Paint Components, Evaporative Condenser Water Systems, Fountain Solutions and Ink /Ink Components[*], Hydrostatic Sterilizer Water Systems, Immersion Ultrasonic Tank Water [*], In-container Preservation, Industrial Process Water Systems, Industrial Scrubbing Systems, Industrial Wastewater Treatment Systems [*], Influent Water Filtration Systems, Laboratory Equipment Water Baths [*], Metal Working and Metal Cleaning Fluid Preservation, Oil Field Injection Waters, Paint and Coating Preservation, Paint Spray Booth Systems, Photoplate Processing [*], Polymer Latexes [*], Pulp and Papermills [*], Recirculating Closed Loop Water Cooling Systems, Recirculating Electrodeposition Systems, Recirculating Water Cooling Towers, Retort Water Systems, Reverse Osmosis and Ultra Filtration Systems, Sewage Systems [*], Textile Chemicals Preservation [*], Water Based Hydraulic Fluid Preservation, and Wood and Wood Products [*].

ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one 1.2%

2-Methyl-4-isothiazolin-3-one 0.4%

OTHER INGREDIENTS: 98.4%

TOTAL: 100.0%

KEEP OUT OF REACH OF CHILDREN (KOROC)

DANGER / PELIGRO

Si usted no entiende la etiqueta, busque a alguien para que se la explique a usted en detalle. (If you do not understand the label, find someone to explain it to you in detail.)

| FIRST AID | |
|---|--|
| IF IN EYES: | <ul style="list-style-type: none"> ● Hold eye open and rinse slowly and gently with water for 15-20 minutes. ● Remove contact lenses, if present, after first 5 minutes, then continue rinsing. ● Call a poison control center or doctor for treatment advice. |
| IF ON SKIN OR CLOTHING: | <ul style="list-style-type: none"> ● Take off contaminated clothing. ● Rinse skin immediately with plenty of water for 15-20 minutes. ● Call a poison control center or doctor for treatment advice. |
| IF INHALED: | <ul style="list-style-type: none"> ● Move person to fresh air. ● If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible. ● Call a poison control center or doctor for further treatment advice. |
| IF SWALLOWED: | <ul style="list-style-type: none"> ● Call a poison control center or doctor immediately for treatment advice. ● Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person. |
| GENERAL INFORMATION: Have the product container or label with you when calling a poison control center or doctor or going for treatment. For non-emergency and general information on product use, etc., information pertaining to this product, call the National Pesticides Information Center (NPIC) at 1-800-858-7378, Monday – Friday, 8:00 am – 12:00 pm Pacific Time; email: npic@ace.orst.edu ; or web site: www.npic.orst.edu . For emergencies, call the Poison Control Center 1-800-222-1222. | |
| NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measure against circulatory shock, respiratory depression and convulsions may be necessary. | |

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

EPA Reg. No.: 87857-

EPA Est. No.:

Manufactured for : Dalian Bio-Chem Company Limited

NET CONTENTS:

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

CORROSIVE.

CAUSES IRREVERSIBLE EYE DAMAGE AND SKIN BURNS.

MAY BE FATAL IF INHALED OR ABSORBED THROUGH SKIN.

HARMFUL IF SWALLOWED.

Do not get in eyes, skin, or on clothing. Do not breathe spray mist. Wear protective eyewear, such as goggles, face shield, or safety glasses. Wear coveralls over long-sleeved shirt and long pants, socks, chemical-resistant footwear, and chemical resistant gloves (Barrier Laminate, Butyl Rubber \geq 14 mils, Nitrile Rubber \geq mils, Neoprene Rubber \geq 14 mils, Natural Rubber \geq 14 mils, Polyethylene, Polyvinyl Chloride (PVC) \geq 14 mils, or Viton \geq 14 mils) when handling this product. When mixing and loading, wear a chemical resistant apron. Wear a minimum of a NIOSH-approved particulate filtering facepiece respirator with any N1, R, or P filter; OR a NIOSH-approved elastomeric particulate respirator with any N1, R, or P filter; OR a NIOSH-approved powered air purifying respirator with HE filters. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.

ENVIRONMENTAL HAZARDS

This chemical is toxic to aquatic plants, fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer system without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label.

DIRECTIONS FOR USE

[READ AND FOLLOW THE DIRECTIONS FOR USE ON THE ACCOMPANYING INFORMATION SHEET.]

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

ADHESIVE AND TACKIFIER PRESERVATION

EXTRACIDE F1.5 microbicide is recommended as an in-container preservative for the control of non-public health bacteria and fungi in water soluble and water dispersed adhesives such as animal glues, vegetable glues, natural rubber latices, polyvinyl acetate, styrene-butadiene and acrylic latices.

EXTRACIDE F1.5 microbicide is recommended as a preservative for tackifiers derived from rosin and hydrocarbon resins. Add 0.43-1.65 pounds (195-750 grams) of EXTRACIDE F1.5 to each 1000 pounds (454 kilograms) of fluid to provide 425-1675 ppm product.

AIR WASHER SYSTEMS/PAINT SPRAY BOOTHS

For use only in industrial air washing systems that maintain effective mist eliminating components.

Add to the air washer sump, chill water sump or paint spray booth to ensure uniform mixing, 35-883 ppm EXTRACIDE F1.5 microbicide (0.3-7.46 pounds or 4.5-113 fluid ounces of EXTRACIDE F1.5 per 1000 gallons of water in the system) depending upon the severity of contamination to control microbial slime, non-public health bacteria, fungi, and algae which cause fouling in industrial air washer systems and paint spray booths.

INTERMITTENT OR SLUG METHOD

INITIAL DOSE: When the system is noticeably fouled, apply 148-883 ppm EXTRACIDE F1.5 microbicide (1.26-7.46 pounds or 19-113 fluid ounces of EXTRACIDE F1.5 per 1000 gallons of water in the system). Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 35-219 ppm EXTRACIDE F1.5 microbicide (0.3-1.86 pounds or 4.5-28 fluid ounces of EXTRACIDE F1.5 per 1000 gallons of water) in the system weekly or as needed to maintain control. Clean badly fouled systems before treatment is begun.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is noticeably fouled, apply 148-883 ppm EXTRACIDE F1.5 microbicide (1.26-7.46 pounds or 19-113 fluid ounces of EXTRACIDE F1.5 per 1000 gallons of water in the system).

SUBSEQUENT DOSE: Maintain this treatment level by adding a continuous feed of 35-219 ppm EXTRACIDE F1.5 (0.3-1.86 pounds or 4.5-28 fluid ounces of EXTRACIDE F1.5 per 1000 gallons of makeup water). Clean badly fouled systems before treatment is begun.

AQUEOUS COMPOSITIONS[*]

EXTRACIDE F1.5 microbicide is recommended as an in-container preservative for the control of non-public health bacteria and fungi in aqueous products such as: fiberglass sizing solutions and aqueous emulsions and dispersions including surfactants, stabilized oil /water emulsions, surface preparation compounds, foam control products, nutrient solutions and pesticide formulations. Add 0.5-3.3 pounds (227-1.5 kilograms) of EXTRACIDE F1.5 per 1000 pounds (454 kilograms) of aqueous product to provide 500-3300 ppm product

CONCENTRATES: EXTRACIDE F150 microbicide should be added to concentrates at a level to ensure that the final use dilution of the product will contain 500-3300 ppm product.

BUILDING MATERIAL PRESERVATION

EXTRACIDE F1.5 microbicide is recommended as an in-container preservative for the control of non-public health bacteria and fungi in building materials such as mastics, caulks, joint cements, concrete admixtures, spackling and grouting. Add 0.43-1.65 pounds (195-750 grams) of EXTRACIDE F1.5 to each 1000 pounds (454 kilograms) of fluid to provide 425-1675 ppm product.

COMMERCIAL PHOTOPROCESSING SYSTEM PRESERVATION [*]

EXTRACIDE F1.5 microbicide is recommended to prevent microbial slime formation or accumulation in filters and ion exchange resin tanks of commercial photoprocessing systems. For the maintenance of a non-fouled system, use at 32-64 fluid ounces (2-4 pounds) per 1000 gallons fluid in the system once weekly, or as needed to maintain control. This corresponds to 250-500 ppm of EXTRACIDE F1.5. For a noticeably fouled system, use an initial dose of 64-148 fluid ounces (4-10 pounds) per 1000 gallons fluid to be followed by subsequent maintenance dosage. This corresponds to 500-1167 ppm EXTRACIDE F1.5. Increased frequency of treatment may be required depending on rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc. The preservative should be dispensed into the final rinse or used water collection tank.

DISPERSED PIGMENT PRESERVATION

EXTRACIDE F1.5 microbicide is recommended for the control of microbial slimes, non-public health bacteria and fungi in the manufacture and storage of dispersed pigments such as kaolin and montmorillonite clays, titanium dioxide, calcium carbonate, calcium sulfate, barium sulfate, magnesium silicate, and kieselguhr used in paint and paper productions. Add 0.43-1.65 pounds of EXTRACIDE F1.5 (195-750 grams) to each 1000 pounds (454 kilograms) of fluid to provide 425-1675 ppm product.

IN-CONTAINER PRESERVATION

EXTRACIDE F1.5 microbicide is recommended as an in-container preservative for the control of non-public health bacteria and fungi in liquid and semi-solid or solid household consumer, janitorial and industrial products, such as air fresheners, automotive products, fabric softeners, hand cleaners, polishes for floors and furniture, shoe polishes, moist sponges, mops, and towelettes, spray starch, waxes and automotive polishes, hand and automatic dish detergents, stain pretreatment products, liquid laundry detergents and car washes, household cleaners, industrial cleaners, liquid hand soaps, oil and grease removers, carpet cleaners, carpet shampoos and spot removers, waterless hand cleaners, raw materials for cleaning products, surfactants and silicone emulsions.

Add 0.4-1.5 pounds of EXTRACIDE F1.5 (180-680 grams) to each 1000 pounds (454 kilograms) of product to be treated to provide 400-1500 ppm EXTRACIDE F1.5. To ensure uniform mixing, slowly disperse EXTRACIDE F1.5 into product with agitation.

EXTRACIDE F1.5 microbicide may be added to those products formulated as concentrates which are in turn diluted for use at a level to ensure that the final use-dilution product will contain between 400-1500 ppm EXTRACIDE F1.5. Add 0.4-1.5 pounds of EXTRACIDE F1.5 (180-680 grams) per 1000 pounds (454 kilograms) of product to be treated. To ensure uniform distribution, slowly disperse EXTRACIDE F1.5 into product with agitation. Mix thoroughly until evenly dispersed throughout product. Wet wipes containing a solution preserved with this product may not be used for personal care, as baby wipes, or for food contact.

INDUSTRIAL RECIRCULATING CLOSED LOOP WATER COOLING SYSTEMS

To maintain control of microbial slimes, non-public health bacteria, fungi and algae, add EXTRACIDE F1.5 microbicide to the reservoir, recirculating line or some other point to ensure uniform mixing.

INITIAL DOSE: When the system is noticeably fouled, apply 148-883 ppm EXTRACIDE F1.5 microbicide (1.26 -7.46 pounds or 19-113 fluid ounces of EXTRACIDE F1.5 per 1000 gallons of water in the system). Repeat until control is achieved. Clean badly fouled systems before treatment is begun.

SUBSEQUENT DOSE: When microbial control is evident, add 35-219 ppm EXTRACIDE F1.5 microbicide (0.3 -1.86 pounds or 4.5-28 fluid ounces of EXTRACIDE F1.5 per 1000 gallons of water in the system) weekly or as needed to maintain control.

INDUSTRIAL RECIRCULATING WATER COOLING TOWERS

For the control of microbial slimes, non-public health bacteria, algae, and fungi add EXTRACIDE F1.5 microbicide to the tower basin, distribution box, or some other point to ensure uniform mixing.

INITIAL DOSE: When the system is noticeably fouled, apply 148-883 ppm EXTRACIDE F1.5 microbicide (1.26 -7.46 pounds or 19-113 fluid ounces of EXTRACIDE F1.5 per 1000 gallons of water in the system). Repeat until control is achieved. Clean badly fouled systems before treatment is begun.

SUBSEQUENT DOSE: When microbial control is evident, add 35-219 ppm EXTRACIDE F1.5 microbicide (0.3- 1.86 pounds or 4.5-28 fluid ounces of EXTRACIDE F1.5 per 1000 gallons of water in the system) weekly or as needed to maintain control.

INDUSTRIAL WASTEWATER TREATMENT SYSTEMS AND SEWAGE SYSTEMS¹

EXTRACIDE F1.5 microbicide is recommended for the control of microbial slimes, non-public health bacteria, fungi, and algae in industrial wastewater treatment and sewage systems. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority.

INITIAL DOSE: When the system is noticeably fouled, apply 148-883 ppm EXTRACIDE F1.5 microbicide (1.26 -7.46 pounds or 19-113 fluid ounces of EXTRACIDE F1.5 per 1000 gallons of water in the system). Repeat until control is achieved. Clean badly fouled systems before treatment is begun.

SUBSEQUENT DOSE: When microbial control is evident, add 35-219 ppm EXTRACIDE F1.5 microbicide (0.3- 1.86 pounds or 4.5-28 fluid ounces of EXTRACIDE F1.5 per 1000 gallons of water in the system) weekly or as needed to maintain control.

METAL CLEANING FLUID PRESERVATION

EXTRACIDE F1.5 microbicide is recommended as a preservative for use in the manufacture and use of alkaline, acid, and emulsion-based metal cleaning fluids typically used in electroplating, phosphatizing, galvanizing and general metal cleaning operations. For addition to a metal cleaning concentrate, add EXTRACIDE F1.5 at a level to ensure that the final use-dilution fluid will contain 425-1675 ppm product. For direct addition to a fouled system, add 54-214 fluid ounces (3.6-14.1 pounds) of EXTRACIDE F1.5 to each 1000 gallons of use-dilution metal cleaning fluid every 3 to 4 weeks to provide 425-1675 ppm product. A higher dosage range and /or increased frequency of treatment may be required depending upon rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc. The preservative should be dispensed as an additive into the circulating use-dilution metal cleaning fluid using a metering pump or by manual pouring and uniformly dispersed throughout the system.

METAL WORKING FLUID PRESERVATION

EXTRACIDE F1.5 microbicide is recommended for the control of microbial slimes, non-public health bacteria and fungi in soluble and emulsifiable-type aqueous metalworking fluids. For the maintenance of a non-fouled system, use EXTRACIDE F1.5 at 32 fluid ounces (2 pounds) per 1000 gallons of emulsion every 4 weeks or 32-148 fluid ounces per 1000 gallons emulsion (2-10 pounds) every 8-12 weeks to provide 250-1167 ppm product. For a noticeably fouled system, use an initial dose of 64-148 fluid ounces (4-10 pounds) per 1000 gallons of emulsion to provide 500-1167 ppm product to be followed by subsequent maintenance dosages depending upon the treatment interval noted above. Increased frequency of treatment may be required depending upon rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc. The preservative should be dispensed as an additive into the circulating use dilution of the metalworking fluid using a metering pump or by manual pouring and uniformly dispersed throughout the system.

OIL FIELD INJECTION WATERS

For the control of microbial slime-forming and sulfate-reducing bacteria in oil and gas field water systems, including enhanced recovery injection fluids, drilling, fracturing and completion fluids, slug treat with 67- 332 ppm EXTRACIDE F1.5 microbicide depending on the severity of contamination.

INITIAL DOSE: Add 166-332 ppm EXTRACIDE F1.5 (6.9-13.9 gallons or 58.0-116.8 pounds EXTRACIDE F1.5 per 1000 barrels of water) at a point in the system where it will be uniformly mixed. Repeat treatment after three days or as needed until control is achieved.

SUBSEQUENT DOSE: Add 67-166 ppm EXTRACIDE F1.5 (2.8-6.9 gallons or 23.5-58.0 pounds EXTRACIDE F1.5 per 1000 barrels of water) every seven days or as needed to maintain control.

PAINT AND COATING PRESERVATION

EXTRACIDE F1.5 microbicide is recommended as an in container preservative for the control of non-public health bacteria and fungi in water-based coatings such as paper and wood coatings and paints used for architectural product finishes and special purpose coatings. Add 0.43-165 pounds (195-750 grams) of EXTRACIDE F1.5 to each 1000 pounds (454 kilograms) of fluid to provide 425-1675 ppm product

PHOTOPLATE PROCESSING, FOUNTAIN SOLUTIONS AND INK/INK COMPONENTS[*]

EXTRACIDE F1.5 microbicide is recommended for the control of non-public health bacteria and fungi in photoplate processing chemicals, fountain solutions, and printing inks and ink components. EXTRACIDE F1.5 should be added to achieve 0.1% to 0.3% on a total weight basis. EXTRACIDE F1.5 should be added to fountain solution concentrates at a level to ensure that the final use-dilution of the product will contain 0.1% to 0.3% EXTRACIDE F1.5 on a total weight basis. To ensure uniform mixing, add EXTRACIDE F1.5 to the product slowly with agitation. The actual concentration required will depend upon the specific substance to be treated, frequency of repeated microbial contamination expected and level of protection required.

POLYMER LATEX PRESERVATION[*]

EXTRACIDE F1.5 microbicide is recommended for the control of non-public health bacteria and fungi in the manufacture and storage of synthetic and natural polymer latices including: acrylics, styrene/butadiene, carboxylated styrene/butadiene, ethylene/vinyl acetate; and biopolymers intended for industrial use, such as a xanthan gum, gum arabic, guar gum, protein-derived polymers, starches, casein-derived polymer latices, and solution polymers. Add 0.43-3.3 pounds of EXTRACIDE F1.5 (195 grams-1.5 kilograms) to each 1000 pounds (454 kilograms) of emulsion to provide 425-3350 ppm product.

NOTE: To ensure uniform mixing, add EXTRACIDE F1.5 to latex or solutions slowly with agitation. The actual required concentrations will depend upon such factors as the specific substance to be treated, frequency of repeated microbial contamination expected, and level of production required.

PULP AND PAPER MILLS[*]

For the control of microbial slimes, non-public health bacteria, algae and fungi, add EXTRACIDE F1.5 microbicide to the Beater, Hydropulper, or Fan or Broke Storage Pumps or some other point in the system to ensure uniform mixing. Apply 0.44 to 1.5 pounds (7-23 fluid ounces) of EXTRACIDE F1.5 microbicide per ton (dry basis) of pulp or paper produced as a slug dose. If needed, repeat daily. Clean badly fouled systems before initial treatment.

RECIRCULATING ELECTRODEPOSITION SYSTEMS

METHOD OF ADDITION

EXTRACIDE F1.5 microbicide is recommended as a tankside additive for the control of non-public health bacteria, fungi, and algae in recirculating electrodeposition systems and associated rinse systems. Alternatively,

EXTRACIDE F1.5 microbicide may be added through the components of the electrodeposition paint prior to their addition to the electrodeposition system.

TANKSIDE ADDITION TO ELECTRODEPOSITION SYSTEMS

EXTRACIDE F1.5 microbicide should be dispensed into the recirculating rinse system, ultrafilter permeate, or final distilled rinse system at a point to ensure uniform mixing.

INITIAL DOSE: When the system is noticeably fouled, add 667-2333 ppm EXTRACIDE F1.5 microbicide (6.7-23.3 gallons per 10,000 gallons of fluid in the system). Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 333-1000 ppm EXTRACIDE F1.5 microbicide (3.3-10 gallons per 10,000 gallons of fluid in the system) weekly or as needed. A change of frequency of treatment may be required depending upon the rate of dilution of the preservative with the makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, and system design.

TREATMENT OF ELECTRODEPOSITION PAINT COMPONENTS

INITIAL DOSE OF PAINT COMPONENTS

EXTRACIDE F1.5 microbicide should be added to the resin, pigment, or other component of the electrodeposition paint at a level to ensure that the final use-dilution fluid will contain 333-2333 ppm product.

SUPPLEMENTAL TANKSIDE DOSING OF ELECTRODEPOSITION SYSTEMS

If additional microbial control is necessary, EXTRACIDE F1.5 microbicide may be added to the electrodeposition system tankside to supplement the microbicide incorporated through paint components.

INITIAL DOSE: if the system becomes noticeably fouled, add 667-2333 ppm EXTRACIDE F1.5 (6.7-23.3 gallons per 10,000 gallons of fluid in the system). Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 333-1000 ppm EXTRACIDE F1.5 (3.3-10 gallons per 10,000 gallons of fluid in the system) weekly or as needed.

NOTE: Regardless of the manner of incorporation, the total product concentration in the system should at no time exceed 2333 ppm EXTRACIDE F1.5 or 23.3 gallons per 10,000 gallons of fluid in the system.

TEXTILE CHEMICALS PRESERVATION[*]

Use EXTRACIDE F1.5 microbicide for the control of non-public health bacteria and fungi in the manufacture and storage of textile processing chemicals such as fiber lubricants, spin finishes, sizes, dyestuffs, textile printing inks, dispersants, thickeners, dye fixatives, hand builders and weighters. These textile processing chemicals are commonly used in the production of natural and synthetic fibers and fabrics.

Add 0.4-1.67 pounds (181-757 grams) of EXTRACIDE F1.5 to each 1000 pounds (454 kilograms) of fluid to provide 400-1667 ppm product.

ULTRA FILTRATION UNITS AND NON-MEDICAL/NON-POTABLE REVERSE OSMOSIS SYSTEMS

EXTRACIDE F1.5 microbicide is recommended for the control of microbial slimes, non-public health bacteria and fungi in ultra filtration units and nonmedical/non-potable reverse osmosis systems. Use of EXTRACIDE F1.5 microbicide in potable water or dialysis is prohibited. Add 10-333 ppm of EXTRACIDE F1.5 microbicide into industrial ultra filtration or reverse osmosis systems by either continuous feed or periodic injection.

Compatibility of EXTRACIDE F1.5 microbicide with reverse osmosis membranes should be confirmed with membrane manufacturers.

For the control of non-public health bacteria and fungi in carbon beds, add 10-333 ppm of EXTRACIDE F1.5 microbicide by either continuous or batch feed.

For periodic membrane cleaning, add 0.4-1.0 pounds (181-454 grams) of EXTRACIDE F1.5 microbicide to every 120 gallons of cleaning solution to provide 400-1000 ppm product. Badly fouled systems should be cleaned before treatment is begun.

WATER BASED HYDRAULIC FLUID PRESERVATION

EXTRACIDE F1.5 microbicide is recommended as a preservative for use in the manufacture and use of high water-based hydraulic fluids and invert emulsion hydraulic fluids typically prepared by emulsifying 40% by volume water in 60% by volume of mineral oil using an oil soluble emulsifying agent.

For the maintenance of a non-fouled system, use EXTRACIDE F1.5 at 110-135 fluid ounces (7.2-8.8 pounds) per 1000 gallons fluid every 8 weeks. This corresponds to 980-1200 ppm product.

For a noticeably fouled system, use an initial dose of 135-235 fluid ounces (8.8-15.4 pounds) per 1000 gallons fluid to be followed by subsequent maintenance dosage. This corresponds to 1200-2100 ppm product. Increased frequency of treatment may be required depending upon rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc.

The preservative should be dispensed as an additive into the circulating use-dilution of the hydraulic fluid using a metering pump or by manual pouring and uniformly dispersed throughout the system.

WATER SYSTEMS

For the control of microbial slimes, non-public health bacteria, fungi and algae, add EXTRACIDE F1.5 microbicide to air conditioner/refrigeration condensate water systems, can warmers, coal slurry systems, evaporative condenser water systems, hydrostatic sterilizer water systems, immersion ultrasonic tank water [*], industrial scrubbing systems, influent water filtration systems, laboratory equipment water baths [*], brewery pasteurizers, retort water systems, and industrial process water systems.

Add EXTRACIDE F1.5 microbicide at some point in the system to ensure uniform mixing.

INITIAL DOSE: When the system is noticeably fouled, apply 148-883 ppm EXTRACIDE F1.5 microbicide (1.26 -7.46 pounds or 19-113 fluid ounces of EXTRACIDE F1.5 per 1000 gallons of water in the system). Repeat until control is achieved. Clean badly fouled systems before treatment is begun.

SUBSEQUENT DOSE: When microbial control is evident, add 35-219 ppm EXTRACIDE F1.5 microbicide (0.3-1.86 pounds or 4.5-28 fluid ounces of EXTRACIDE F1.5 per 1000 gallons of water in the system) weekly or as needed to maintain control.

WOOD AND WOOD PRODUCTS[*]

EXTRACIDE F1.5 microbicide is recommended for the protection of wood and wood products, such as landscape timbers, fences, posts, pilings, cross ties, decks, and similar exterior structures from mold and mildew. Treat southern yellow pine, hemlock, ponderosa pine, and other soft woods with 148-1000 ppm EXTRACIDE F1.5 (1.26-8.4 pounds or 13-128 fluid ounces of EXTRACIDE F1.5 per 1000 gallons) as an aqueous dip or pressure treatment for mold and mildew control. Thoroughly wet and allow to dry. A single application will afford protection for 12 weeks.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage, disposal or cleaning of equipment.

PESTICIDE STORAGE

Keep this product in the original container when not in use. Container must be stored and transported in an upright position to prevent spilling the contents.

PESTICIDE DISPOSAL

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER HANDLING

[Use the following for product sold in nonrefillable containers, >5 gallons:]

Nonrefillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying. Triple Rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container 1/4 full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times. Then offer for recycling if available, or reconditioning if appropriate, or puncture and dispose of in a sanitary landfill or by incineration.

[Use the following for product sold in nonrefillable containers, <5 gallons:]

Nonrefillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying. Triple Rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container 1/4 full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

[Use the following for product sold in refillable containers:]

Refillable container. Refill this container with pesticide only. Do not reuse this container for any other purpose. Cleaning the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller. To clean the container before final disposal, empty the remaining contents from this container into application equipment or a mix tank. Fill the container about 10 percent full with water. Agitate vigorously or recirculate water with the pump for 2 minutes. Pour or pump rinsate into application equipment or rinsate collection system.

Repeat this rinsing procedure two more times. Then offer container for recycling if available, or reconditioning if appropriate, or puncture and dispose of in sanitary landfill, or by incineration, or by other procedures approved by state and local authorities.

CONDITIONS OF SALE AND WARRANTY

Dalian Bio-Chem Company Limited warrants that this product conforms to its chemical description and is reasonably fit for the purpose stated on the label only when used in accordance with label directions as defined under the Directions for Use on this label. Dalian Bio-Chem Company Limited makes no other express or implied warranties, either of merchantability or fitness, for a particular use. Handling, storage, and use of the product by Buyer or User are beyond the control of Dalian Bio-Chem Company Limited and Seller. Risks such as ineffectiveness or other unintended consequences resulting from, but not limited to, failure to follow directions will be assumed by the Buyer or User. To the extent permitted by law, neither Dalian Bio-Chem Company Limited nor Seller shall be liable for consequential, special, or indirect damages resulting from the use, handling, application, storage, or disposal of this product.

[Batch code]

[*] Not a use registered by California.