

88346-4

04/18/2012

1/21

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

April 18, 2012

Sherman Wang
Tianjin Pool & Spa Corporation
2522 Malt Avenue
Commerce, CA 90040

Subject: Pooline Super Trichlor Granules
EPA Registration Number: 88346-4
Letter Date: February 21, 2012
EPA Receipt Date: February 22, 2012

Dear Mr. Wang:

The label amendment, submitted in connection with registration under section of the federal Insecticide, Fungicide, and Rodenticide Act (FIFRA), as amended, is acceptable.

Proposed amendments:

- Submission of final printed labeling.

General comments:

A stamped accepted copy of the label is enclosed for your records. A copy of the label has been added to the product's file.

Should you have any questions or comments concerning this letter, please contact Eliza Blair via email at blair.eliza@epa.gov or by telephone at (703) 308-7279.

Sincerely,

Monisha Harris
Product Manager (32)
Regulatory Management Branch II
Antimicrobials Division (7510P)

CONCURRENCES

SYMBOL	SURNAME	DATE					

2/21

TIANJIN POOL & SPA CORPORATION POOLINE SUPER TRICHLOR GRANULES

ACTIVE INGREDIENT:

Trichloro-s-triazinetriene..... 99.0%

OTHER INGREDIENTS..... 1.0%

Total..... 100 %

Provides 90% Available Chlorine

KEEP OUT OF REACH OF CHILDREN

DANGER

FIRST AID	
IF IN EYES	<ul style="list-style-type: none"> • Hold eye open and rinse slowly and gently with water for 15 to 20 minutes • Remove contact lenses if present after the first 5 minutes then continue rinsing eye • Call a poison control center or doctor for treatment advice
IF ON SKIN OR CLOTHING	<ul style="list-style-type: none"> • Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15-20 minutes. • Call a poison control center or doctor for treatment advice.
IF SWALLOWED	<ul style="list-style-type: none"> • Have person sip a glass of water if able to swallow. • Do not induce vomiting unless told to by a poison control center or doctor. • Do not give anything to an unconscious person. • Call a poison control center or doctor for treatment advice
IF INHALED	<ul style="list-style-type: none"> • Move person to fresh air. • If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. • Call a poison control center or doctor for treatment advice.
HOT LINE NUMBER	
<ul style="list-style-type: none"> • Have the product container or label with you when calling a poison control center or doctor, or going for treatment. • You may also contact 1-800-535-5053, collect day or night, for emergency medical treatment information. 	
NOTE TO PHYSICIAN	
Probable mucosal damage may contraindicate the use of gastric lavage	

Tianjin Pool & Spa Corporation
2522 Malt Avenue
Commerce, CA 90040

EPA Reg. No. 88346-4
EPA Est. No. 87966-CHN-001
Net Wt. 50 lbs. / 22.7 kg.

ACCEPTED
APR 18 2012
Under the Federal Insecticide, Fungicide, and
Rodenticide Act as amended for the
pesticide, registered under
EPA Reg. No. 88346-4

PRECAUTIONARY STATEMENTS

DANGER – HAZARD TO HUMANS AND DOMESTIC ANIMALS

Corrosive: Causes irreversible eye damage and skin burns. May be fatal if inhaled. Harmful if swallowed or absorbed through skin. Do not get in eyes, on skin or clothing. Do not breathe dust, vapor or spray mist. Irritating to nose and throat. Wear goggles, face shield or safety glasses. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARD

This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product into sewer systems without previously notifying the sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of EPA.

PHYSICAL OR CHEMICAL HAZARD

Strong oxidizing agent. Contact with water slowly liberates irritating and hazardous chlorine containing gases. Decomposes at temperatures above 437°F (225°C) with liberation of harmful gases. When ignited, will burn with the evolution of chlorine and equally toxic gases.

Never add water to product. Always add product to large quantities of water. Use clean, dry utensils. Do not add this product to any dispensing device containing remnants of any other product. Such use may cause a violent reaction leading to fire or explosion. Contamination with moisture, organic material, or other chemicals may start a chemical reaction with generation of heat, liberation of hazardous gases, and possible fire and explosion.

IN CASE OF FIRE OR SMOKE: Call the fire department. Do not attempt to extinguish the fire without a self contained breathing apparatus (SCBA). Do not let the fire burn. Flood with copious amounts of water. Do not use ABC or other dry chemical extinguishers since there is the potential for a violent reaction.

IN CASE OF CONTAMINATION OR DECOMPOSITION: Do not reseal container. Neutralize material to a non-oxidizing state for safe disposal.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

This product may be used in accordance with the directions for use as a microbicide/microbistat, (slime forming bacteria, fungi, algae), disinfectant, sanitizer, fungicide, algaecide and bacteriostat into the end-use products for the following use sites: aquatic non-food industrial, aquatic non-food residential, indoor food, indoor non-food, indoor medical and indoor residential.

AQUATIC NON-FOOD INDUSTRIAL:

RECIRCULATING WATER SYSTEMS-

This product is intended for the control of bacteria, fungi and algae in the following aquatic sites: Air Washer Water Systems, Commercial/Industrial Water Cooling Systems, Evaporative Condenser Water Systems, Secondary Oil Recovery Injection Water, Heat Exchange Water Systems, Lakes/Ponds/Reservoirs (Without Human or Wildlife Use), Industrial Scrubbing Systems, Oil Recovery Drilling Muds/Packer Fluids.

This product may be added to the system by direct placement into the water at a point where the product will be uniformly mixed with water. The frequency of feeding and duration of the treatment will depend on the severity of the contamination. Badly fouled systems must be cleaned before treatment begins.

Intermittent or slug method

Initial Dose: When the system is noticeably fouled, add this product at the rate of 0.1 to 0.5 pounds per 1000 gallons (12 to 60 grams per 1000 liters) in the system to achieve 0.5-10 ppm (mg/L) available chlorine, as measured by a suitable test kit. Repeat dosage until residual is achieved.

Subsequent Dose: When microbial control is evident, add this product at the rate of 0.02 to 0.1 pounds per 1000 gallons (2.4 to 12 grams per 1000 liters) in the system to achieve 0.5-1 ppm (mg/L) available chlorine, as measured by a suitable test kit. Repeat periodically as needed to maintain control.

Continuous feed method

Initial dose: When the system is noticeably fouled, add this product at the rate of 0.1 to 0.5 pounds per 1000 gallons (12 to 60 grams per 1000 liters) in the system to achieved 0.5-10 ppm (mg/L) available chlorine, as measured by a suitable test kit. Repeat dosage until residual is achieved.

Subsequent Dose: When microbial control is evident, add this product at the rate of 0.02 to 0.1 pounds per day per 1000 gallons (2.4 to 12 grams per day per 1000 liters) in the system to maintain 0.5-1 ppm (mg/L) available chlorine, as measured by a suitable test kit.

AQUATIC NON-FOOD INDUSTRIAL:

SEWAGE WASTE WATER SYSTEMS

This product is intended for the control of bacteria, fungi and algae in sewage waste water systems. This product provides rapid disinfection of primary, secondary and tertiary wastewater treatment systems.

Dose Rate: Add this product at the rate of 0.02 to 0.5 pounds per 1000 gallons (2.4 to 60 grams per 1000 liters) in the system to achieve 0.2-3 ppm (mg/L) available chlorine, as measured by a suitable test kit, at the injection point in the disinfection contact chamber. Adjust the dosage to achieve disinfection and minimize the halogen concentration at the exit of the contact chamber.

FOR ONCE-THROUGH WATER SYSTEMS

This product is intended for control of bacteria, fungi and algae in open or closed cycle, fresh or salt water, once-through cooling systems.

Initial Dose: When the system is noticeably fouled, add this product at the rate of 0.02 to 0.5 pounds per 1000 gallons (2.4 to 60 grams per 1000 liters) of water treated to achieve 0.2-5 ppm (mg/L) total available chlorine as measured by a suitable test kit, in the water treated. Repeat dosage until residual is achieved.

Subsequent Dose: When microbial control is evident, add this product at the rate of 0.02 to 0.1 pounds per 1000 gallons (2.4 to 12 grams per 1000 liters) of water treated to achieve 0.2-5 ppm (mg/L) total available chlorine, as measured by a suitable test kit, in the water treated. Repeat periodically as needed to maintain control.

AQUATIC NON-FOOD RESIDENTIAL:

SWIMMING POOL WATER SYSTEMS

This product is intended for use in controlling bacteria and algae in swimming pools. This slow dissolving product is to be used in suitable granular chlorinating devices. DO NOT add directly to the swimming pool.

Re-entry into treated swimming pools is prohibited above levels of 3 ppm (mg/L) available chlorine.

Start up- Before using this product, make sure that the filtration system is clean and operating properly. Adjust the pH of the water to the range of 7.2-7.6 using suitable products and reliable test kit. Adjust the alkalinity of the water to a minimum of 125 ppm (mg/L), based on the test kit reading.

Shock (super-chlorinate) the pool with an appropriate product, followed by maintenance treatment.

Shock treatment- The pool water must be super chlorinated or shocked every seven days or whenever the combined chlorine level is above 0.5 ppm (mg/L). Combined chlorine is the difference between total and free chlorine, as measured by a suitable test kit.

Add a sufficient amount of this product directly to the surface of circulating water to raise the available chlorine level to 5-6 ppm (mg/L), based on test kit readings. The addition of 10 ounces of this product per 10,000 gallons of water (7.5 grams per 1,000 liters) will provide approximately 5 ppm (mg/L) of available chlorine. If the combined chlorine reading is not below 0.5 ppm (mg/L) and the water has not been restored to its normal clarity, repeat the shock treatment described above.

Do not enter water until free available chlorine reading is below 3 ppm (mg/L), combined chlorine is below 0.5 ppm (mg/L) and the water is restored to its normal clarity.

Maintenance treatment- Add this product to the granular feeder (or chlorinating device). Adjust the feeder to maintain the free available chlorine level in the water at 1- 3 ppm (mg/L) as indicated by a reliable test kit. Periodically refill feeding device with enough product to assure a constant treatment level of 1-3 ppm (mg/L) available chlorine. Weather and usage effect sanitizer levels. In addition, some oils, lotions, fragrances, cleaners, etc. may cause foaming or cloudy water as well as reduce the efficiency of this product. Maintain the pH at 7.2-7.6 and the alkalinity at a minimum of 125 ppm (mg/l).

When the total dissolved solid (TDS) reaches 3000 ppm (mg/L) or whenever the water becomes difficult to manage, drain the water and add fresh water to the pool.

Winterizing- Thoroughly clean and vacuum the pool. While the water is still clear and clean, apply 16 ounces of an appropriate shock product, such as sodium dichloro-s-triazynetrione for each 10,000 gallons of water (12 grams per 1,000 liters), while the filtration system is running. This will increase the available chlorine by approximately 8 ppm (mg/L). Cover pool, prepare heater, filter and heater components for winter by following manufacturer's instructions.

AQUATIC NON-FOOD RESIDENTIAL:

SPAS AND HOT-TUBS

This product is intended for use in controlling bacteria in spas and hot tubs. This product is also highly effective in controlling and destroying algae in outdoor spas and hot tubs. This slow dissolving product is to be used in a suitable granular chlorinating device. DO NOT add directly to the spa water.

Re-entry into treated spa or hot tub is prohibited above levels of 3 ppm (mg/L) of available chlorine.

SPAS AND HOT TUBS DISINFECTION

Start up- Before using this product; make sure that the filtration system is clean and operating properly. Adjust the pH of the water to the range of 7.2-7.6 and the alkalinity of the water to a minimum of 125 ppm (mg/L), using suitable products and reliable test kits. For bather safety, do not have the water temperatures exceed 104°F (40°C).

Add a sufficient amount of an appropriate shock product directly to the surface of circulating water to raise the free chlorine level in the water to 5-6 ppm (mg/L), based on suitable test kit readings. The addition of one ounce of sodium dichloro-s-triazynetrione product per 1,000 gallons (0.75 grams per 100 liters) of water will increase the available chlorine by 5 ppm (mg/L).

Shock treatment- After each use, the water must be super chlorinated or shocked. Add a sufficient amount of an appropriate shock product directly to the surface of circulating water to raise the available chlorine level to 5-6 ppm (mg/L), based on test kit readings. The addition of one ounce of sodium dichloro-s-triazynetrione per 1,000 gallons (0.75 grams per 100 liters) of water will increase the available chlorine by 5 ppm (mg/L). If the combined chlorine reading is not below 0.5 ppm (mg/L) and the water has not been restored to its normal clarity, repeat the shock treatment described above. Combined chlorine is the difference between total and free chlorine, as measured by as suitable test kit.

Maintenance treatment- Add this product to the granular feeder (or chlorinating device). Adjust the feeder to maintain the free available chlorine level in the water at 3 - 5 ppm (mg/L) as indicated by a reliable test kit. Periodically refill feeding device with enough product to assure a constant treatment level of 1-3 ppm (mg/L) available chlorine. Weather and usage effect sanitizer levels. In addition, some oils, lotions, fragrances, cleaners, etc. may cause foaming or cloudy water as well as reduce the efficiency of this product. Maintain the pH at 7.2-7.6 and the alkalinity at a minimum of 125 ppm (mg/L).

When the total dissolved solid (TDS) reaches 3000 ppm (mg/L) or whenever the water becomes difficult to manage, drain the water and thoroughly clean the spa/hot tub before adding fresh water.

AQUATIC NON-FOOD RESIDENTIAL:

SWIMMING POOLS, SPAS AND HOT TUB SHOCK TREATMENT

As a preventative measure, shock treat (super-chlorinate) once per week or after heavy rains, windstorms, or high bather loads, to minimize pool problems. In addition, Shock Treatment may be required to remedy cloudy, dull or hazy water, unpleasant odors, eye irritation or when pool turns green or slimy (algae problems).

To achieve a shock of 10 ppm (mg/L) available chlorine use 1 pound of this product per 11,000 gallons of pool water.

Re-entry into the treated swimming pool, spa or hot tub is prohibited above levels of 3 ppm (mg/L) available chlorine.

To Determine Pool Volume:

Rectangular pools – length (ft.) times width (ft.) times average depth (ft.) times 7.5 equals volume.

Round and Oval pools- Maximum diameter (ft.) times minimum diameter (ft.) times average depth (ft.) time 5.9 equals gallons.

Start up- Before using this product; make sure that the filtration system is clean and operating properly. Adjust the pH of the water to the range of 7.2-7.6 and the alkalinity of the water to a minimum of 125 ppm (mg/L), based on test kit readings.

Shock treatment:

1. Remove as much debris as possible from the pool using hand skimmer, pool leaf rake or by vacuuming to waste.
2. Empty skimmer of any chemicals or debris.
3. Make sure filter is on and water is properly circulating through skimmer.
4. Remove any chemicals from in line automatic dispensing devices that are not chlorinated isocyanurates (trichlor or dichlor).
5. Slowly pour product into skimmer making sure that it is drawn into the filter system.
6. **Operate the pump/filter continuously for at least two hours** (without back-washing) to insure the product is dissolved out of the filter and is well mixed into the pool.
Caution: a large stagnant accumulation of wet product can generate decomposition of products that can cause an explosion. Do not shut off pump/filter circulation for two hours after adding this product or perform other operations with the pool filter system during this time.
7. If necessary repeat treatment.

AQUATIC NON-FOOD RESIDENTIAL:

ORNAMENTAL PONDS / AQUARIA

This product is intended for use in controlling bacteria and algae in residential ornamental ponds and similar aquaria. This product may be added to the system by direct placement into the water at a point where the product will be uniformly mixed with water (avoid if bleaching may be a problem). The frequency of feeding and duration of the treatment will depend on the severity of the contamination. Badly fouled system must be cleaned before treatment begins.

It should be noted that very low levels of chlorine can be highly toxic to certain fish and other aquatic species.

Start up- Before using this product, make sure that the system is clean and the circulation system is operating properly.

Shock (super-chlorinate) the pool with an appropriate product, followed by maintenance treatment.

Shock treatment – The water should be super chlorinated or shocked every two weeks or whenever the combined chlorine level is above 0.5 ppm (mg/L). Combined chlorine is the difference between total and free chlorine, as measured by a suitable test kit.

Add a sufficient amount of this product directly to the surface or circulating water to raise the free chlorine level to 5-6 ppm (mg/L), based on test kit readings. The addition of one ounce of sodium dichloro-s-triazynetrione will provide about 5 ppm (mg/L) of available chlorine to 1,000 gallons of water (0.75 grams per 100 liters). If the combined chlorine reading is not below 0.5 ppm (mg/L) and the water has not been restored to its normal clarity, repeat the shock treatment described above.

Maintenance treatment- Add this product daily or as needed to maintain the available chlorine in the water at 1-3 ppm (mg/L) as indicated by a reliable test kit. The addition of 1.5 ounces of this product per 10,000 gallons of water (1 gram per 1,000 liters) will provide approximately 1 ppm (mg/L) of available chlorine. Weather and usage effect sanitizer levels. Maintain the pH of 7.2-7.6 and the alkalinity at a minimum of 125 ppm (mg/L).

INDOOR FOOD:

This product may be used on food contact surfaces in accordance with 21 CFR 178.1010 of the Federal Food, Drug and Cosmetic Act.

SOLUTION PREPARATION- Prepare a 100 ppm (mg/L) sanitizing solution by thoroughly mixing 0.15 oz. of this product with 10 gallons of water (0.11 gram per liter). Solutions containing an initial concentration of 100 ppm (mg/L) available chlorine must be tested with a suitable chlorine test kit and adjusted periodically to insure that the available chlorine does not drop below 50 ppm (mg/L). Should the available chlorine level drop below 50 ppm (mg/L), either discard the solution or add 0.75 ounce of this product per 10 gallons of water (55 milligrams per liter) to increase the available chlorine level 50 ppm (mg/L) and maintain the 100 ppm (mg/L) solution strength.

SANITIZATION OF NON-POROUS FOOD CONTACT SURFACES

This product is recommended for use in poultry (egg/meat), egg handling equipment (commercial), dairy farm milk handling facilities/equipment, dairy farm milking equipment, agricultural/farm structures/buildings and equipment, agricultural/farm premises, household/domestic dwellings indoor food handling areas, food processing plant premises and equipment (food and non-food contact), poultry processing plant premises and equipment (food and non-food contact), meat processing plant premises and equipment (food and non-food contact), fish/seafood processing plant premises and equipment (food and non-food contact), eating establishments, eating establishments equipment/utensils and food handling areas (food contact).

RINSE OR SPRAY METHOD- Clean equipment surfaces in the normal manner and rinse with potable water. It may be necessary to remove gross filth and heavy soil from surfaces by a pre-scrape, pre-flush, and where necessary, a pre-soak treatment. Prior to use, rinse all surfaces thoroughly with the sanitizing solution, maintaining contact with the sanitizer for 2 to 5 minutes. Do not rinse equipment with water after treatment.

The same solution may not be re-used for sanitizing activity; but, may be re-used for other purposes such as a cleaner in the feed tank of spray type machines.

IMMERSION METHOD - Clean equipment in the normal manner. Prior to use, immerse equipment in the sanitizing solution for 2 to 5 minutes and allow the sanitizer to drain. Do not rinse equipment with water after treatment.

INDOOR FOOD:

EGG WASHING

This product is recommended for use in egg washing treatments (commercial).

Only clean, whole eggs can be used for sanitizing. Dirty, cracked or punctured eggs cannot be sanitized.

To sanitize clean egg shells intended for food or food products, spray with a solution of 0.15 ounce of this product in 10 gallons of water, providing 100 ppm (mg/L) available chlorine. The solution must be equal to or warmer than the eggs, but not exceeding 130°F. Wet eggs thoroughly allow to drain. Eggs that have been sanitized with this chlorine compound may be broken for use in the manufacture of egg products without prior potable water rinse. Eggs must be reasonably dry before casing or breaking. The solution must not be re-used for sanitizing eggs.

This product complies with the provisions of 21CFR, Section 178.1010 of the federal Food, Drug and Cosmetic Act. If this product is intended or recommended for use in plants operating under the U.S. Department of Agriculture egg grading and egg products inspection programs, authorization must be obtained for this specific product.

INDOOR FOOD:

PASTEURIZER/WARMER/CANNERY COOLING WATER SYSTEMS

This product is intended for the control of bacteria, fungi and algae in pasteurizer/warmer/cannery cooling water systems.

This product may be added to the system continuously or intermittently as needed with granular product feeding device or by direct placement into the water at a point where the product will be uniformly mixed with water. Their frequency of feeding and duration of the treatment will depend on the severity of the contamination. Badly fouled systems must be cleansed before treatment begins.

Intermittent or slug method

Initial Dose: When the system is noticeably fouled, add this product at the rate of 0.1 to 0.5 pounds per 1000 gallons (12 to 60 grams per 1000 liters) in the system to achieve 0.5-10 ppm (mg/L) available chlorine as measured by a suitable test kit. Repeat dosage until residual is achieved.

Subsequent Dose: When microbial control is evident, add this product at the rate of 0.02 to 0.1 pounds per 1000 gallons (2.4 to 12 grams per 1000 liters) in the system to achieve 0.5-1 ppm (mg/L) available chlorine as measured by a suitable test kit. Repeat periodically as needed to maintain control.

Continuous feed method

Initial Dose: When the system is noticeably fouled add this product at the rate of 0.1 to 0.5 pounds per day per 1000 gallons (2.4 to 12 grams per day per 1000 liters) in the system to maintain 0.5-1 ppm (mg/L) available chlorine, as measured by a suitable test kit.

Subsequent Dose: When microbial control is evident, add this product at the ratio of 0.02 to 0.1 pounds per day per 1000 gallons (2.4 to 12 grams per day per 1000 liters) in the system to maintain 0.5-1 ppm (mg/L) available chlorine, as measured by a suitable kit.

This product may be used on food contact surfaces in accordance with 21CFR 178.1010 of the Federal Drug and Cosmetic Act.

INDOOR FOOD:

WATER WELL SYSTEMS

This product is recommended for use in water well formation treatment where strong sanitizer solutions are needed. The product may be used before, during or after treatment with polyphosphates or other compatible material used to remove lime scale deposits in well formations. This product is intended for use by trained well treating professionals as described below.

Shock Load Sanitizer Solution: Dissolve six (6) pounds of this product in 1000 gallons of water to obtain a solution containing 600 ppm (mg/L) of available chlorine. Pump this solution down the well to clear the screen and water bearing sand of any iron and sulfur forming bacteria that may be present. Follow Shock Load Sanitizer Solution with Displacement Water Sanitizer Solution prepared as described below.

Displacement water Sanitizer Solution: Dissolve one pound of this product in 1000 gallons of water and pump it down the well on top of the Shock Load Sanitizer Solution. Several batches of the Displacement Water Sanitizer solution may be required for the desired penetration of the formation.

These solutions should be allowed to contact the formation for a period of time from 30 minutes to four hours. At the end of this time, the sanitizer solution should be pumped from the well, the rate of improvement in pumping rate noted, and the solution monitored for chlorine level in accordance with the NPDES permit.

Repeat until the maximum pumping rate is achieved.

The product water must be of raw potable water quality after this sanitizing treatment. Therefore, before connection of the treated well to any potable water system, it must contain acceptable levels of phosphate. After the well has stabilized following the treatment, take two or three additional sample at hourly intervals to determine that the stabilized background level of PO4 has been established.

13/21

INDOOR NON-FOOD:

SANITIZATION OF HARD NON-POROUS NON -FOOD CONTACT SURFACES

This product is recommended for use in egg plant/hatcheries/brooder rooms and shoe baths (hatching).

SOLUTION PREPARATION- Prepare a 100 ppm (mg/L) sanitizing solution by thoroughly mixing 0.15 oz. of this product with 10 gallons of water (0.11 gram per liter). Solutions containing an initial concentration of 100 ppm (mg/L) available chlorine must be tested with a suitable chlorine test kit and adjusted periodically to insure that the available chlorine does not drop below 50 ppm (mg/L). Should the available chlorine level drop below 50 ppm (gm/L), either discard the solution or add 0.075 ounces of this product per 10 gallons of water (55 milligrams per liter) to increase the available chlorine level 50 ppm (gm/L) and maintain the 100 ppm (mg/L) solution strength.

RINSE OR SPRAY METHOD- Clean equipment surfaces in the normal manner and rinse with potable water. It may be necessary to remove gross filth and heavy soil form surfaces by a pre-scrape, pre-flush, and where necessary, a pre-soak treatment. Prior to use, rinse all surfaces thoroughly with the sanitizing solution, maintaining contact with the sanitizer for 2 to 5 minutes. Do not rinse equipment with water after treatment.

The same solution may not be used in the feed tanks of spray type machines providing at least one minute contact time to sanitize equipment.

IMMERSION METHOD- Clean equipment in the normal manner. Prior to use, immerse equipment in the sanitizing solution for at least 2 minutes and allow the sanitizer to drain. Do not rinse equipment with water after treatment and do not soak equipment overnight.

14/21

INDOOR RESIDENTIAL:

HARD NON-PORUS SURFACE SANITIZATION

This product is recommended for use as a hard surface sanitizer in laundries (household and coin operated) bathrooms premises.

SOLUTION PREPARATION – Prepare a 100 ppm (mg/L) sanitizing solution by thoroughly mixing 0.15 oz. of this product with 10 gallons of water (0.11 gram per liter). Solutions containing an initial concentration of 100 ppm (mg/L) available chlorine must be tested with a suitable chlorine test kit and adjusted periodically to insure that the available chlorine does not drop below 50 ppm (mg/L). Should the available chlorine level drop below 50 ppm (mg/L), either discard the solution or add 0.075 ounce of this product per 10 gallons of water (55 milligrams per liter) to increase the available chlorine level 50 ppm (mg/L) and maintain the 100 ppm (mg/L) solution strength.

RINSE OR SPRAY METHOD- Clean equipment surfaces in the normal manner and rinse with potable water. It may be necessary to remove gross filth and heavy soil from surfaces by a pre-scrape, pre-flush, and where necessary, a pre-soak treatment. Prior to use, rinse all surfaces thoroughly with the sanitizing solution, maintaining contact with the sanitizer for 2 to 5 minutes. Do not rinse equipment with water after treatment.

The same solution may not be re-used for sanitizing activity; but, may be re-used for other purposes such as a cleaner in the feed tanks of spray type machines.

IMMERSION METHOD- Clean equipment in the normal manner. Prior to use, immerse equipment in the sanitizing solution for at least 2 minutes and allow the sanitizer to drain. Do not rinse equipment with water after treatment and do not soak equipment overnight.

This product may be used on food contact surfaces in accordance with 21CFR 178.1010 of the Federal Food, Drug and Cosmetic Act.

INDOOR MEDICAL:

This product is recommended for use as a sanitizer on hospital/medical premises (human/veterinary), hospital non-critical items (bedpans/furniture), hospital/medical institutions non-conductive floors.

SOLUTION PREPARATION – Prepare a 100 ppm (mg/L) sanitizing solution by thoroughly mixing 0.15 oz. of this product with 10 gallons of water (0.11 gram per liter). Solutions containing an initial concentration of 100 ppm (mg/L) available chlorine must be tested with a suitable chlorine test kit and adjusted periodically to insure that the available chlorine does not drop below 50 ppm (mg/L). Should the available chlorine level drop below 50 ppm (mg/L), either discard the solution or add 0.075 ounce of this product per 10 gallons of water (55 milligrams per liter) to increase the available chlorine level 50 ppm (mg/L) and maintain the 100 ppm (mg/L) solution strength.

RINSE OR SPRAY METHOD - Clean equipment surfaces in the normal manner and rinse with potable water. It may be necessary to remove gross filth and heavy soil from surfaces by a pre-scrape, pre-flush, and where necessary, a pre-soak treatment. Prior to use, rinse all surfaces thoroughly with the sanitizing solution, maintaining contact with the sanitizer for 2 to 5 minutes. Do not rinse equipment with water after treatment.

The same solution may not be re-used for sanitizing activity; but, may be re-used for other purposes such as a cleaner in the feed tanks of spray type machines.

This product is not to be used as a terminal sterilant/high level disinfectant on any surface or instruments that (1) is introduced directly into the human body, either into or in contact with the bloodstream or normally sterile areas of the body, or (2) contacts intact mucous membranes but which does not ordinarily penetrate the blood barrier or otherwise enter normally sterile areas of the body. This product may be used to pre-clean or decontaminate critical or semi-critical medical devices prior to sterilization or high level disinfection.

**DISINFECTION OF DRINKING WATER
(EMERGENCY/PUBLIC/INDIVIDUAL SYSTEMS)**

PUBLIC SYSTEMS: Feed 1 ounce of this product per 9000 gallons of water until a free available chlorine residual of a least 0.2 ppm is attained throughout the distribution system. Check water frequently with a chlorine test kit. Bacteriological sampling must be conducted at a frequency no less than that prescribed by the National Interim Primary Drinking Water Regulations. Contact your local Health Department for further details.

INDIVIDUAL SYSTEMS: DUG WELLS – Upon completion of the casing (lining) wash the interior of the casing (lining) with a 100 ppm available chlorine solution using a stiff brush. This solution can be made by dissolving 1 ounce of this product into 60 gallons of water. After covering the well, pour the disinfecting solution into the well through both the pipe sleeve opening and the pipeline. Wash the exterior of the pump cylinder also with the disinfecting solution. Start pump and pump water until strong odor of chlorine in water is noted. Stop pump and wait at least 24 hours. After 24 hours flush well until all traces of chlorine have been removed from the water. Contact your local Health Department for further details.

INDIVIDUAL WATER SYSTEMS: DRILLED, DRIVEN & BORED WELLS – Run pump until water is as free from turbidity as possible. Pour a 100 ppm available chlorine disinfecting solution into the well. This solution can be made by dissolving 1 ounce of this product into 60 gallons of water. Add 5 to 10 gallons of clean, chlorinated water to the well in order to force the disinfectant into the rock formation. Wash the exterior of pump cylinder with the disinfectant. Drop pipeline into well, start pump and pump water until strong odor of chlorine in water is noted. Stop pump and wait at least 24 hours. After 24 hours flush well until all traces of chlorine have been removed from the water. Deep wells with high water levels may necessitate the use of special methods of introduction of the disinfectant into the well. Consult your local Health Department for further details.

INDIVIDUAL WATER SYSTEMS: FLOWING ARTESIAN WELLS – Artesian wells generally do not require disinfection. If analyses indicate persistent contamination the well should be disinfected. Consult your local Health Department for further details.

EMERGENCY DISINFECTION:

This product is recommended for disinfecting raw or pre-treated (settled, coagulated and /or filtered) water supplies intended for use as drinking water for humans and domestic animals.

The source of the water to be treated may be a river, lake, well, cistern or similar system. To obtain the desired disinfection results, the water to be treated should be clear and free of dirt and organic debris. If the source of the water is cloudy and contains dirt and organic debris, hold the water in holding tanks to be treated with coagulating agents and filtered to remove the dirt and organic debris.

Dissolve 0.1 ounce of this product in 60 gallons of water (120 milligrams per 10 liters) to obtain a concentration of 10 ppm (mg/L) of available chlorine. Let the water stand for one hour before using. A residual of 1 ppm (mg/L) of available chlorine, as measured by a reliable test kit, should be maintained in the water to insure disinfection.

PUBLIC WATER SYSTEMS:

RESERVOIRS: ALGAE CONTROL – Continuous chlorination is the most effective method for destroying algae; however, slug treatment can also be effective. Suitable chlorine feeding points should be selected on each stream at least 50 yards upstream from the points of entry into the reservoir. Add this product at the following rates:

Initial dose: When the system is noticeably fouled, add this product at the rate of 1 to 5 ounces per 10,000 gallons to achieve 0.5-1.5 ppm (mg/L) available chlorine, as measured by a suitable test kit. Repeat dosage until residual is achieved.

Subsequent dose: When control is evident, add this product at the rate of 0.3 to 1.5 ounces per 10,000 gallons to maintain 0.2-0.5 ppm (mg/L) available chlorine, as measured by a suitable test kit.

MAINS – Thoroughly flush section to be disinfected by discharging from hydrants. Permit a water flow of at least 2.5 feet per minute to continue under pressure while injecting this product by means of a chlorinator. Stop water flow when a chlorine residual test of 50 ppm is obtained at the low pressure end of the new main section after a 24 hour retention time. When chlorination is completed, the system must be flushed free of all heavily chlorinated water.

NEW TANKS, BASINS, ETC. – Remove all physical soil from surfaces. Place 6 ounces of this product for each 10 cubic feet of moving capacity (500 ppm available chlorine.) Fill to working capacity and allow to stand for at least 4 hours. Drain and flush with potable water and return to service.

NEW FILTER SAND - Apply 12 ounces of this product for each 150 to 200 cubic feet of sand. The action of the product dissolving as the water passes through the bed will aid in disinfecting the new sand.

NEW WELLS – Flush the casing with a 50 ppm available chlorine solution of water containing 0.8 ounce of this product for each 100 gallons of water. The solution should be pumped or fed by gravity into the well after thorough mixing with agitation. After 24 hours flush well, until all traces of chlorine have been removed from the water. It may then be pumped until a representative raw water sample is obtained. Bacterial examination of the water will indicate whether further treatment is necessary. Contact your local Health Department for further details.

EXISTING EQUIPMENT – Remove equipment from service, thoroughly clean surfaces of all physical soil. Disinfect by placing 6 ounces of this product for each 10 cubic feet capacity (approximately 500 ppm available chlorine). Fill to working capacity and let stand at least 4 hours. Drain and place in service. If the previous treatment is not practical, surfaces may be sprayed with a solution containing 0.8 ounces of this product for each 5 gallons of water (approximately 1000 ppm available chlorine). After drying, flush with water and return to service.

EMERGENCY DISINFECTION AFTER FLOODS:

WELLS – Thoroughly flush contaminated casing with a 500 ppm available chlorine solution. Prepare this solution by mixing 0.8 ounces of this product with 10 gallons of water. Backwash the well to increase yield and reduce turbidity, adding sufficient chlorinating solution to the backwash to produce a 10 ppm available chlorine residual, as determined by a chlorine test kit. After the turbidity has been reduced and the casing has been treated, add sufficient chlorinating solution to produce a 50 ppm available chlorine residual. After 24 hours flush well until all traces of chlorine have been removed from the water. It may then be pumped until a representative raw water sample is obtained. Bacterial examination of the water will indicate whether further treatment is necessary. Retreat well if water samples are biologically unacceptable. Contact your local Health Department for further details.

RESERVOIRS – In case of contamination by overflowing streams, establish chlorinating stations upstream of the reservoir. Chlorinate the inlet water until the entire reservoir obtains a 0.2 ppm available chlorine residual, as determined by a suitable chlorine test kit. In case of contamination from surface drainage, apply sufficient product directly to the reservoir to obtain a 0.2 ppm available chlorine residual in all parts of the reservoir.

BASINS, TANKS, FLUMES, ETC. – Thoroughly clean all equipment; then apply 6 ounces of product per 10 cu. Ft. of water to obtain 500 ppm available chlorine, as determined by a suitable test kit. After 24 hours drain, flush, and return to service. If the previous method is not suitable, spray or flush the equipment with a solution containing 0.8 ounces of this product for each 5 gallons of water (1000 ppm available chlorine). Allow to stand for 2 to 4 hours, flush and return to service.

FILTERS – When the sand filter needs replacement, apply 12 ounces of this product for each 150 to 200 cubic feet of sand. When the filter is severely contaminated, additional product should be distributed over the surface at the rate of 12 ounces per 20 sq. ft. Water should stand a depth of 1 foot above the surface of the filter bed for 4 to 24 hours. When filter beds can be back – washed of mud and silt, apply 12 ounces of this product per each 50 sq. ft. allowing the water to stand at a depth of 1 foot above the filter sand. After 30 minutes, drain water to the level of the filter. After 4 to 6 hours drain, and proceed with normal back – washing.

DISTRIBUTION SYSTEM – Flush repaired or replaced section with water. Establish a chlorinating station and apply sufficient product until a consistent available chlorine residual of at least 10 ppm (as measured by a chlorine test kit) remains after a 24 hour retention time.

EMERGENCY DISINFECTION AFTER FIRES:

CROSS CONNECTIONS FOR EMERGENCY CONNECTIONS – Set up a chlorine feed system near the intake of the untreated water supply. Add 0.75 ounces of this product per 1,000 gallons of water until a chlorine residual of at least 0.2 ppm (as measured by a chlorine test kit) at the point where the untreated supply enters the regular distribution system.

EMERGENCY DISINFECTION AFTER DROUGHT:

SUPPLEMENTARY WATER SUPPLIES – A chlorine feed system should be set up on the supplementary water line. This product should be added at 0.45 ounces per 1,000 gallons until a minimum chlorine residual of 0.2 ppm (as measured by a chlorine test kit) is achieved. The water should be held for 20 minutes before use.

19/21

WATER SHIPPED IN BY TANKS, TANK CARS, ETC. – Thoroughly clean all containers and equipment. Spray a 500 ppm available chlorine solution and rinse with potable water after 5 minutes. This solution is made by mixing 0.4 ounces of this product for each 5 gallons of water. During the filling of the containers, dose with sufficient amounts of this product to provide at least a 0.2 ppm chlorine residual, as measured by a chlorine test kit.

EMERGENCY DISINFECTION AFTER MAIN BREAKS:

MAINS – Before assembly of the repaired section, flush out mud and soil. Permit a water flow of at least 2.5 feet per minute to continue under pressure while injecting this product by means of a chlorinator. Stop water flow when a chlorine residual test of 50 ppm is obtained at the low pressure end of the new main section after a 24 hour retention time. When chlorination is completed, the system must be flushed free of all heavily chlorinated water.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

STORAGE: Keep material dry and in a dry area. Store in original container where temperatures do not exceed 125°F (52°C) for 24 hours. Keep container tightly closed.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance. The preferred disposal methods are incineration or chemical treatment in accordance with Federal, State and Local regulations.

DO NOT put product, spilled product, or filled or partially filled containers into the trash or waste compactor. Contact with incompatible materials could cause a reaction and fire. Do not transport wet or damp material.

{Text for bulk bags}

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Completely empty liner by shaking and tapping sides and bottom to loosen clinging particles. Empty residue into application equipment. Then offer for recycling if available or reconditioning if appropriate or dispose of empty bag in a sanitary landfill or by incineration, or, if allowed by State and local authorities, by burning. If burned, stay out of smoke.

{Text for Bulk Bin}

CONTAINER DISPOSAL: Refillable Container. Refill this container with pesticide only. Do not reuse this container for any other purpose.

Pressure rinsing the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller

To clean the container before final disposal pressure rinse as follows: Empty the remaining contents into application equipment or mix tank. Hold container upside down over application equipment or mix tank or collect rinsate for later use or disposal. Insert pressure rinsing nozzle in the top of the container, rinse at 40 PSI for at least 30 seconds. Drain for 10 seconds after the flow begins to drop. Then offer for recycling if available or reconditioning if appropriate or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

{Text for Fiber Drum with Liner}

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Completely empty liner by shaking and tapping sides and bottom to loosen clinging particles. Empty residue into application equipment. Then offer for recycling if available or dispose of liner in a sanitary landfill or by incineration as allowed by state and local authorities. If drum is contaminated and cannot be reused, dispose of in the same manner required for its liner.

{Text for Plastic Container with liner}

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Completely empty liner by shaking and tapping sides and bottom to loosen clinging particles. Empty residue into application equipment. Then offer for recycling, if available, or dispose of liner in a sanitary landfill or by incineration. For outer container triple rinse (or equivalent) promptly after emptying. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by State and local authorities, by burning. If burned, stay out of smoke.

To clean the outer container before final disposal triple rinse as follows: Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

{Text for Plastic Container without liner}

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying. Then offer for recycling, if available or puncture and dispose of in a sanitary landfill, or by incineration.

Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

{Text for household or residential use products}

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Then offer for recycling, if available. Rinse empty container thoroughly with water to dissolve all material prior to disposal.