

# UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

September 18, 2017

Cinda Bell SciReg, Inc. 12733 Director's Loop Woodbridge, VA 22192

Subject: Label Amendment – updating establishment number on label and CSFs

Product Name: T\*A\*P

Application Date: May 8, 2017 EPA Registration Number: 89140-1 Application Date: May 8, 2017 Decision Number: 529378, 529377

Dear Ms. Bell:

The amended label and CSF(s) referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, are acceptable. This approval does not affect any conditions that were previously imposed on this registration. You continue to be subject to existing conditions on your registration and any deadlines connected with them.

A stamped copy of your labeling is enclosed for your records. This labeling supersedes all previously accepted labeling. You must submit one copy of the final printed labeling before you release the product for shipment with the new labeling. In accordance with 40 CFR 152.130(c), you may distribute or sell this product under the previously approved labeling for 18 months from the date of this letter. After 18 months, you may only distribute or sell this product if it bears this new revised labeling or subsequently approved labeling. "To distribute or sell" is defined under FIFRA section 2(gg) and its implementing regulation at 40 CFR 152.3.

Please note that the record for this product currently contains the following CSF(s):

• Basic & Alternate #'s 1-6 CSFs dated 5/8/2017

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false

Page 2 of 2 EPA Reg. No. 89140-1 Decision No. 529378, 529377

or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

Your release for shipment of the product constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6. If you have any questions, please contact Autumn Metzger at 703-305-5314, or Metzger.autumn@epa.gov.

Sincerely,

Michael Wagman, Acting Product Manager 4

Invertebrate and Vertebrate Branch 1

Registration Division (7505P)

Office of Pesticide Programs

Enclosure

# ACCEPTED

09/18/2017

Under the Federal Insecticide, Fungicide and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No.

89140-1

[Note to EPA: Intended for Pest Control Operator Use]

**Brand name: T•A•P<sup>TM</sup>** 

Alternate brand names: OrkinTherm Pro, OrkinTherm, BugSnipeR

# KEEP OUT OF THE REACH OF CHILDREN CAUTION

See First Aid Statement [this statement optional if first aid statement not on front panel]

# **FIRST AID**

#### IF ON SKIN or CLOTHING:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

#### IF IN EYES:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing.
- Call a poison control center or doctor for treatment advice.

Have the product container or label with you when calling a Poison Control Center or doctor, or when going for treatment.

## PRECAUTIONARY STATEMENTS:

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION. Harmful if absorbed through skin. Causes moderate eye irritation. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water after handling.

#### Personal Protective Equipment (PPE)

Applicators, mixers, and other handlers must wear:

- long-sleeved shirt
- long pants
- socks, shoes
- chemical-resistant gloves
- NIOSH-approved N95 or higher disposable or reusable particulate respirator
- dust goggles

**READY-TO-USE** [T•A•P<sup>TM</sup> Thermal, Acoustical, and Pest Control Insulation] is an insect/arthropod control insulation. This product is toxic to listed insects and other arthropods and is intended to prevent their infestations in those building voids (attic, wall, between-floors, crawlspace) where the product is applied. Its toxic effect begins only after insect/arthropod contact with the product.

#### KILLS:

Cockroaches, Termites (including Formosan Termites), Ants, Silverfish, Earwigs, Crickets, Sowbugs, Darkling Beetles, Millipedes, Centipedes, and Booklice.

This insulation contains material toxic to these insects/arthropods and is intended to prevent new infestations in walls and attics where the product is applied. Control of insects/arthropods is limited to contact with insulation.

## DIRECTIONS FOR USE

It is a violation of Federal law to apply this product in a manner inconsistent with its labeling. "R" means resistance to heat flow. The higher the **R-value** the greater the insulating power. To get the marked **R-value**, it is essential that this insulation be installed properly. Insulation applicators installing this material should be familiar with and carefully follow installation instructions from the manufacturer.

NOT FOR USE AS SOLE PROTECTION AGAINST TERMITES. Use of this product does not substitute for pre- and/or post-construction mechanical alteration, soil treatment or foundation treatment. For active termite infestations, you should consult a licensed pest control operator.

#### EASY AS 1 • 2 • 3

#### Attic Preparation:

- Maintain attic ventilation. Insulation should not cover any attic ventilation. Use baffles or vent chutes. Do not cover soffit vents.
- Insulation should not cover or touch heat producing components like light fixtures. Create barriers to maintain a 3" clearance.
- Create a barrier around your attic access to keep the insulation in place when entering or exiting the attic.

FOLLOW INSTRUCTIONS FOR SET UP AND OPERATION OF BLOWING MACHINE [Graphics may accompany items 1 – 3 below]

- 1. Position Blowing Machine outside house. Plug in and attach 100' hose.
- 2. Run hose to attic through nearest access. Avoid tight turns.
- 3. Blow insulation into attic or on top of existing insulation to desired thickness/R-Value.

#### [OPTIONAL statement]:

Watch our YouTube video to see how easy it is to use.

[OPTIONAL image]:

{QR Code Image}

CAUTION! TO HELP AVOID FIRE: Keep cellulose insulation at least three inches away from the sides of recessed light fixtures. Do not place insulation over such fixtures so as to entrap heat. Also keep this insulation away from exhaust flues of furnaces, water heaters, space heaters or other heat-producing devices unless the device is rated zero "0" clearance to combustibles. To be sure that insulation is kept away from light fixtures and flues, use a barrier to permanently maintain clearance around these areas. Check with local building or fire officials for guidance on installation and barrier requirements. Do not install or use cellulose insulation around heat or ignition sources or operations such as welding, metal cutting, grinding, or other potentially flammable situations. [or additional required FTC language]

REQUEST TO INSTALLER: Remove this label and give it to the consumer at completion of job.

#### STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

Pesticide Storage: Store product in a dry area.

**Pesticide Disposal:** Waste resulting from the use of this product must be disposed of on site or at an approved waste disposal facility.

**Container Handling:** Nonrefillable container. Do not reuse or refill this container. Completely empty bag into application equipment, then offer for recycling if available or dispose of empty bag in a trash can or by incineration.

[MIN.] or [AVG.] NET WT.: lbs [kg]

[For T•A•P Brand or OrkinTherm Pro]:

Manufactured for Pest Control Insulation LLC 5285 Mountain Center Plaza Lula, GA 30554 Tel: 770.766.6050 www.TAPinsulation.com US Patent Number 6,578,782 EPA REG. NO. 89140-1

[For OrkinTherm and BugSnipeR brands]:

# Manufactured by US GreenFiber, LLC Toll Free 800-228-0024 www.greenfiber.com

GreenFiber is a registered trademark of US GreenFiber, LLC © 2012 US GreenFiber, LLC. All rights reserved.

US GreenFiber, LLC 2500 Distribution Street, Suite 200 Charlotte, NC 28203

EPA REG. NO. 89140-1

Bucyrus, OH 44820

Item Code:		
Template Co	ntrol: _	

[some or all of these locations may appear on label]:

EPA EST. NO. Bloomer, WI 54724 EPA EST. NO. 72787-WI-001 Hickory, KY 42051 EPA EST. NO. 73840-KY-001 Webberville, MI 48892 EPA EST. NO. 73854-MI-001 Chambersburg, PA 17201 EPA EST. NO. 73864-PA-001 Eastanollee, GA 30538 EPA EST. NO. 73744-GA-001 Monroe, LA 71202 EPA EST. NO. 73755-LA-001 Houston, TX 77241 EPA EST. NO. 75642-TX-001 Chandler, AZ 85225 EPA EST. NO. 70106-AZ-002 Crothersville, IN 47229 EPA EST. NO. 86171-IN-001 Penrose, CO 81240 EPA EST. NO. 72787-CO-001 Ronda, NC 28670 EPA EST. NO. 87149-NC-001 Charlotte, NC 28206 EPA EST. NO. 70106-NC-001 Delphos, OH 45833 EPA EST. NO. 70106-OH-002 Norfolk, NE 68701 EPA EST. NO. 70106-NE-002 Tampa, FL 33605 EPA EST. NO. 70106-FL-001 Waco, TX 76704 EPA EST. NO. 70106-TX-001 West Valley, UT 84119 EPA EST. NO. 70106-UT-001 McClellan, CA 95652 EPA EST. NO. 87715-CA-001 Laflin, PA 18702 EPA EST. NO. 070106-PA-001

EPA EST. NO. 93223-OH-1

# [ADDITIONAL MARKETING CLAIMS AND GRAPHICS (OPTIONAL TEXT)]

Thermal, Acoustical, and Pest Control Insulation

3 - insulations - in - 1

INSULATION MADE FROM RECYCLED PAPER

- Helps protect your home environment from annoying insects and other arthropods\*
- Contains 87% recycled paper
- Helps keep you warm in winter & cool in summer
- Highly resistant to air infiltration
- Helps deaden sound as an acoustical barrier
- This *clean-blowing* insulation is the result of a patented process.
- helps prevent listed pests\*
- EXCLUSIVE FORMULA offers one time application for long-lasting protection against listed pests\* where applied
- EXCLUSIVE FORMULA helps prevent ants, cockroaches, termites, and other listed insects\*
   where applied
- EXCLUSIVE FORMULA does not require retreating for long-term control of ants, cockroaches, termites, and other listed insects\* where applied
- EXCLUSIVE FORMULA provides long-term control of ants, cockroaches, termites, and other listed insects\* where applied
- Provides long-lasting control of ants, cockroaches, termites, and other listed insects\* where applied
- For lasting pest protection against listed pests\* where applied
- For long-term pest protection against listed pests\* where applied
- Simply blow in a minimum of \_\_\_ bags per \_\_\_ sq. ft.
- Additional bags can be used to increase R value (see reverse for additional details)
- pest protection\* + energy saving insulation
- fire resistant
- Bug Protection\* Insulation
- energy saving
- simple-to-use [GreenFiber] blower machine rentable at this store
- Can be applied over *ANY* existing insulation.
- Save up to 20% in energy costs\*\*
- Reduces Noise
- Superior Sound Deadening Properties

\*\* Savings vary. Find out why in the seller's Fact Sheet on R-values. Higher R-values mean greater insulating power.

<sup>\*</sup> effective against cockroaches, termites (including Formosan termites), ants, silverfish, earwigs, crickets, sowbugs, darkling beetles, millipedes, centipedes, and booklice [NOTE TO EPA: this footnote will appear on the same panel as asterisked statements]

# FOR USE IN NEW CONSTRUCTION AND RETROFIT APPLICATIONS

- ATTICS FLOORS WALLS CRAWLSPACES • OVERLAY FIBER GLASS OR OTHER INSULATIONS •
- HOMES
- APARTMENTS & CONDOMINIUMS
- OFFICES & INDUSTRIAL BUILDINGS
- HOTELS & MOTELS
- HOSPITALS & NURSING HOMES
- RESTAURANTS
- SCHOOLS

## Commercial Size

Save Energy and Money!

- Helps Keep Bugs Out\* & Comfort In!
- Easy Blow In Attic Insulation
- Resists Mold
- Itch Free Insulation No Cutting

For your Tax Credit information of up to visit [www.TAPinsulation.com] [www.orkintherm.com][www.bugsniper.com]
{Energy Star Graphic}
{Recycle Symbol}
{PC Barcode}
{Recycled Plastic Package Graphic}
{Lifetime Guaranteed Graphic}
{Made in U.S.A. Graphic} [see p. 13 for example]
{UL Graphic}
{SCS Recycled Content Graphic}
{ORKIN logo} [see p. 13 for example]
{QR Code Symbol}
{Facebook Symbol}

{LinkedIn Symbol}
{Twitter Symbol}
{YouTube Symbol}
{GreenFiber logo} [see p. 13 for example]
{Energy Savings logo} [see p. 13 for example]
This product approved by Pest Control Insulation, LLC
MADE IN U.S.A
[INSULATION INDUSTRY STANDARD INFORMATION (NON-FIFRA TEXT)]
[Note to EPA: charts are completed when the bag is manufactured]
From R to R or higher
[or]
RR for attics and walls
Covers up to SQ FT
[ALTERNATIVE COVERAGE CHART 1]

				/F4		1	
	TAP COVERAGE CHART ([bag weight])						
	R-	INSTALLED	COVERAGE	BAGS PER	WEIGHT	٠,	
	VALUE	THICKNESS	SF/BAG	1000 SF	LBS/SF	columns/information as needed]	
						mal	
						ıfor	
location]						s/in ed]	
cat						lumns/i needed	
[]0						olu s ne	
						additional	
						lditi	
						[ad	

This bag covers \_\_\_\_ sq ft @ R-\_\_\_ where framing is \_\_\_\_\_ OC

# [ALTERNATIVE COVERAGE CHART 2]

R- Value @ 75°F	Initial Installed Thickness (in.)	Minimum Settled Thickness (in.)	Bags/ 1,000 Sq. Ft. 2"x6" Joists 16" On Ctr.	Net Coverage Sq. Ft./ Bag	Bags/ 1,000 Sq. Ft. 2"x6" Joists 24" On Ctr.	Net Coverage Sq. Ft. / Bag	Bags/ 1,000 Sq. Ft. No Joists	Net Coverage Sq. Ft. / Bag	Minimum Weight Per Sq. Ft. (Lbs.)

The listed values are based on settled thickness and can be obtained only by an insulation
applicator using equipment supplied by the manufacturer and specifically designed for the
product and application techniques.
R-Value (@")
ATTIC INSTALLED DENSITY (LB/FT³)

## [ALTERNATIVE COVERAGE CHART 3]

Application Cov	erage Chart					LBS	INS641LD
						Gross Covera	ge (Based on 2"x6"
						Framing o	on 16" Centers)
							ıra neta (con
				e (No Adjustment			ación para una
	Minimum Thick		Cobertura i	neta (sin compesa	ción para la		2" x 6" en centros
	Espesor minimo	(en pulgadas)	estructura)			C	le 16")
				Minimum			
				Bags per	Minimum		
R-value at 75 F			Maximum	1,000 Square	Weight per	Maximum	Minimum Bags
Mean Temp			Square Feet	Feet	Square Foot	Square Feet	per 1,000 Square
Valor de			per Bag		(lbs/ft2)	per Bag	Feet
resistencia	Initial Installed	Settled		Cantidad	_		
termica (valor	Thickness	Thickness	Pies	minima de	Peso	Pies	Cantidad minima
R) a 75 F de		_	cuadrados	bolsas por	minimo por	cuadrados	de bolsas por
temperature	Espesor inicial	Espesor	máximos	1,000 pies	pie	máximos	1,000 pies
media	instalado	asentado	por bolsa	cuadrados	cuadrado	por bolsa	cuadrados

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT OF \_\_\_\_ LBS. USING THE \_\_\_\_\_ BLOWING MACHINE. SETTINGS ARE NOT ADJUSTABLE. THE CHART IS BASED ON SETTLED THICKNESS AND IS FOR ESTIMATING PURPOSES ONLY. DO NOT EXCEED MAXIMUM SQUARE FEET COVERAGE PER BAG. THE APPLICATOR MUST INSTALL BOTH THE MINIMUM NUMBER OF BAGS PER \_\_\_\_\_ SQ. FT. AND THE MINIMUM INSTALLED THICKNESS TO INSURE THE STATED R-VALUE HAS BEEN REACHED. FAILURE TO MEET BOTH THESE REQUIREMENTS MAY PREVENT THE APPLICATION OF SPECIFIED R-VALUE. THIS PRODUCT MUST BE INSTALLED DRY. THE COVERAGE CHART DOES NOT APPLY TO FLOOR APPLICATIONS. DO NOT ADD WATER TO THIS PRODUCT. JOB CONDITIONS, APPLICATION TECHNIQUES, EQUIPMENT, AND SETTINGS CAN INFLUENCE ACTUAL COVERAGE. MINIMUM NET WEIGHT IS \_\_\_\_ LBS.

## [ALTERNATIVE COVERAGE CHART 4]

				Maximum Coverage per Bag (no adjustment for Framing) (ft²/Bag)	Maximum Co Bag (Adj Frami	usted for
Thermal Resistance		Installed Thickness	Minimum Wt Per Square Foot	Cobertura máxima por bolsa (sin compensación para la estructura) ft²/Bag	Cobertura máxima compensación par	
(R-value)  Resistencia térmica (R)	Framing Estructura	(inches)  Espesor instalado (pulgadas)	(lb/ft²)  Peso mínimo por pie cuadrado lb/ft²	16 inch o.c. (ft²/Bag)	16 inch o.c. (ft²/Bag)	24 inch o.c. (ft²/Bag)
terrined (K)	LSCIUCTUIA	(puigauas)	cuaurado is/it-	10 men o.c. (11 / bag)	(it / Dag)	(10 / 506)

THIS COVERAGE CHART IS FOR DRY APPLICATIONS ONLY AND IS BASED ON THE [Name of insulation blowing machine], WITH MATERIAL APPLIED DRY. FOR MAXIMUM COVERAGE PER BAG (ADJUSTED FOR FRAMING), THE FRAMING FACTOR FOR \_\_\_\_\_ OC STUD SPACING IS \_\_\_\_\_\_%; FOR \_\_\_\_\_ OC STUD SPACING THE FRAMING FACTOR IS \_\_\_\_\_.

[OPTIONAL TEXT]:
Follow the instructions carefully. For further information, visit our web site at [www.TAPinsulation.com][www.orkintherm.com][www.bugsniper.com]. Tested and approved
to meet quality standards of the State of California Department of Consumer Affairs, Bureau of
Home Furnishings and Thermal Insulation, License No, Registry No The
material content of T•A•P insulation consists of at least 85% recycled paper fiber. This insulation
does not use asbestos, fiberglass or formaldehyde in its manufacturing process. According to
T•A•P's Material Safety Data Sheet (MSDS), the application of the product requires the use of
safety eyewear and a NIOSH-approved N95 or higher disposable or reusable particulate
respirator if housekeeping and engineering controls do not maintain nuisance levels below regulatory limits or dust concentration is unknown. If you suffer from asthma or respiratory
ailment we recommend you consult your physician prior to using this product.
This product meets the amended Consumer Product Safety Commission (CPSC) standard for flame resistance and corrosiveness of cellulose insulation.
Class 1 Building Material
[appropriate standards to be inserted, as applicable]
Tested and approved to meet the quality standards of the State of California Department of
Consumer Affairs, Bureau of Home Furnishings and Thermal Insulation, License #
Testing services furnished by
[WH stamp on product manufactured at GreenFiber establishments; may include following text]
US GreenFiber WH
Licensed Manufacturers:
LISTED: Cellulose Insulation Albany, NY
Norfolk, NE
Delphos, OH
Salt Lake City, UT
Intertek
W/N 14001
or
[UL stamp on product manufactured at GreenFiber establishments; may include following text]
UL CLASSIFIED
[Note to EPA: this information is completed when the bag is manufactured]
R15890 [R27651]
Issue No. F-9706
Loose Fill
US GreenFiber, LLC [Pest Control Insulation LLC]
Classified in accordance with the following American Society for Testing and Materials (ASTM)

Characteristics
Flammability Characteristics
Critical Radiant Flux: Greater Than or Equal to W/cm <sup>2</sup>
Smoldering Combustion: Less Than or Equal to percent
Environmental Characteristics
Corrosiveness: Acceptable
Fungi Resistance: Acceptable
Moisture Absorption: Acceptable
Odor Emission: Acceptable
Density (Settled): Thermal Resistance: () R/in. (at in. thickness)
Thermal Resistance: () R/III. (at III. thickness)
[ALTERNATIVE ATTIC CARD 1]:
[Note to EPA: attic cards are completed by the installer]
CUT OUT AND STAPLE IN ATTIC
ATTIC CARD: STATEMENT OF COMPLIANCE FOR LOOSE FILL INSULATION: THIS
INSULATION HAS BEEN INSTALLED IN CONFORMANCE WITH THE ABOVE
RECOMMENDATIONS TO PROVIDE A VALUE OF R USING BAGS OF
INSULATION TO COVER SQUARE FEET OF AREA.
Builder's Signature Company Name Date
Installer's Name Company Name Date
[ALTERNATIVE ATTIC CARD 2]:
THIS FORM IS ONLY FOR PEST CONTROL OPERATOR USE.
CERTIFICATION
This insulation has been installed in conformance with the above recommendation, to provide a value of:
R bags of this insulation to cover square feet of area.
Builder's Signature:
Company: Date:
Applicator's Signature: Date:
Company:Date:
PCO License#:







