

OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

WASHINGTON, D.C. 20460

December 2, 2025

Abigail Wacek Regulatory Agent for, Xypex Chemical Corporation

Electronic Transmittal: Abigail.wacek@tsgconsulting.com

Subject: Notification per PRN 98-10 – To Update the Product Label as per PR Notice 98-10

Product Name: XYPEX BIO-SAN C-500 EPA Registration Number: 92393-2

Received Date: 06/24/2025 Action Case Number: 00660608

Dear Ms. Wacek:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped "Notification" and will be placed in our records.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) lists examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Assurance.

Page 2 of 2 EPA Reg. No. 92393-2 Action Case Number 00660608

If you have any questions, please contact Karen Leavy at (202)-566-0668 or by email at Leavy.Karen@epa.gov.

Sincerely,

Luisa C. Samalot-Freire, Product Manager (31)

Regulatory Management Branch I Antimicrobials Division (7510M)

Office of Pesticide Programs

U.S. Environmental Protection Agency

Xypex Bio-San C-500

[Alternate Brand Name: Xypex Admix C-500S]

NOTIFICATION

92393-2

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

12/02/2025

Active ingrealents:	Active	Ingredients:
---------------------	--------	--------------

Silver	0.12%
Copper	5.55%
Other Ingredients	<u>94.33%</u>
Total	100.00%

KEEP OUT OF REACH OF CHILDREN CAUTION

FIRST AID		
If Swallowed	Call a poison control center or doctor immediately for treatment advice.	
	• Have person sip a glass of water if able to swallow.	
	• Do not induce vomiting unless told to by a poison control center or doctor.	
	• Do not give anything to an unconscious person.	
If on Skin	Take off contaminated clothing.	
	• Rinse skin immediately with plenty of water for 15-20 minutes.	
	• Call a poison control center or doctor for treatment advice.	
Call a poison con	trol center or doctor immediately for treatment advice. Have the product	
container or label	with you when calling a poison control center or doctor, or when going for	
treatment.		
In case of emerge	ency, call +1 (604) 2735265	

[See back/side panel for additional first aid / precautionary statements]

Toll-free: 1.800.961.4477

EPA Reg. No: 92393-2E

EPA Est. No.: Net Contents:

Manufactured For/Sold By:

Xypex Chemical CorporationTel: 604.273.526513731 Mayfield PlaceFax: 604.270.0451

Richmond, BC E-mail: <u>info@xypex.com</u>
Canada V6V 2G9 Web: <u>www.xypex.com</u>

PRECAUTIONARY STATEMENTS

Hazards to Humans and Domestic Animals

CAUTION. Harmful if swallowed or absorbed through skin. Avoid contact with skin, eyes, or clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse.

Environmental Hazards

(For container > 5 gallons) This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

(For containers ≤ 5 gallons) This product is toxic to fish and aquatic invertebrates.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Xypex Bio-San C-500 is added to the concrete at the time of batching. It is important to obtain a homogeneous mixture of Xypex Bio-San C-500 with the concrete. Do not add dry powder directly to wet mixed concrete as this could cause clumping and thorough dispersion may not occur. The sequence of procedures for addition will vary according to the type of batch plant operation and equipment. The following methods have been used successfully in the past and it is recommended that the local Xypex Technical Services Representative be consulted about the best method to use.

- 1. **ADDITION TO COARSE AGGREGATE BELT** Add Xypex Bio-San C-500 powder directly to the coarse aggregate conveyor belt manually or through computer controlled mass batching system. Account for worker health and safety issues with moving belts and wind-blown dust issues.
- 2. **ADDITION TO CENTRAL MIXER** Load the Xypex Bio-San C-500 in bulk powder form along with the other components. Mix as per standard batching practices to ensure thorough dispersal of the Admix resulting in a homogeneous mixture. Account for worker safety issues when accessing the equipment.
- 3. TRUCK ADDITION (AT PLANT) Add Xypex Bio-San C-500 in bulk powder form to the drum of the ready-mix truck immediately prior to driving the truck under the batch plant and adding the balance of the materials in accordance with standard concrete batching practices. Avoid delays in adding other components and utilize high speed mixing to ensure homogeneity of mix. Where there may be insufficient water for thorough dispersion of the bulk powder a water slurry can be made with the Admix and added to the truck mixer drum prior to batching. Account for added water in the mix design and slump.

NOTE:

- i. For installations involving pan mixers, the recommended procedure would be to initially add some of the mix water and coarse aggregate to the pan mixer begin mixing and slowly add the Xypex Bio-San C-500 powder. Mix until the Admix is thoroughly dispersed and forms a slurry, then add the balance of the materials and continue to mix as per normal.
- ii. Concrete containing the Xypex Bio-San C-500 does not preclude the requirement for design of crack control, construction joint detailing, proper placement, consolidation and curing of the concrete and measures for repairing defects such as honeycombing, tie holes, cracks beyond specified limits.
- iii. Further guidelines are available that address the use of Xypex Bio-San C-500 for a specific situation, (e.g. dry mixes, use of ice in hot ambient conditions, cold-weather concreting, etc.). Consult with a local Xypex Technical Services Representative or Xypex's Technical Services Department for further information.

Setting Time and Strength

The setting time of concrete is affected by the chemical and physical composition of ingredients, temperature of the concrete and climatic conditions. Xypex Bio-San C-500 is designed for concrete mix designs where a normal or mildly delayed set is desired. Concrete containing the Xypex Bio-San C-500 may develop higher ultimate strengths than plain concrete. Trial mixes should be carried out under project conditions to determine the setting time and strength of the concrete dosed with Xypex Bio-San C-500. Consult with a Xypex Technical Services Representative for the most appropriate Xypex Bio-San C-500 for your project.

Concrete should be a minimum of 28 days age prior to placement into service.

Dosage Rates

1% by weight of cementing materials (including: fly ash, slag, and other supplementary cementing materials).

Recommended for:

- Clarifiers
- Digesters
- Head Works
- Industrial Structures
- Lift Stations
- Manholes

- Pump Stations
- Septic Tanks
- Sewer Pipes
- repair and renewal of waste water structures

Limitations

When incorporating Xypex Bio-San C-500, the temperature of the concrete mix should be above 40°F (4°C).

STORAGE AND DISPOSAL

Do not contaminate food or feed by storage or disposal or cleaning of equipment.

STORAGE: Xypex products must be stored dry at a minimum temperature of 45°F (7°C). Store away from children. Reclose cap tightly after use. Store this product upright in a cool dry area away from direct sunlight and heat to avoid deterioration. In case of spill, sweep spilled material and flood areas with large quantities of water.

PESTICIDE DISPOSAL: Wastes resulting from the use of this product must be disposed of on site or at an approved waste disposal facility.

CONTAINER HANDLING: Non-refillable container. Do not reuse or refill container. Offer for recycling if available or reconditioning if appropriate or place in trash.

OPTIONAL MARKETING CLAIMS

- Advantages
 - o Resists extreme hydrostatic pressure
 - o Resists microbial induced corrosion with H₂S concentrations of 50 ppm
 - o Highly resistant to aggressive chemicals
 - o Can seal static hairline cracks up to 0.4 mm
 - o Becomes an integral part of the substrate and cannot be punctured or damaged
 - o Permanent
 - o No VOCs
 - Less costly to apply than most other methods
 - Added to the concrete at the time of batching and therefore not subject to weather and surface moisture restraints
- [Boy in bucket] (Note to reviewer: The following graphics is an example graphic. Another image may be substituted.)



- Independent tests showed that in concrete treated with Xypex Bio-San C-500, the microbe *Thiobacillus novellus / Starkeya novella* was substantially reduced.
- Is recommended for use in sewage systems especially in areas where H2S gas is likely to accumulate. This includes areas of high turbulence such as lift stations, drop structures, force main outflows and headworks. It will also include areas where H2S is more likely to be generated or retained including sewer lines with long retention times (flat, long, low flow), sealed or unvented manholes and various areas within waste water treatment plants. As microbial growth rates are encouraged by higher temperature and humidity, certain geographical areas will benefit from the protection provided by Xypex Bio-San C-500.
- Kills microbes that induce/cause concrete corrosion (MIC)

- Kills acid generating microbes present in sewage environments
- Manufactured in Canada
- Portland cement; Quartz; calcium dihydroxide
- Protects concrete from high concentrations of hydrogen sulphide
- protects concrete in concentrations of H2S up to 50 ppm
- Waterproofing and Protection Against Microbial Induced Corrosion and Chemical Attack
- Will protect concrete from microbial induced corrosion
- Will actively inhibit the generation of microbes thus preventing microbial induced corrosion
- Xypex Bio-San C-500 is a uniquely designed admixture for integral, long-term protection of concrete in sewage conditions with levels of H₂S that cause microbial induced corrosion.
- Xypex Bio-San C-500 is a unique, integral chemical treatment for the waterproofing, protection and improvement of concrete and is specially formulated to protect against acid and sulphate attack caused by microbial induced corrosion. Xypex Bio-San C-500 has the same unique crystalline technology as the Xypex C-Series with the addition of bio-active mineral solids. The Xypex crystalline technology consists of Portland cement and various active, proprietary chemicals that react with the moisture in fresh concrete and with the by-products of cement hydration to cause a catalytic reaction. This reaction generates a nonsoluble crystalline formation throughout the pores and capillary tracts of the concrete that becomes permanently sealed against the penetration of water and any other liquids from any direction. The acid and sulphate resistance properties of Xypex Bio-San C-500 are further enhanced by the addition of bio-active mineral solids which fix permanently within the cement matrix preventing bio-film formation and microbial induced corrosion. Xypex Bio-San C-500 significantly extends the life of sewer and waste water infrastructure by inhibiting the growth of acid-producing sewer bacteria such as Thiobacillus that cause MIC (microbial induced corrosion) as well as increasing both acid and sulfate resistance of the concrete. Test show a substantial reduction in sewer bacteria Thiobacillus Novellus / Starkeva novella / MIC causing bacteria indicating a definite antibacterial effect. Long term exposure trials showed that treated concrete had seven times less concrete mass loss compared to control samples when exposed for 6 years in a wastewater facility. The protection provided by Xypex Bio-San C-500 stays effective even if the concrete surface is abraded. Xypex Bio-San C-500 provides a broad spectrum protection against bacteria. 1 and/or 2
- XYPEX is a registered trademark of Xypex Chemical Corporation.
- The following Non-FIFRA related symbols and graphics:

XYPEX BIO-SAN C-500



¹ Excluding public health bacteria.

² Acid-producing sewer bacteria.

Technical Services

For more instructions, alternative installation methods, or information concerning the compatibility of the Xypex treatment with other products or technologies, contact the Technical Services Department of Xypex Chemical Corporation or your local Xypex Technical Services Representative.

Warranty

The Manufacturer warrants that the products manufactured by it shall be free from material defects and will be consistent with its normal high quality. Should any of the products be proven defective, the liability to the Manufacturer shall be limited to replacement of the product ex factory. The Manufacturer makes no warranty as to merchantability or fitness for a particular purpose and this warranty is in lieu of all other warranties expressed or implied. The user shall determine the suitability of the product for his intended use and assume all risks and liability in connection therewith.