



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

February 15, 2017

Angie Custer
Regulatory Affairs Specialist
Kop-Coat, Inc.
3040 William Pitt Way
Pittsburgh, PA 15238

Subject: Notification per PRN 98-10 Updating EPA product number
On the master label, since the product was transfer on 11/30/2016.
Product Name: Bazooka® Sapstain and Mold Control Product
EPA Registration Number: 92617-12
Application Date: January 18, 2017
Decision Number: 525735

Dear Ms. Custer,

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped "Notification" and will be placed in our records.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

If you have any questions, you may contact Lorena Rivas at 703-305-5027 or via email at rivas.lorena@epa.gov.

Sincerely,

A handwritten signature in blue ink, consisting of several overlapping, fluid strokes that form a stylized representation of the name Stacey Grigsby.

for

Stacey Grigsby, Acting Product Manager 34
Regulatory Management Branch II
Antimicrobials Division (7510P)
Office of Pesticide Programs

Enclosure: Notification Label

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.
GENERAL PRECAUTIONS AND RESTRICTIONS:
FOR INDUSTRIAL USE

CONSULT SAFETY DATA SHEET (SDS) BEFORE USING

DILUTE BEFORE USING
Do not apply this product in a way that will contact workers or other persons, either directly or through spray drift. Only protected handlers may be in the area during application.

Wear synthetic rubber gloves or plastic coated gloves in handling solutions and freshly treated lumber.

Treated sawdust and other wood wastes should be disposed of properly and should not be used as mulch where it will come into contact with useful living plants. Care should be taken to prevent drip or spray from contacting ornamental shrubs, trees, grass, and other desirable vegetation.

GENERAL INFORMATION
Freshly dipped or sprayed lumber should be protected from rain-washing. Dip tanks and drip aprons must be roofed, paved, and drained to prevent dilution and loss of the anti-stain solution. Treatment concentrations must be geared to achieve protection of the thickest or most valuable item being treated. The concentration of the ready-to-use solution must be adjusted to accommodate seasonal changes in the exposure, species being treated, dip tanks, and spray equipment must be properly maintained.

MIXING INSTRUCTIONS
For high-pressure spray applications: Thoroughly mix one gallon of Bazooka® Sapstain and Mold Control Product per 2 to 500 gallons of water.

For dip applications: Thoroughly mix one gallon of Bazooka® Sapstain and Mold Control Product per 20 to 1,000 gallons of water. In all cases, dilution levels will depend upon application methods, lumber species, and conditions of lumber storage. Mills should conduct tests to determine treatment requirements for their individual needs. Contact Kop-Coat for further information. When using proportioning pumps for mixing, this product should be maintained at temperatures above 50°F to prevent inaccurate mixing due to viscosity changes. Minor proportioning rate changes can be affected by changing the setting on the pump dial.

Maximum application rate is 0.8% w/w Diiodomethyl-para-Tolyl sulfone for sapstain wood preservation.
Maximum application rate is 0.7 lb Diiodomethyl-para-Tolyl sulfone for pressure treated wood application.

NOTE: With normal dip or spray application long-term control of decay cannot be achieved. This product is intended to provide decay, mold, and blue stain control during storage. Such control would not likely extend to the use site.

NOTIFICATION

92617-12

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

STORAGE AND DISPOSAL

02/15/2017

Do not contaminate water, food, or feed by storage or disposal.
Storage: Store in a closed, properly labeled container in a cool place. If static generating conditions exist, provide necessary grounding and bonding. Keep containers closed when not in use.
Pesticide Disposal: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.
Container Handling: Nonrefillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth ensuring at least one complete revolution for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times. Then offer for recycling if available.



Bazooka®

Sapstain and Mold Control Product

U.S. Patent Number 6,375,727 and 7,056,919. Additional Patents Pending

Aids in the control of blue stain, mold and decay of freshly cut lumber, dry lumber and other wood based products when properly used. Effective on softwoods including Douglas fir, White fir, Spruce, Hemlock, the Pines including both the Southern and Western Yellow Pines, Eastern and Western White Pines and many of the hardwoods.

KEEP OUT OF REACH OF CHILDREN

DANGER

| | | |
|--|---|---------|
| EPA Reg. No. 92617-12 | ACTIVE INGREDIENTS | |
| EPA Est. No. 60061-MO-1 | Diiodomethyl-para-Tolyl sulfone | 0.95% |
| | (Propiconazole) 1-[12-(2,4-dichlorophenyl)-4-propyl-1,3-dioxolan-2-yl]-methyl-1H-1,2,4-triazole | 3.50% |
| | (IPBC) 3-Iodo-2-Propynyl Butyl Carbamate | 3.50% |
| | OTHER INGREDIENTS | 92.05% |
| | TOTAL | 100.00% |
| Read Warranty on side panel before buying or using. If such terms are not acceptable, return at once unopened. | | |

| FIRST AID | |
|---------------------------|---|
| IF ON SKIN OR ON CLOTHING | <ul style="list-style-type: none">Take off contaminated clothing.Rinse skin immediately with plenty of water for 15 to 20 minutes.Call poison control center or doctor for treatment advice. |
| IF IN EYES | <ul style="list-style-type: none">Hold eye open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.Call poison control center or doctor for treatment advice. |
| IF INHALED | <ul style="list-style-type: none">Move person to fresh air.If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.Call a poison control center or doctor for further treatment advice. |
| IF SWALLOWED | <ul style="list-style-type: none">Call a poison control center or doctor immediately for treatment advice.Have a person sip a glass of water if able to swallow.Do not induce vomiting unless told to do so by a poison control center or doctor.Do not give anything by mouth to an unconscious person. |
| HOT LINE NUMBERS | <ul style="list-style-type: none">Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 800-548-0489 for emergency medical treatment information.Transportation emergency contact 800-424-9300. |
| NOTE TO PHYSICIAN | <ul style="list-style-type: none">Probable mucosal damage may contraindicate the use of gastric lavage.Corrosive to eyes and skin. Continue to flush eyes and skin with water until treatment advice is provided by poison control center or doctor. |

Kop-Coat, Inc.
Protection Products Division
5137 Southwest Avenue, St. Louis MO 63110

Net Contents

Gallons

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

Corrosive. Causes skin burns. Causes irreversible eye damage. Harmful if swallowed, absorbed through skin, or inhaled. Do not get in eyes, on skin, or clothing. Avoid breathing vapor or spray mist. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

Applicators and other handlers must wear:
1. Coveralls over long-sleeved shirt and long pants
2. Chemical-resistant footwear plus socks
3. Goggles or face shield
4. Chemical-resistant gloves (such as barrier laminate, nitrile rubber, neoprene rubber and vilon)

USER SAFETY RECOMMENDATIONS

User must:
• Follow manufactures instructions for clean/maintaining PPE. If no such instructions exist, use detergent and hot water. Keep and wash PPE separately from other laundry.
• Discard clothing and other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them.

USER SAFETY INSTRUCTIONS

Users should:
• Wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet.
• Remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing.
• Remove personal protective equipment immediately after handling this product. Wash outside of gloves before removing. As soon as possible wash thoroughly and change into clean clothing.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and aquatic invertebrates. Do not apply directly to water. Do not contaminate water when disposing equipment wastewaters. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of Environmental Protection Agency.

Until product has dried, antisapstain treated lumber must be stored under cover, indoors, or at least 100 feet from any pond, lake, stream, wetland, or river to prevent possible runoff of the product into the waterway. Treated lumber stored within 100 feet of a pond, lake stream, or river must be either covered with plastic or surrounded by a berm to prevent surface water runoff into the nearby waterway. If a berm or curb is used around the site, it should consist of impermeable material (clay, asphalt, concrete) and be of sufficient height to prevent runoff during heavy rainfall events.

PHYSICAL OR CHEMICAL HAZARDS

COMBUSTIBLE - Do not use, pour, spill, or store near heat or open flame.

IN CASE OF FIRE

Use water, fog, foam, carbon dioxide or dry chemical. Cool closed container with water.

LIMIT OF WARRANTY AND LIABILITY

We warrant this material to comply with our published specifications and to be of good merchantable quality and such as will regularly pass in the trade for goods within the description, and further warrant such goods to be fit for the normal purposes for which goods are used. We assume no responsibility that the goods concerned in this contract are fit for any particular purpose for which they are being bought outside of the general purposes of goods of the description.