



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY  
AND POLLUTION PREVENTION

May 3, 2018

Ronald W. Clawson, Jr. Ph D.  
Kop-Coat, Inc.  
436 Seventh Avenue  
Pittsburgh, PA 15238

Subject: Notification per PRN 98-10 –*Updating: Company name, Establishment number and Emergency number and verbiage for emergency number*  
Product Name: Bazooka Sapstain and Mold Control Product  
EPA Registration Number: 92617-12  
Application Date: April 3, 2018  
Decision Number: 541212

Dear Dr. Clawson, Jr.:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped "Notification" and will be placed in our records.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

If you have any questions, please contact Stacey Grigsby by phone at 703.305.6440, or via email at [grigsby.stacey@epa.gov](mailto:grigsby.stacey@epa.gov).

Sincerely,

A handwritten signature in cursive script that reads "Stacey Grigsby".

Stacey Grigsby  
Risk Manager  
Regulatory Management Branch II  
Antimicrobials Division (7510P)

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

GENERAL PRECAUTIONS AND RESTRICTIONS:

FOR INDUSTRIAL USE  
CONSULT SAFETY DATA SHEET (SDS) BEFORE USING

DILUTE BEFORE USING

Do not apply this product in a way that will contact workers or other persons, either directly or through spray drift. Only protected handlers may be in the area during application.

Wear synthetic rubber gloves or plastic coated gloves in handling solutions and freshly treated lumber.

Treated sawdust and other wood wastes should be disposed of properly and should not be used as mulch where it will come into contact with useful living plants. Care should be taken to prevent drip or spray from contacting ornamental shrubs, trees, grass, and other desirable vegetation.

GENERAL INFORMATION

Freshly dipped or sprayed lumber should be protected from rain-washing. Dip tanks and drip aprons must be roofed, paved, and drained to prevent dilution and loss of the anti-stain solution. Treatment concentrations must be geared to achieve protection of the thickest or most valuable item being treated. The concentration of the ready-to-use solution must be adjusted to accommodate seasonal changes in the exposure, species being treated, dip tanks, and spray equipment must be properly maintained.

MIXING INSTRUCTIONS

**For high-pressure spray applications:** Thoroughly mix one gallon of Bazooka® Sapstain and Mold Control Product per 2 to 500 gallons of water.

**For dip applications:** Thoroughly mix one gallon of Bazooka® Sapstain and Mold Control Product per 20 to 1,000 gallons of water. In all cases, dilution levels will depend upon application methods, lumber species, and conditions of lumber storage. Mills should conduct tests to determine treatment requirements for their individual needs. Contact Kop-Coat for further information. When using proportioning pumps for mixing, this product should be maintained at temperatures above 50°F to prevent inaccurate mixing due to viscosity changes. Minor proportioning rate changes can be affected by changing the setting on the pump dial.

Maximum application rate is 0.8% w/w Diiodomethyl-para-Tolyl sulfone for sapstain wood preservation. Maximum application rate is 0.7 lb Diiodomethyl-para-Tolyl sulfone for pressure treated wood application.

**NOTE:** With normal dip or spray application long-term control of decay cannot be achieved. This product is intended to provide decay, mold, and blue stain control during storage. Such control would not likely extend to the use site.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

**Storage:** Store in a closed, properly labeled container in a cool place. If static generating conditions exist, provide necessary grounding and bonding. Keep containers closed when not in use.

**Pesticide Disposal:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**Container Handling:** Nonrefillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth ensuring at least one complete revolution for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times. Then offer for recycling if available.



Bazooka®

Sapstain and Mold Control Product

U.S. Patent Number 6,375,727and 7,056,919. Additional Patents Pending

Aids in the control of blue stain, mold and decay of freshly cut lumber, dry lumber and other wood based products when properly used. Effective on softwoods including Douglas fir, White fir, Spruce, Hemlock, the Pines including both the Southern and Western Yellow Pines, Eastern and Western White Pines and many of the hardwoods.

KEEP OUT OF REACH OF CHILDREN

DANGER

EPA Reg. No. 92617-12  
EPA Est. No. **92617-MO-1**

Read Disclaimer on side panel before buying or using. If such terms are not acceptable, return at once unopened.

ACTIVE INGREDIENTS	
Diiodomethyl-para-Tolyl sulfone	0.95%
(Propiconazole) 1-[[(2-(2,4-dichlorophenyl)-4-propyl-1,3-dioxolan-2-yl)-methyl]-1H-1,2,4-triazole	3.50%
(IPBC) 3-Iodo-2-Propynyl Butyl Carbamate	3.50%
OTHER INGREDIENTS	<u>92.05%</u>
TOTAL	100.00%

NOTIFICATION

92617-12

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

05/03/2018

FIRST AID	
IF ON SKIN OR ON CLOTHING	<ul style="list-style-type: none"><li>Take off contaminated clothing.</li><li>Rinse skin immediately with plenty of water for 15 to 20 minutes.</li><li>Call poison control center or doctor for treatment advice.</li></ul>
IF IN EYES	<ul style="list-style-type: none"><li>Hold eye open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.</li><li>Call poison control center or doctor for treatment advice.</li></ul>
IF INHALED	<ul style="list-style-type: none"><li>Move person to fresh air.</li><li>If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.</li><li>Call a poison control center or doctor for further treatment advice.</li></ul>
IF SWALLOWED	<ul style="list-style-type: none"><li>Call a poison control center or doctor immediately for treatment advice.</li><li>Have a person sip a glass of water if able to swallow.</li><li>Do not induce vomiting unless told to do so by a poison control center or doctor.</li><li>Do not give anything by mouth to an unconscious person.</li></ul>
HOT LINE NUMBERS	<ul style="list-style-type: none"><li>For medical emergencies call your poison control center at 1-800-222-1222. Have the product container or label with you when calling a poison control center or doctor, or going for treatment. For non-emergency information concerning this product, call the National Pesticides Information Center (NPIC) at 1-800-858-7378 (NPIC Web site: <a href="http://www.npic.orst.edu">www.npic.orst.edu</a>).</li><li>For transportation emergencies, call Chemtrec at: 800-424-9300.</li></ul>
NOTE TO PHYSICIAN	<ul style="list-style-type: none"><li>Probable mucosal damage may contraindicate the use of gastric lavage.</li><li>Corrosive to eyes and skin. Continue to flush eyes and skin with water until treatment advice is provided by poison control center or doctor.</li></ul>

Kop-Coat Protection Products  
5137 Southwest Avenue, St. Louis MO 63110  
314-772-2200

Net Contents

Gallons

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS  
DANGER

**Corrosive.** Causes skin burns. Causes irreversible eye damage. Harmful if swallowed, absorbed through skin, or inhaled. Do not get in eyes, on skin, or clothing. Avoid breathing vapor or spray mist. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

Applicators and other handlers must wear:

- Coveralls over long-sleeved shirt and long pants
- Chemical-resistant footwear plus socks
- Goggles or face shield
- Chemical-resistant gloves (such as barrier laminate, nitrile rubber, neoprene rubber and vilon)

USER SAFETY RECOMMENDATIONS

User must:

- Follow manufactures instructions for clean/maintaining PPE. If no such instructions exist, use detergent and hot water. Keep and wash PPE separately from other laundry.
- Discard clothing and other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them.

USER SAFETY INSTRUCTIONS

Users should:

- Wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet.
- Remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing.
- Remove personal protective equipment immediately after handling this product. Wash outside of gloves before removing. As soon as possible wash thoroughly and change into clean clothing.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and aquatic invertebrates. Do not apply directly to water. Do not contaminate water when disposing equipment wastewaters. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of Environmental Protection Agency.

Until product has dried, antispain treated lumber must be stored under cover, indoors, or at least 100 feet from any pond, lake, stream, wetland, or river to prevent possible runoff of the product into the waterway. Treated lumber stored within 100 feet of a pond, lake stream, or river must be either covered with plastic or surrounded by a berm to prevent surface water runoff into the nearby waterway. If a berm or curb is used around the site, it should consist of impermeable material (clay, asphalt, concrete) and be of sufficient height to prevent runoff during heavy rainfall events.

PHYSICAL OR CHEMICAL HAZARDS

**COMBUSTIBLE** - Do not use, pour, spill, or store near heat or open flame.

IN CASE OF FIRE

Use water, fog, foam, carbon dioxide or dry chemical. Cool closed container with water.

DISCLAIMER

To the extent consistent with applicable law, seller (whether manufacturer, distributor, or other) makes no warranty express or implied, including the implied warranty of merchantability AND IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE regarding this product except the composition as set forth in the ingredient statement herein, and shall not be liable for LOST PROFITS, LOST PRODUCTION, LABOR COSTS, TRANSPORTATION CHARGES, OR ANY special, consequential, INCIDENTAL OR DELAY damages, the exclusive remedy being the replacement of the product. To the extent consistent with applicable law, buyer or user assumes all risk of possession, handling or use of this material when such use and/or handling is contrary to label instructions.