



U.S. ENVIRONMENTAL PROTECTION AGENCY
Office of Pesticide Programs
Antimicrobials Division (7510P)
1200 Pennsylvania Ave., N.W.
Washington, D.C. 20460

EPA Reg. Number:

94602-44

Date of Issuance:

1/25/24

NOTICE OF PESTICIDE:

Registration
 Reregistration
(under FIFRA, as amended)

Term of Issuance:

Conditional

Name of Pesticide Product:

GBS Q-1776-5% WT

Name and Address of Registrant (include ZIP Code):

Dennis Daun
Grey Beard, LLC
Electronic Transmittal: [Dennis.Daun@greybeardllc.com]

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Antimicrobials Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA).

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA section 3(c)(7)(A). You must comply with the following conditions:

1. Submit and/or cite all data required for registration/reregistration/registration review of your product under FIFRA when the Agency requires all registrants of similar products to submit such data.

Signature of Approving Official:

Luisa Samalot-Freire, Acting Product Manager 31
Regulatory Management Branch II, Antimicrobials Division
(7510P)

Date:

1/25/24

2. You are required to comply with the data requirements described in the DCI or EDSP Order identified below:
 - a. Alkyl (60%C14, 30%C16, 5%C12, 5% C18) dimethyl benzyl ammonium chloride GDCI-069104-30081
 - b. Alkyl (60%C14, 30%C16, 5%C12, 5% C18) dimethyl benzyl ammonium chloride GDCI-069104-1739
 - c. Dialkyl (60%C14, 30%C16, 5%C12, 5% C18) methyl benzyl ammonium chloride GDCI-069119-30894
 - d. Dialkyl (60%C14, 30%C16, 5%C12, 5% C18) methyl benzyl ammonium chloride GDCI-069119-1743

You must comply with all of the data requirements within the established deadlines. If you have questions about the Generic DCI or EDSP Order listed above, you may contact the Reevaluation Team Leader (Team 36): <http://www2.epa.gov/pesticide-contacts/contacts-office-pesticide-programs-antimicrobial-division>

3. Make the following label changes before you release the product for shipment:
 - Revise the EPA Registration Number to read, "EPA Reg. No. 94602-44."
4. Submit one copy of the final printed label for the record before you release the product for shipment.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under FIFRA and is subject to review by the Agency. See FIFRA section 2(p)(2). If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) lists examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process, FIFRA section 12(a)(1)(B). Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Assurance.

If you fail to satisfy these data requirements, EPA will consider appropriate regulatory action including, among other things, cancellation under FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions. A stamped copy of the label is enclosed for your records. Please also note that the record for this product currently contains the following CSFs:

- Basic CSF dated 08/08/2023
- Alternate CSF 1 dated 08/08/2023

Page 3 of 3
EPA Reg. No. 94602-44
Action Case No. 00436343

If you have any questions, please contact Karen Leavy by phone at (202)-566-0668, or via email at Leavy.Karen@epa.gov or Samalot.luisa@epa.gov

Enclosure

Gray Beard, LLC

1931G Rohlwing Road • Rolling Meadows, IL 60008 • 800-837-0499

GBS 1776-5% WT

EPA Reg. No. 94602-
EPA Est. No

(Note to Reviewer: Marketing claims may be used on the front panel.)

ACTIVE INGREDIENTS:

Alkyl (60%C ₁₄ , 30%C ₁₆ , 5%C ₁₂ , 5% C ₁₈) dimethyl benzyl ammonium chloride	4.98%
Dialkyl (60%C ₁₄ , 30%C ₁₆ , 5%C ₁₂ , 5% C ₁₈) methyl benzyl ammonium chloride	0.02%
OTHER INGREDIENTS	<u>95.00%</u>
TOTAL:	100.00%

ACCEPTED

01/25/2024

Under the Federal Insecticide, Fungicide
and Rodenticide Act as amended, for the
pesticide registered under
EPA Reg. No. 94602-44

{Weight Approx. 8.3 lbs./gallon}

**KEEP OUT OF REACH OF CHILDREN
DANGER {PELIGRO}**

See {{left} {back} {side} {right} {insert} {panel} {of label}} {below} for {additional}
{precautionary statements}}.

(Note to Reviewer: In accordance with 40 CFR 156.68(d), all first aid statements, as prescribed, will appear on the front panel of the product label.)

FIRST AID

In case of emergency, call a poison control center or doctor for treatment advice. Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible.

IF SWALLOWED: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

{For {{chemical} {and} {or} {medical} {and} {or} {environmental}} emergencies, call {insert name and/or number of emergency contact} {hours of operation} {24 hours a day} {7 days a week}}.

(Note to Reviewer: This referral statement may be organized in any order to be grammatically correct.)

{{Consult} {See {additional} {sheet} {insert} {inside} {outer container} {Product Information} {Bulletin} for {other} {directions for use} {and} {information} {claims} {organisms} {applications}}.

Manufactured for: Gray Beard LLC
1931G Rohlwing Road
Rolling Meadows, IL 60008

Net Contents:

{{Batch} {Lot} No} {Manufacturing Date}:
{Product of USA} {Made in the USA}

MARKETING CLAIMS

(Note to Reviewer: Marketing text is considered optional. Commas and the words “and” “or” can be added to phrases to make text grammatically correct.)

{LOCATIONS/SURFACES}

(Note to Reviewer: The locations/surfaces have been grouped for space purposes only; they can be used individually or grouped together in any order however at least **one** location/surface must appear on the label. In the case where one or more location/surface is chosen, an “and” “&” “or” may be used to link locations/surfaces.) In the case where the location/surface is not registered in the State of California the statement “(Not for use in CA.)” may be added to the location/surface.)

This product is for use in (insert location)
For use {in} {on} (insert location/surface).

{LOCATIONS}

{Swimming Pool}

- {Containerized} Fountains (**Note to Reviewer:** “Containerized” must be used in CA.)
- Ponds
- Swimming pools
- Whirlpools, spas, hot tubs

{Water Treatment} {Not for use in California}

- Air washers
- Auxiliary water systems
- Commercial recirculating cooling water towers
- Drilling, completion and workover fluids systems
- Gas production and transmission pipeline and systems
- Gas storage wells and systems
- Hydrotesting facilities
- Industrial {and/or} {commercial} recirculating cooling towers.
- Oil field water flood or salt water disposal systems {and fracturing fluid systems}
- Oil field injection and waste water
- Once through fresh {and sea} water cooling systems
- Once through freshwater systems
- Packer fluid systems
- Pipeline pigging and scraping operations
- Recirculating water systems
- Retort water systems
- Waste water systems
- Water cooling systems
- Paper manufacturing
- Pulp and paper mills {water processing systems}
- Paper and paperboard (*Not for use in CA.*)

[{WATER TREATMENT} {AND} {OIL AND GAS}] MARKETING CLAIMS

{Not for use in California}

(Note to Reviewer: The following marketing claims may be used with the prefix “This product” or “This product is {a} {an}”.)

- Algaecide
- Aids in the control of bacterial, fungal and algal slimes in evaporative condensers, heat exchange water systems, industrial and commercial cooling towers, air washers, retorts, pasteurizers, and industrial water scrubbing systems.
- Water treatment microbiocide for industrial and/or commercial recirculating cooling water towers, retort water systems and flood systems and fracturing fluids.
- Aids in the control of bacterial, fungal and algal slimes in evaporative condensers, heat exchange water systems, industrial and commercial cooling towers, Influent systems such as flow through filters and lagoons, industrial water systems and brewery pasteurizers.
- Aids in the control of bacterial, fungal and algal slimes in retort water systems
- Water treatment microbiocide for industrial and/or commercial recirculating cooling water towers, and oil field flood/salt water disposal systems and fracturing fluids.
- Microbiocide for use in controlling sulfate-reducing bacteria and slime forming bacteria in oil well drilling, oil field processing applications, oil field water systems, oil and gas productions and transmission pipelines and systems, and gas storage fields

and equipment; such as steam-injection water holding tanks, flood water, injection water, holding pond water, disposal-well water, water holding tanks, fuel storage tanks and related refinery and oil field closed systems, industrial recirculating water handling systems.

- A water treatment microbiocide for retort water systems.
- Water treatment microbiocide for use in controlling microorganisms such as sulfate-reducing bacteria, slime forming bacteria, algae, and mold and yeast in oil and gas systems, and building and industrial cooling tower systems.
- Microbiocide for use in controlling slime forming bacteria, sulfate-reducing bacteria (SRB) and fungi (yeast and molds) and algae in air washers and industrial scrubbing systems, process water systems including those that contain reverse osmosis membranes and in service water and auxiliary systems and heat transfer systems and in wastewater systems including wastewater sludge and holding tanks, and in paper mills and paper mill process water systems and water based coatings for paper and paperboard.
- Controls, algae and algal slime growth in industrial and/or commercial recirculating cooling water towers and once through freshwater cooling systems.
- Effective against the growth of algae.
- For control of algae, algal, fungal and bacterial slimes in recirculating water systems, auxiliary water and waste water systems and water cooling systems, oil field water flood systems.
- Has been designed specifically for control of sulfate-reducing bacteria that contribute to souring, the production of sulfide, and abiotic corrosion in water cooling systems, paper mill process water systems, oil field systems, gas production and transmission pipelines and systems.
- Kills and prevents algae.
- The residual effectiveness of this algaecide tends to stabilize the total chemical treatment system.
- This product is effective for the control of odor-forming and slime-forming bacterial, fungi and algae in auxiliary service water systems such as fire protection systems and pump or screen bays, waste water systems such as storage tanks, storage piles, associated piping, setting ponds or lagoons, transport spillways or canals and disposal wells.
- This product reduces bacterial contamination and degradation of fracturing fluids and gels used in oil and gas well stimulations.

SWIMMING POOL TREATMENT MARKETING CLAIMS

(Note to Reviewer: *The following marketing claims may be used with the prefix "This product" or "This product is {a} {an}."*)

- Algaecide
- Kills and prevents algae.
- For control of algae {and algae slime} growth in swimming pools, {outside} spas/whirlpools/hot tubs {baths}, {containerized} {decorative} fountains {"Containerized" must be used for products used in California}
- The residual effectiveness of this algaecide tends to stabilize the total chemical treatment system.
- Compatible with most {swimming pool} chemicals {used in pool water} {and} {when used as directed} is not harmful to the metal, paint, plastic or non-porous glazed tile {surfaces} {of swimming pool}. will not damage tile, concrete, metal or plastics.
- Keeps pool water free and sparkling, clear of visible green and blue-green algae, slime {slime} and green brown colors. (*Not for use in CA.*)
- This product improves filter operation and reduces need for other chemicals.
- This product is formulated to complement swimming pool water being treated with normal chlorine systems.
- Effective against growth of algae
- Aids in maintaining pool water clarity and sparkle.
- The residual effectiveness of this algaecide tends to stabilize the total chemical treatment system.
- Especially effective against growth of algae and being non-volatile, aids in maintaining pool water clarity and sparkle
- Formulated to complement swimming pool water being treated with [{BioGuard Softswim System,} {Bacquacil,} {and} {other non-halogen systems}].
- Supports your overall pool chemical maintenance program, offering a residual effectiveness that protects your pool against algae formation while keeping your pool water sparkling clear.
- This product is effective in controlling the growth of the following types of algae: Chlorella pyrenoidosa (green algae), Phormidium inundatum (blue-green algae) and Phormidium retzii.
- Protects the unattended pool when you're away (refer to Vacation Treatment section under Directions For Use).

PULP AND PAPER MILL MARKETING CLAIMS

{Not for use in California}

(Note to Reviewer: *The following marketing claims may be used with the prefix "This product" or "This product is {a} {an}."*)

- Is used to inhibit fungal growth, which causes discoloration, odor and degradation of paper, paperboard, or wet lap.
- Can be used as a slimicide in the manufacture of paper and paperboard, depending on the type of stock, quality of raw water, complexity of the system, and degree of contamination.
- For control of bacterial and fungal slimes in pulp mills, paper mills and paper manufacturing.

- This product can be used as a slimicide in the manufacture of paper and paperboard, depending on the type of stock, quality of raw water, complexity of the system, and degree of contamination. Do not use to treat paper or paperboard which will contact food.
- This product is used to inhibit fungal growth which causes discoloration, odor and degradation of paper or paperboard or wet lap.

GENERAL MARKETING CLAIMS

(Note to Reviewer: The following marketing claims may be used with the prefix “This product” or “This product is {a} {an}”.)

- Efficient and non-staining when used as directed.
- Cleans exterior surfaces {with no pressure washing or scrubbing required. Apply with pump up garden sprayer.}
- Mold and mildew and algae stain remover
- No Bleach
- Is non-staining
- Will not damage tile, concrete, metal or plastics.

PACKAGING CLAIMS

- Concentrate{d}
- 5% Concentration
- Make (insert value) [{Gal.} {quarts} {Containers}]
- Easy to use.
- Economy size. **(Note to Reviewer:** To be used on applicable container)
- Is an economical concentrate.
- 1 gal. treats 50,000 gal. *(For swimming pool applications.)*
- This [{container} {bottle}] is made of {at least} (x)% post-consumer recycled plastic.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

(Note to Reviewer (General Considerations): Numbered instructions will be used if label space permits, otherwise may appear in paragraph format. Unit abbreviations can be spelled out. When choosing optional text, appropriate punctuation can be inserted or deleted. Equivalent use dilution ratios may be substituted within the directions.)

{Please read entire label and use strictly in accordance with precautionary statements and directions.}

(Note to Reviewer: In the case where a direction for use is not registered in the State of California, as noted in the section heading, the statement “(Not for use in CA.)” may be added to the relevant text.)

WATER TREATMENT

{Not for use in California}

Do not use water containing residues from use of this product to irrigate crops for food or feed.

(Note to Reviewer: The following sentence must be used with the air washer use listed in the direction:)

For use only in industrial air washers and air washer systems which have mist-eliminating components.

INDUSTRIAL {{AND/OR} COMMERCIAL} RECIRCULATING COOLING WATER TOWERS, RETORT WATER SYSTEMS, EVAPORATIVE CONDENSERS, HEAT {{EXCHANGE} {TRANSFER}} {WATER} SYSTEMS, INFLUENT SYSTEMS:

For best results, clean heavily contaminated systems before treatment with this product. If soap or anionic detergent is used, rinse thoroughly before charging with this algaecide. {Cooling tower waters that are inherently low in algae growth and bacteria count may be adequately controlled by the lower range of these dosages.} Repeat every 7 days or increase frequency if needed. Should slime develop again, repeat initial dosage.

1. **Dosing Location:** This product is to be applied at a point in the system where it will be uniformly mixed, such as [{the basin area,} {the sump,} {or another reservoir or collecting area.}]
2. **Dosing Conditions:** This product must be applied when the system is in jeopardy of being affected or after cleaning systems where efficiency is already impaired. {Tower bleed off valves must be closed to permit a retention time of 4 hours.}
3. **Method of Application:**
 - a) **INTERMITTENT OR SLUG METHOD**

Initial Dose: When the system is noticeably fouled, apply 51.2 – 102.4 fl. oz. of this product per 1,000 gal. of water {(20-40 ppm active)} in the system. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 12.8 – 38.4 fl. oz. of this product per 1,000 gal. of water {(5-15 ppm active)} in the system weekly or as needed to maintain control.

b) **MODIFIED INTERMITTENT METHOD**

Initial Dose: When the system is noticeably fouled, apply 51.2 – 102.4 fl. oz. of this product per 1,000 gal. of water {(20-40 ppm active)} in the system. Apply half this initial dose when half of the water in the system has been lost by blowdown.

Subsequent Dose: When microbial control is evident, add 12.8 – 38.4 fl. oz. of this product per 1,000 gal. of water {(5-15 ppm active)} in the system. Apply half this initial dose when half of the water in the system has been lost by blowdown.

c) **CONTINUOUS FEED METHOD**

Initial Dose: When the system is noticeably fouled, apply 51.2 – 102.4 fl. oz. of this product per 1,000 gal. of water {(20-40 ppm active)} in the system.

Subsequent Dose: Maintain this treatment by starting a continuous feed of 12.8 – 38.4 fl. oz. {of this product per 1,000 gal. of water {(5-15 ppm active)} lost by blowdown.

ONCE THROUGH FRESH {AND SEA} WATER COOLING SYSTEMS: Use of this product in either public/municipal or single or multiple family private/residential potable/drinking water systems is strictly prohibited. Use of the product in any cooling water system that discharges effluent within ¼ mile of either public/municipal or single or multiple family private/residential potable/drinking water intake is strictly prohibited

{For best results, slug feed. The frequency of addition of microbicide needed depends on many factors. To optimize your use of water treatment microbicide, follow this procedure.}

1. **Dosing Location:** This product is to be applied at a point in the system where it will be uniformly mixed, such as at the sump.
2. **Dosing Conditions:** This product must be applied when the system is in jeopardy of being affected or after cleaning systems where efficiency is already impaired.
3. **Method of Applications:**
 - a) Wear safety glasses, rubber gloves and impervious apron.
 - b) To reduce foaming, mix 2 parts of water to 1 part of this product.
 - c) {Use} {Add} 1.5 to 15 fl. oz. {(0.6- 6 ppm on an active quaternary basis)} per 1,000 gal.
 - d) Do not discharge without performing proper deactivation.
 - e) Treatment time cannot exceed 120 hours/application nor exceed 4 times per year.
 - f) Avoid oxidizers and reducing agents. Product is cationic and must not be mixed with soap or anionic surfactants.

(OR)

{Note to reviewer: Alternate Method of Application language can be used in place of item #3 directly above.}

3 **Method of Application:**

INTERMITTENT OR SLUG METHOD

Initial Dose: When the system is noticeably fouled, apply 1.5 – 15 fl. oz. of this product per 1000 gal. of water {(0.6 - 6 ppm active)} based on system flow rates. The minimum treatment is 6 to 24 hours. Repeat until control is achieved. Deactivation must be conducted prior to discharge from the system.

Subsequent Dose: When microbial control is evident, add 0.75 – 7.5 fl. oz. of this product per 1000 gal. of water {(0.3 - 3 ppm active)} based on system flow rates on an as needed basis to maintain control. Frequency of feed must be tied to an in-plant monitoring program for macro cowling growth. Deactivation must be conducted prior to discharge from the system.

{Note to Reviewer: Deactivation instructions must be used with the above Once Through directions for use.}

DEACTIVATION: Use bentonite clay at the minimum ratio of 5 ppm clay to 1 ppm product. Deactivation must occur prior to discharge of the NPDES outfall. Do not apply this product more than 4 times a year.

AUXILIARY SERVICE WATER AND WASTE WATER SYSTEMS: Add 0.1. – 3.6 gal. of this product per 1,000 gal. of water {(5-180 ppm active)} in the system continuously. This product must be added to the system at a point of uniform mixing by slug or intermittent feed or by spraying onto a waste pile. The frequency of feed or spray and the duration of treatment will depend upon the severity of the contamination. Additions to water systems must be made during the pumping operation and as close to the pump as possible to ensure adequate mixing.

{OIL FIELD, GAS PRODUCTION AND TRANSMISSION PIPELINE AND SYSTEMS}

{Not for use in California}

{{OIL FIELD} {GAS PRODUCTION} {TRANSMISSION PIPELINE} {AND} {SYSTEMS}}: Specific treatment requirements vary among oil and/or gas field sites and subsystem components. {Oil field fluids and subsystems most commonly requiring microbial contamination control are raw water sources, separators, ballasts, storage and mixing tanks, screens, surface injection equipment, production equipment {(such as injection and production piping casting, completion and valving)} and the formation itself.} The primary point of treatment will vary among oil and/or gas field operations depending on the site problems, water-flood treatment methods and equipment. This product must be added where it will disperse rapidly and uniformly to the desired area of treatment.

Additions of this product must be made with the proper type of metering pump equipment, suction (low pressure) side of pumping

equipment or similar device. This product must be added to the system by slug, continuous or on an intermittent basis, depending on the degree of system fouling.

{OIL FIELD} WATER FLOOD {or SALT WATER} {DISPOSAL} SYSTEMS, AND FRACTURING FLUIDS: This product must be added to the water flood at a point of uniform mixing.

1. **Continuous Use:** Add 1 – 4 gal. of this product per 10,000 gal. of water {(5-20 ppm active)} to control slime forming and sulfate reducing bacteria. Levels for effective control will vary depending on conditions at the site.
2. **{Slug Dose} {Intermittent Use}:** {[Add] {Dose}] at a rate of 1 – 4 gal. of this product per 10,000 of water {(5-20 ppm active)} for 4 to 8 hours per day, one to four times a week as needed to maintain control.
3. **Treatment of flow back return water {(Post Hydraulic Fracturing)}:** Dose at a rate of 1 – 4 gal. of this product per 10,000 gal. of water {(5-20 ppm active)} for 4-8 hours per day, one to four times a week as needed to maintain control.

OIL FIELD INJECTION AND WASTE WATER: This product must be added to the water handling system at a point of uniform mixing such as the area of addition of make-up water to the holding tank.

Method of Application:

1. **Continuous Injection:** Add at a rate of 38.4 – 76.8 fl. oz. of this product per 1,000 gal. of water {(15 - 30 ppm {active})} when system is noticeably fouled. When microbial control is evident, add 38.4 fl. oz. of this product per 1,000 gal. of water {(15 ppm {active})} to maintain control.
2. **Batch Treatment:** Add at a rate 1.2 – 3.6 gal. of this product per 1,000 gal. of water {(60- 180 ppm {active})} over a period of 4 – 6 hours one or more times per week when the system is noticeably fouled. When microbial control is evident, add this product at 0.6 – 1.8 gal. per 1,000 gal. of water {(30 - 90 ppm {active})} over a period of 4 – 6 hours one or more time per week.

{OIL AND GAS PRODUCTION AND TRANSMISSION PIPELINES AND SYSTEMS: For the control of sulfate-reducing bacteria and slime forming bacteria, this product must be added to a gas production or transmission pipeline via direct injection at a point where uniform and maximum distribution will occur. The application must be conducted to ensure maximum distribution of the product through the internal surface of the pipeline by adding an amount of biocide which eventually comes out the other end of the pipeline. Criteria for success of the treatment will be reduction in bacterial count and/or corrosion rates. To facilitate application, it is desirable to dilute the product with an appropriate solvent immediately before use. The concentration in the solvent must not fall below an active concentration range of 500 - 5000 ppm active based on the volume of water in the pipeline. Injections to the system must be weekly, or as needed to maintain control.)

GAS STORAGE WELLS AND SYSTEMS: Treat individual injection wells with 1.3 - 20 gal. of this product per 1,000 gal. of water {(65-1,000 ppm active)}. Update treatment rate as needed. This product must be diluted by the water present in the formation. Injection takes place before gas is injected and may be repeated yearly or as needed to maintain control.

PIPELINE PIGGING AND SCRAPING OPERATIONS: Add this product to slug water immediately following the scraper {(keep the water volume to a minimum and contained between the scraper and the {[following] {trailing}] pig)}. Add an effective concentration of 0.15 – 1 gal. of product per 100 gal. of water {(75-500 ppm active)} depending on the length of the pipeline and the severity of the biofouling.

DRILLING {(MUDS)}, COMPLETION AND WORKOVER FLUIDS SYSTEMS: This product is to be added to these fluid systems at a point of uniform mixing, such as a circulating, holding or mud tank. Levels for effective control will vary depending on conditions at the site and the severity of the contamination.

1. **Initial treatment:** Add 1.3 - 20 gal. of this product per 1,000 gal. of freshly prepared fluid {(65-1,000 ppm active)}.
2. **Maintenance dosage:** Add 1.3 - 20 gal. of this product per 1,000 gal. of freshly prepared fluid {(65-1,000 ppm active)}.

PACKER FLUIDS: This product is to be added to the packer fluid at a point of uniform mixing such as a circulating holding tank {or} {other mixing device locations}. Add 1.3 - 20 gal. of this product per 1,000 gal. to a freshly prepared packer fluid {(65-1,000 ppm active)}. Levels for effective control vary depending on conditions at the site and the severity of contamination. Seal the treated packer fluid in the wall between the casing and the production tube.

HYDROTESTING: Treat water used to hydro test pipelines or vessels by adding 1.3 - 20 gal. of this product per 1,000 of water {(65-1,000 ppm active)} depending on the water quality and length of time the equipment will remain idle.

SWIMMING POOL

(Note to Reviewer: The following statement must be used if the label contains any pool, spa, hot tub, or fountain directions.)

Before draining a treated [pool], [spa], [hot tub] or [fountain] contact your local sanitary sewer and storm drain authorities and follow their discharge instructions. Do not discharge treated [pool], [spa], [hot tub] or [fountain] water to any location that flows to a gutter, storm drain or natural water body unless discharge is allowed by state and local authorities.

This product is compatible with most chemicals normally used in swimming pool maintenance. However, in its concentrated form, this chemical must not come in contact with high concentrations of chlorine or any other oxidizer. **DO NOT MIX THIS PRODUCT AND CHLORINE OR ANY OTHER OXIDIZER TOGETHER** before adding to the pool. These chemicals must be handled separately.

This product was formulated to complement most swimming pool sanitizers. This product is not a stand-alone product. It must be used with either halogen based or non-halogen based pool sanitizers. When using other products as outlined in directions for this product, always follow directions on those products.

This product requires no special equipment for treating swimming pool water. The correct use dilution may be added directly to the pool in any spot or added to the water circulation equipment. This product works the best when added by itself directly to pool water by pouring around entire outside perimeter of pool.

Do not allow swimming in pool for at least 15 minutes after this product has been applied.

Ensure all pool equipment is working properly. Backwash the filter system following manufacturer's directions. Adjust pH between 7.2 - 7.6. Check for metals and if present add stain and scale inhibitor to prevent staining of pool surface due to metals. {In a chlorine treated pool, add stabilizer to establish a minimum level of 40 - 50 ppm to reduce the degradative effects of sunlight upon the chlorine residual. Check chlorine residual and adjust to 1 - 3 ppm.}

TO DETERMINE POOL CAPACITY

Rectangular Pools: Length (times) width (times) average depth (in feet) (times) 7.5 (equals) gal.

Round and Oval Pools: Long diameter (times) short diameter (times) average depth (in feet) (times) 5.9 (equals) gal.

(Note to Reviewer: Appropriate dilution rates may be substituted as long as they are equivalent dilution rates.)

{SWIMMING POOL TREATMENT DILUTION TABLE: (Note to reviewer: This DILUTION TABLE is optional.)}

Swimming Pool Capacity Gallon of Water	Initial Treatment	Maintenance Dose Booster Dose
2,500	12.8 fl. oz.	3.2 fl. oz.
5,000	25.6 fl. oz.	6.4 fl. oz.
10,000	51.2fl. oz.	12.8 fl. oz.
15,000	76.8 fl. oz.	19.2 fl. oz.
20,000	102.4 fl. oz.	25.6 fl. oz.
25,000	128.0 fl. oz.	32.0 fl. oz.
30,000	153.6 fl. oz.	38.4 fl. oz.
40,000	204.8 fl. oz.	51.2 fl. oz.
50,000	256.0 fl. oz.	64.0 fl. oz.

INITIAL APPLICATION FOR SWIMMING POOLS {{USING}} {{HALOGENATED}} {NON-HALOGENATED}} {SANITIZERS}}:

1. Backwash the filter thoroughly.
2. Vacuum algae debris and thoroughly brush pool.
3. Add 2 gal. of this product to each 50,000 gal. of water {{(51.2 fl. oz. per 10,000 gal.)}}.
4. Vacuum pool after 24 hours to remove dead algae.
5. If algae is still visible repeat dose (steps 3 & 4) as necessary until pool is free of visible algae.
6. Allow the filter to run for at least six (6) hours after adding algaecide. During this period, swimmers must not be allowed into the water.
7. Once algae are under control, clean filter and return to normal operation.

MAINTENANCE APPLICATION: Add 0.5 gal. of this product per 50,000 gal. of water {{(or equivalent use dilution)}} every 3 - 5 days. If high temperatures prevail or pool has unusually heavy use, add maintenance dose more frequently.

{For persistent algae, {or slime producing organisms} add 0.5 gal. of this product per 50,000 gal. of water {{(or equivalent use dilution)}} into the skimmer with the filter pump running. After 1 minute shut off pump and allow the system to remain off overnight. The following day, restart the filter pump and add 0.5 gal. of this product per 50,000 gal. of water {{(or equivalent use dilution)}} to the pool. Run filter continuously for 24 - 48 hours brushing the sides and bottom of the pool frequently.}

BOOSTER APPLICATION: Add 0.5 gal. of this this product per 50,000 gal. of water {{(or equivalent use dilution)}} after a heavy or prolonged rainfall or when there is a heavy bathing load.

The directions must be followed even when the pool is not in use. If algae growth is noticeable, apply initial dose. {For persistent algae {or slime producing organisms} add 0.5 gal of this product per 50,000 gal. of water {{(or equivalent use dilution)}} in to the skimmer with the filter pump running. After one minute shut off pump and allow the system to remain off overnight. The following day, restart the filter pump and add 0.5 gal. of this product per 50,000 gal. of water {{(or equivalent use dilution)}} to the pool. Run filter

continuously for 24-48 hours brushing the sides and bottom of the pool frequently.}

VACATION TREATMENT: When you are going to be away for 1 week or more add 51.2 fl. oz. of this product per 10,000 gal. of water {(or equivalent use dilution)} for every week unattended. Pour product around the edges of the shallow end of the pool, if shock is also being applied in the deep end of pool.

WINTERIZING TREATMENT {Not for use in California}: {When swimming pool season is over, add 160 fl. oz. of this product per 10,000 gal. of water {(or equivalent use dilution)} left in pool. This dose helps provide a measure of control of algae growth during the winter months. {Clean pool water line, shut down filter, drain pump and winterize as per manufacturer’s instructions. Cover pool with solid cover, if possible. Pools without a solid cover may need a second treatment later in the non-swimming season.}}

FOR ALGAE TREATMENT OF [{SPAS} {WHIRLPOOLS} {HOT {TUBS} {BATHS}}] {Not for use in California}

Initial Dose: Add 25.6 fl. oz. of this product per 5,000 gal. of pool water {(or equivalent use dilution)}. Initial dose is used upon filling of [{spa} {whirlpool} {hot {tub} {bath}}].

Maintenance Dose: Add 6.4 fl. oz. of this product per 5,000 gal. of water {(or equivalent use dilution)}. Maintenance dose must be added at 3 – 5 day intervals. If high temperatures prevail or [{spa} {whirlpool} {hot} {tub} {bath}] has unusually heavy use, add maintenance dose more frequently. Drain and clean [{spa} {whirlpool} {hot} {tub} {bath}] at least once a month or as needed depending upon bather load.

BIRD BATHS {Not for use in California}: DO NOT use when fish are present. Clean to remove algae growth prior to filling birdbath and spray the exposed surfaces with a solution of 2 fl. oz. of this product per gal. of water {(or equivalent use dilution)}. Allow to air dry and brush off dead algae.

WALKWAYS {Not for use in California}: This product will inhibit the growth of algae on hard, non-porous walkways. For heavy infestations, spray or swab a solution of 2 fl. oz. of this product per gal. of water {(or equivalent use dilution)}. Let stand for an hour or more then brush and wash away dead algae. Soak area again with the solution. Do not rinse. Allow to dry on the surface and repeat application when algae growth returns. For sprayer applications, use a coarse spray only. Allow surfaces to remain wet for 10 minutes the air dry. Prepare a fresh solution daily or when visibly dirty.

FOUNTAIN AND POOL TREATMENT DILUTION TABLE: (Note to Reviewer: This DILUTION TABLE is optional.

Fountain or Pools Capacity in gallons of water	Initial Treatment	Maintenance Dose Booster Dose
195	1 fl. oz.	0.25 fl. oz.
390	2 fl. oz.	0.5 fl. oz.
781	4 fl. oz.	1 fl. oz.
1,562	8 fl. oz.	2 fl. oz.
3,125	16 fl. oz.	4 fl. oz.
6,250	32 fl. oz.	8 fl. oz.
12,500	64 fl. oz.	16 fl. oz.
25,000	128 fl. oz.	32 fl. oz.

FOR ALGAE TREATMENT OF {CONTAINERIZED} FOUNTAINS, WATER DISPLAYS, DECORATIVE AND SWIMMING POOL/PONDS: AND POOLS {“Containerized” must be used for products used in California}: DO NOT use when fish or other wildlife are present. This product is not to be used in open water ways connected to larger watersheds or in waters that serve as natural habitats for aquatic and amphibious organisms.

Remove floating algae by raking, dragging with cable or chain, skimming, or any other suitable method. {It is more economical to remove floating type algae before the water is treated.}

{{Treat water by “dribbling” this product using 1 part to 4 parts water {(or equivalent use dilution)} around the edges where visible algae growth is evident.} {Apply 64 fl. oz. of this product per 12,500 gal. of water {(or equivalent use dilution)}.}} Apply prepared solution liberally along the windward side to float across the water and along the leeward side where contamination gathers. Each week repeat maintenance dosage or add this product using a test kit to maintain the proper concentration.}

Initial Dose: Add 64 fl. oz. per 12,500 gal. of water {(or equivalent use dilution)} at any point that is convenient, such as the bowl, pool, or sump.

Weekly Maintenance Dose: Add 16 fl. oz. of this product per 12,500 gal. of water {(or equivalent use dilution)} every 3 – 5 days as to maintain 0.5 ppm active. Each month drain and clean bowl. Refill with fresh water and repeat initial treatment. Draining removes airborne dirt, dust, contamination and alkali buildup.

{**Note:** Algae does not usually grow in water that is 5 feet or more in depth. However, floating type algae may grow on pond weeds that grow on the surface of the water.}

PULP AND PAPER MILLS {AND PAPER MANUFACTURING}

{Not for use in California}

Do not use to treat paper or paperboard which will contact food

SLIMICIDE APPLICATIONS: Do not use to treat paper or paperboard which will contact food. Apply this product to the paper making system at a point of uniform mixing such as, thin, or thick stock chests, save-all tank, process tank or whitewater tank.

Initial Dose: When system is noticeably contaminated, add 2 - 400 gal. of this product per 100,000 gal. of whitewater {(1 - 200 ppm active)} to be treated as a continuous or slug dose. Repeat until control is achieved. Heavily fouled systems must be boiled out prior to initial treatment.

Subsequent Dose: When microbial control is evident, add 2- 400 gal. of this product per 100,000 gal. of whitewater {(1 - 200 ppm active)} to be treated as necessary to maintain control.

CONTROL OF BACTERIAL, FUNGI/MOLD AND ALGAE {SLIME} ON PULP, PAPERBOARD, AND WET LAP: Application of this product must be made at a point in the system where mixing action is good or can be made at the size press or water box. For inhibition of wet lap or sheet pulp this product must be applied to the dewatered pulp surface via applicator rolls or showers.

Dosing Application: Apply at a rate of 4 - 200 lbs. of this product per ton {(dry basis)} of pulp or paperboard produced. This product may be drip fed continuously from the drum, diluted, and showered to the wet sheet or fed by suitable pumps.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage and disposal.

{PESTICIDE} STORAGE: Store only in original container. Keep this product under locked storage sufficient to make it inaccessible to children or persons unfamiliar with its proper use. Keep from freezing.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

CONTAINER HANDLING:

{Note to Reviewer: One or more of the following paragraphs for Container Handling will be selected, depending on packaging use/type.}

{For non-refillable containers equal to or less than 5 gal.}

Non-Refillable Container. Do not reuse or refill this container. Triple rinse container {(or equivalent)} promptly after emptying. Triple rinse as follows: Fill the container $\frac{1}{4}$ full with water and recap. Shake for 10 seconds. Drain for 10 seconds after the flow begins to drip. Follow Pesticide Disposal instructions for rinsate disposal. Repeat this procedure two more times. Then offer for recycling if available or puncture and dispose of in a sanitary landfill, or by incineration.

{For non-refillable containers greater than 5 gal.}

Non-Refillable Container. Do not reuse or refill this container. Triple rinse container {(or equivalent)} promptly after emptying. Triple rinse as follows: Fill the container $\frac{1}{4}$ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip back and forth several times. Turn the container over onto its other end and tip back and forth several times. Follow Pesticide Disposal instructions for rinsate disposal. Repeat this procedure two more times. Then offer for recycling if available or puncture and dispose of in a sanitary landfill, or by incineration.

{Refillable containers}

Refillable Container. Refill this container with this product only. Do not reuse this container for any other purpose. Cleaning the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller. To clean the container before final disposal, empty the remaining contents from this container into application equipment or a mix tank. Fill container about 10 percent full with water. Agitate vigorously or recirculate water with the pump for 2 minutes. Pour or pump rinsate into application equipment or rinsate collection system. Repeat this rinsing procedure two more times.

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER. Corrosive. Causes irreversible eye damage and skin burns. Harmful if swallowed or absorbed through skin. Do not get in eyes, on skin, or on clothing. Wear appropriate protective eyewear such as goggles, face shield, or safety glasses. Wear coveralls over long-sleeved shirt and long pants, socks, shoes, and chemical resistant gloves. When mixing and loading wear a chemical-resistant apron. Wash thoroughly with soap and water after handling and before eating, drinking, and chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse.

ENVIRONMENTAL HAZARDS

(If container is equal to or greater than 5 gallons, the following statement must appear on the label.)

This product is toxic to fish, aquatic invertebrates, oysters and shrimp. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product into sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

(If container is less than 5 gallons, use the following as an alternate to the above statement.)

This product is toxic to fish, aquatic invertebrates, oysters and shrimp.

{SPANISH ADVISORY STATEMENTS}

(Note to Reviewer: This statement is optional except when used on labels with agricultural uses.)

{SI USTED NO ENTIENDE LA ETIQUETA, BUSQUE A ALGUIEN PARA QUE SE LA EXPLIQUE A USTED EN DETALLE. IF YOU DO NOT UNDERSTAND THE LABEL, FIND SOMEONE TO EXPLAIN IT TO YOU IN DETAIL.}

{GRAPHICS AND ICONS}

(Note to Reviewer: These are representative icons for use sites/application methods that may appear on the label with the appropriate directions for use, PPE or package type.)

{Baby Drowning in Bucket Warning Graphic}

{Made in USA Logo/Flag}

{Recycling Logo}

{Mixing Chemical Warning Graphic}

{WARRANTY STATEMENT}

(Note to Reviewer: This statement is optional.)

Read Product Safety Data Sheet prior to use, PRODUCT WARRANTY, DISCLAIMER AND LIMITATION OF LIABILITY ARE FOUND on the Product Material Safety Data Sheet. Unless inconsistent with applicable law, use of Product signifies agreement with these provisions.

Lea la Hoja de Seguridad del Producto antes de usarlo. LA GARANTIA DEL PRODUCTO, DECLINACION Y LIMITACION DE RESPONSABILIDAD SE ENCUENTRAN en la Hoja de Seguridad del Producto. A menos de que sea inconsistence con la ley, el uso del product signigica acuerdo con esteas disposiconies.