

U.S. ENVIRONMENTAL PROTECTION AGENCY

Office of Pesticide Programs Antimicrobials Division (7510P) 1200 Pennsylvania Ave., N.W.

Washington, D.C. 20460

Date of Issuance:

94602-68

EPA Reg. Number:

2/26/25

Term of Issuance:

Conditional

Name of Pesticide Product:

GBS 445-WM

Name and Address of Registrant (include ZIP Code):

Christina Swick Agent

Gray Beard, LLC

Electronic Transmittal: cswick@lewisharrison.com

NOTICE OF PESTICIDE:

X Registration

___ Reregistration (under FIFRA, as amended)

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Antimicrobials Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA).

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA section click to select. You must comply with the following conditions:

1. Submit and/or cite all data required for registration/reregistration/registration review of your product under FIFRA when the Agency requires all registrants of similar products to submit such data.

Signature of Approving Official:

Date:

2/26/25

Luisa C. Samalot-Freire, Product Manager 31

Regulatory Management Branch I, Antimicrobials Division (7510P)

EPA Form 8570-6

Page 2 of 2 EPA Reg. No. 94602-68 Action Case No. 00499041

- 2. You are required to comply with the data requirements described in the DCI Order identified below:
 - DDAC GDCI-069149-30869, GDCI-069149-0681

You must comply with all of the data requirements within the established deadlines. If you have questions about the Generic DCI listed above, you may contact the Reevaluation Team Leader (Team 36): http://www2.epa.gov/pesticide-contacts/contacts-office-pesticide-programs-antimicrobial-division

- 3. Make the following label changes before you release the product for shipment:
 - Revise the EPA Registration Number to read, "EPA Reg. No. 94602-68."
- 4. Submit one copy of the final printed label for the record before you release the product for shipment.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under FIFRA and is subject to review by the Agency. See FIFRA section 2(p)(2). If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) lists examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process, FIFRA section 12(a)(1)(B). Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Assurance.

If you fail to satisfy these data requirements, EPA will consider appropriate regulatory action including, among other things, cancellation under FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions. A stamped copy of the label is enclosed for your records. Please also note that the record for this product currently contains the following CSFs:

Basic CSF dated 12/5/2024

If you have any questions, please contact Oiguenblik. Emilia @epa.gov or Samalot. Luisa@epa.gov.

Enclosure: Stamped label

Gray Beard, LLC

1931G Rohlwing Road • Rolling Meadows, IL 60008 • 800-837-0499

GBS 445-WM

RESTRICTED USE PESTICIDE DUE TO HIGH ACUTE TOXICITY

For retail sale to and use only by Certified Applicators or person under their direction supervision and only for those uses covered by the Certified Applicator's Certifications

EPA Reg. No.94602-EPA Est. No

(Note to Reviewer: Marketing claims may be used on the front panel.)

ACTIVE INGREDIENTS:

Didecyl dimethyl ammonium chloride	50.0%
OTHER INGREDIENTS	<u>50.0%</u>
TOTAL:	100.0%

{Weight Approx. 7.18 lbs./gallon}

DANGER {PELIGRO}



POISON {VENENO}

{See [{left} {back} {side} {right} {insert} {panel} {of label}} {below}] for {additional} {precautionary statements}}.

{Note to Reviewer: In accordance with 40 CFR 156.68(d), all first aid statements, as prescribed, will appear on the front panel of the product label.}

FIRST AID

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

IF SWALLOWED: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.

IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for treatment advice.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment. For general information on product use, etc., call the National Pesticides Information Center at 1-800-858-7378. You may also call the poison control center 1-800-222-1222 for emergency medical treatment information.

{For [{chemical} {and} {or} {medical} {and} {or} {environmental}] emergencies, call {insert name and/or number of emergency contact} {hours of operation} {24 hours a day} {7 days a week}}.

(Note to Reviewer: This referral statement may be organized in any order to be grammatically correct.)
{{Consult} {See {additional} {sheet} {insert} {outer container} {Product Information} {Bulletin} for {other} {directions for use} {and} {information} {claims} {organisms} {applications}.}

in CA.)" may be added to the location/surface/use.)

(Note to Reviewer: Text in {} is optional. Brackets [] indicate that at least one option within the brackets must be used in the final label text. Parentheticals () are meant to appear on final label. "This product" can be substituted with actual product name in the marketing and directions for use. In the case where the location/surface/use is not registered in the State of California the statement "(Not registered for use

ACCEPTED

02/26/2025

Under the Federal Insecticide, Fungicide and Rodenticide Act as amended, for the

94602-68

pesticide registered under

EPA Reg. No.

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER. POISON. Corrosive. Fatal if swallowed, inhaled, or absorbed through skin. Causes irreversible eye damage and skin burns. Do not get in eyes, on skin, or on clothing. Do not breathe vapor or spray mist. Wear goggles or face shield. Wear coveralls worn over long-sleeved shirt and long pants, socks, chemical-resistant footwear, and chemical-resistant gloves. When mixing and loading wear a chemical-resistant apron. Wear a minimum of a NIOSH-approved particulate filtering facepiece respirator with any N, R, or P filter; OR a NIOSH-approved elastomeric particulate respirator with any N, R, or P filter; OR a NIOSH-approved powered air purifying respirator with HE filters. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using restroom.

Discard clothing and other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them.

Follow the manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry

Methanol may cause blindness.

ENVIRONMENTAL HAZARDS

(If container is equal to or greater than 5 gallons, the following statement must appear on the label.)

This product is toxic to fish, aquatic invertebrates, oysters and shrimp. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product into sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA

(If container is less than 5 gallons, use the following as an alternate to the above statement.)

This product is toxic to fish, aquatic invertebrates, oysters and shrimp.

PHYSICAL OR CHEMICAL HAZARDS

Do not mix with soap, anionic detergents or oxidizers. Flammable. Keep away from heat and open flame.

Manufactured for: Gray Beard LLC 1931G Rohlwing Road Rolling Meadows, IL 60008

> Net Contents: {{Batch} {Lot} No} {Manufacturing Date}: {Product of USA} {Made in the USA}

MARKETING CLAIMS

(Note to Reviewer: Marketing text is considered optional. Commas and the words "and" "or" can be added to phrases to make text grammatically correct.)

{LOCATIONS/SURFACES}

(Note to Reviewer: The locations/surfaces have been grouped for space purposes only; they can be used individually or grouped together in any order however at least one location/surface must appear on the label. In the case where one or more location/surface is chosen, an "and" "&" "or" may be used to link locations/surfaces.)

an "and	" "&" "or" may be used to link locations/surfaces.)
	oduct is for use in (insert location) {in} {on} (insert location/surface).
	TIONS}
Water '	Treatment}
	Air washers
	Auxiliary water systems
	Commercial recirculating cooling water towers
	Drilling, completion and workover fluids systems
	Gas production and transmission pipeline and systems
	Gas storage wells and systems
	Hydrotesting facilities
	Industrial {and/or} {commercial} recirculating cooling towers.
	Industrial scrubbing systems
	Oil field water flood systems {and fracturing fluid systems}
	Oil field injection and waste water
	Once through fresh water cooling systems
	Once through freshwater systems
	Packer fluid systems
	Pipeline pigging and scraping operations
	Recirculating water systems
	Retort water systems (Not for use in CA)
	Waste water systems
	Water cooling systems
	WATER TREATMENT MARKETING CLAIMS

(Note to Reviewer: The following marketing claims may be used with the prefix "This product" or "This product is {a} {an}".)

	Algaecide
	Aids in the control of bacterial, fungal and algal slimes in evaporative condensers, heat exchange water systems, industrial and commercial cooling towers, air washers, retorts (Not for use in CA), pasteurizers, warmers, and industrial water scrubbing systems.
	Water treatment microbiocide for industrial and/or commercial recirculating cooling water towers, retort water systems (Not for use in CA), and flood systems and fracturing fluids.
	Aids in the control of bacterial, fungal and algal slimes in evaporative condensers, heat exchange water systems, industrial and commercial cooling towers, Influent systems such as flow through filters and lagoons, industrial water systems and brewery pasteurizers.
	A water treatment microbiocide for retort water systems. (Not for use in CA)
	Aids in the control of bacterial, fungal and algal slimes in retort water systems. (Not for use in CA)
	Water treatment microbiocide for industrial and/or commercial recirculating cooling water towers, and oil filed flood/salt water disposal systems and fracturing fluids.
	Microbiocide for use in controlling sulfate-reducing bacteria and slime forming bacteria in oil well drilling, oil field processing applications, oil field water systems, oil and gas productions and transmission pipelines and systems, and gas storage fields and equipment; such as steam-injection water holding tanks, flood water, injection water, holding pond water, disposal-well water, water holding tanks, fuel storage tanks and related refinery and oil field closed systems, industrial recirculating water handling systems.
	Water treatment microbiocide for use in controlling microorganisms such as sulfate-reducing bacteria, slime forming bacteria, algae, and mold and yeast in oil and gas systems, and building and industrial cooling tower systems.
	Microbiocide for use in controlling slime forming bacteria, sulfate-reducing bacteria (SRB) and fungi (yeast and molds) and
3S 445-	-WM, EPA Reg. No. 94602-AI (Note to Reviewer: Text in {} is optional. Brackets [] indicate that at least one option within the based on the control of the c

GBS 445-WM, EPA Reg. No. 94602-Al Page 3 of 7 20250130

s a violation of Federal law to use this product in a manner inconsistent with its labeling. The to Reviewer (General Considerations): Numbered instructions will be used if label space permits, otherwise may appear in regraph format. Unit abbreviations can be spelled out. When choosing entired text, appropriate puretuation can be inserted or deleted.					
DIRECTIONS FOR USE					
	Concentrate{d} 50% Concentration This [{container} {bottle}] is made of {at least} (x)% post-consumer recycled plastic.				
	PACKAGING CLAIMS				
	*non-food contact use only				
	This product is ideal for cold weather oil and gas applications.				
	This product is a winterized microbiocide which remains a thick pourable fluid.				
	This product has been {specially} formulated to withstand winter conditions.				
	For use in cold weather {The product is} freeze resistant.				
	This product has been {specially} formulated for use in cold weather environments.				
	Winterized (Formula)				
	Cold Temperature Formula				
	To control algae and bacterial slimes, use this water treatment microbiocide as directed.				
	associated piping, setting ponds or lagoons, transport spillways or canals and disposal wells. This product reduces bacterial contamination and degradation of fracturing fluids and gels used in oil and gas well stimulations.				
	systems such as fire protection systems and pump or screen bays, waste water systems such as storage tanks, storage piles,				
	This product is effective for the control of odor-forming and slime-forming bacterial, fungi and algae in auxiliary service water				
	The residual effectiveness of this algaecide tends to stabilize the total chemical treatment system.				
	Is a water treatment microbiocide that will control algae and bacterial slimes found in recirculating cooling towerwaters. Kills and prevents algae.				
	Is a microbiocide that helps clean and loosen slime debris from cooling and flooding system surfaces.				
	Helps inhibit the growth of unsightly algae.				
	pipelines and systems.				
	Has been designed specifically for control of sulfate-reducing bacteria that contribute to souring, the production of sulfide, and abiotic corrosion in water cooling systems, paper mill process water systems*, oil field systems, gas production and transmissio				
	and water cooling systems, oil field water flood systems.				
	For control of algae, algal, fungal and bacterial slimes in recirculating water systems, auxiliary water and waste water systems				
	of the dosages on the label. Effective against the growth of algae.				
	Cooling tower waters that are inherently low in algae growth and bacteria count may be adequately controlled by the lower range				
	freshwater cooling systems.				
	Controls algae and algal slime growth in industrial and/or commercial recirculating cooling water towers and once through				
	wastewater sludge and holding tanks, and in paper mills* and paper mill process water systems* and water based coatings for paper and paperboard*.				
	membranes and in service water and auxiliary systems and heat transfer systems and in wastewater systems including				
	algae in air washers and industrial scrubbing systems, process water systems including those that contain reverse osmosis				

paragraph format. Unit abbreviations can be spelled out. When choosing optional text, appropriate punctuation can be inserted or deleted. Equivalent use dilution ratios may be substituted within the directions.)

{Please read entire label and use strictly in accordance with precautionary statements and directions.}

WATER TREATMENT

Do not use water containing residues from use of this product to irrigate crops for food or feed.

(Note to Reviewer: The following sentence must be used with the air washer use listed in the direction:) For use only in industrial air washers and air washer systems which have mist-eliminating components.

AIR WASHERS, COOLING TOWERS, INDUSTRIAL {{AND/OR} COMMERCIAL} RECIRCULATING COOLING WATER TOWERS, RETORT WATER SYSTEMS, EVAPORATIVE CONDENSERS, HEAT {{EXCHANGE} {TRANSFER}} {WATER} SYSTEMS, PASTEURIZERS AND WARMERS (RETORT WATER SYSTEMS not for use in CA): For best results, clean heavily contaminated systems before treatment with this product. If soap or anionic detergent is used, rinse thoroughly before charging with this algaecide. (Cooling tower waters that are inherently low in algae growth and bacteria count may be adequately controlled by the lower range of these dosages.} {Product application may be made intermittently (slug dose) or continuously. Noticeably fouled systems can be shocked with this product. Under these conditions, blow down should be discontinued for up to 24 hours.} Repeat every seven days or increase frequency if needed. Should slime develop again, repeat initial dosage. Noticeably fouled systems must be cleaned before treatment is begun.

- 1. **Dosing Location:** This product is to be applied at a point in the system where it will be uniformly mixed, such as the basin area, the sump, or another reservoir or collecting area.
- 2. **Dosing Conditions:** This product must be applied when the system is in jeopardy of being affected or after cleaning systems where efficiency is already impaired. {Tower bleed off valves must be closed to permit a retention time of 4 hours.}
- 3. Method of Application:

a) INTERMITTENT OR SLUG METHOD

Initial Dose: When the system is noticeably fouled, apply 5 - 9 fl. oz. $\{(0.04 - 0.07 \text{ gal})\}$ of this product per 1,000 gal. of water $\{(20-35 \text{ ppm active})\}$ in the system. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 2 - 3 fl. oz. {(0.016 - 0.023 gal.)} of this product per 1,000 gal. of water {(8-12 ppm active)} in the system weekly or as needed to maintain control.

b) MODIFIED INTERMITTENT METHOD

Initial Dose: When the system is noticeably fouled, apply 5 - 9 fl. oz. {(0.04 - 0.07 gal.)} of this product per 1,000 gal. of water {(20-35 ppm active)} in the system. Apply half this initial dose when half of the water in the system has been lost by blowdown.

Subsequent Dose: When microbial control is evident, add 2 – 3 fl. oz. {(0.016-0.023 gal.)} of this product per 1,000 gal. of water {(8-12 ppm active)} in the system. Apply half this initial dose when half of the water in the system has been lost by blowdown.

c) **CONTINUOUS FEED METHOD**

Initial Dose: When the system is noticeably fouled, apply 5 - 9 fl. oz. {(0.04 - 0.07 gal.)} of this product per 1,000 gal. of water {(20-35 ppm active)} in the system.

Subsequent Dose: Maintain this treatment by starting a continuous feed of 2 - 3 fl. oz. {(0.016 - 0.023 gal.)} of this product per 1,000 gal. of water {(8-12 ppm active)} lost by blowdown.

ONCE THROUGH FRESH {AND SEA} WATER COOLING SYSTEMS: Use of this product in either public/municipal or single or multiple family private/residential potable/drinking water systems is strictly prohibited. Use of the product in any cooling water system that discharges effluent within ¼ mile of either public/municipal or single or multiple family private/residential potable/drinking water intake is strictly prohibited

{For best results, slug feed. The frequency of addition of microbicide needed depends on many factors. To optimize your use of water treatment microbiocide, follow this procedure.}

- 1. **Dosing Location:** This product is to be applied at a point in the system where it will be uniformly mixed, such as at the sump.
- 2. **Dosing Conditions:** This product must be applied when the system is in jeopardy of being affected or after cleaning systems where efficiency is already impaired.
- 3. Method of Applications:
 - a) Wear safety glasses, rubber gloves and impervious apron.
 - b) To reduce foaming, mix 2 parts of water to 1 part of this product.
 - c) Add 0.15 to 1.5 fluid ounces (0.6-6 ppm on an active quaternary basis) per thousand gal.
 - d) Do not discharge without performing proper deactivation.
 - e) Treatment time cannot exceed 120 hours/application nor exceed 4 times per year.
 - f) Avoid oxidizers and reducing agents. Product is cationic and must not be mixed with soap or anionic surfactants.

(OR)

(Note to reviewer: Alternate Method of Application language can be used in place of item #3 directly above.)

3) Method of Application:

INTERMITTENT OR SLUG METHOD

Initial Dose: When the system is noticeably fouled, apply 0.15-1.5 fl. oz. of this product per 1000 gal. of water {(0.6-6 ppm active)} based on system flow rates. The minimum treatment is 6 to 24 hours. Repeat until control is achieved. Deactivation must be conducted prior to discharge from the system by using bentonite clay at a minimum ratio of 5 ppm clay to 1 ppm product. Subsequent Dose: When microbial control is evident, add 0.07-0.7 fl. oz. of this product per 1000 gal. of water {(0.3-3 ppm active)} based on system flow rates on an as needed basis to maintain control. Frequency of feed must be tied to an in-plant monitoring program for macro cowling growth. Deactivation must be conducted prior to discharge from the system by using bentonite clay at a minimum ratio of 5 ppm clay to 1 ppm product.

(Note to Reviewer: Deactivation instructions must be used with the above Once Through directions for use.)

DEACTIVATION: Use bentonite clay at the minimum ratio of 5 ppm clay to 1 ppm product. Deactivation must occur prior to discharge of the NPDES outfall. Do not apply this product more than 4 times a year.

AUXILIARY SYSTEMS AND SERVICE WATER: Add 4 fl. oz. - 1.2 gal. of this product per 3,000 gal. of water {(5-180 ppm active)} in the system continuously. This product must be added to the system at a point of uniform mixing by slug or intermittent feed or by spraying onto a waste pile. The frequency of feed or spray and the duration of treatment will depend upon the severity of the contamination. Additions to water systems must be made during the pumping operation and as close to the pump as possible to ensure adequate mixing.

INDUSTRIAL WASTEWATER SYSTEMS {Wastewater Systems, Wastewater Sludge and Wastewater Holding Tanks}

This product is added to a wastewater system or sludge at a convenient point of uniform mixing such as digester. Add 4 fl. oz. - 1.2 gal. of this product per 3,000 gal. of wastewater or sludge {(5-180 ppm active)}

OIL FIELD, GAS PRODUCTION AND TRANSMISSION PIPELINE AND SYSTEMS

{OIL FIELD} WATER FLOOD SYSTEMS, {OR SALT WATER DISPOSAL SYSTEMS] AND FRACTURING {(STIMULATION)} FLUIDS (Not for use in CA): This product must be added to the water flood at a point of uniform mixing.

- 1. **Continuous Use:** Add 6.5 96 fl. oz. of this product per 1,000 gal. of water {(25 375 ppm active)} to control slime forming and sulfate reducing bacteria. Levels for effective control will vary depending on conditions at the site.
 - 2. [{Slug Dose} {Intermittent Use}]: Add at a rate of 13 fl. oz. 96 fl. oz of this product per 1,000 gal. of water {(5-375 ppm active)} for 4 to 8 hours per day, one to four times a week as needed to maintain control.
 - 3. **Treatment of flow back return water** {(Post Hydraulic Fracturing)}: Dose at a rate of 13 fl. oz. 96 fl. oz. of this product per 1,000 gal. of water {(5-375 ppm active)} for 4-8 hours per day, one to four times a week as needed to maintain control.

OIL FIELD INJECTION AND WASTE WATER: This product must be added to the water handling system at a point of uniform mixing such as the area of addition of make up water to the holding tank.

Method of Application:

- 1. **Continuous Injection:** Add this product at 7.68 fl. oz of this product per 1,000 gal. of water {(30 ppm {active}) when system is noticeably fouled. When microbial control is evident, add 3.84 fl. oz. of this product per 1,000 gal. of water {(15 ppm {active}) to maintain control.
- 2. **Batch Treatment:** Add this product at 46 fl. oz. of this product per 1,000 gal. of water {(180 ppm {active}) over a period of 4 6 hours one or more times per week when the system is noticeably fouled. When microbial control is evident, add 23 fl. oz. of this product per 1,000 gal. of water {(90 ppm {active}) over a period of 4 6 hours one or more time per week.

[{FRACTURING} {FRAC}] FLUIDS: Add this product to the frac water storage tanks or directly into the well head injection pipeline as the water is being pumped down-hole. **Dose Range:** Add 13 fl. oz. - 1.2 gal. of this product per 10,000 gal. of flood water {(5-60 ppm active)} to control slime forming and sulfate reducing bacteria. Levels for effective control will vary depending on conditions at the site.

{OIL AND GAS PRODUCTION AND TRANSMISSION PIPELINES AND SYSTEMS: For the control of sulfate-reducing bacteria and slime forming bacteria, this product must be added to a gas production or transmission pipeline via direct injection at a point where uniform and maximum distribution will occur. The application must be conducted to ensure maximum distribution of the product through the internal surface of the pipeline by adding an amount of biocide which eventually comes out the other end of the pipeline. Criteria for success of the treatment will be reduction in bacterial count and/or corrosion rates. To facilitate application, it is desirable to dilute the product with an appropriate solvent immediately before use. The concentration in the solvent must not fall below an active concentration range of 500 - 1000 ppm active based on the volume of water in the pipeline. For pipeline uses, after application and complete distribution throughout the pipeline, a detectable amount of residue product should be present at the back end of the pipeline system. Injections to the system must be weekly, or as needed to maintain control.}

GAS STORAGE WELLS AND SYSTEMS: Treat individual injection wells with 17 fl. oz. - 2 gal. of this product per 1,000 gal. of water {(65-1,000 ppm active)}. Update treatment rate as needed. This product must be diluted by the water present in the formation. Injection takes place before gas is injected and may be repeated yearly or as needed to maintain control.

PIPELINE PIGGING AND SCRAPING OPERATIONS: Add this product to slug water immediately following the scraper {(keep the water volume to a minimum and contained between the scraper and the [following] trailing] pig)}. Add an effective concentration of 2 – 13 fl. oz. of product per 100 gal. of water {(75-500 ppm active)} depending on the length of the pipeline and the severity of the biofouling.

DRILLING {(MUDS)}, **COMPLETION AND WORKOVER FLUIDS SYSTEMS:** This product is to be added to these fluid systems at a point of uniform mixing, such as a circulating, holding or mud tank. Levels for effective control will vary depending on conditions at the site and the severity of the contamination.

- 1. Initial treatment: Add 17 fl. oz. 2 gal. of this product per 1,000 gal. of freshly prepared fluid {(65-1,000 ppm active)}.
- 2. Maintenance dosage: Add 17 fl. oz. 2 gal. of this product per 1,000 gal. of freshly prepared fluid {(65-1,000 ppm active)}.

PACKER FLUIDS: This product is to be added to the packer fluid at a point of uniform mixing such as a circulating holding tank {and} {other mixing device locations}. Add 17 fl. oz. - 2 gal. of this product per 1,000 gal. to a freshly prepared packer fluid {(65-1,000 ppm active)}. Levels for effective control vary depending on conditions at the site and the severity of contamination. Seal the treated packer fluid in the wall between the casing and the production tube.

HYDROTESTING: Treat water used to hydrotest pipelines or vessels by adding 17 fl. oz. - 2 gal. of this product per 1,000 of water {(65-1,000 ppm active)} depending on the water quality and length of time the equipment will remain idle.

{{{OIL FIELD} {GAS PRODUCTION} {TRANSMISSION PIPELINE} {AND} {SYSTEMS} (Not for use in CA):**}** (Specific treatment requirements vary among oil and/or gas field sites and subsystem components. {Oil field fluids and subsystems most commonly requiring microbial contamination control are raw water sources, separators, ballast, storage and mixing tanks, screens, surface injection equipment,

production equipment {(such as injection and production piping casing, completion and valving)} and the formation itself.} The primary point of treatment will vary among oil and/or gas field operations depending on the site problems, water-flood treatment methods and equipment. This product must be added where it will disperse rapidly and uniformly to the desired area of treatment.

Additions of this product must be made with the proper type of metering pump equipment, suction (low pressure) side of pumping equipment or similar device. This product must be added to the system by slug, continuous or on an intermittent basis, depending on the degree of system fouling.}

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage and disposal.

(PESTICIDE) STORAGE: Store only in original container. Keep this product under locked storage sufficient to make it inaccessible to children or persons unfamiliar with its proper use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

CONTAINER HANDLING:

(Note to Reviewer: One or more of the following paragraphs for Container Handling will be selected, depending on packaging use/type.)

{For non-refillable containers equal to or less than 5 gallons}

Non-Refillable Container. Do not reuse or refill this container. Triple rinse container {(or equivalent)} promptly after emptying. Triple rinse as follows: Fill the container ¼ full with water and recap. Shake for 10 seconds. Drain for 10 seconds after the flow begins to drip. Follow Pesticide Disposal instructions for rinsate disposal. Repeat this procedure two more times. Then offer for recycling if available or puncture and dispose of in a sanitary landfill, or by incineration.

{For non-refillable containers greater than 5 gallons}

Non-Refillable Container. Do not reuse or refill this container. Triple rinse container {(or equivalent)} promptly after emptying. Triple rinse as follows: Fill the container ¼ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip back and forth several times. Turn the container over onto its other end and tip back and forth several times. Follow Pesticide Disposal instructions for rinsate disposal. Repeat this procedure two more times. Then offer for recycling if available or puncture and dispose of in a sanitary landfill, or by incineration.

{Refillable containers}

Refillable Container. Refill this container with this product only. Do not reuse this container for any other purpose. Cleaning the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller. To clean the container before final disposal, empty the remaining contents from this container into application equipment or a mix tank. Fill container about 10 percent full with water. Agitate vigorously or recirculate water with the pump for 2 minutes. Pour or pump rinsate into application equipment or rinsate collection system. Repeat this rinsing procedure two more times.

(SPANISH ADVISORY STATEMENTS)

(Note to Reviewer: This statement is optional except when used on labels with agricultural uses.)
{SI USTED NO ENTIENDE LA ETIQUETA, BUSQUE A ALGUIEN PARA QUE SE LA EXPLIQUE A USTED EN DETALLE. IF YOU DO NOT UNDERSTAND THE LABEL, FIND SOMEONE TO EXPLAIN IT TO YOU IN DETAIL.}

{GRAPHICS AND ICONS}

(Note to Reviewer: These are representative icons for use sites/application methods that may appear on the label with the appropriate directions for use, PPE or package type.)

{Baby Drowning in Bucket Warning Graphic} {Made in USA Logo/Flag} {Recycling Logo} {Mixing Chemical Warning Graphic}

{WARRANTY STATEMENT}

(Note to Reviewer: This statement is optional.)

Read Product Safety Data Sheet prior to use, PRODUCT WARRANTY, DISCLAIMER AND LIMITATION OF LIABILITY ARE FOUND on the Product Material Safety Data Sheet. Unless inconsistent with applicable law, use of Product signifies agreement with these provisions.

Lea la Hoia de Seguridad del Producto antes de usarlo. LA GARANTIA DEL PRODUCTO, DECLINACION Y LIMITACION DE RESPONSBILDAD SE ENCUENTRAN en la Hoia de Seguridad del Producto. A menos de que sea inconsistence con la ley, el uso del

product signigica acuerdo con esteas disposiconies.							