



U.S. ENVIRONMENTAL PROTECTION AGENCY

Office of Pesticide Programs
Registration Division (7505T)
1200 Pennsylvania Ave., N.W.
Washington, D.C. 20460

EPA Reg. Number:

95009-15

Date of Issuance:

5/6/24

NOTICE OF PESTICIDE:

☒ Registration
☐ Reregistration
(under FIFRA, as amended)

Term of Issuance:

Unconditional

Name of Pesticide Product:

Maxunitech Ethephon 6

Name and Address of Registrant (include ZIP Code):

Liqing Li
Maxunitech North America, Inc.
11601 Shadow Creek Pkwy, Suite 111-573
Pearland, TX 77584

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered under the Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA).

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is unconditionally registered in accordance with FIFRA section 3(c)(5) provided that you:

1. Submit and/or cite all data required for registration/reregistration/registration review of your product when the Agency requires all registrants of similar products to submit such data.

Continues page 2

Signature of Approving Official:

Kristy Crews, Ph.D., Product Manager 22
Fungicide Branch, Registration Division (7505T)
Office of Pesticide Programs, USEPA

Date:

5/6/24

2. Make the following label changes before you release the product for shipment:
 - Revise the EPA Registration Number to read, "EPA Reg. No. 95009-15."
3. Submit one copy of the final printed label for the record before you release the product for shipment.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under FIFRA and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) lists examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6. Your release for shipment of the product constitutes acceptance of these conditions. A stamped copy of the label is enclosed for your records.

The record for this product currently contains the following CSF(s):

- Basic CSF dated 07/18/2023

If you have any questions, please contact Thomas Harty at 202-566-0394 or at harty.thomas@epa.gov.

Enclosure- Stamped Label

ACCEPTED

05/06/2024

Under the Federal Insecticide, Fungicide
and Rodenticide Act as amended, for the
pesticide registered under
EPA Reg. No. 95009-15

Maxunitech Ethephon 6

**FOR COMMERCIAL USE OR AGRICULTURAL USE ONLY
NOT FOR RESIDENTIAL USE**

ACTIVE INGREDIENT:

Ethephon (2-Chloroethyl) phosphonic acid*55.4%

INERT INGREDIENTS:44.6%**TOTAL**100.0%

*This product contains 6 pounds ethephon per gallon

KEEP OUT OF REACH OF CHILDREN**DANGER PELIGRO**

Si usted no entiende la etiqueta, busque a alguien para que se la explique a usted en detalle. (If you do not understand this label, find someone to explain it to you in detail.)

FIRST AID	
IF IN EYES	<ul style="list-style-type: none">• Hold eye open and rinse slowly and gently with water for 15-20 minutes.• Remove contact lenses, if present after the first 5 minutes, then continue rinsing eye.• Call a poison control center or doctor for treatment advice.
IF ON SKIN OR CLOTHING	<ul style="list-style-type: none">• Take off contaminated clothing.• Rinse skin immediately with plenty of water for 15-20 minutes.• Call a poison control center or doctor for treatment advice.
IF SWALLOWED	<ul style="list-style-type: none">• Call a poison control center or doctor immediately for treatment advice.• Have person sip a glass of water if able to swallow.• Do not give anything by mouth to an unconscious person.• Do not induce vomiting unless told to by a poison control center or doctor.
IF INHALED	<ul style="list-style-type: none">• Move person to fresh air.• If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.• Call a poison control center or doctor for further treatment advice.
NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Treat symptomatically, as there is no specific antidote. Additionally, patient may have been exposed to materials other than this product. This product is an acid; therefore, it is contraindicated to attempt to neutralize it with alkaline materials. Gastric lavage should be undertaken with care to victims of overexposure by ingestion, given the potential for esophageal or stomach perforation. Due to a potential for pulmonary edema, any patients that have had severe exposure to this product should be kept under medical observation for up to 72 hours.	
HOTLINE NUMBER	
EMERGENCY TELEPHONE NUMBERS: Have the product container or label with you when calling a poison control center or doctor or going for treatment.	
FOR CHEMICAL EMERGENCY: Spill, leak, fire, exposure, or accident call CHEMTREC 1-800-424-9300	

Refer to side panel for additional precautionary statements.

EPA Reg. No. 95009-XX

EPA Est. No. _____

AD xxxxxx

NET CONTENTS: _____

Manufactured For:
Maxunitech North America, Inc.
11601 Shadow Creek Pkwy, Suite 111-573
Pearland, TX 77584

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Causes irreversible eye damage and skin burns. Harmful if swallowed. Harmful if absorbed through skin. Do not get in eyes or on clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or using tobacco. Remove and wash contaminated clothing before reuse.

PERSONAL PROTECTIVE EQUIPMENT

Applicators and other handlers must wear:

1. Coveralls over long-sleeved shirt and long pants.
2. Chemical-resistant gloves made of any waterproof material, such as polyvinyl chloride, nitrile rubber, or butyl rubber.
3. Chemical-resistant footwear plus socks
4. Protective eyewear (goggles, face, shield, or safety glasses).
5. Chemical-resistant headgear for overhead exposure.
6. Chemical-resistant apron when mixing or loading or cleaning equipment.

Discard clothing and other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them. Follow manufacturer's instructions for cleaning and maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry.

When handlers use closed systems, enclosed cabs, or aircraft in a manner that meets the requirements listed in the Worker Protection Standard (WPS) for agricultural pesticides 40 CFR 170.240(d)(4-6), the handler PPE requirements may be reduced or modified as specified in the WPS.

USER SAFETY RECOMMENDATIONS

Users should:

1. Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet.
2. Remove clothing/PPE immediately if pesticide gets inside. Then wash body thoroughly and put on clean clothing.
3. Remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing.

ENVIRONMENTAL HAZARDS

Do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment washwaters. Do not contaminate water used for domestic purposes or irrigation.

NON-TARGET ORGANISM ADVISORY STATEMENT: This product is toxic to plants and may adversely impact the forage and habitat of non-target organisms, including pollinators, in areas adjacent to the treated site. Protect the forage and habitat of non-target organisms by following label directions intended to minimize spray drift.

USE PRECAUTIONS

Do not plant another crop within 30 days after treatment.

When preparing a spray solution of this product, do not mix any more spray solution than is needed for applications to be made that day. When applications are finished for the day, dispose of any remaining spray solution in a manner as directed by this label.

Do not apply Maxunitech Ethephon 6 through any type of irrigation system.

Avoid spray drift to nearby crops, as this product will cause modifications in plant growth. Plant injury or reduced

yields will result.

SPRAY DRIFT ADVISORIES

THE APPLICATOR IS RESPONSIBLE FOR AVOIDING OFF-SITE SPRAY DRIFT.
BE AWARE OF NEARBY NON-TARGET SITES AND ENVIRONMENTAL CONDITIONS.

IMPORTANCE OF DROPLET SIZE

An effective way to reduce spray drift is to apply large droplets. Use the largest droplets that provide target pest control. While applying larger droplets will reduce spray drift, the potential for drift will be greater if applications are made improperly or under unfavorable environmental conditions.

Controlling Droplet Size - Ground Boom

- Volume - Increasing the spray volume so that larger droplets are produced will reduce spray drift. Use the highest practical spray volume for the application. If a greater spray volume is needed, consider using a nozzle with a higher flow rate.
- Pressure - Use the lowest spray pressure recommended for the nozzle to produce the target spray volume and droplet size.
- Spray Nozzle - Use a spray nozzle that is designed for the intended application. Consider using nozzles designed to reduce drift.

Controlling Droplet Size - Aircraft

- Adjust Nozzles - Follow nozzle manufacturers recommendations for setting up nozzles. Generally, to reduce fine droplets, nozzles should be oriented parallel with the airflow in flight.

BOOM HEIGHT - Ground Boom

For ground equipment, the boom should remain level with the crop and have minimal bounce.

RELEASE HEIGHT - Aircraft

Higher release heights increase the potential for spray drift.

SHIELDED SPRAYERS

Shielding the boom or individual nozzles can reduce spray drift. Consider using shielded sprayers. Verify that the shields are not interfering with the uniform deposition of the spray on the target area.

TEMPERATURE AND HUMIDITY

When making applications in hot and dry conditions, use larger droplets to reduce effects of evaporation.

TEMPERATURE INVERSIONS

Drift potential is high during a temperature inversion. Temperature inversions are characterized by increasing temperature with altitude and are common on nights with limited cloud cover and light to no wind. The presence of an inversion can be indicated by ground fog or by the movement of smoke from a ground source or an aircraft smoke generator. Smoke that layers and moves laterally in a concentrated cloud (under low wind conditions) indicates an inversion, while smoke that moves upward and rapidly dissipates indicates good vertical air mixing. Avoid applications during temperature inversions.

WIND

Drift potential generally increases with wind speed. AVOID APPLICATIONS DURING GUSTY WIND CONDITIONS. Applicators need to be familiar with local wind patterns and terrain that could affect spray drift.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Do not apply this product in a way that will contact workers or other persons, either directly or through drift. Only protected handlers may be in the area during application. For any requirements specific to your State or Tribe, consult the agency responsible for pesticide regulation.

SPRAY DRIFT

AERIAL APPLICATIONS

- Do not release spray at a height greater than 10 feet above the vegetative canopy, unless a greater application height is necessary for pilot safety.
- For all applications, applicators are required to use a fine to medium or coarser droplet size (ASABE S572.1).
- The boom length must not exceed 65% of the wingspan for airplanes or 75% of the rotor blade diameter for helicopters.
- Applicators must use ½ swath displacement upwind at the downwind edge of the field.
- Nozzles must be oriented so the spray is directed toward the back of the aircraft.
- Do not apply when wind speeds exceed 10 miles per hour at the application site.
- Do not apply during temperature inversions.

GROUND BOOM APPLICATIONS

- Apply with the nozzle height recommended by the manufacturer, but no more than 3 feet above the ground or crop canopy.
- For all applications, applicators are required to use a fine to medium or coarser droplet size (ASABE S572.1).
- Do not apply when wind speeds exceed 10 miles per hour at the application site.
- Do not apply during temperature inversions.

AGRICULTURAL USE REQUIREMENTS

Use this product only in accordance with its labeling and with the Worker Protection Standard, 40 CFR part 170. This standard contains requirements for the protection of agricultural workers on farms, forests, nurseries, and greenhouses, and handlers of agricultural pesticides. It contains requirements for training, decontamination, notification, and emergency assistance. It also contains specific instructions and exceptions pertaining to the statements on this label about personal protective equipment, notification to workers, and restricted-entry intervals. The requirements in this box only apply to uses of this product that are covered by the Worker Protection Standard.

Do not enter or allow worker entry into treated areas during the restricted-entry interval (REI) of 48 hours.

The REI increases to 72 hours in outdoor areas where average rainfall is less than 25 inches a year.

PPE required for early entry to treated areas that is permitted under the Worker Protection Standard and that involves contact with anything that has been treated such as plants, soil, or water, is:

1. Coveralls over long-sleeved shirt and long pants.
2. Chemical-resistant gloves made of any waterproof material, such as polyvinyl chloride, nitrile rubber, or butyl rubber.
3. Chemical-resistant footwear plus socks.
4. Protective eyewear.
5. Chemical-resistant headgear for overhead exposure.

Notify workers of the application by warning them orally and by posting warning signs at entrances to treated areas.

PRODUCT INFORMATION

COTTON

Maxunitech Ethephon 6 used as a foliar spray will improve boll opening of mature bolls that are unopened and assist in overall defoliation, which can result in improved yields and earlier harvesting. Foliar sprays of Maxunitech Ethephon 6 promote once-over harvesting that can increase efficiency.

TOBACCO (FLUE-CURED)

A foliar spray of Maxunitech Ethephon 6 promotes early and uniform maturing of tobacco. Maxunitech Ethephon 6 reduces curing time, allowing more efficient use of curing barn space, and increased control over harvest schedules.

SPRAY PREPARATION

Begin by filling the spray tank with 1/2 to 3/4 of the necessary spray volume and begin agitation. The required amount of Maxunitech Ethephon 6 and remaining amount of water can then be added. Prepare only as much spray solution as can be used on the day the product and water are mixed. Do not allow spray solution to stand overnight. Prevent spillage of concentrated product onto airplane parts or spray equipment.

ANY SPILLS SHOULD BE RINSED IMMEDIATELY WITH PLENTY OF WATER.

This product is corrosive. Therefore, spills of concentrated product on the aircraft or other spray equipment should be avoided. Should such contact be made, immediately rinse with water. Use of a nurse tank is highly recommended for avoiding possible spills of concentrated formulation on spray equipment or any airplane parts.

TANK MIXTURES WITH DEFOLIANTS AND INSECTICIDES

It is the pesticide user's responsibility to ensure that all products are registered for the intended use. Read and follow the applicable restrictions and limitations and directions for use on all product labels involved in tank mixing. Users must follow the most restrictive directions for use and precautionary statements of each product in the tank mixture.

When tank-mixing or applying products in conjunction with Maxunitech Ethephon 6, you must observe all applicable use precautions and recommended application rates on each product's label. This product, when tank-mixed with defoliants, may slightly inhibit boll-opening response.

Adequate agitation is essential in the spray tank. Tank mixtures need continuous agitation; do not allow to stand more than 5 to 10 minutes without agitation. Appropriate label use directions and precautions concerning defoliants and insecticides must be carefully read and observed.

IF COTTON IS TO BE SPINDLE PICKED DO NOT MIX WITH DESICCANTS.

MAXUNITECH ETHEPHON 6, WHEN TANK MIXED WITH SODIUM CHLORATE DEFOLIANTS. FORMS HYPOCHLOROUS ACIDS THAT UPON HEATING EMIT TOXIC CHLORINE FUMES. TANK MIXTURE OF THIS PRODUCT WITH SODIUM CHLORATE DEFOLIANTS IS PROHIBITED.

EQUIPMENT CLEANING

MAXUNITECH ETHEPHON 6 is an acid based product and prolonged exposure to deposits will cause damage to metals, acrylic plastics and certain paints.

Within an hour of any contact with spray deposits, you should carefully rinse all exposed acrylic plastic-type materials, like aircraft windshields, and painted surfaces with detergent and water.

When applications are complete for the day, you should carefully rinse any and all metal parts of the aircraft and any spray equipment that has been in contact with spray deposits with a detergent and water solution.

COTTON

PRODUCTS USED	WEATHER CONDITIONS	RATE OF APPLICATION		ONE GALLON TREATS	SPRAY VOLUME Gallons/Acre		TIMING
		PT/A	LB AI	ACRES	GROUND	AIR**	
Maxunitech Ethephon 6*	80°F or higher, hot and dry	1 1/3	1.0	6	10-50	2 - 5	Test for boll maturity* and when sufficient mature bolls for desired yield are present make application. Bolls open 7 to 14 days earlier when treated.
	75° to 80° F and Dry	2	1.5	4			
	Above 65° F but cool or Rank cotton	2 2/3	2	3			
Maxunitech Ethephon 6 + FOLEX Defoliant Tank Mix	Cotton that is rank Or Has excess Fertility or Soil moisture	1/3	0.25	24	10 - 50	5 - 10	As a sequential treatment apply 5 to 7 days prior to Maxunitech Ethephon 6 boll opening application but NOT instead of the Maxunitech Ethephon 6 boll opening treatment
Maxunitech Ethephon 6 + Thidiazuron	Cotton that is rank Or Has excess Fertility or Soil moisture	1/3	0.25	24	10 - 50	3 - 10	As a sequential treatment apply 5 to 7 days prior to Maxunitech Ethephon 6 boll opening application but NOT instead of the Maxunitech Ethephon 6 boll opening treatment.
For Use as a Pre-Conditioner for Defoliation	Above 80° F, Hot and Dry	2/3	0.5	12	15-50	2-5	Maxunitech Ethephon 6 should be used 5 to 7 days before use of a defoliant. Used to promote top crop defoliation to prevent bottom crop deterioration and allow earlier harvest.
	Above 65° F and cool or Rank cotton	1 1/3	1.0	6			

*A pretreatment with a defoliant will enhance spray coverage when using Maxunitech Ethephon 6 in a boll opening treatment on cotton that has excessive vegetative growth or otherwise is spread across the middles. Use boll opening rates of Maxunitech Ethephon 6 as recommended. Observe label recommendations for the defoliant used and follow all label directions and precautions.

****NOTE:** For aerial applications in Arizona and California, use an application rate of at least 5 gallons of water per acre.

Boll Maturity

A boll is mature when it is difficult to make a crosswise cut with a sharp knife, and when the outer seed coat has changed from white to a tan or light brown color. In addition, when squeezed between the thumb and fingers, a mature boll will not dent.

Use Limitations

- Maximum labeled rate of Maxunitech Ethephon 6 is 2.0 lb ai for combined uses of Maxunitech Ethephon 6 (or other ethephon containing products) per acre per year. Do not exceed 2.0 lb ai/A/year.
- Boll Opening: If cotton is to be spindle picked do not mix with desiccants.
- Pre-Condition for Defoliation: Maxunitech Ethephon 6 and desiccants should not be tank mixed unless desiccation is desired. The use of a defoliant before there are sufficient mature unopened bolls can reduce expected yield.

When to Harvest

Allow 7 days after a treatment with Maxunitech Ethephon 6 before harvesting. Harvest may commence at the point of optimum boll opening; however, please note that premature harvesting could reduce the boll opening advantage of the treatment and a delayed harvest could reduce quality and affect total yield due to lint dropping from the plant.

TOBACCO
(Flue-Cured Only)

APPLICATION TYPE	RATE OF MAXUNITECH ETHEPHON 6		SPRAY VOLUME (GAL/A)	REMARKS
	PT/A	LB AI		
Directed Spray	1 1/3	1.0	50-60	Drop nozzles recommended. When selecting spray tips, use types TG or OC built to dispense 50-60 gallons of spray solution per acre at a tractor speed of 2-3 mph and a pressure of 35-40 psi. Place one nozzle on each side of the row and point the sprays at the leaves that are to be ripened and harvested, so as to ensure coverage. After this kind of application, it is essential to harvest any and all leaves showing yellowing of 20% or more.
Over-The-Top	1 1/3-2 2/3	1.0-2.0	40-60	Once the rest of the leaves on the stalk have reached maturity, you may make an Over-the-Top application. Follow directions as described under the section "Application Timing" to ensure that leaves are mature. When it appears that a normally mature crop requires some slight inducement in ripening, you may use the low usage rate. The high usage rate is advised under cooler than normal temperatures, and when plants have a predisposition to be rank and heavy. Test spray to verify maturity before spraying as outlined in "Application Timing". Use three nozzles (one nozzle on each side of the row and one over the center of the row). Select nozzles that produce a fine mist and provide thorough coverage of all leaves, calibrated to apply appropriate volume at 40 to 60 psi.

USE LIMITATIONS

- Applications of Maxunitech Ethepon 6 to immature leaves can result in loss of weight, reduced leaf quality and substandard coloring.
- Reduction in quality and yield may result from letting the crop over-ripen in the field following an application of this product.
- Treatment with Maxunitech Ethepon 6 should be delayed if inclement weather is expected that

- could prevent harvest.
- Applications of Maxunitech Ethephon 6 should not be made if rain is anticipated within 6 hours. Rainfall within this time period may reduce desired benefits.

APPLICATION TIMING

For the best results Maxunitech Ethephon 6 should be applied when leaves have reached maturity and are not overly rank and green. Treatment timing and the number of leaves per stalk ready for harvest can be determined by test spraying several plants in various portions of the field and observing the response. Yellowing of a mature leaf will begin in 24 to 72 hours. If within 72 hours treated leaves fail to yellow this is an indication that they are not mature and will not respond to Maxunitech Ethephon 6. Repeat above procedure after several days of natural maturing to verify proper application timing.

Determine the number of acres to be treated for available curing barn space by calculating the number of leaves per plant that will color.

TEST SPRAY MIXTURE DIRECTIONS: (1) Mix one tsp of this product into 1 qt of water. (2) Apply approximately 1 oz of this solution to every test plant. Be sure to cover each entire plant with a light mist. (3) If treated leaves do not color, then they are immature.

WHEN TO HARVEST

Coloring of all mature leaves will begin within 24 to 72 hours post application of Maxunitech Ethephon 6. Weather conditions such as, hot and sunny conditions can speed up the process while cool weather will delay the yellowing process. Treated leaves can be harvested when desired color intensity has been achieved.

Do not allow tobacco to become over ripe before starting harvest. Leaf drop can occur when tobacco is over ripe and left on the stalk. If a number of the bottom leaves have yellowed at the time of treatment, they should be harvested prior to spraying with Maxunitech Ethephon 6.

With an over-the-top application, harvesting can begin 48 hours after Maxunitech Ethephon 6 application depending on weather conditions or to avoid over ripe tobacco. Tobacco harvested 48 hours after treatment may require more time in the coloring phase of the curing process.

CURING MAXUNITECH ETHEPHON 6 TREATED TOBACCO

Experience in the curing procedures can be helpful in assessing tobacco condition and the time interval between treatment and harvest. Curing facilities vary greatly and along with weather conditions must be included before prescription temperature and ventilations schedules can be implemented. During the stages of late coloring and early drying of the leaves, great care must be observed.

The coloring process of Maxunitech Ethephon 6 treated tobacco will have begun when harvested, which can reduce the coloring phase time of curing. Drying treated tobacco faster should be considered. Additional coloring time of a few hours may be required if tobacco leaves are green or contain some green when harvested. Temperature and ventilation should be adjusted to dry tobacco as fast as possible without scalding if the leaves were completely yellow at harvest.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

PESTICIDE STORAGE

Store in a cool, dry place and away from food, feed and other pesticides.

TO CONTAIN A SPILL

Be sure to wear the following when dealing with a spill of this product: Goggles or face shield, long-sleeved shirt, protective gloves, and full-length trousers. Surround the spill with a barrier and then absorb liquid by covering it with cat litter, sand or a commercial clay. If the product container is damaged, place the entire container along with the product in a secure receptacle and clearly label the contents. For any type of product spill, avoid contact with the spilled product and evacuate the area, keeping all unprotected persons and animals at a safe distance.

PESTICIDE DISPOSAL

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER HANDLING

Rigid, Non-Refillable containers small enough to shake (i.e., with capacities equal to or less than 5 gallons)

Nonrefillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container 1/4 full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times. Offer for recycling, if available or puncture and dispose of in a sanitary landfill, or by incineration, or if allowed by state and local authorities, by burning. If container is burned, stay out of smoke.

Rigid, Non-Refillable containers that are too large to shake (i.e., with capacities greater than 5 gallons or 50 lbs.)

Non-refillable container. Do not reuse or refill this container. Triple rinse or pressure rinse container (or equivalent) promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container 1/4 full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times. Offer for recycling, if available or puncture and dispose of in a sanitary landfill, or by incineration, or if allowed by state and local authorities, by burning. If container is burned, stay out of smoke.

Pressure rinse as follows: Empty the remaining contents into application equipment or a mix tank and continue to drain for 10 seconds after the flow begins to drip. Hold container upside down over application equipment or mix tank or collect rinsate for later use or disposal. Insert pressure rinsing nozzle in the side of the container, and rinse at about 40 PSI for at least 30 seconds. Drain for 10 seconds after the flow begins to drip. Offer for recycling, if available or puncture and dispose of in a sanitary landfill, or by incineration, or if allowed by state and local authorities, by burning. If container is burned, stay out of smoke.

LIMITATION OF WARRANTY AND LIABILITY

Read the entire directions for use, conditions of warranties and limitations of liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or buyer accepts the following **CONDITIONS, DISCLAIMER OF WARRANTIES and LIMITATIONS OF LIABILITY. CONDITIONS:** The directions for use of this product are believed to be adequate and must be followed carefully. However, it is impossible to eliminate all risks associated with the use of this product. Crop injury, ineffectiveness or other unintended consequences may result because of such factors as weather conditions, presence of other materials, or the manner of use or application, all of which are beyond the control of Maxunitech North America, Inc. All such risks shall be assumed by the user or buyer. **DISCLAIMER OF WARRANTIES:** To the extent consistent with applicable law, Maxunitech North America,

Inc. makes no other warranties, express or implied, of merchantability or of fitness for a particular purpose or otherwise, that extend beyond the statements made on this label. No agent of Maxunitech North America, Inc. is authorized to make any warranties beyond those contained herein or to modify the warranties contained herein. To the extent consistent with applicable law, Maxunitech North America, Inc. disclaims any liability whatsoever for special, incidental or consequential damages resulting from the use or handling of this product. **LIMITATIONS OF LIABILITY:** To the extent consistent with applicable law, the exclusive remedy of the user or buyer for any and all losses, injuries or damages resulting from the use or handling of this product, whether in contract, warranty, tort, negligence, strict liability or otherwise, shall not exceed the purchase price paid or at Maxunitech North America, Inc.'s election, the replacement of product.