# 

# UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

# Region 1 5 Post Office Square, Suite 100 Boston, MA 02109-3912

## VIA EMAIL

December 12, 2018

Rick Lennon
John Moriarty & Associates
3 Church Street, Suite 2
Winchester, MA 01890
rlennon@jm-a.com

Re: Authorization to discharge under the Remediation General Permit (RGP) – Authorization #MAG910823 for the 150 Seaport Boulevard site located in Boston, MA

Dear Mr. Lennon:

Based on the review of a Notice of Intent (NOI) received October 24, 2018 and revised October 26, 2018 submitted by Haley & Aldrich, Inc. for the site referenced above, the U.S. Environmental Protection Agency, Region 1 (EPA) hereby authorizes John Moriarty & Associates, as the named operator, to discharge in accordance with the provisions of the RGP from this site via the City of Boston storm sewer system to the Boston Inner Harbor (MA70-02). Please note that the operator is responsible for obtaining permission to discharge to this system, prior to initiating discharges. EPA's authorization to discharge does not convey any such permission. The authorization number is listed above. The effective date of coverage is the date of this authorization letter.

Enclosed with this RGP authorization to discharge is a summary of the applicable effluent limitations and monitoring requirements for your activity category III, contaminated site dewatering discharge. Where a given parameter does not apply to the discharge, EPA has indicated "Not Required" in the enclosed summary. A dilution factor of zero (i.e., 1:1) was used in calculating effluent limits applicable to the proposed discharge from this site. Please note that this summary does not represent the complete requirements of the RGP. Operators must comply with all of the applicable requirements of the RGP, including influent and effluent monitoring, record keeping, and reporting requirements. For the complete general permit, see EPA's RGP website, currently available at: https://www.epa.gov/npdes-permits/remediation-general-permit-rgp-massachusetts-new-hampshire.

This EPA general permit and authorization to discharge will expire on April 8, 2022, or upon Notice of Termination (NOT), whichever occurs first. In accordance with Part 5.3 of the RGP, your permit coverage will be administratively continued upon expiration if the RGP has not been reissued. Please note that you must submit a NOT within thirty (30) days of the termination of discharges. Since you have reported your discharges are expected to last twelve (12) months or more. EPA expects you will be subject to NetDMR reporting requirements, which will begin

on January 1, 2020. See Part 4.6 and 5.2 and Appendix IV, Part 3 and Appendix VIII of the RGP for more information regarding reporting requirements. For additional Appendix VIII resources, including instructions for establishing a NetDMR account, see EPA's RGP website noted above.

Please ensure that sufficiently sensitive test methods are used for all sample analyses conducted for this permit. To be considered sufficiently sensitive, test methods must achieve a minimum level (ML) for analysis for a given parameter that is no greater than the effluent limitation for that parameter, unless otherwise specified for that parameter. Where no effluent limitation applies, EPA has provided the ML required with the enclosed summary. Where a compliance level applies, EPA has provided the required compliance level with the enclosed summary. See Part 4.1 of the RGP, and Appendix VII for more information regarding sufficiently sensitive test methods.

Thank you in advance for your cooperation in this matter. Please contact Shauna Little at (617) 918-1989 or little.shauna@epa.gov, if you have any questions.

Sincerely,

Thelma Murphy, Chief

Stormwater and Construction Permits Section

Stuhna Murphy

Office of Ecosystem Protection

cc: Jon Cronin, 150 Seaport LLC, via email Lee S. Vanzler, PE, Haley & Aldrich, Inc., via email Samantha Butwill, EIT, Haley & Aldrich, Inc., via email Cathy Vakalopoulos, MassDEP, via email Boston Water and Sewer Commission, via email

# GENERAL PERMIT FOR REMEDIATION ACTIVITY DISCHARGES

**Table 1: Authorization Information** 

Permit Number	MAG910823	
Receiving Water	Boston Inner Harbor	
Outfall Number	Outfall 001 to City of Boston	
Monitoring Requirements	See Table 2 through Table 6, below; See Part 4.1, and 4.3 of the RGP; WET testing not required	
Reporting Requirement	See Part 4.6.1 of the RGP; NetDMR reporting will begin Jan 1, 2020 unless NOT received by EPA	

Table 2: Chemical-Specific Effluent Limitations and Monitor-Only Requirements<sup>1</sup>

Parameter	Effluent Limitation <sup>2</sup>	
A. Inorganics		
Ammonia <sup>3</sup>	Report mg/L	
Chloride <sup>4</sup>	Report μg/L	
Total Residual Chlorine <sup>5</sup>	Not Required	
Total Suspended Solids	30 mg/L	
Antimony <sup>6</sup>	206 μg/L	
Arsenic <sup>6</sup>	104 μg/L	
Cadmium <sup>6</sup>	10.2 μg/L	
Chromium III <sup>6</sup>	323 μg/L	
Chromium VI <sup>6</sup>	323 μg/L	
Copper <sup>6</sup>	242 μg/L	
Iron <sup>6</sup>	5,000 μg/L	
Lead <sup>6</sup>	8.5 μg/L	
Mercury <sup>6</sup>	0.739 μg/L	
Nickel <sup>6</sup>	1,450 μg/L	
Selenium <sup>6</sup>	235.8 μg/L	
Silver <sup>6</sup>	35.1 μg/L	
Zinc <sup>6</sup>	86 μg/L	
Cyanide <sup>7</sup>	Not Required	
B. Non-Halogenated Volatile Organic Compounds		
Total BTEX	100 μg/L	
Benzene	5.0 μg/L	
1,4 Dioxane	Not Required	
Acetone	7.97 mg/L	
Phenol	Not Required	
C. Halogenated Volatile Organic Compounds		

Carbon Tetrachloride	Not Required	
1,2 Dichlorobenzene	Not Required	
1.3 Dichlorobenzene	Not Required	
1,4 Dichlorobenzene	Not Required	
1,1 Dichloroethane	Not Required	
1,2 Dichloroethane	Not Required	
1,1 Dichloroethylene	Not Required	
Ethylene Dibromide	Not Required	
Methylene Chloride	Not Required	
1,1,1 Trichloroethane	Not Required	
1,1,2 Trichloroethane	Not Required	
	Not Required	
Trichloroethylene	Not Required	
Tetrachloroethylene	Not Required	
cis-1,2 Dichloroethylene	Not Required	
Vinyl Chloride  D. Non-Halogenated Semi-Volatile Organic Compounds	110t Requires	
	Not Required	
Total Phthalates	Not Required	
Diethylhexyl Phthalate	1.0 μg/L	
Total Group 1 Polycyclic Aromatic Hydrocarbons <sup>8</sup>	Report µg/L	
Benzo(a)anthracene <sup>8</sup>	Report µg/L	
Benzo(a)pyrene <sup>s</sup>		
Benzo(b)fluoranthene <sup>8</sup>	Report μg/L	
Benzo(k)fluoranthene <sup>8</sup>	Report µg/L	
Chrysene <sup>8</sup>	Report μg/L Report μg/L	
Dibenzo(a,h)anthracene <sup>8</sup>	Report µg/L Report µg/L	
Indeno(1,2,3-cd)pyrene <sup>8</sup>	100 μg/L	
Total Group II Polycyclic Aromatic Hydrocarbons	20 μg/L	
Naphthalene	20 μg/L	
E. Halogenated Semi-Volatile Organic Compounds	0.000064.ug/I	
Total Polychlorinated Biphenyls <sup>9</sup>	0.000064 μg/L Not Required	
Pentachlorophenol	Not Kequired	
F. Fuels Parameters	5 O ~/I	
Total Petroleum Hydrocarbons	5.0 mg/L	
Ethanol	Not Required	
Methyl-tert-Butyl Ether	Not Required	
tert-Butyl Alcohol	Not Required	
tert-Amyl Methyl Ether	Not Required	

# Table 2 Notes:

- <sup>1</sup> The following abbreviations are used in Table 2, above:
  - a mg/L = milligrams per liter
  - $^{b}$  µg/L = micrograms per liter
- <sup>2</sup> The limitation type for all parameters is monthly average.
- <sup>3</sup> The minimum level (ML) for analysis of ammonia must be less than or equal to 0.1 mg/L.
- <sup>4</sup> The ML for analysis of chloride must be less than or equal to 230 mg/L.
- $^5$  The ML for analysis of total residual chlorine (TRC) must be less than or equal to 50  $\mu g/L$  .
- <sup>6</sup> The limitation for this parameter is on the basis of total recoverable metal in the water column.
- $^7$  Total cyanide must be reported. The ML for analysis of total cyanide must be less than or equal to 5.0  $\mu g/L$ .
- $^{8}$  The ML for analysis of group I polycyclic aromatic hydrocarbons (PAHs) must be less than or equal to 0.1  $\mu$ g/L.
- <sup>9</sup> The ML for analysis of total polychlorinated biphenyls (PCBs) must be less than or equal to 0.5 μg/L. The compliance level for total PCBs is 0.5 μg/L.

Table 3: Effluent Flow Limitation1

Effluent Flow	Effluent Limitation <sup>2</sup>	
	0.2448 MGD	

## **Table 3 Notes**

- <sup>1</sup> The following abbreviations are used in Table 3, above:
  - <sup>a</sup> MGD = million gallons per day
- <sup>2</sup> The limitation type for effluent flow is daily maximum.

Table 4: pH Limitations1

Effluent Limitation <sup>2</sup>	
6.5 to 8.5 SU	

## **Table 4 Notes**

<sup>1</sup> The following abbreviations are used in Table 4, above:

a SU = standard units

Table 5: Temperature Limitations1

Receivin	g Water Class	Effluent Limitation <sup>2</sup>	ΔT Limitation <sup>3</sup>
Class SB		Not Required	Not Required

#### Table 5 Notes

<sup>1</sup> The following abbreviations are used in Table 5, above:

<sup>a</sup> <sup>o</sup>F = degrees Fahrenheit

<sup>b</sup>  $\Delta T$  = change in temperature

 $c \le = less than or equal to$ 

<sup>2</sup> The limitation type for temperature is daily maximum.

<sup>3</sup> Change in temperature from background shall be determined by subtracting the temperature of the effluent from the temperature of the receiving water measured at a point immediately upstream of a discharge's zone of influence at a reasonably accessible location

Table 6: Additional Requirements1

Parameter <sup>2</sup>	Effluent Limitation <sup>3</sup>	
None Required	NA	

## **Table 6 Notes**

<sup>1</sup> The following abbreviations are used in Table 6, above:

a NA = not applicable

2 NA

3 NA

<sup>&</sup>lt;sup>2</sup> The limitation type for pH is range.