

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

Region 1 5 Post Office Square, Suite 100 Boston, MA 02109-3912

VIA EMAIL

November 20, 2020

Christopher Mora
DIV BMT, LLC c/o The Davis Companies
125 High Street
Boston, MA 02110

Re: Authorization to discharge under the Remediation General Permit (RGP) – Authorization #MAG910956 for the Boston Market Terminal Culvert Replacement site located at 34 Market Street in Everett, MA

Christopher Mora:

Based on the review of a Notice of Intent (NOI) dated September 18, 2020 submitted by Haley & Aldrich, Inc. for the site referenced above, the U.S. Environmental Protection Agency, Region 1 (EPA) hereby authorizes DIV BMT, LLC, as the named operator, to discharge in accordance with the provisions of the RGP from this site via the City of Everett and/or Chelsea storm sewer system to the Island End River (MA71-03). Please note that the operator is responsible for obtaining permission to discharge to these systems, prior to initiating discharges. EPA's authorization to discharge does not convey any such permission. The authorization number is listed above. The effective date of coverage is the date of this authorization letter. The RGP and this authorization to discharge will expire on April 8, 2022, or upon Notice of Termination, whichever occurs first. In accordance with Part 5.3 of the RGP, your permit coverage will be administratively continued upon expiration if the RGP has not been reissued.

Enclosed with this RGP authorization to discharge is a summary of the applicable effluent limitations and monitoring requirements for your activity category VII, collection structure dewatering/remediation discharge. Where a given parameter does not apply to the discharge, EPA has indicated "Not Required" in the enclosed summary. No dilution factor was used in calculating effluent limits applicable to the proposed discharge from this site. Please note that this summary does not represent the complete requirements of the RGP. Operators must comply with all of the applicable requirements of the RGP, including influent and effluent monitoring, record keeping, and reporting requirements. For the complete general permit, see EPA's RGP website, currently available at: https://www.epa.gov/npdes-permits/remediation-general-permit-rgp-massachusetts-new-hampshire.

A Best Management Practices Plan (BMPP) and Best Management Practices (BMPs) are required for all operators. This includes corrective actions required upon discovery of a violation of a permit limitation or requirement. See Part 2.5.1 and 2.5.2 of the RGP for more information.

In accordance with Part 2.5.3 of the RGP, no discharges chemical(s) and/or additive(s) are authorized. To discharge any new chemical(s) and/or additive(s), a Notice of Change is required. See Part 5.1 and Appendix IV, Part 2 of the RGP for more information.

Monitoring requirements begin upon initiation of discharge. Please ensure that sufficiently sensitive test methods are used for all sample analyses conducted for this permit. To be considered sufficiently sensitive, test methods must achieve a minimum level (ML) for analysis for a given parameter that is no greater than the effluent limitation for that parameter, unless otherwise specified for that parameter. Where no effluent limitation applies, EPA has provided the ML required with the enclosed summary. Where a compliance level applies, EPA has provided the required compliance level with the enclosed summary. See Part 4.1, 4.3, and 4.4 of the RGP for more information regarding monitoring requirements. Also see Appendix VII for more information regarding sufficiently sensitive test methods.

You must submit a Notice of Termination (NOT) within thirty (30) days of the termination of discharges, which must include an electronic attachment in accordance with Appendix VIII of all monitoring data collected. Since you have reported your discharges are not expected to last twelve (12) months or more, EPA expects you will not be subject to NetDMR reporting requirements. However, if EPA does not receive a NOT, you must begin submitting monitoring data using NetDMR for the monitoring period beginning on December 1, 2021. See Parts 4.6, 5.1, 5.2 and 6, Appendix IV, and Appendix VIII of the RGP for more information regarding reporting requirements. For additional Appendix VIII resources, including instructions for establishing a NetDMR account, see EPA's RGP website noted above.

Thank you in advance for your cooperation in this matter. Please contact Shauna Little at (617) 918-1989 or little.shauna@epa.gov, if you have any questions.

Sincerely,

Todd Borci, Acting Chief Stormwater and Construction Permits Section Water Division

Enclosure

cc: Liza Joyce, Haley & Aldrich, Inc., via email Ian Phillips, Haley & Aldrich, Inc., via email Cathy Vakalopoulos, MassDEP, via email City of Everett DPW, via email City of Chelsea DPW, via email

GENERAL PERMIT FOR REMEDIATION ACTIVITY DISCHARGES

Table 1: Authorization Information

Permit Number	MAG910956	
Receiving Water	Island End River	
Outfall Number(s)	Outfall 001 to City of Everett and/or Chelsea	
	See Table 2 through Table 6, below;	
Monitoring Requirements	See Parts 4.1, 4.3 and 4.4 of the RGP;	
	WET testing not required	
	See Parts 4.6, 5.1, 5.2 and 6 of the RGP;	
Reporting Requirements	NetDMR reporting will begin Dec 1, 2021	
-	unless NOT received by EPA	

Table 2: Chemical-Specific Effluent Limitations and Monitor-Only Requirements¹

Parameter ²	Effluent Limitation ³	
A. Inorganics		
Ammonia ⁴	Report mg/L	
Chloride ⁵	Report µg/L	
Total Residual Chlorine ⁶	Not Required	
Total Suspended Solids	30 mg/L	
Antimony ⁷	Not Required	
Arsenic ⁷	104 μg/L	
Cadmium ⁷	Not Required	
Chromium III ⁷	323 μg/L	
Chromium VI ⁷	323 μg/L	
Copper ⁷	Not Required	
Iron ⁷	5,000 μg/L	
Lead ⁷	8.5 μg/L	
Mercury ⁷	Not Required	
Nickel ⁷	Not Required	
Selenium ⁷	Not Required	
Silver ⁷	Not Required	
Zinc ⁷	Not Required	
Cyanide ⁸	1.0 μg/L	
B. Non-Halogenated Volatile Organic Compounds		
Total BTEX ⁹	Not Required	
Benzene	Not Required	
1,4 Dioxane	Not Required	
Acetone	Not Required	
Phenol	Not Required	
C. Halogenated Volatile Organic Compounds		
Carbon Tetrachloride	Not Required	
1,2 Dichlorobenzene	Not Required	
1,3 Dichlorobenzene	Not Required	
1,4 Dichlorobenzene	Not Required	
1,1 Dichloroethane	Not Required	
1,2 Dichloroethane	Not Required	

1,1 Dichloroethylene	Not Required	
Ethylene Dibromide	Not Required	
Methylene Chloride	Not Required	
1,1,1 Trichloroethane	Not Required	
1,1,2 Trichloroethane	Not Required	
Trichloroethylene	Not Required	
Tetrachloroethylene	Not Required	
cis-1,2 Dichloroethylene	Not Required	
Vinyl Chloride	Not Required	
D. Non-Halogenated Semi-Volatile Organic Compounds		
Total Phthalates ¹⁰	Not Required	
Diethylhexyl Phthalate	Not Required	
Total Group I Polycyclic Aromatic Hydrocarbons ¹¹	1.0 µg/L	
Benzo(a)anthracene ¹¹	$0.0038~\mu g/L$	
Benzo(a)pyrene ¹¹	$0.0038~\mu \mathrm{g/L}$	
Benzo(b)fluoranthene ¹¹	0.0038 μg/L	
Benzo(k)fluoranthene ¹¹	0.0038 μg/L	
Chrysene ¹¹	0.0038 μg/L	
Dibenzo(a,h)anthracene ¹¹	0.0038 μg/L	
Indeno(1,2,3-cd)pyrene ¹¹	0.0038 μg/L	
Total Group II Polycyclic Aromatic Hydrocarbons ¹²	100 μg/L	
Naphthalene	20 μg/L	
E. Halogenated Semi-Volatile Organic Compounds		
Total Polychlorinated Biphenyls ¹³	Not Required	
Pentachlorophenol	Not Required	
F. Fuels Parameters		
Total Petroleum Hydrocarbons	Not Required	
Ethanol ¹⁴	Report mg/L	
Methyl-tert-Butyl Ether	Not Required	
tert-Butyl Alcohol	Not Required	
tert-Amyl Methyl Ether	Not Required	

Table 2 Notes:

1: The following abbreviations are used in Table 2, above:

a: mg/L = milligrams per liter

b: $\mu g/L = micrograms per liter$

- 2: The sample type required for all parameters is grab. Grab samples must be analyzed individually and cannot be composited.
- 3: The effluent limitation and/or monitor-only requirement for any parameter applies, unless "Not Required" is shown. The limitation type for all parameters is monthly average.
- 4: The minimum level (ML) for analysis of ammonia must be less than or equal to 0.1 mg/L.
- 5: The ML for analysis of chloride must be less than or equal to 230 mg/L.

- 6: The ML for analysis of total residual chlorine (TRC) must be less than or equal to 50 μg/L.
- 7: The limitation for this parameter is on the basis of total recoverable metal in the water column.
- 8: The ML for analysis of total cyanide must be less than or equal to $5.0 \mu g/L$. The compliance level for total cyanide is $5.0 \mu g/L$.
- 9: Total BTEX is the sum of: benzene; toluene; ethylbenzene; and (m,p,o) xylenes.
- 10: Total Phthalates is the sum of: diethylhexyl phthalate; butyl benzyl phthalate; di-n-butyl phthalate; diethyl phthalate; dimethyl phthalate; and di-n-octyl phthalate.
- 11: Total Group I PAHs is the sum of: benzo(a)anthracene; benzo(a)pyrene; benzo(b)fluoranthene; benzo(k)fluoranthene; chrysene; dibenzo(a,h)anthracene; indeno(1,2,3-cd)pyrene. ML for analysis of group I polycyclic aromatic hydrocarbons (PAHs) must be less than or equal to 0.1 µg/L using a test method in 40 CFR §136 with selected ion monitoring. MassDEP (e.g., EPH) and RCRA (e.g., 8260) methods cannot be used for analysis. The compliance level for group I PAHs is 0.1 µg/L.
- 12: Total Group II PAHs is the sum of: acenaphthene; acenaphthylene; anthracene (CAS No. 120-12-7); benzo(g,h,i)perylene; fluoranthene; fluorene; naphthalene; phenanthrene; pyrene. MassDEP (e.g., EPH) and RCRA (e.g., 8270) methods cannot be used for analysis.
- 13: Total PCBs is the sum of the following aroclors: PCB-1016, PCB-1221, PCB-1232, PCB-1242, PCB-1248, PCB-1254, and PCB-1260. The ML for analysis of total polychlorinated biphenyls (PCBs) must be less than or equal to $0.5~\mu g/L$.

Table 3: Effluent Flow Limitation¹

Effluent Flow	Effluent Limitation
Elliuent Flow	0.216 MGD

Table 3 Notes:

- 1: The following abbreviations are used in Table 3, above: a: MGD = million gallons per day
- 2: The limitation type for effluent flow is daily maximum.

Table 4: pH Limitations¹

Receiving Water Class	Effluent Limitation ²
Saltwater	6.5 to 8.5 SU

Table 4 Notes:

- 1: The following abbreviations are used in Table 4, above:
 - a: SU = standard units
- 2: The limitation type for pH is range. The sample type required for pH is grab.

Table 5: Temperature Limitations¹

Receivi	ng Water Class	Effluent Limitation ²	ΔT Limitation
Saltwater	Class SB	Not Required	Not Required

Table 5 Notes

1: The following abbreviations are used in Table 5, above:

a: °F = degrees Fahrenheit

b: ΔT = change in temperature

c: \leq = less than or equal to

2: The limitation type for temperature is daily maximum. The ample type required for temperature is grab.

3: Change in temperature from background shall be determined by subtracting the temperature of the effluent from the temperature of the receiving water measured at a point immediately upstream of a discharge's zone of influence at a reasonably accessible location.

Table 6: Additional Requirements

Parameter ²	Effluent Limitation ³
None Required	NA

Table 6 Notes:

1: The following abbreviations are used in Table 6, above:

a: NA = not applicable

2: NA

3: NA