

**APPENDIX H**

Requirements Related to Discharges to Certain Water Quality Limited Waterbodies

**Table of Contents**

I. Discharges to water quality limited waterbodies and their tributaries where nitrogen is the cause of the water quality limitation .....2

II. Discharges to water quality limited waterbodies and their tributaries where phosphorus is the cause of the water quality limitation .....5

III. Discharges to water quality limited waterbodies where bacteria or pathogens is the cause of the water quality limitation .....8

IV. Discharges to water quality limited waterbodies where chloride is the cause of the water quality limitation .....10

V. Discharges to water quality limited waterbodies and their tributaries where solids, oil and grease, or metals is the cause of the water quality limitation .....13

**I. Discharges to water quality limited waterbodies and their tributaries where nitrogen is the cause of the impairment**

1. Part 2.2.2.a.i. of the permit identifies the permittees subject to additional requirements to address nitrogen in their stormwater discharges because they discharge to waterbodies that are water quality limited due to nitrogen, or their tributaries, without an EPA approved TMDL. Permittees identified in Part 2.2.2.a.i of the permit must identify and implement BMPs designed to reduce nitrogen discharges in the impaired catchment(s). To address nitrogen discharges each permittee shall comply with the following requirements:

- a. Additional or Enhanced BMPs

- i. The permittee remains subject to all the requirements of Part 2.3. of the permit and shall include the following enhancements to the BMPs required by Part 2.3 of the permit:

1. Part 2.3.2, Public Education and Outreach: The permittee shall replace its Residential and Business/Commercial/Institution program with annual timed messages on specific topics, at a minimum. The permittee shall distribute an annual message in the spring (April/May) timeframe that encourages the proper use and disposal of grass clippings and encourages the proper use of slow-release fertilizers. The permittee shall distribute an annual message in the summer (June/July) timeframe encouraging the proper management of pet waste, including noting any existing ordinances where appropriate. The permittee shall distribute an annual message in the Fall (August/September/October) timeframe encouraging the proper disposal of leaf litter. The permittee shall deliver an annual message on each of these topics, unless the permittee determines that one or more of these issues is not a significant contributor of nitrogen to discharges from the MS4 and the permittee retains documentation of this finding in the SWMP.
2. Part 2.3.6, Stormwater Management in New Development and Redevelopment: the requirement for adoption/amendment of the permittee's ordinance or other regulatory mechanism shall include a requirement that new development and redevelopment stormwater management BMPs be optimized for nitrogen removal; retrofit inventory and priority ranking under 2.3.6.e shall include consideration of BMPs to reduce nitrogen discharges.
3. Part 2.3.7, Good House Keeping and Pollution Prevention for Permittee Owned Operations: establish requirements for use of slow release fertilizers on permittee owned property currently using fertilizer, in addition to reducing and managing fertilizer use as provided in 2.3.7.1; establish procedures to properly manage grass cuttings and leaf litter on permittee property, including prohibiting blowing organic waste materials onto adjacent impervious surfaces; increased street sweeping frequency of all municipal owned streets and parking lots to a minimum of two times per year, once in the spring (following winter activities such as sanding) and at least once in the fall (following leaf fall). Permittees

may also choose, in lieu of post-leaf drop street sweeping, to implement a fall leaf litter collection program to effectively minimize leaf litter on impervious surfaces and in stormwater drainage structures. Either choice will be outlined in the permittee's SWMP.

b. Nitrogen Source Identification Report

- i. Within four years of the permit effective date the permittee shall complete a Nitrogen Source Identification Report. The report shall include the following elements:
  1. Calculation of total MS4 area draining to the water quality limited water segments or their tributaries, incorporating updated mapping of the MS4 and catchment delineations produced pursuant to Part 2.3.4.6,
  2. All screening and monitoring results pursuant to Part 2.3.4.7.d., targeting the receiving water segment(s)
  3. Impervious area and DCIA for the target catchment
  4. Identification, delineation and prioritization of potential catchments with high nitrogen loading
  5. Identification of potential retrofit opportunities or opportunities for the installation of structural BMPs during redevelopment
- ii. The final Nitrogen Source Identification Report shall be submitted to EPA as part of the year 4 annual report.

c. Potential Structural BMPs

- i. Within five years of the permit effective date, the permittee shall evaluate all permittee-owned properties identified as presenting retrofit opportunities or areas for structural BMP installation under permit Part 2.3.6.e. or identified in the Nitrogen Source Identification Report that are within the drainage area of the impaired water or its tributaries. The evaluation shall include:
  1. The next planned infrastructure, resurfacing or redevelopment activity planned for the property (if applicable) OR planned retrofit date;
  2. The estimated cost of redevelopment or retrofit BMPs; and
  3. The engineering and regulatory feasibility of redevelopment or retrofit BMPs.
- ii. The permittee shall provide a listing of planned structural BMPs and a plan and schedule for implementation in the year 5 annual report. The permittee shall plan and install a minimum of one structural BMP as a demonstration project within the drainage area of the water quality limited water or its tributaries within six years of the permit effective date. The demonstration project shall be installed targeting a catchment with high nitrogen load potential. The permittee shall install the

remainder of the structural BMPs in accordance with the plan and schedule provided in the year 5 annual report.

- iii. Any structural BMPs listed in Attachment 3 to Appendix F installed in the regulated area by the permittee or its agents shall be tracked and the permittee shall estimate the nitrogen removal by the BMP consistent with Attachment 3 to Appendix F. The permittee shall document the BMP type, total area treated by the BMP, the design storage volume of the BMP and the estimated nitrogen removed in mass per year by the BMP in each annual report.
2. At any time during the permit term the permittee may be relieved of additional requirements in Appendix H part I.1. applicable to it when in compliance with this part.
    - a. The permittee is relieved of its additional requirements as of the date when one of the following criteria are met:
      - i. The receiving water and all downstream segments are determined to no longer be impaired due to nitrogen by NH DES and EPA concurs with such determination.
      - ii. An EPA approved TMDL for the receiving water or downstream receiving water indicates that no additional stormwater controls for the control of nitrogen are necessary for the permittee's discharge based on wasteload allocations as part of the approved TMDL.
    - b. In such a case, the permittee shall document the date of the determination provided for in paragraph a. above or the approved TMDL date in its SWMP and is relieved of any additional requirements of Appendix H part I.1. as of the applicable date and the permittee shall comply with the following:
      - i. The permittee shall identify in its SWMP all activities that have been implemented in accordance with the requirements of Appendix H part I.1. as of the applicable date to reduce nitrogen in its discharges, including implementation schedules for non-structural BMPs and any maintenance requirements for structural BMPs
      - ii. The permittee shall continue to implement all requirements of Appendix H part I.1. required to be done prior to the date of determination or the date of the approved TMDL, including ongoing implementation of identified non-structural BMPs and routine maintenance and replacement of all structural BMPs in accordance with manufacturer or design specifications.

**II. Discharges to water quality limited waterbodies and their tributaries where phosphorus is the cause of the impairment**

- 1) Part 2.2.2.b.i. of the permit identifies the permittees subject to additional requirements to address phosphorus in their stormwater discharges because they discharge to waterbodies that are water quality limited due to phosphorus, or their tributaries, without an EPA approved TMDL. Permittees identified in Part 2.2.2.b.i. of the permit must identify and implement BMPs designed to reduce phosphorus discharges in the impaired catchment(s). To address phosphorus discharges each permittee shall comply with the following requirements:
  - a. Additional or Enhanced BMPs
    - i. The permittee remains subject to the requirements of Part 2.3. of the permit and shall include the following enhancements to the BMPs required by Part 2.3 of the permit:
      1. Part 2.3.2, Public education and outreach: The permittee shall replace its Residential and Business/Commercial/Institution program with annual timed messages on specific topics, at a minimum. The permittee shall distribute an annual message in the spring (March/April) timeframe that encourages the proper use and disposal of grass clippings and encourages the proper use of slow-release and phosphorous-free fertilizers. The permittee shall distribute an annual message in the summer (June/July) timeframe encouraging the proper management of pet waste, including noting any existing ordinances where appropriate. The permittee shall distribute an annual message in the fall (August/September/October) timeframe encouraging the proper disposal of leaf litter. The permittee shall deliver an annual message on each of these topics, unless the permittee determines that one or more of these issues is not a significant contributor of phosphorous to discharges from the MS4 and the permittee retains documentation of this finding in the SWMP.
      2. Part 2.3.6, Stormwater Management in New Development and Redevelopment: the requirement for adoption/amendment of the permittee's ordinance or other regulatory mechanism shall include a requirement that new development and redevelopment stormwater management BMPs be optimized for phosphorus removal; retrofit inventory and priority ranking under 2.3.6.e. shall include consideration of BMPs that infiltrate stormwater where feasible.
      3. Part 2.3.7, Good House Keeping and Pollution Prevention for Permittee Owned Operations: Establish procedures to properly manage grass cuttings and leaf litter on permittee property, including prohibiting blowing organic waste materials onto adjacent impervious surfaces; increased street sweeping frequency of all municipal owned streets and parking lots to a minimum of two times per year, once in the spring (following winter activities such as sanding) and at least once in the fall (following leaf fall). Permittees may also choose, in lieu of post-leaf drop street sweeping, to implement a fall leaf litter collection program to effectively minimize leaf litter on impervious surfaces and in stormwater

drainage structures. Either choice will be outlined in the permittee's SWMP.

b. Phosphorus Source Identification Report

- i. Within four years of the permit effective date the permittee shall complete a Phosphorus Source Identification Report. The report shall include the following elements:
  1. Calculation of total MS4 area draining to the water quality limited receiving water segments or their tributaries, incorporating updated mapping of the MS4 and catchment delineations produced pursuant to Part 2.3.4.6,
  2. All screening and monitoring results pursuant to Part 2.3.4.7.d., targeting the receiving water segment(s)
  3. Impervious area and DCIA for the target catchment
  4. Identification, delineation and prioritization of potential catchments with high phosphorus loading
  5. Identification of potential retrofit opportunities or opportunities for the installation of structural BMPs during redevelopment, including the removal of impervious area of permittee-owned properties
- ii. The final phosphorus source identification report shall be submitted to EPA as part of the year 4 annual report.

c. Potential Structural BMPs

- i. Within five years of the permit effective date, the permittee shall evaluate all permittee-owned properties identified as presenting retrofit opportunities or areas for structural BMP installation under permit Part 2.3.6.e or identified in the Phosphorus Source Identification Report that are within the drainage area of the water quality limited water or its tributaries. The evaluation shall include:
  1. The next planned infrastructure, resurfacing or redevelopment activity planned for the property (if applicable) OR planned retrofit date;
  2. The estimated cost of redevelopment or retrofit BMPs; and
  3. The engineering and regulatory feasibility of redevelopment or retrofit BMPs.
- ii. The permittee shall provide a listing of planned structural BMPs and a plan and schedule for implementation in the year 5 annual report. The permittee shall plan and install a minimum of one structural BMP as a demonstration project within the drainage area of the water quality limited water or its tributaries within six years of the permit effective date. The demonstration project shall be installed targeting a catchment with high phosphorus load potential. The permittee shall install the

remainder of the structural BMPs in accordance with the plan and schedule provided in the year 5 annual report.

- iii. Any structural BMPs installed in the regulated area by the permittee or its agents shall be tracked and the permittee shall estimate the phosphorus removal by the BMP consistent with Attachment 3 to Appendix F. The permittee shall document the BMP type, total area treated by the BMP, the design storage volume of the BMP and the estimated phosphorus removed in mass per year by the BMP in each annual report.
2. At any time during the permit term the permittee may be relieved of additional requirements in Appendix H part II.1. applicable to it when in compliance with this part.
    - a. The permittee is relieved of its additional requirements as of the date when one of the following criteria are met:
      - i. The receiving water and all downstream segments are determined to no longer be impaired due to phosphorus by NH DES and EPA concurs with such determination.
      - ii. An EPA approved TMDL for the receiving water or downstream receiving water indicates that no additional stormwater controls for the control of phosphorus are necessary for the permittee's discharge based on wasteload allocations as part of the approved TMDL.
    - b. In such a case, the permittee shall document the date of the determination provided for in paragraph a. above or the approved TMDL date in its SWMP and is relieved of any additional requirements of Appendix H part II.1. as of the applicable date and the permittee shall comply with the following:
      - i. The permittee shall identify in its SWMP all activities that have been implemented in accordance with the requirements of Appendix H part II.1. as of the applicable date to reduce phosphorus in its discharges, including implementation schedules for non structural BMPs and any maintenance requirements for structural BMPs
      - ii. The permittee shall continue to implement all requirements of Appendix H part II.1. required to be done prior to the date of determination or the date of the approved TMDL, including ongoing implementation of identified non-structural BMPs and routine maintenance and replacement of all structural BMPs in accordance with manufacturer or design specifications.

**III. Discharges to water quality limited waterbodies where bacteria or pathogens is the cause of the impairment**

1. Part 2.2.2.c.i. of the permit identifies the permittees subject to additional requirements to address bacteria or pathogens (Enterococcus or Escherichia Coli) in their stormwater discharges because they discharge to waterbodies that are water quality limited due to bacteria or pathogens without an EPA approved TMDL. Permittees identified in Part 2.2.2.c.i. of the permit must identify and implement BMPs designed to reduce bacteria or pathogens discharges in the impaired catchment(s). To address bacteria or pathogens discharges each permittee shall comply with the following requirements:
  - a. Additional or Enhanced BMPs
    - i. The permittee remains subject to the requirements of Part 2.3. of the permit and shall include the following enhancements to the BMPs required by Part 2.3 of the permit:
      1. Part 2.3.2. Public Education: The permittee shall replace its Residential program with an annual message encouraging the proper management of pet waste, including noting any existing ordinances where appropriate, at a minimum. The permittee or its agents shall disseminate educational materials to dog owners at the time of issuance or renewal of a dog license, or other appropriate time. Education materials shall describe the detrimental impacts of improper management of pet waste, requirements for waste collection and disposal, and penalties for non-compliance. The permittee shall also provide information to owners of septic systems (if applicable) about proper maintenance in any catchment that discharges to a water body impaired for bacteria or pathogens.
      2. Part 2.3.4 Illicit Discharge: The permittee shall implement the illicit discharge program required by this permit. Catchments draining to any waterbody impaired for bacteria or pathogens shall be designated either Problem Catchments or HIGH priority in implementation of the IDDE program.
2. At any time during the permit term the permittee may be relieved of additional requirements in Appendix H part III.2. applicable to it when in compliance with this part.
  - a. The permittee is relieved of its additional requirements as of the date when one of the following criteria are met:
    - i. The receiving water is determined to be no longer impaired due to bacteria or pathogens by NH DES and EPA concurs with such a determination.
    - ii. An EPA approved TMDL for the receiving water indicates that no additional stormwater controls are necessary for the control of bacteria or pathogens from the permittee's discharge based on wasteload allocations as part of the approved TMDL.



- iii. The permittee's discharge is determined to be below applicable water quality criteria<sup>1</sup> and EPA agrees with such a determination. The permittee shall submit data to EPA that accurately characterizes the concentration of bacteria or pathogens in their discharge. The characterization shall include water quality and flow data sufficient to accurately assess the concentration of bacteria or pathogens in all seasons during storm events of multiple sizes and for the duration of the storm events including the first flush, peak storm flow and return to baseflow.
- b. In such a case, the permittee shall document the date of the determination, date of approved TMDL or date of EPA concurrence that the discharge meets water quality criteria in its SWMP and is relieved of any additional requirements of Appendix H part III.2. as of that date and the permittee shall comply with the following:
  - i. The permittee shall identify in its SWMP all activities implemented in accordance with the requirements of Appendix H part III.2. to date to reduce bacteria or pathogens in its discharges, including implementation schedules for non-structural BMPs and any maintenance requirements for structural BMPs
  - ii. The permittee shall continue to implement all requirements of Appendix H part III.3. required to be done prior to the date of determination date, date of approved TMDL, or date of EPA concurrence that the discharge meets water quality criteria, including ongoing implementation of identified non-structural BMPs and routine maintenance and replacement of all structural BMPs in accordance with manufacturer or design specifications

---

<sup>1</sup> Applicable water quality criteria are the state standards that have been federally approved as of the effective date of this permit and are compiled by EPA at <http://www.epa.gov/waterscience/standards/wqslibrary/>

**IV. Discharges to water quality limited waterbodies where chloride is the cause of the impairment**

1. Part 2.2.2.d.i. of the permit identifies the permittees subject to additional requirements to address chloride in their stormwater discharges because they discharge to waterbodies that are water quality limited due to chloride without an EPA approved TMDL. Permittees identified in Part 2.2.2.d.i. of the permit must identify and implement BMPs designed to reduce chloride discharges in the impaired catchment(s). To address chloride discharges each permittee shall comply with the following requirements.
2. Permittees discharging to a waterbody listed as impaired due to chloride in categories 5 or on the most recent EPA approved New Hampshire Clean Water Act section 303(d) list or New Hampshire Integrated Report under Clean Water Act section 305(b)4b shall develop a Salt Reduction Plan that includes specific actions designed to achieve salt reduction on municipal roads and facilities, and on private facilities that discharge to its MS4. The Salt Reduction Plan shall be completed within three years of the effective date of the permit and include the BMPs in Part IV 4) below. The Salt Reduction Plan shall be fully implemented five years after the effective date of the permit.
3. Permittees that, during the permit term, become aware that their discharge is to a waterbody that is impaired due to chloride must update their Salt Reduction Plan within 60 days of becoming aware of the situation to include salt reduction practices targeted at lowering chloride in discharges to the impaired waterbody. If the permittee does not have a Salt Reduction Plan already in place, then the permittee shall complete a Salt Reduction Plan that includes the BMPs in Part IV 4) below within 3 years of becoming aware of the situation and fully implement the Salt Reduction Plan within 5 years of becoming aware of the situation.
  - a. Additional or Enhanced BMPs
    - i. For municipally maintained surfaces:
      - (i) Tracking of the amount of salt applied to all municipally owned and maintained surfaces and reporting of salt use using the UNH Technology Transfer Center online tool (<http://www.roadsalt.unh.edu/Salt/>) beginning in the year 2 annual report;
      - (ii) Planned activities for salt reduction on municipally owned and maintained surfaces, which may include but are not limited to:
        - Operational changes such as pre-wetting, pre-treating the salt stockpile, increasing plowing prior to de-icing, monitoring of road surface temperature, etc.;
        - Implementation of new or modified equipment providing pre-wetting capability, better calibration rates, or other capability for minimizing salt use;
        - Training for municipal staff and/or contractors engaged in winter maintenance activities;
        - Adoption of guidelines for application rates for roads and parking lots (see NHDES, *Chloride Reduction Implementation Plan for Dinsmore*

*Brook, App. J and K* (February 2011), <http://des.nh.gov/organization/commissioner/pip/publications/wd/documents/wd-11-13.pdf> ;: *Winter Parking Lot and Sidewalk Maintenance Manual (Revised edition June 2008)* <http://www.pca.state.mn.us/publications/parkinglotmanual.pdf>; and the application guidelines on page 17 of *Minnesota Snow and Ice Control: Field Handbook for Snow Operators (September 2012)* <http://www.mnltap.umn.edu/publications/handbooks/documents/snowice.pdf> for examples );

- Regular calibration of spreading equipment;
- Designation of no-salt and/or low salt zones;
- Public education regarding impacts of salt use, methods to reduce salt use on private property, modifications to driving behavior in winter weather, etc.; and
- Measures to prevent exposure of salt stockpiles (if any) to precipitation and runoff; and

(iii) An estimate of the total tonnage of salt reduction expected by each activity; and

(iv) A schedule for implementation of planned activities including immediate implementation of operational and training measures, continued annual progress on other measures, and full implementation of the Plan by the end of the permit term.

b. For privately maintained facilities that drain to the MS4:

(i) Identification of private parking lots with 10 or more parking spaces draining to the MS4;

(ii) Requirements for private parking lot owners and operators and private street owners and operators (1) that any commercial salt applicators used for applications of salt to their parking lots or streets be trained and certified in accordance with Env-Wq 2203, and (2) to report annual salt usage within the municipal boundaries using the UNH Technology Transfer Center online tool (<http://www.roadsalt.unh.edu/Salt/>) or report salt usage directly to the permittee, in which case this information should be reported on the permittees annual report.

(iii) Requirements for new development and redevelopment to minimize salt usage, and to track and report amounts used using the UNH Technology Transfer Center online tool (<http://www.roadsalt.unh.edu/Salt/>).

4. At any time during the permit term the permittee may be relieved of additional requirements in Appendix H part IV as follows:

- a. The permittee is relieved of its additional requirements as of the date when one of the following criteria are met:
  - i. The receiving water is determined to be no longer impaired due to chloride by NH DES and EPA concurs with such a determination.

- ii. An EPA approved TMDL for the receiving water indicates that no additional stormwater controls are necessary for the control of chloride from the permittee's discharge based on wasteload allocations as part of the approved TMDL.
  - iii. The permittee's discharge is determined to be below applicable water quality criteria<sup>2</sup> and EPA agrees with such a determination. The permittee shall submit data to EPA that accurately characterizes the concentration of chloride in their discharge during the deicing season (November – March). The characterization shall include water quality and flow data sufficient to accurately assess the concentration of chloride in the deicing season during storm events of multiple sizes and for the duration of the storm events including the first flush, peak storm flow and return to baseflow and include samples collected during deicing activities.
- b. In such a case, the permittee shall document the date of the determination, date of approved TMDL or date of EPA concurrence that the discharge meets water quality criteria in its SWMP and is relieved of any additional requirements of Appendix H part IV as of that date and the permittee shall comply with the following:
- i. The permittee shall identify in its SWMP all activities implemented in accordance with the requirements of Appendix H part IV to date to reduce chloride in its discharges, including implementation schedules for non-structural BMPs
  - ii. The permittee shall continue to implement all requirements of Appendix H part IV required to be done by the date of determination date, date of approved TMDL, or date of EPA concurrence that the discharge meets water quality criteria, including ongoing implementation of identified non-structural BMPs

---

<sup>2</sup> Applicable water quality criteria are the state standards that have been federally approved as of the effective date of this permit and are compiled by EPA at <http://www.epa.gov/waterscience/standards/wqslibrary/>

**V. Discharges to water quality limited waterbodies and their tributaries where solids, oil and grease (hydrocarbons), or metals is the cause of the impairment**

1. Part 2.2.2.e.i. of the permit identifies the permittees subject to additional requirements to address solids (Sedimentation/Siltation or Turbidity), metals (Cadmium, Copper, Iron, Lead or Zinc) and oil and grease (Benzo(a)pyrene (PAHs)) in their stormwater discharges because they discharge to waterbodies that are water quality limited due to solids, metals, or oil and grease, without an EPA approved TMDL. Permittees identified in Part 2.2.2.e.i. of the permit must identify and implement BMPs designed to reduce solids, metals, or oil and grease discharges in the impaired catchment(s). To address solids, metals, or oil and grease discharges each permittee shall comply with the following requirements:
  - a. Additional or Enhanced BMPs
    - i. The permittee remains subject to the requirements of Part 2.3. of the permit and shall include the following enhancements to the BMPs required by Part 2.3 of the permit:
      1. Part 2.3.6, Stormwater Management in New Development and Redevelopment: stormwater management systems designed on commercial and industrial land use area draining to the water quality limited waterbody shall incorporate designs that allow for shutdown and containment where appropriate to isolate the system in the event of an emergency spill or other unexpected event. EPA also encourages the permittee to require any stormwater management system designed to infiltrate stormwater on commercial or industrial sites to provide the level of pollutant removal equal to or greater than the level of pollutant removal provided through the use of biofiltration as calculated using the methodologies contained in the EPA document: Stormwater Best Management Practices (BMP) Performance Analysis (2010). of the same volume of runoff to be infiltrated, prior to infiltration.
      2. Part 2.3.7, Good House Keeping and Pollution Prevention for Permittee Owned Operations: increased street sweeping and catch basin cleaning frequency of all municipal owned streets and parking lots to a schedule determined by the permittee to target areas with potential for high pollutant loads. This may include, but is not limited to, increased street sweeping frequency in commercial areas and high density residential areas, or drainage areas with a large amount of impervious area. Each annual report shall include the street sweeping schedule determined by the permittee to target high pollutant loads.
2. At any time during the permit term the permittee may be relieved of additional requirements in Appendix H part V.2. applicable to it when in compliance with this part.
  - a. The permittee is relieved of its additional requirements as of the date when one of the following criteria are met:
    - i. The receiving water is determined to be no longer impaired due to solids, metals, or oil and grease (hydrocarbons) by NH DES and EPA concurs with such a determination.

- ii. An EPA approved TMDL for the receiving water indicates that no additional stormwater controls are necessary for the control of solids, metals, or oil and grease (hydrocarbons) from the permittee's discharge based on wasteload allocations as part of the approved TMDL.
  - iii. The permittee's discharge is determined to be below applicable water quality criteria and EPA agrees with such a determination<sup>3</sup>. The permittee shall submit data to EPA that accurately characterizes the concentration of solids, metals, or oil and grease (hydrocarbons) in their discharge. The characterization shall include water quality and flow data sufficient to accurately assess the concentration of solids, metals, or oil and grease (hydrocarbons) in all seasons during storm events of multiple sizes and for the duration of the storm events including the first flush, peak storm flow and return to baseflow.
- b. In such a case, the permittee shall document the date of the determination, date of approved TMDL or date of EPA concurrence that the discharge meets water quality criteria in its SWMP and is relieved of any additional requirements of Appendix H part V.2. as of that date and the permittee shall comply with the following:
- i. The permittee shall identify in its SWMP all activities implemented in accordance with the requirements of Appendix H part V.2. to date to reduce solids, metals, or oil and grease (hydrocarbons) in its discharges, including implementation schedules for non-structural BMPs and any maintenance requirements for structural BMPs
  - ii. The permittee shall continue to implement all requirements of Appendix H part V.3. required to be done by the date of determination date, date of approved TMDL, or date of EPA concurrence that the discharge meets water quality criteria, including ongoing implementation of identified non-structural BMPs and routine maintenance and replacement of all structural BMPs in accordance with manufacturer or design specifications

---

<sup>3</sup> Applicable water quality criteria are the state standards that have been federally approved as of the effective date of this permit and are compiled by EPA at <http://www.epa.gov/waterscience/standards/wqslibrary/>