

NPDES PERMIT NO. TX0134032
STATEMENT OF BASIS

FOR THE DRAFT NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM
(NPDES) PERMIT TO DISCHARGE TO WATERS OF THE UNITED STATES

APPLICANT:

CMR Energy, L.P.
CMR1025H
4265 San Felipe, Suite 1040
Houston, TX 77027

ISSUING OFFICE:

U.S. Environmental Protection Agency
Region 6
1445 Ross Avenue
Dallas, Texas 75202-2733

PREPARED BY:

Maria E. Okpala
Environmental Engineer
NPDES Permits Branch (6WQ-PP)
Water Quality Protection Division
Voice: 214-665-3152
Fax: 214-665-2191
Email: okpala.maria@epa.gov

DATE PREPARED:

August 29, 2016

PERMIT ACTION

It is proposed that the facility be issued an NPDES permit for a 5-year term in accordance with regulations contained in 40 Code of Federal Regulations (CFR) 122.46(a).

40 CFR CITATIONS: Unless otherwise stated, citations to 40 CFR refer to promulgated regulations listed at Title 40, Code of Federal Regulations, revised as of August 26, 2016.

RECEIVING WATER – BASIN

Unnamed intermittent stream 1.6 miles upstream of Comanche Creek and thence Farias Lake (2.3 miles total). Comanche Creek flows into Turkey Creek, and then into Nueces River (Nueces River above Holland Dam), Texas Segment 2105 of the Nueces River Basin.

DOCUMENT ABBREVIATIONS

For brevity, Region 6 used acronyms and abbreviated terminology in this Statement of Basis document whenever possible. The following acronyms were used frequently in this document:

BAT	Best Available Technology Economically Achievable)
BOD ₅	Biochemical oxygen demand (five-day unless noted otherwise)
BOPD	Barrels of oil per day
BPJ	Best professional judgment
CFR	Code of Federal Regulations
cfs	Cubic feet per second
COD	Chemical oxygen demand
COE	United States Corp of Engineers
CWA	Clean Water Act
DMR	Discharge monitoring report
ELG	Effluent limitation guidelines
EPA	United States Environmental Protection Agency
ESA	Endangered Species Act
F&WS	United States Fish and Wildlife Service
GPD	Gallon per day
IP	Procedures to Implement the Texas Surface Water Quality Standards
µg/l	Micrograms per liter (one part per billion)
mg/l	Milligrams per liter (one part per million)
Menu 8	Intermittent stream within 3 miles of a lake or a reservoir
MGD	Million gallons per day
MSGP	Multi-Sector General Permit
ND	Non Detect
NPDES	National Pollutant Discharge Elimination System
MQL	Minimum quantification level
O&G	Oil and grease
RRC	Railroad Commission of Texas
RP	Reasonable potential
SIC	Standard industrial classification
s.u.	Standard units (for parameter pH)
TAC	Texas Administrative Code
TCEQ	Texas Commission on Environmental Quality
TDS	Total dissolved solids
TMDL	Total maximum daily load
TOC	Total Organic Carbon
TRC	Total residual chlorine
TSS	Total suspended solids
TSWQS	Texas Surface Water Quality Standards
WET	Whole effluent toxicity
WQMP	Water Quality Management Plan
WQS	Water Quality Standards

I. PROPOSED CHANGES FROM PREVIOUS PERMIT

New Discharger

II. APPLICANT LOCATION and ACTIVITY

Under the SIC Code 1311, the applicant is engaged in crude petroleum and natural gas.

As described in the application, the facility is located at 19468 Southeast Hwy 277, Eagle Pass, Maverick County, Texas. Produced water discharges from the facility flows into unnamed tributary of Comanche Creek, an intermittent stream, within 3 miles of a lake or a waterbody that acts like a lake. The facility discharges into an unnamed intermittent stream 1.6 miles upstream of Comanche Creek and thence Farias Lake (2.3 miles total). Comanche Creek flows into Turkey Creek, and then into Nueces River (Nueces River above Holland Dam), Texas Segment 2105 of the Nueces River Basin.

Discharges are located on that water at:

Outfall 001: Latitude 28° 32' 40" N; Longitude 100° 6' 58" W

III. PROCESS AND DISCHARGE DESCRIPTION

The facility generates fresh water from oil production. Produced water is separated from the oil in a Gun Barrel of 750 bbl. The water flows on to a 400 bbl. settling tank before flowing into a 200 bbl. open top skimming tank. Produced water is then allowed to settle via gravity separation of produced water from oil, before discharging. The facility does not use any chemicals during this process.

Produced water produces an estimated average of 960 bbls/day of fresh water. Produced water is being discharged into unnamed tributary of Comanche Creek.

Table 1: Discharge Characteristics for Outfall 001

The table below shows facility's pollutant concentrations contained in the NPDES application.

Parameter	Max Concentration, mg/L unless noted	Average Concentration, mg/L unless noted
Flow, MGD	0.03	0.03
PH	5.4 – 6.6	5.4 – 6.6
BOD	14	9.9
TSS	8.33	7.63
COD	48.3	34.03
TOC	9.01	7.93
Ammonia-N	0.855	0.623
Oil & Grease	4.03	3.5
Temperature, winter	20 °C	20 °C
Temperature, summer	23 °C	23 °C
Chloride	262	257.33
Sulfate	767	755.33

Parameter	Max Concentration, mg/L unless noted	Average Concentration, mg/L unless noted
Total Dissolved Solids	1,780	1,713
Aluminum	0.0982	0.08
Arsenic	0.0026	0.0023
Nickel	0.002	0.002
Mercury	0.0002	0.0002
Selenium	0.002	0.002
Silver	0.001	0.001
Zinc	0.0131	0.00995

IV. REGULATORY AUTHORITY/PERMIT ACTION

In November 1972, Congress passed the Federal Water Pollution Control Act establishing the NPDES permit program to control water pollution. These amendments established technology-based or end-of-pipe control mechanisms and an interim goal to achieve “water quality which provides for the protection and propagation of fish, shellfish, and wildlife and provides for recreation in and on the water;” more commonly known as the “swimmable, fishable” goal. Further amendments in 1977 of the CWA gave EPA the authority to implement pollution control programs such as setting wastewater standards for industry and established the basic structure for regulating pollutants discharges into the waters of the United States. In addition, it made it unlawful for any person to discharge any pollutant from a point source into navigable waters, unless a permit was obtained under its provisions. Regulations governing the EPA administered NPDES permit program are generally found at 40 CFR §122 (program requirements & permit conditions), §124 (procedures for decision making), §125 (technology-based standards) and §136 (analytical procedures). Other parts of 40 CFR provide guidance for specific activities and may be used in this document as required.

It is proposed that the permit be issued for a 5-year term following regulations promulgated at 40 CFR 122.46(a). This is a first-time permit issuance. An NPDES Application for a Permit to Discharge (Form 1) was received on February 15, 2015. Additional permit application information, including form 2E were received on June 1, 2016; June 6, 2016; via email on June 23, 2016; and August 3, 2016. The application was deemed administratively complete on August 10, 2016.

V. DRAFT PERMIT RATIONALE AND PROPOSED PERMIT CONDITIONS

A. OVERVIEW of TECHNOLOGY-BASED VERSUS WATER QUALITY STANDARDS-BASED EFFLUENT LIMITATIONS AND CONDITION FOR PERMIT ISSUANCE

Regulations contained in 40 CFR §122.44 NPDES permit limits are developed that meet the more stringent of either technology-based effluent limitation guidelines, numerical and/or narrative water quality standard-based effluent limits, on best professional judgment (BPJ) in the absence of guidelines, and/or requirements pursuant to 40 CFR 122.44(d), whichever are more stringent. Technology-based effluent limitations are established in the proposed draft permit for Chemical Oxygen Demand and Oil & grease. Water quality-based effluent limitations are established in the proposed draft permit for pH and dissolved oxygen.

TECHNOLOGY-BASED EFFLUENT LIMITATIONS/CONDITIONS

Regulations promulgated at 40 CFR §122.44 (a) require technology-based effluent limitations to be placed in NPDES permits based on ELGs where applicable, on BPJ in the absence of guidelines, or on a combination of the two. In the absence of promulgated guidelines for the discharge, permit conditions may be established using BPJ procedures. EPA establishes limitations based on the following technology-based controls: BPT, BCT, and BAT. These levels of treatment are:

BPT - The first level of technology-based standards generally based on the average of the best existing performance facilities within an industrial category or subcategory.

BCT - Technology-based standard for the discharge from existing industrial point sources of conventional pollutants including BOD, TSS, fecal coliform, pH, and O&G.

BAT - The most appropriate means available on a national basis for controlling the direct discharge of toxic and non-conventional pollutants to navigable waters. BAT effluent limits represent the best existing performance of treatment technologies that are economically achievable within an industrial point source category or subcategory.

Effluent Limitations

Produced Water discharges are covered under the effluent guideline for onshore oil and gas operations. These activities are subject to the Oil and Gas Extraction Point Source Category (40 CFR Part 435). The Oil and Gas Extraction Point Source Category Subpart C - Onshore Subcategory establishes the effluent limitation for produced water from Onshore operations as "No Discharge" [40 CFR 435.32 (a)]. Oil wells with very small production (i.e. Stripper wells producing less than 10 bbl/day of oil) are not regulated by the Onshore Subcategory but are regulated by the Stripper Subcategory (40 CFR 435.60). CMR 1025H falls under the Stripper Subcategory. However, Subpart E - Agricultural and Wildlife Water Use Subcategory, allows the discharge of produced water from facilities west of the 98th meridian for use in agricultural and wildlife propagation. Since discharges west of the 98th meridian has a use in agricultural and wildlife propagation, Subpart F- Stripper Subcategory does not apply to CMR 1025H. CMR 1025H is located west of the 98th meridian. The effluent guideline further requires ". . . that the produced water is of good enough quality to be used for wildlife or livestock watering or other agricultural uses and that the produced water is actually put to such use during periods of discharge." The technology base limit for oil and grease is 35 mg/l.

In order to protect water quality from impacts to DO in the receiving water, a Chemical Oxygen Demand limit of 100 mg/l, daily maximum is established in the draft permit based on BPJ.

Produced wastewater discharges may contain various organic chemicals, inorganic chemicals, metals, and naturally occurring radioactive materials (NORM). Monitoring and reporting requirements for Total Petroleum Hydrocarbons will be proposed based on Best Professional Judgment, BPJ. The data reported for these pollutants will be evaluated during the next permit cycle to see if a discharge limit is required.

C. WATER QUALITY BASED LIMITATIONS

1. General Comments

Water quality based requirements are necessary where effluent limits more stringent than technology-based limits are necessary to maintain or achieve federal or state water quality limits. Under Section 301(b)(1)(C) of the CWA, discharges are subject to effluent limitations based on federal or state WQS. Effluent limitations and/or conditions established in the draft permit are in compliance with applicable State WQS and applicable State water quality management plans to assure that surface WQS of the receiving waters are protected and maintained, or attained.

2. Implementation

The NPDES permits contain technology-based effluent limitations reflecting the best controls available. Where these technology-based permit limits do not protect water quality or the designated uses, additional water quality-based effluent limitations and/or conditions are included in the NPDES permits. State narrative and numerical water quality standards are used in conjunction with EPA criteria and other available toxicity information to determine the adequacy of technology-based permit limits and the need for additional water quality-based controls.

3. State Water Quality Standards

The Clean Water Act in Section 301 (b) requires that effluent limitations for point sources include any limitations necessary to meet water quality standards. Federal regulations found at 40 CFR 122.44(d) state that if a discharge poses the reasonable potential to cause an in-stream excursion above a water quality criterion, the permit must contain an effluent limit for that pollutant. If the discharge poses the reasonable potential to cause an in-stream violation of narrative standards, the permit must contain prohibitions to protect that standard. Additionally, the TWQS found at 30 TAC Chapter 307 states that "surface waters will not be toxic to man from ingestion of water, consumption of aquatic organisms, or contact with the skin, or to terrestrial or aquatic life." The methodology outlined in the "Procedures to Implement the Texas Surface Water Quality Standards" (IP) is designed to ensure compliance with 30 TAC Chapter 307. Specifically, the methodology is designed to ensure that no source will be allowed to discharge any wastewater which: (1) results in instream aquatic toxicity; (2) causes a violation of an applicable narrative or numerical state water quality standard; (3) results in the endangerment of a drinking water supply; or (4) results in aquatic bioaccumulation which threatens human health.

The IP document is not a state water quality standard, but rather, a non-binding, non-regulatory guidance document. See IP at page 2 stating that "this is a guidance document and should not be interpreted as a replacement to the rules. The TWQS may be found in 30 TAC Sections (§§) 307.1-.10."). EPA does not consider the IP to be a new or revised water quality standard and has never approved it as such. EPA did comment on and conditionally "approve" the IP as part of the Continuing Planning Process (CPP) required under 40 CFR §130.5(c) and the Memorandum of Agreement between TCEQ and EPA, but this does not constitute approval of the IP as a water quality standard under CWA section 303(c). Therefore, EPA is not bound by the IP in establishing limits in this permit – but rather, must ensure that the limits are consistent with the EPA-approved state WQS. However, EPA has made an effort, where we believe the IP procedures are consistent with all applicable State and Federal regulations, to use those procedures.

The general criteria and numerical criteria which make up the stream standards are provided in the 2000 EPA-approved Texas Water Quality Standards, Texas Administrative Code (TAC), 30 TAC Sections 307.1 - 307.9, effective September 23, 2014.

The designated uses of Atascosa River, Segment 2105 are primary contact recreation, high aquatic life, and public water supply.

4. Reasonable Potential- Procedures

EPA develops draft permits to comply with State WQS, and for consistency, attempts to follow the IP where appropriate. However, EPA is bound by the State's WQS, not State guidance, including the IP, in determining permit decisions. EPA performs its own technical and legal review for permit issuance, to assure compliance with all applicable State and Federal requirements, including State WQS, and makes its determination based on that review. Waste load allocations (WLA's) are calculated using estimated effluent dilutions, criteria outlined in the TWQS, and partitioning coefficients for metals (when appropriate and designated in the implementation procedures). The WLA is the end-of-pipe effluent concentrations that can be discharged and still meet instream criteria after mixing with the receiving stream. From the WLA, a long term average (LTA) is calculated, for both chronic and acute toxicity, using a log normal probability distribution, a given coefficient of variation (0.6), and either a 90th or a 99th percentile confidence level. The 90th percentile confidence level is for discharges to rivers, freshwater streams and narrow tidal rivers with upstream flow data, and the 99th percentile confidence level is for the remainder of cases. For facilities that discharge into receiving streams that have human health standards, a separate LTA will be calculated. The implementation procedures for determining the human health LTA use a 99th percentile confidence level, along with a given coefficient of variation (0.6). The lowest of the calculated LTA; acute, chronic and/or human health, is used to calculate the daily average and daily maximum permit limits.

Procedures found in the IP for determining significant potential are to compare the reported analytical data either from the DMR history and/or the application information, against percentages of the calculated daily average water quality-based effluent limitation. If the average of the effluent data equals or exceeds 70% but is less than 85% of the calculated daily average limit, monitoring for the toxic pollutant will usually be included as a condition in the permit. If the average of the effluent data is equal to or greater than 85% of the calculated daily average limit, the permit will generally contain effluent limits for the toxic pollutant. The permit may specify a compliance period to achieve this limit if necessary.

Procedures found in the IP require review of the immediate receiving stream and effected downstream receiving waters. Further, if the discharge reaches a perennial stream or an intermittent stream with perennial pools within three-miles, chronic toxicity criteria apply at that confluence.

5. Permit-Action - Water Quality-Based Limits

Regulations promulgated at 40 CFR §122.44(d) require limits in addition to, or more stringent than effluent limitation guidelines (technology based). State WQS that are more stringent than effluent limitation guidelines are as follows:

a. pH

Wastewater discharges from the facility flow into an unnamed intermittent stream 1.6 miles upstream of Comanche Creek and thence Farias Lake (2.3 miles total). Comanche Creek flows into Turkey Creek, and then into Nueces River (Nueces River above Holland Dam), Texas Segment 2105 of the Nueces River Basin. pH shall be limited to the standards for the Nueces River above Holland Dam in Water Body Segment No. 2105 of the Nueces River Basin to the range of 6.5 to 9.0 s.u.

b. Oil and Grease

To ensure that this discharge is of sufficient quality for livestock and wildlife water use, and therefore meets the requirements of Subpart E, the proposed permit establishes a more stringent Oil and Grease limit of 10 mg/L monthly average, with a daily maximum limit of 15 mg/l. This limit is based on BPJ in accordance with 40 CFR 125.3(h)(1) and is consistent with other produced water permit issued by other EPA Regions.

c. Narrative Limitations

Narrative protection for aesthetic standards will propose that surface waters shall be maintained so that oil, grease, or related residue will not produce a visible film or globules of grease on the surface or coat the banks or bottoms of the watercourse; or cause toxicity to man, aquatic life, or terrestrial life.

The discharge shall not present a hazard to humans, wildlife, or livestock.

The following narrative limitations in the proposed permit represent protection of water quality for Outfall 001:

“The effluent shall contain no visible film of oil or globules of grease on the surface or coat the banks or bottoms of the watercourse.”

d. Toxics

The CWA in Section 301 (b) requires that effluent limitations for point sources include any limitations necessary to meet water quality standards. Federal regulations found at 40 CFR §122.44 (d) state that if a discharge poses the reasonable potential to cause an in-stream excursion above a water quality criteria, the permit must contain an effluent limit for that pollutant.

The critical low flow, 7Q2 for the receiving stream is 0 cfs, while the harmonic mean is 7.15 cfs. The facility discharges into an unnamed intermittent stream 1.6 miles upstream of Comanche Creek and thence Farias Lake (2.3 miles total). Comanche Creek flows into Turkey Creek, and then into Nueces River (Nueces River above Holland Dam), Texas Segment 2105 of the Nueces River Basin. TCEQ’S TEXTOX Menu 8 (Discharge is to an intermittent water body within 3 miles of a lake or a water body that acts like a lake) is appropriate for evaluating the discharge.

The reasonable potential calculations were performed based on data obtained from the permit application. Segment specific values for pH, TSS, total hardness, TDS, chloride, and sulfate values were obtained from table 5 of the IP. These values were also used in Menu 8 to calculate

reasonable potential. The result of the Menu 8 model run revealed that none of the pollutants showed reasonable potential to violate TSWQS.

TDS, sulfate and chloride are present in the discharge and were screened using the procedures found on page 175/176 of the IP. Using these procedures, the geometric mean of the effluent concentration of TDS obtained from the permit application (1,713 mg/l) was compared to the screening value to determine whether a TDS permit limit is needed. The calculations are shown below:

$$C_{TDS} = (C_c / 500 \text{ mg/L}) * 2,500 \text{ mg/L}$$

where: C_{TDS} = TDS concentration (mg/L) used to determine the TDS screening value

C_c = TDS criterion (mg/L) at the first downstream Segment = 900 mg/L

$$C_{TDS} = (900 / 500 \text{ mg/L}) * 2,500 \text{ mg/L} = 4,500 \text{ mg/L}$$

According to page 176 of ITWQS, if C_{TDS} is $> 2,500 \text{ mg/L}$ but $\leq 6,000 \text{ mg/L}$, then $C_{SV} = C_{TDS}$ where C_{SV} is the TDS screening value. Since the effluent concentration (1,713 mg/L) is less than the TDS screening value (4,500 mg/L), TDS limitations and monitoring requirements are not established in the draft permit.

TDS screening guidelines for intermittent streams are intended to protect livestock, wildlife, shoreline vegetation, and aquatic life during periods when the stream is flowing; the screening is also intended to preclude excessive TDS loading in watersheds that could eventually impact distant downstream perennial waters.

Similarly, sulfate and chloride concentrations were also screened using equation 1b found on page 177 of the ITWQS as shown below:

$$C_{Cl \text{ or } SO_4} C_{SV} = (TDS C_{SV} / TDS \text{ Criterion}) * C_{Cl \text{ or } SO_4} \text{ Criterion}$$

$$C_{SO_4} = (4,500/900) * 200 \text{ mg/L} = 1,000 \text{ mg/L};$$

$$C_{Cl} = (4,500 / 900 \text{ mg/L}) * 200 \text{ mg/L} = 1,000 \text{ mg/L}$$

According to page 175 of ITWQS, the values of 1,000 mg/L are both less than 4,500 mg/L. As a result, 4,500 mg/L is their respective screening value. But the respective effluent concentrations of sulfate and chloride (755.33 mg/L and 257.33 mg/L respectively) are both less than 4,500 mg/L. As a result, the proposed permit did not established limitation and monitoring requirements for sulfate and chloride.

Produced wastewater discharges may contain various organic chemicals, inorganic chemicals, metals, and naturally occurring radioactive materials (NORM). Monitoring and reporting requirements for Benzene, BETX (sum of benzene, ethyl benzene, toluene and xylene), radium 226, radium 228, radium 226 + radium 228 and adjusted gross alpha will be proposed based on Best Professional Judgment, BPJ. The data reported for these pollutants will be evaluated during the next permit cycle to see if a discharge limit is required.

Solids and Foam

The prohibition of the discharge of floating solids or visible foam in other than trace amounts is established in the proposed permit. In addition, there shall be no discharge of visible films of oil, globules of oil, grease or solids in or on the water, or coatings on stream banks.

D. MONITORING FREQUENCY FOR LIMITED PARAMETERS

Regulations require permits to establish monitoring requirements to yield data representative of the monitored activity, 40 CFR §122.48(b), and to assure compliance with permit limitations, 40 CFR §122.44(i)(1). The monitoring frequencies are based on BPJ, taking into account the nature of the facility, the previous permit, and past compliance history.

Flow shall be measured weekly. pH, oil & grease, TDS, sulfate, chloride, chemical oxygen demand and dissolved oxygen shall be monitored twice a month, using grab sample. For any monitoring event, the first sample of any event shall be collected at least seven (7) days from the first sample of the previous monitoring event.

Total Petroleum Hydrocarbon, Benzene, BETX (sum of benzene, ethyl benzene, toluene and xylene), radium 226, radium 228, radium 226 + radium 228 and adjusted gross alpha shall be monitored once per three months using grab sample.

E. WHOLE EFFLUENT TOXICITY LIMITATIONS

Biomonitoring is the most direct measure of potential toxicity which incorporates both the effects of synergism of effluent components and receiving stream water quality characteristics. Biomonitoring of the effluent is, therefore, required as a condition of this permit to assess potential toxicity.

Guidance in the ITWQS requires that a discharge to an intermittent stream within three miles of a perennial freshwater stream conduct either a 48-hour acute or a 7-day chronic test. Further, the ITWQS states that if the effluent flow equals or exceeds 10% of the low-flow of the perennial water, the permittee will conduct 7-day chronic testing. The low-flow of the unnamed intermittent stream is 0 cfs. The facility effluent flow is 0.03 MGD, therefore, a 7-day chronic testing with semiannual monitoring for *Pimephales promelas* and *Ceriodaphnia dubia* is required according to the provisions indicated in Parts I and II of this permit.

OUTFALL 001

The 2010 TCEQ Implementation Plan directs the WET test to be a 7 day chronic test using chronic test species *Ceriodaphnia dubia* and *Pimephales promelas* at a quarterly frequency for the first year of the permit. If all WET tests pass during the first year, the permittee may request a monitoring frequency reduction for the either or both of the test species for the following 2-5 years of the permit. The invertebrate species (*Ceriodaphnia dubia*) may be reduced to twice per year and the vertebrate species (*Pimephales promelas*) may be reduced to once per year. If any tests fail during that time, the frequency will revert back to the once per three months frequency for the remainder of the permit term. Both test species shall resume monitoring at a quarterly frequency on the last day of the permit.

The proposed permit requires five (5) dilutions in addition to the control (0% effluent) to be used in the toxicity tests based on a 0.75 dilution series. These additional effluent concentrations shall be 32%, 42%, 56%, 75%, and 100%. The low-flow effluent concentration (critical low-flow dilution) is defined as 100% effluent.

Since the facility is a new discharger, there is no WET data; as a result, EPA will not perform reasonable potential analysis.

During the period beginning the effective date of the permit and lasting through the expiration date of the permit, the permittee is authorized to discharge from Outfall **001** - the discharge to an unnamed intermittent stream 1.6 miles upstream of Comanche Creek and thence Farias Lake (2.3 miles total). Comanche Creek flows into Turkey Creek, and then into Nueces River (Nueces River above Holland Dam), Texas Segment 2105 of the Nueces River Basin. Discharges shall be limited and monitored by the permittee as specified below:

<u>EFFLUENT CHARACTERISTIC</u>	<u>DISCHARGE MONITORING</u>	
	<u>30-DAY AVG MINIMUM</u>	<u>7-DAY MINIMUM</u>
Whole Effluent Toxicity Testing (7 Day Static Renewal) <u>1/</u>		
<u>Ceriodaphnia dubia</u>	REPORT	REPORT
<u>Pimephales promelas</u>	REPORT	REPORT

<u>EFFLUENT CHARACTERISTIC</u>	<u>MONITORING REQUIREMENTS</u>	
	<u>FREQUENCY</u>	<u>TYPE</u>
Whole Effluent Toxicity Testing (7 Day Static Renewal) <u>1/</u>		
<u>Ceriodaphnia dubia</u>	1/Quarter	24-Hr. Composite
<u>Pimephales promelas</u>	1/Quarter	24-Hr. Composite

FOOTNOTES

1/ Monitoring and reporting requirements begin on the effective date of this permit. See Part II, Whole Effluent Toxicity Testing Requirements for additional WET monitoring and reporting conditions.

In addition to conducting the 7-day chronic test, the facility is required to conduct 24-hour acute tests using 100% effluent. This end-of pipe test measures compliance with 30 TAC §307.6(e)(2)(B) of the TSWQS, which requires that greater than 50% of the test organisms survive exposure to 100% effluent for 24 hours. This provision is designed to ensure that water in the state will not be acutely toxic to aquatic life.

The test shall be a 24-Hour, LC-50 at 100% critical dilution. This test shall be protective of the direct end-of-pipe discharge. The frequency for this test shall be once/six months when discharging.

During the period beginning the effective date of the permit and lasting through the expiration date of the permit, the permittee is authorized to discharge from Outfall 001. Discharges shall be limited and monitored by the permittee as specified below:

<u>EFFLUENT CHARACTERISTIC</u>	<u>DISCHARGE MONITORING</u>	
	<u>30-DAY AVG</u>	<u>24-Hr.</u>
	<u>MINIMUM</u>	<u>MINIMUM</u>
Whole Effluent Toxicity Testing (TX 24-Hr. LC50)		
<u>Ceriodaphnia dubia</u>	REPORT	REPORT
<u>Pimephales promelas</u>	REPORT	REPORT
<u>EFFLUENT CHARACTERISTIC</u>	<u>MONITORING REQUIREMENTS</u>	
	<u>FREQUENCY</u>	<u>SAMPLE TYPE</u>
Whole Effluent Toxicity Testing (TX 24-Hr. LC50)		
<u>Ceriodaphnia dubia</u>	1/6 MONTHS	GRAB
<u>Pimephales promelas</u>	1/6 MONTHS	GRAB

F. FINAL EFFLUENT LIMITATIONS

See the draft permit for limitations.

VI. FACILITY OPERATIONAL PRACTICES

A. WASTE WATER POLLUTION PREVENTION REQUIREMENTS

The permittee shall institute programs directed towards pollution prevention. The permittee will institute programs to improve the operating efficiency and extend the useful life of the treatment system.

B. OPERATION AND REPORTING

The permittee must submit Discharge Monitoring Report's (DMR's) quarterly, beginning on the effective date of the permit, lasting through the expiration date of the permit or termination of the permit, to report on all limitations and monitoring requirements in the permit.

The permittee must submit monitoring results to EPA on either the electronic or paper Discharge Monitoring Report (DMR) approved formats. Monitoring results can be submitted electronically in lieu of the paper DMR Form. All DMRs shall be electronically reported effective December 21, 2016, per 40 CFR 127.16. To submit electronically, access the NetDMR website at

www.epa.gov/netdmr and contact the R6NetDMR@epa.gov in-box for further instructions. Until the permittee is approved for Net DMR, it must report on the Discharge Monitoring Report (DMR) Form EPA No. 3320-1 in accordance with the "General Instructions" provided on the form. No additional copies are needed if reporting electronically, however when submitting paper form EPA No. 3320-1, the permittee shall submit the original DMR signed and certified as required by Part III.D.11 and all other reports required by Part III.D. to the EPA and other agencies as required. (See Part III.D.IV of the permit.)

Electronic Reporting Rule

The EPA published the electronic reporting rule in the federal register (80 FR 64063) on October 22, 2015. The rule became effective on December 21, 2015. One year after the effective date of the final rule, NPDES regulated entities that are required to submit DMRs (including majors and non-majors, individually permitted facilities and facilities covered by general permits) must do so electronically. EPA and authorized NPDES programs will begin electronically receiving these DMRs from all DMR filers and start sharing these data with each other.

Sufficiently Sensitive Analytical Methods (SSM)

The permittee must use sufficiently sensitive EPA-approved analytical methods (SSM) (under 40 CFR part 136 or required under 40 CFR chapter I, subchapters N or O) when quantifying the presence of pollutants in a discharge for analyses of pollutants or pollutant parameters under the permit. In case the approved methods are not sufficiently sensitive to the limits, the most SSM with the lowest method detection limit (MDL) must be used as defined under 40 CFR 122.44(i)(1)(iv)(A). If no analytical laboratory is able to perform a test satisfying the SSM in the region, the most SSM with the lowest MDL must be used after adequate demonstrations by the permittee and EPA approval.

VII. IMPAIRED WATER - 303(d) LIST AND TMDL

Wastewater discharges from the facility flow into an unnamed intermittent stream 1.6 miles upstream of Comanche Creek and thence Farias Lake (2.3 miles total). Comanche Creek flows into Turkey Creek, and then into Nueces River (Nueces River above Holland Dam), Texas Segment 2105 of the Nueces River Basin.

The receiving stream is listed as impaired for depressed dissolved oxygen in the 2014 State of Texas 303(d) List for Assessed River/Stream Reaches Requiring Total Maximum Daily Loads (TMDLs). All the impaired parameters are under TCEQ's Category 5c. Category 5c implies that additional data or information will be collected and/or evaluated for one or more parameters before a management strategy is selected. However, since the receiving stream is impaired for depressed dissolved oxygen, the proposed permit establishes an end-of-pipe DO limit of 3.0 mg/l minimum, with a mean DO of 5.0 mg/l; and in the spring (March 21 to June 20), an end-pipe limit of minimum DO limit of 4.5 mg/l, with a mean DO of 5.5 mg/l. If the waterbody is listed at a later date for additional pollutants, and a total maximum discharge loading determined for the segment, the standard reopener clause would allow the permit to be revised and additional pollutants and/or limits added. No additional requirements beyond the already proposed technology-based and/or water-quality based requirements are needed in the proposed permit.

VIII. ANTIDEGRADATION

The Texas Commission on Environmental Quality, Texas Surface Water Quality Standards, Antidegradation, Title 30, Part 1, Chapter 307, Rule §307.5 sets forth the requirements to protect designated uses through implementation of the State WQS. The limitations and monitoring requirements set forth in the proposed permit are developed from the State WQS and are protective of those designated uses. Furthermore, the policy sets forth the intent to protect the existing quality of those waters, whose quality exceeds their designated use. The permit requirements are protective of the assimilative capacity of the receiving waters, which is protective of the designated uses of that water. There are no increases of pollutants being discharged to the receiving waters authorized in the proposed permit. This facility is currently authorized by the Texas Railroad Commission to discharge produced water.

IX. ANTIBACKSLIDING

The proposed permit is consistent with the requirements and exemption to meet Antibacksliding provisions of the Clean Water Act, Section 402(o) and 40 CFR Part 122.44(i)(B), which state in part that interim or final effluent limitations must be as stringent as those in the previous permit, unless information is available which was not available at the time of permit issuance. Since this is a first time NPDES Permit for this discharge, antibacksliding does not apply.

X. ENDANGERED SPECIES

According to the most recent county listing available at US Fish and Wildlife Service (USFWS), Southwest Region 2 website, at US Fish and Wildlife Service (USFWS), Southwest Region 2 website, <http://ecos.fws.gov/ipac/wizard/chooseLocation!prepare.action>, five species are listed as endangered or threatened in Maverick County. The listed species are Least tern (*Sterna antillarum*), Red Knot (*Calidris canutus*), Piping Plover (*Charadrius melodus*), Gulf Coast Jaguarundi (*Herpailurus Yagouaroundi Cacomitli*), and Ocelot (*Leopardus Pardalis*). A description of the species and its effects to the proposed permit follows:

LEAST TERN (*Sterna Antillarum*)

The Least tern populations have declined due to habitat destruction by permanent inundation, destruction by reservoir releases, channelization projects, alterations of Natural River or lake dynamics resulting in vegetational succession of potential nesting sites, and recreational use of potential nesting sites. Issuance of this permit is found to have no impact on the habitat of this species, as none of the aforementioned listed activities is authorized by this permitting action.

RED KNOT (*Calidris canutus*)

Red Knot is a medium-sized shorebird and the largest of the "peeps" in North America, and one of the most colorful. It makes one of the longest yearly migrations of any bird, traveling 15,000 km (9,300 mile) from its Arctic breeding grounds to Tierra del Fuego in southern South America.

Their diet varies according to season; arthropods and larvae are the preferred food items at the breeding grounds, while various hard-shelled molluscs are consumed at other feeding sites at other times.

The Red Knot nests on the ground, near water, and usually inland. The nest is a shallow scrape lined with leaves, lichens and moss. Males construct three to five nest scrapes in their territories prior to the arrival of the females. The female lays three or more usually four eggs, apparently laid over the course of six days. Both parents incubate the eggs, sharing the duties equally. The incubation period last around 22 days.

The birds have become threatened as a result of commercial harvesting of horseshoe crabs in the Delaware Bay which began in the early 1990s. Delaware Bay is a critical stopover point during spring migration; the birds refuel by eating the eggs laid by these crabs (with little else to eat in the Delaware Bay).

PIPING PLOVER (*Charadrius melodus*)

A small plover has wings approximately 117 mm; tail 51 mm; weight 46-64 g (average 55 g); length averages about 17-18 cm. Inland birds have more complete breast band than Atlantic coast birds. The nonbreeding plovers lose the dark bands. In Laguna Madre, Texas, non-breeding home ranges were larger in winter than in fall or spring. The breeding season begins when the adults reach the breeding grounds in mid- to late-April or in mid-May in northern parts of the range. The adult males arrive earliest, select beach habitats, and defend established territories against other males. When adult females arrive at the breeding grounds several weeks later, the males conduct elaborate courtship rituals including aerial displays of circles and figure eights, whistling song, posturing with spread tail and wings, and rapid drumming of feet. The plovers defend territory during breeding season and at some winter sites. Nesting territory may or may not contain the foraging area. Home range during the breeding season generally is confined to the vicinity of the nest. Plovers are usually found in sandy beaches, especially where scattered grass tufts are present, and sparsely vegetated shores and islands of shallow lakes, ponds, rivers, and impoundments.

Food consists of worms, fly larvae, beetles, crustaceans, mollusks, and other invertebrates. The plovers prefer open shoreline areas, and vegetated beaches are avoided. It also eats various small invertebrates. It obtains food from surface of substrate, or occasionally probes into sand or mud.

Strong threats related primarily to human activity; disturbance by humans, predation, and development pressure are pervasive threats along the Atlantic coast.

JAGUARUNDI, GULF COAST (*Herpailurus Yagouarundi Cacomitli*)

The Jaguarundi is a small weasel-like wild cat with short rounded ears. It is also called Otter cats because of their shot legs, slender elongated bodies, and small flattened heads, giving them an otter-like appearance. They prefer lowland brush areas close to water or dense tropical areas as their habitat. They are good tree climbers and swimmers. Jaguarundis eat fish that they catch from streams and rivers. Mating occurs from September to November. The cat is suffering decline due to loss of habitat.

EPA has determined that the re-issuance of the permit will have “no effect” on the Gulf Coast Jaguarundi based on the limited information available on the species which indicates that in Texas, any current presence of jaguarundi apparently is confined to the southernmost four counties of Cameron, Willacy, Hidalgo and Starr.

OCELOT (*Leopardus Pardalis*)

The ocelot is a small cat, ranging from 15 to 30 pounds and measuring an average 3 feet 9 inches in length. Its coat has black spots, bars, and stripes on a rich tan to gray background, with irregular black dots on a white underside and dark bars on the tail. The ocelot is listed endangered due to habitat alteration and loss (primarily due to brush clearing), and predator control activities. EPA has determined that the issuance of the permit will have “no effect” on the Ocelot.

The Environmental Protection Agency has evaluated the potential effects of issuance of this permit upon listed endangered or threatened species. After review, EPA has determined that the issuance of this permit will have “no effect” on listed threatened and endangered species nor will adversely modify designated critical habitat. EPA makes this determination based on the following:

1. The proposed permit establishes limits to meet the current state water quality standards for the area of discharge. The limits established in the proposed permit are protective and will have no impact on the habitats of this species. The permit includes limitations and/or monitoring requirements for pH, oil & grease, chemical oxygen demand, TDS, sulfate, chloride, dissolved oxygen, total Petroleum Hydrocarbon, benzene, BETX (sum of benzene, ethyl benzene, toluene and xylene), radium 226, radium 228, radium 226 + radium 228 and adjusted gross alpha. The proposed permit also includes biomonitoring requirements for *Ceriodaphnia dubia* and *Pimephales promelas* (7 -day static renewal). It also includes biomonitoring requirements for *Ceriodaphnia dubia* *Pimephales promelas* (24-hr LC50). These requirements are also consistent with the State of Texas implementation guidance.
2. The issuance of this permit will have no effect above the environmental baseline on the listed species.

Based on information described above, EPA Region 6 has determined that discharges proposed to be authorized by the proposed permit will have no effect on the listed species in Maverick County. The standard reopener clause in the permit will allow EPA to reopen the permit and impose additional limitations if it is determined that changes in species or knowledge of the discharge would require different permit conditions.

The Environmental Protection Agency has evaluated the potential effects of issuance of this permit upon listed endangered or threatened species. After review, EPA has determined that the issuance of this permit will have “no effect” on listed threatened and endangered species nor will adversely modify designated critical habitat. EPA makes this determination based on the following:

2. The proposed permit establishes limits to meet the current state water quality standards for the area of discharge. The limits established in the proposed permit are protective and will have no impact on the habitats of this species. The permit includes limitations and monitoring requirements for pH, oil & grease, TDS, sulfate, chloride, dissolved oxygen, cadmium, total Petroleum Hydrocarbon, benzene, BETX (sum of benzene, ethyl benzene, toluene and xylene), radium 226, radium 228, radium 226 + radium 228 and adjusted gross alpha. The proposed permit also includes biomonitoring requirements for *Ceriodaphnia dubia* and *Pimephales*

promelas (7 -day static renewal). It also includes biomonitoring requirements for *Ceriodapnia dubia* *Pimephales promelas* (24-hr LC50). These requirements are also consistent with the State of Texas implementation guidance.

2. The issuance of the CMR 1025H will have no effect above the environmental baseline on the listed species.

Based on information described above, EPA Region 6 has determined that discharges proposed to be authorized by the proposed permit will have no effect on the listed species in Maverick County. The standard reopener clause in the permit will allow EPA to reopen the permit and impose additional limitations if it is determined that changes in species or knowledge of the discharge would require different permit conditions.

XI. HISTORICAL AND ARCHEOLOGICAL PRESERVATION CONSIDERATIONS

The issuance of the permit should have no impact on historical and/or archeological sites since no construction activities are planned in the issuance.

XII. PERMIT REOPENER

The permit may be reopened and modified during the life of the permit if relevant portions of the Texas WQS are revised or remanded. In addition, the permit may be reopened and modified during the life of the permit if relevant procedures implementing the WQS are either revised or promulgated. Should the State adopt a new WQS, and/or develop a TMDL, this permit may be reopened to establish effluent limitations for the parameter(s) to be consistent with that approved State standard and/or water quality management plan, in accordance with 40 CFR §122.44(d). Modification of the permit is subject to the provisions of 40 CFR §124.5.

XIII. VARIANCE REQUESTS

No variance requests have been received.

XIV. COMPLIANCE HISTORY

None

XV. CERTIFICATION

This permit is in the process of certification by the State agency following regulations promulgated at 40 CFR 124.53. A draft permit and draft public notice will be sent to the District Engineer, Corps of Engineers; to the Regional Director of the U.S. Fish and Wildlife Service and to the National Marine Fisheries Service prior to the publication of that notice.

XVI. FINAL DETERMINATION

The public notice describes the procedures for the formulation of final determinations.

XVII. ADMINISTRATIVE RECORD

The following information was used to develop the proposed permit:

A. APPLICATION

NPDES Application for a Permit to Discharge (Form 1) was received on February 15, 2015. Additional permit application information, including form 2E were received on June 1, 2016; June 6, 2016; via email on June 23, 2016; and August 3, 2016.

B. State of Texas References

The State of Texas Water Quality Inventory, 13th Edition, Publication No. SFR-50, Texas Commission on Environmental Quality, December 1996.

"Procedures to Implement the Texas Surface Water Quality Standards via Permitting," Texas Commission on Environmental Quality, June 2010.

Texas Surface Water Quality Standards, 30 TAC Sections 307.1 - 307.9, September 23, 2014.

<http://ecos.fws.gov/ipac/wizard/chooseLocation!prepare.action>

D. 40 CFR CITATIONS

Sections 122, 124, 125, 133, and 136

E. MISCELLANEOUS CORRESPONDENCE

Letter from Dorothy Brown, EPA, to Mr. Jim Cook, Operations Consultant, CMR Energy, dated August 10, 2016, informing the applicant that its' NPDES application received February 15, 2016, is administratively complete.

Email from Robert Kirkland, EPA, to Maria Okpala, EPA, dated August 2, 2016, on critical conditions information.

Letter from Mr. J.E. Cook, Operations Consultant, CMR Energy, L.P. to Ms. Brown, EPA, dated May 24, 2016, and received June 1, 2016; dated June 1, 2016, and received on June 6, 2016; via email on June 23, 2016; and August 3, 2016, on additional permit application information.

Letter from Ms. Dorothy Brown, EPA to Mr. Jim Cook, Operations Consultant, CMR Energy, L.P. dated April 15, 2016, informing the applicant that its' NPDES application received February 15, 2016, is administratively incomplete.