

BARCLAYS OFFICIAL CALIFORNIA CODE OF REGULATIONS
TITLE 13. MOTOR VEHICLES
DIVISION 3. AIR RESOURCES BOARD
CHAPTER 5. STANDARDS FOR MOTOR VEHICLE FUELS
ARTICLE 1. STANDARDS FOR GASOLINE
SUBARTICLE 2. STANDARDS FOR GASOLINE SOLD BEGINNING MARCH 1, 1996

This database is current through 12/26/2003, Register 2003, No. 52.

the standards set forth in this subarticle 2, an applicable sampling methodology set forth in 13 C.C.R. section 2296 shall be used.

(b)Test Methods.

(1) In determining compliance with the standards set forth in this subarticle 2, the test methods presented in Table 1 shall be used. All identified test methods are incorporated herein by reference.

s 2263. Sampling Procedures and Test Methods.

Table 1

(a)Sampling Procedures. In determining compliance with

Section	Gasoline Specification	Test Method [FNa]
2262	Reid Vapor Pressure	ASTM D 323-58 [FNb] or or 13 C.C.R. Section 2297
2262	Sulfur Content	ASTM D 2622-94 [FNc, d] or ASTM D 5453-93
2262	Benzene Content	ASTM D 5580-00 [FNe]
2262	Olefin Content	ASTM D 1319-95a [FNf] (Through December 31, 2001) ASTM D 6550-00 [FNg, h, i] (Starting January 1, 2002)
2262	Oxygen Content	ASTM D 4815-99
2262	T90 and T50	ASTM D 86-99ae1
2262	Aromatic Hydrocarbon Content	ASTM D 5580-00 [FNj]
2262.5(b)	Ethanol Content	ASTM D 4815-99
2262.6	MTBE Content	ASTM D 4815-99
2262.6(c)	Oxygen from oxygenates	ASTM D 4815-99 identified in section 2262.6(c) (4)

 [FNa] Do not report values below the limit of detection (LOD) specified in the test method. Where a test method does not specify a LOD, do not report values below the lower limit of the scope of the test method.

[FNb] Delete paragraph 4(b) concerning sampling.

[FNc] Make the following modifications to paragraph 9.1:

Low Level Sulfur Calibration Procedure

Reagents Thiophene, at least 99% purity
 2-Methylthiophene, at least 98% purity
 Toluene, reagent grade
 2,2,4-Trimethylpentane, reagent grade

Preparation of Stock Standard Weigh standard materials thiophene (° 0.7290 gm) and 2-methylthiophene (° 0.7031 gm) separately into a tared volumetric flask and record the individual mass to 0.1 mg. Add "mixed solvent" containing

25% toluene and 75% iso-octane (by volume) into the flask to a net weight of approximately 50 gm and record the weight. This "Stock Standard" contains approximately 10 mg/gm sulfur. The actual sulfur concentration can be calculated as follows:

$$\text{Sulfur from thiophene (gm)} = \text{Weight of thiophene} * 32.06 * \text{purity} / 84.14$$

$$\text{Sulfur from 2-methylthiophene (gm)} = \text{Weight of 2-methylthiophene} * 32.06 * \text{purity} / 98.17$$

$$\text{Sulfur concentration of Stock Standard (gm/gm)} = (\text{sulfur from thiophene} + \text{sulfur from 2-methylthiophene}) / \text{net weight of the stock standard}$$

Multiply the sulfur concentration by 1000 to convert the

Sulfur Content, ppm	Reproducibility
10 to 30	40.5xSulfur Content (ppm)
>30	19.2x Sulfur Content (ppm)

[FNe] The reproducibility of benzene is as follows:
Reproducibility = 0.1409 (X^{1.133}), where X = vol %

	Range	Reproducibility
Olefins	0.3 - 33	0.819 (X) ^{0.6}
X = Volume %		

[FNg] Replace ASTM D6550-00 reproducibility equation with the following:
Reproducibility = 0.32 X^{0.5} where X is between 0.3 and 25 mass % olefin

[FNh] The conversion from mass % olefin to volume % olefin is defined as follows: volume % olefin = 0.857 * mass % olefin

[FNi] Replace the last sentence in ASTM D6550-00 section 1.1 with the following: The application range is from 0.3 to 25 mass % total olefins.

[FNj] The reproducibility of total aromatic hydrocarbon is as follows:

$$\text{Reproducibility} = 1.4 \text{ volume}\%$$

(c)Equivalent Test Methods. Whenever this section pro-

unit to mg/gm.

Preparation of Calibration Standards Pipet 2.5 ml of the Stock Standard to 250 ml flask and dilute with the "mixed solvent" to the mark. The "Diluted Standard" contains approximately 100 mg/kg sulfur. Prepare 5, 10, 20, 30, 50, 75 ppm calibration standards by pipetting 5, 10, 20, 30, 50, 75 ml of the Diluted Standard into a 100 ml flask, respectively, and diluting with the "mixed solvent" to the mark. The actual concentration of the calibration standard should be determined from the stock standard. The standards with concentration ranging from 5 to 100 ppm and the "mixed solvent" are to be used for calibrating the instrument.

[FNd] Replace ASTM D 2622-94 reproducibility values with the following:

[FNf] Add the following reproducibility statement for oxygenate-containing samples:

vides for the use of a specified test method, another test method may be used following a determination by the executive officer that the other method produces results equivalent to the results with the specified method.

<General Materials (GM) - References, Annotations, or Tables>

Note: Authority cited: Sections 39600, 39601, 43013, 43013.1, 43018 and 43101, Health and Safety Code; and Western Oil and Gas Ass'n. v. Orange County Air Pollution Control District, 14 Cal.3d 411, 121 Cal. Rptr. 249 (1975). Reference: Sections 39000, 39001, 39002, 39003, 39010, 39500, 39515, 39516, 41511, 43000, 43013, 43013.1, 43016, 43018 and 43101, Health and Safety Code; and Western Oil and Gas Ass'n. v. Orange County Air Pollution Control District, 14 Cal.3d 411, 121 Cal. Rptr. 249 (1975).

HISTORY

1. New section filed 11-16-92; operative 12-16-92 (Register 92, No. 47).
2. Repealer of designation of subsection (b) (1), amendment of Table 1 and repealer of subsections (b) (2)-(2) (C) filed 9-1-94; operative 9-1-94 (Register 94, No. 35).
3. Amendment of Table 1 filed 8-7-95; operative 8-7-95 pursuant to Government Code section 11343.4(d) (Register 95, No. 32).
4. Redesignation of first paragraph of subsection (b) as (b) (1), amendment of Table 1, new Table 1 footnote a and footnote relettering, repealer of former footnote b, and new footnotes c-g, filed 2-26-96; operative 2-26-96 pursuant to Government Code section 11343.4(d) (Register 96, No. 9).
5. Editorial correction of subsection (b) (1) - Table (Register 2000, No. 31).
6. Amendment of section and Notefiled 8-3-2000; operative 9-2-2000 (Register 2000, No. 31).
7. Amendment filed 8-20-2001; operative 8-20-2001 pursuant to Government Code section 11343.4 (Register 2001, No. 34).
8. Amendment of subsection (b)-Table 1 filed 8-29-2001; operative 9-28-2001 (Register 2001, No. 35).
9. Amendment filed 5-1-2003; operative 5-1-2003 pursuant to Government Code section 11343.4 (Register 2003, No. 18).

13 CA ADC s 2263
END OF DOCUMENT